SI2306

N-Channel Enhancement Mode MOSFET


V_{DSS}	30 V
I_D	3.16 A
$R_{DS(ON)}$	38 m Ω

FEATURES

- High density cell design for low $R_{DS(ON)}$
- Voltage controlled small signal switch
- Rugged and reliable
- High saturation current capability


A6SHB

SOT-23



1. GATE
2. SOURCE
3. DRAIN

Equivalent Circuit



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Maximum Ratings and Thermal Characteristics (TA = 25°C unless otherwise noted)

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V_{DS}	30	V
Gate-source Voltage	V_{GS}	± 20	V
Drain Current (Continuous)	I_D	3.16	A
Drain Current (Pulsed)[a]	I_{DM}	10	A
Total Power Dissipation @TA=25°C	P_D	0.75	W
Operating Junction and Storage Temperature Range	T_j, T_{stg}	-55 to +150	°C
Thermal Resistance Junction to Ambient (PCB mounted)	$R_{\theta JA}$	100	°C/W

Electrical Characteristics (TA=25°C, unless otherwise noted)


Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DS}$	V_{GS} = 0V, I_D =250μA	30			V
Gate-Threshold Voltage	$V_{GS(th)}$	V_{DS} =V_{GS}, I_D =250μA	1.0		3.0	
Gate-Body Leakage	I_{GSS}	V_{DS} =0V, V_{GS} =±20V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} =30V, V_{GS} =0V			0.5	μA
Drain-Source On-Resistance[a]	$R_{DS(on)}$	V_{GS} =10V, I_D =3.5A		0.038	0.047	Ω
		V_{GS} =4.5V, I_D =2.8A		0.052	0.065	
Forward Transconductance[a]	g_{fs}	V_{DS} =4.5V, I_D =2.5A		7.0		S
Diode Forward Voltage	V_{SD}	I_S=1.25A,V_{GS}=0V		0.8	1.2	V
Dynamic						
Gate Charge	Q_g	V_{DS} =15V,V_{GS} =5V,I_D =2.5A		3.0	4.5	nC
Total Gate Charge	Q_{gt}	V_{DS} =15V,V_{GS} =10V,I_D =2.5A		6	9	
Gate-Source Charge	Q_{gs}			1.6		
Gate-Drain Charge	Q_{gd}			0.6		
Gate Resistance	R_g	f =1.0MHz	2.5	5	7.5	Ω
Input Capacitance	C_{iss}	V_{DS} =15V,V_{GS} =0V,f =1MHz		305		pF
Output Capacitance	C_{oss}			65		
Reverse Transfer Capacitance	C_{rss}			29		
Switching						
Turn-On Delay Time	$t_{d(on)}$	V_{DD}=15V, R_L=15Ω, I_D ≈1A, V_{GEN}=10V,Rg=6Ω		7	11	ns
Rise Time	t_r			12	18	
Turn-Off Delay Time	$t_{d(off)}$			14	25	
Fall Time	t_f			6	10	

Notes :


a.Pulse Test : Pulse Width≤300μs, duty cycle ≤2%.

RATING AND CHARACTERISTIC CURVES


Output Characteristics




Transfer Characteristics




RDS(ON) — ID




RDS(ON) — VGS



IS — VSD




Threshold Voltage



Soldering parameters


Reflow Condition		Pb-Free assembly (see as bellow)
Pre Heat	-Temperature Min ($T_{s(min)}$)	+150℃
	-Temperature Max($T_{s(max)}$)	+200℃
	-Time (Min to Max) (ts)	60-180 secs.
Average ramp up rate (Liquid us Temp (T_L) to peak)		3℃/sec. Max
$T_{s(max)}$ to T_L - Ramp-up Rate		3℃/sec. Max
Reflow	-Temperature(T_L)(Liquid us)	+217℃
	-Temperature(t_L)	60-150 secs.
Peak Temp (T_p)		+260(+0/-5)℃
Time within 5℃ of actual Peak Temp (t_p)		30 secs. Max
Ramp-down Rate		6℃/sec. Max
Time 25℃ to Peak Temp (T_P)		8 min. Max
Do not exceed		+260℃


FIG5: Reflow condition



Package Dimensions & Suggested Pad Layout

SOT23






SOT-23 mechanical data

UNIT		A	C	D	E	H_E	e	M	L	L_1	a
mm	max	1.1	0.15	1.4	3.0	2.6	0.5	1.95	0.55 (ref)	0.36 (ref)	0.0
	min	0.9	0.08	1.2	2.8	2.2	0.3	1.7			0.15
mil	max	43	6	55	118	102	20	77	22 (ref)	14 (ref)	0.0
	min	35	3	47	110	87	12	67			6

Dimensions	SOT23
Z	2.9
X	0.8
Y	0.9
C	2.0
E	1.35


Tape & rell specification

Tape



Symbol	Dimension (mm)
P0	4.00±0.10
P1	4.00±0.10
P2	2.00±0.10
D0	1.55±0.10
D1	1.05±0.10
E	1.55±0.10
F	3.60±0.10
W	8.00±0.10
A0	3.80±0.20
B0	3.25±0.20
K0	1.45±0.10
T	0.25±0.05

7” Reel



D2	178.0±3.0
D3	55Min.
D4	R24.0±3.0
G	R82.0±3.0
I	13.0±2.0
W1	11.0±3.0

Quantity: 3000PCS

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.