V_{DSS}	1200V
I_D	25 A
$R_{DS(ON)}$	80 mΩ

FEATURES


- Wide Bandgap SiC MOSFET Technology
- Low On-Resistance with High Blocking Voltage
- Low Capacitances with High-Speed Switching
- Low Reverse Recovery (Qrr)
- Easy to Parallel and Simple to Drive


BENEFITS

- Reduced Switching Losses
- Increased System Switching Frequency
- Increased Power Density
- Reduction of Heat Sink Requirements
- Reduced EMI


APPLICATION


- Power Factor Correction Modules
- Switch Mode Power Supplies
- DC-AC Inverters
- High Voltage DC/DC Converters





TO-247





ABSOLUTE MAXIMUM RATINGS (T_C = 25°C, unless otherwise specified)

Parameter	Symbol	Test Condition	Value	Unit
Drain to Source Voltage	V_{DS}	V_{GS} = 0V, I_D = 100μA	1200	V
Gate to Source Voltage	V_{GS}	Absolute maximum values	-10/+22	V
Recommended Operation Voltage of Gate to Source	V_{GSop}	Recommended operational values	-4/+18	V
Continuous Drain Current	I_D	V_{GS}=18V, T_C=25℃	36	A
		V_{GS}=18V, T_C=100℃	25	
Pulsed Drain Current	I_{DM}	Pulse with T_p limited by T_{jmax}	80	A
Power Dissipation	P_{tot}	T_C=25℃, T_j=175℃	283	W
Operating and Storage Temperature	T_j, T_{stg}		-55 to +175	℃

ELECTRICAL CHARACTERISTICS (T_C=25°C, unless otherwise specified)

Static Characteristics

Parameter	Symbol	Test Condition	Value			Unit
			Min.	Typ.	Max.	
Drain to Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS}=0V, I_D=500μA	1200			V
Gate Threshold Voltage	$V_{GS(th)}$	V_{GS}= V_{DS}, I_D=5mA, T_j=25℃	2		4	V
Zero Gate Voltage Drain Current	I_{DSS}	V_{GS}=0V, V_{DS}=1200V			10	μA
Gate to Source Leakage Current	I_{GSS}	V_{GS}=18V, V_{DS}=0V			100	nA
Drain to Source on Resistance	$R_{DS(on)}$	V_{GS}=18V, I_D=20A		80	104	mΩ
		V_{GS}=18V, I_D=20A, T_j=175℃		122		

Dynamic Characteristics

Parameter	Symbol	Test Condition	Value			Unit
			Min.	Typ.	Max.	
Input Capacitance	C_{iss}	V_{GS}=0V, V_{DS}=800V, f=1MHz, T_j=25℃		944		pF
Output Capacitance	C_{oss}			42.6		
Reverse Transfer Capacitance	C_{rss}			4.1		
Total Gate Charge	Q_g	V_{GS}=-4/18V, V_{DS}=800V, I_D=20A, T_j=25℃		51		nC
Gate-Source Charge	Q_{gs}			13		
Gate-Drain Charge	Q_{gd}			25		
Gate Resistance	R_g	V_{AC}=25mV, f=1MHz		4		Ω

Thermal Characteristics

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
Thermal Resistance from Junction to Case	$R_{th(j-c)}$	-	0.55	-	℃/W

ELECTRICAL CHARACTERISTICS (T_C=25°C, unless otherwise specified)

Switching Characteristics

Parameter	Symbol	Test Condition	Value			Unit
			Min.	Typ.	Max.	
Turn-On Delay Time	$t_{d(on)}$	V_{GS}=-4/18V, V_{DD}=800V, I_D=20A, R_g=10Ω		38		ns
Rise Time	t_r			46		
Turn-Off Delay Time	$t_{d(off)}$			32		
Fall Time	t_f			41		
Turn-On Energy	E_{on}			108		μJ
Turn-Off Energy	E_{off}			49		

Reverse Diode Characteristics

Parameter	Symbol	Test Condition	Value			Unit
			Min.	Typ.	Max.	
Diode Forward Voltage	V_{SD}	V_{GS}=-4V, I_{SD}=10A, T_j=25℃	-	4.5		V
Continuous Diode Forward Current	I_S	V_{GS}=-4V, T_j=25℃		36		A
Reverse Recovery Time	t_{rr}	V_{GS} = -4V, I_{SD}=20A, V_R=800V, di/dt=800A/us, T_j=25℃		17.5		ns
Reverse Recovery Charge	Q_{rr}			71.4		nC
Peak Reverse Recovery Current	I_{rrm}			6.8		A

RATING AND CHARACTERISTIC CURVES




Fig1. Output Characteristics T_j=25℃




Fig2. Output Characteristics T_j=175℃




Fig3. Output Characteristics T_j=-55℃




Fig4. Typical Transfer Characteristics




Fig5. Normalized On-Resistance vs. Temperature




Fig6. Normalized On-Resistance vs. Drain Current for Various Temperatures

RATING AND CHARACTERISTIC CURVES




Fig7. Capacitances vs. Drain-Source Voltage (0-200V)




Fig8. Capacitances vs. Drain-Source Voltage (0-1200V)




Fig9. Body Diode Characteristics




Fig10. Normalized Threshold Voltage vs. Temperature




Fig11. Gate Charge Characteristics




Fig12. Power Dissipation vs. Case Temperature

RATING AND CHARACTERISTIC CURVES





Fig13. Maximum DC Drain to Source Current vs. Case Temperature


Soldering parameters

Reflow Condition		Pb-Free assembly (see as bellow)
Pre Heat	-Temperature Min ($T_{s(min)}$)	+150℃
	-Temperature Max($T_{s(max)}$)	+200℃
	-Time (Min to Max) (ts)	60-180 secs.
Average ramp up rate (Liquid us Temp (T_L) to peak)		3℃/sec. Max
$T_{s(max)}$ to T_L - Ramp-up Rate		3℃/sec. Max
Reflow	-Temperature(T_L)(Liquid us)	+217℃
	-Temperature(t_L)	60-150 secs.
Peak Temp (T_p)		+260(+0/-5)℃
Time within 5℃ of actual Peak Temp (t_p)		30 secs. Max
Ramp-down Rate		6℃/sec. Max
Time 25℃ to Peak Temp (T_P)		8 min. Max
Do not exceed		+260℃

FIG5: Reflow condition



Package Dimensions & Suggested Pad Layout



Dimensions in inches and (millimeters)

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.