
N-Channel 80-V (D-S) 175°C MOSFET

PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
80	0.016 @ V_{GS} = 10 V	40

FEATURES

- TrenchFET® Power MOSFET
- 175°C Maximum Junction Temperature
- 100% R_g Tested

TO-252




Drain Connected to Tab

Top View

Ordering Information:

SUD40N08-16
SUD40N08-16—E3 (Lead Free)



N-Channel MOSFET

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C UNLESS OTHERWISE NOTED)				
Parameter		**Symbol**	**Limit**	**Unit**
Drain-Source Voltage		V_{DS}	80	V
Gate-Source Voltage		V_{GS}	±20	
Continuous Drain Current (T_J = 175°C)[b]	T_C = 25°C	I_D	40	A
	T_C = 125°C		30	
Pulsed Drain Current		I_{DM}	60	
Continuous Source Current (Diode Conduction)		I_S	40	
Avalanche Current		I_{AR}	40	
Repetitive Avalanche Energy (Duty Cycle ≤ 1%)	L = 0.1 mH	E_{AR}	80	mJ
Maximum Power Dissipation	T_C = 25°C	P_D	136[b]	W
	T_A = 25°C		3[a]	
Operating Junction and Storage Temperature Range		T_J, T_{stg}	–55 to 175	°C

THERMAL RESISTANCE RATINGS					
Parameter		**Symbol**	**Typical**	**Maximum**	**Unit**
Junction-to-Ambient[a]	t ≤ 10 sec	R_{thJA}	15	18	°C/W
	Steady State		40	50	
Junction-to-Case		R_{thJC}	0.85	1.1	

Notes
a. Surface Mounted on 1" x1" FR4 Board.
b. See SOA curve for voltage derating.


SPECIFICATIONS (T_J = 25°C UNLESS OTHERWISE NOTED)

Parameter	Symbol	Test Condition	Min	Typ[a]	Max	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 250 μA	80			V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250 μA	2.0		4.0	
Gate-Body Leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ±20 V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 80 V, V_{GS} = 0 V			1	μA
		V_{DS} = 80 V, V_{GS} = 0 V, T_J = 125°C			50	
		V_{DS} = 80 V, V_{GS} = 0 V, T_J = 175°C			250	
On-State Drain Current[b]	$I_{D(on)}$	V_{DS} = 5 V, V_{GS} = 10 V	60			A
Drain-Source On-State Resistance[b]	$r_{DS(on)}$	V_{GS} = 10 V, I_D = 40 A		0.013	0.016	Ω
		V_{GS} = 10 V, I_D = 40 A, T_J = 125°C			0.027	
		V_{GS} = 10 V, I_D = 40 A, T_J = 175°C			0.037	
Forward Transconductance[b]	g_{fs}	V_{DS} = 15 V, I_D = 40 A		45		S
Dynamic[a]						
Input Capacitance	C_{iss}	V_{GS} = 0 V, V_{DS} = 25 V, F = 1 MHz		1960		pF
Output Capacitance	C_{oss}			370		
Reverse Transfer Capacitance	C_{rss}			200		
Total Gate Charge[c]	Q_g	V_{DS} = 40 V, V_{GS} = 10 V, I_D = 40 A		42	60	nC
Gate-Source Charge[c]	Q_{gs}			7		
Gate-Drain Charge[c]	Q_{gd}			13		
Gate Resistance	R_g		0.5		2.7	Ω
Turn-On Delay Time[c]	$t_{d(on)}$	V_{DD} = 40 V, R_L = 1.0 Ω I_D ≅ 40 A, V_{GEN} = 10 V, R_g = 2.5 Ω		12	20	ns
Rise Time[c]	t_r			52	80	
Turn-Off Delay Time[c]	$t_{d(off)}$			25	38	
Fall Time[c]	t_f			10	15	
Source-Drain Diode Ratings and Characteristic (T_C = 25°C)						
Pulsed Current	I_{SM}				60	A
Diode Forward Voltage[b]	V_{SD}	I_F = 40 A, V_{GS} = 0 V		1.0	1.5	V
Source-Drain Reverse Recovery Time	t_{rr}	I_F = 40 A, di/dt = 100 A/μs		45	70	ns


Notes
a. Guaranteed by design, not subject to production testing.
b. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.
c. Independent of operating temperature.

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)


Output Characteristics




Transfer Characteristics




Transconductance




On-Resistance vs. Drain Current



Capacitance




Gate Charge




TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

On-Resistance vs. Junction Temperature




Source-Drain Diode Forward Voltage




THERMAL RATINGS


Maximum Avalanche Drain Current vs. Case Temperature



Safe Operating Area



Normalized Thermal Transient Impedance, Junction-to-Case



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.