ALPHA & OMEGA SEMICONDUCTOR

AOB30B65LN2V

650V, 30A AlphaIGBT™
AEC-Q101 Qualified

General Description

- AEC-Q101 qualified
- 650V breakdown voltage
- Low Vce(sat) and fast turn-on speed
- Very low Vf and Qrr
- Low turn-off switching loss and softness
- Very good EMI behavior
- High ruggedness and temperature stable behavior


Applications

- Discharge switch
- Relay replacement
- PTC heater


Product Summary

V_{CE}	650V
I_C (T_C=100°C)	30A
$V_{CE(sat)}$ (T_J=25°C)	1.86V

RoHS Compliant



AOB30B65LN2V



Orderable Part Number	Package Type	Form	Minimum Order Quantity
AOB30B65LN2V	TO263	Tape & Reel	800

Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	AOB30B65LN2V	Units
Collector-Emitter Voltage		V_{CE}	650	V
Gate-Emitter Voltage		V_{GE}	±30	V
Continuous Collector Current	T_C=25°C	I_C	60	A
	T_C=100°C		30	
Pulsed Collector Current, Limited by T_{Jmax}		I_{CM}	90	A
Turn-Off SOA, V_{CE}≤650V, Limited by T_{Jmax}		I_{LM}	90	A
Continuous Diode Forward Current	T_C=25°C	I_F	20	A
	T_C=100°C		10	
Diode Pulsed Current, Limited by T_{Jmax}		I_{FM}	20	A
Short Circuit Withstanding Time (1) V_{GE}=15V, V_{CC}≤400V, T_J≤175°C		t_{SC}	5	µs
Power Dissipation	T_C=25°C	P_D	227	W
	T_C=100°C		114	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 175	°C
Maximum Lead Temperature for Soldering Purpose, 1/8" from case for 5 seconds		T_L	300	°C

Thermal Characteristics

Parameter	Symbol	AOB30B65LN2V	Units
Maximum Junction-to-Ambient	$R_{\theta JA}$	65	°C/W
Maximum IGBT Junction-to-Case	$R_{\theta JC}$	0.66	°C/W
Maximum Diode Junction-to-Case	$R_{\theta JC}$	3.5	°C/W

(1) Allowed number of short circuits: <1000; time between short circuits: >1s.

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions		Min	Typ	Max	Units
STATIC PARAMETERS							
BV_{CES}	Collector-Emitter Breakdown Voltage	I_C=1mA, V_{GE}=0V, T_J=25°C		650	-	-	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	V_{GE}=15V, I_C=30A	T_J=25°C	-	1.86	2.35	V
			T_J=125°C	-	2.32	-	
			T_J=175°C	-	2.58	-	
V_F	Diode Forward Voltage	V_{GE}=0V, I_F=20A	T_J=25°C	-	1.3	1.65	V
			T_J=125°C	-	1.28	-	
			T_J=175°C	-	1.27	-	
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	V_{CE}=5V, I_C=1mA		4	4.7	5.4	V
I_{CES}	Zero Gate Voltage Collector Current	V_{CE}=650V, V_{GE}=0V	T_J=25°C	-	-	10	µA
			T_J=125°C	-	-	500	
			T_J=175°C	-	-	10000	
I_{GES}	Gate-Emitter Leakage Current	V_{CE}=0V, V_{GE}=±30V		-	-	±100	nA
g_{FS}	Forward Transconductance	V_{CE}=20V, I_C=30A		-	20	-	S
DYNAMIC PARAMETERS							
C_{ies}	Input Capacitance	V_{GE}=0V, V_{CC}=25V, f=1MHz		-	1246	-	pF
C_{oes}	Output Capacitance			-	92	-	pF
C_{res}	Reverse Transfer Capacitance			-	38	-	pF
Q_g	Total Gate Charge	V_{GE}=15V, V_{CC}=520V, I_C=30A		-	52	-	nC
Q_{ge}	Gate to Emitter Charge			-	14	-	nC
Q_{gc}	Gate to Collector Charge			-	22	-	nC
$I_{C(SC)}$	Short Circuit Collector Current	V_{GE}=15V, V_{CC}=400V, t_{sc}≤5us, T_J≤175°C		-	150	-	A
R_g	Gate Resistance	V_{GE}=0V, V_{CC}=0V, f=1MHz		-	11	-	Ω
SWITCHING PARAMETERS, (Load Inductive, T_J=25°C)							
$t_{D(on)}$	Turn-On Delay Time	T_J=25°C, V_{GE}=15V, V_{CC}=400V, I_C=30A, R_G=10Ω		-	23	-	ns
t_r	Turn-On Rise Time			-	27	-	ns
$t_{D(off)}$	Turn-Off Delay Time			-	109	-	ns
t_f	Turn-Off Fall Time			-	14	-	ns
E_{on}	Turn-On Energy			-	0.88	-	mJ
E_{off}	Turn-Off Energy			-	0.35	-	mJ
E_{total}	Total Switching Energy			-	1.24	-	mJ
t_{rr}	Diode Reverse Recovery Time	T_J=25°C, I_F=20A, di/dt=200A/µs, V_{CC}=400V		-	312	-	ns
Q_{rr}	Diode Reverse Recovery Charge			-	2.28	-	µC
I_{rm}	Diode Peak Reverse Recovery Current			-	11.4	-	A
SWITCHING PARAMETERS, (Load Inductive, T_J=175°C)							
$t_{D(on)}$	Turn-On Delay Time	T_J=175°C, V_{GE}=15V, V_{CC}=400V, I_C=30A, R_G=10Ω		-	22	-	ns
t_r	Turn-On Rise Time			-	31	-	ns
$t_{D(off)}$	Turn-Off Delay Time			-	133	-	ns
t_f	Turn-Off Fall Time			-	24	-	ns
E_{on}	Turn-On Energy			-	0.85	-	mJ
E_{off}	Turn-Off Energy			-	0.70	-	mJ
E_{total}	Total Switching Energy			-	1.55	-	mJ
t_{rr}	Diode Reverse Recovery Time	T_J=175°C, I_F=20A, di/dt=200A/µs, V_{CC}=400V		-	390	-	ns
Q_{rr}	Diode Reverse Recovery Charge			-	2.63	-	µC
I_{rm}	Diode Peak Reverse Recovery Current			-	10.5	-	A

APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO MAKE CHANGES TO PRODUCT SPECIFICATIONS WITHOUT NOTICE. IT IS THE RESPONSIBILITY OF THE CUSTOMER TO EVALUATE SUITABILITY OF THE PRODUCT FOR THEIR INTENDED APPLICATION. CUSTOMER SHALL COMPLY WITH APPLICABLE LEGAL REQUIREMENTS, INCLUDING ALL APPLICABLE EXPORT CONTROL RULES, REGULATIONS AND LIMITATIONS.

AOS' products are provided subject to AOS' terms and conditions of sale which are set forth at:
http://www.aosmd.com/terms_and_conditions_of_sale

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 1: Output Characteristic (T_j=25°C)




Figure 2: Output Characteristic (T_j=175°C)




Figure 3: Transfer Characteristic




Figure 4: Diode Characteristic




Figure 5: Collector-Emitter Saturation Voltage vs. Junction Temperature




Figure 6: Diode Forward voltage vs. Junction Temperature

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristic




Figure 9: Forward Bias Safe Operating Area (T_C=25°C, V_{GE}=15V)




Figure 10: Power Disspation as a Function of Case




Figure 11: Current De-rating




Figure 12: Diode Reverse Leakage Current vs. Junction Temperature

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 13: Switching Time vs. I_C
(T_j=175°C, V_{GE}=15V, V_{CE}=400V, R_g=10Ω)




Figure 14: Switching Time vs. R_g
(T_j=175°C, V_{GE}=15V, V_{CE}=400V, I_C=30A)




Figure 15: Switching Time vs.T_j
(V_{GE}=15V, V_{CE}=400V, I_C=30A, R_g=10Ω)




Figure 16: $V_{GE(th)}$ vs. T_j




Figure 17: Switching Loss vs. I_C
(T_j=175°C, V_{GE}=15V, V_{CE}=400V, R_g=10Ω)




Figure 18: Switching Loss vs. R_g
(T_j=175°C, V_{GE}=15V, V_{CE}=400V, I_C=30A)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 19: Switching Loss vs. T_j
(V_{GE}=15V, V_{CE}=400V, I_C=30A, R_g=10Ω)




Figure 20: Switching Loss vs. V_{CE}
(T_j=175°C, V_{GE}=15V, I_C=30A, R_g=10Ω)




Figure 21: Diode Reverse Recovery Charge and Peak Current vs. Conduction Current
(V_{GE}=15V, V_{CE}=400V, di/dt=200A/µs)




Figure 22: Diode Reverse Recovery Time and Softness Factor vs. Conduction Current
(V_{GE}=15V, V_{CE}=400V, di/dt=200A/µs)




Figure 23: Diode Reverse Recovery Charge and Peak Current vs. di/dt
(V_{GE}=15V, V_{CE}=400V, I_F=20A)




Figure 24: Diode Reverse Recovery Time and Softness Factor vs. di/dt
(V_{GE}=15V, V_{CE}=400V, I_F=20A)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 25: Normalized Maximum Transient Thermal Impedance for IGBT




Figure 26: Normalized Maximum Transient Thermal Impedance for Diode

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.