ALPHA & OMEGA SEMICONDUCTOR

AOTF600A70L/AOT600A70L/AOB600A70L

700V, αMOS5™ N-Channel Power Transistor

General Description

- Proprietary αMOS5™ technology
- Low $R_{DS(ON)}$
- Optimized switching parameters for better EMI performance
- Enhanced body diode for robustness and fast reverse recovery

Applications

- Flyback for SMPS
- Charger ,PD Adapter, TV, lighting.


Product Summary

V_{DS} @ $T_{j,max}$	800V
I_{DM}	34A
$R_{DS(ON),max}$	< 0.6Ω
$Q_{g,typ}$	15.5nC
E_{oss} @ 400V	1.8μJ

100% UIS Tested
100% R_g Tested

Green Product

Top View



Orderable Part Number	Package Type	Form	Minimum Order Quantity
AOTF600A70L	TO220F Green	Tube	1000
AOT600A70L	TO220 Green	Tube	1000
AOB600A70L	TO263	Tape&Reel	800

Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	AOT(B)600A70L	AOTF600A70L	Units
Drain-Source Voltage		V_{DS}	700		V
Gate-Source Voltage		V_{GS}	±20		V
Gate-Source Voltage (dynamic) AC(f>1Hz)		V_{GS}	±30		V
Continuous Drain Current	T_C=25°C	I_D	8.5	8.5*	A
	T_C=100°C		5	5*	
Pulsed Drain Current [C]		I_{DM}	34		
Avalanche Current [C] L=1mH		I_{AR}	2.1		A
Repetitive avalanche energy [C]		E_{AR}	2.2		mJ
Single pulsed avalanche energy [G]		E_{AS}	19		mJ
MOSFET dv/dt ruggedness		dv/dt	100		V/ns
Peak diode recovery dv/dt			20		
Power Dissipation [B]	T_C=25°C	P_D	104	27	W
	Derate above 25°C		0.8	0.2	W/°C
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150		°C
Maximum lead temperature for soldering purpose, 1/8" from case for 5 seconds		T_L	300		°C

Thermal Characteristics

Parameter	Symbol	AOT(B)600A70L	AOTF600A70L	Units
Maximum Junction-to-Ambient [A,D]	$R_{\theta JA}$	65	65	°C/W
Maximum Case-to-sink [A]	$R_{\theta CS}$	0.5	---	°C/W
Maximum Junction-to-Case	$R_{\theta JC}$	1.2	4.6	°C/W

* Drain current limited by maximum junction temperature.

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=250µA, V_{GS}=0V, T_J=25°C	700			V
		I_D=250µA, V_{GS}=0V, T_J=150°C		800		
BV_{DSS} /ΔTJ	Breakdown Voltage Temperature Coefficient	I_D=250µA, V_{GS}=0V		0.6		V/ °C
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=700V, V_{GS}=0V			1	µA
		V_{DS}=560V, T_J=125°C			10	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±20V			±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=5V, I_D=250µA	2.9	3.5	4.1	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=10V, I_D=2.5A		0.51	0.6	Ω
g_{FS}	Forward Transconductance	V_{DS}=10V, I_D=4A		6.2		S
V_{SD}	Diode Forward Voltage	I_S=4A,V_{GS}=0V		0.86	1.2	V
I_S	Maximum Body-Diode Continuous Current				8.5	A
I_{SM}	Maximum Body-Diode Pulsed Current [C]				34	A
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=100V, f=1MHz		870		pF
C_{oss}	Output Capacitance			23		pF
$C_{o(er)}$	Effective output capacitance, energy related [H]	V_{GS}=0V, V_{DS}=0 to 480V, f=1MHz		20		pF
$C_{o(tr)}$	Effective output capacitance, time related [I]			98		pF
C_{rss}	Reverse Transfer Capacitance	V_{GS}=0V, V_{DS}=100V, f=1MHz		1.3		pF
R_g	Gate resistance	f=1MHz		5		Ω
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	V_{GS}=10V, V_{DS}=480V, I_D=4A		15.5		nC
Q_{gs}	Gate Source Charge			5.6		nC
Q_{gd}	Gate Drain Charge			4.3		nC
$T_{d(on)}$	Turn-On DelayTime	V_{GS}=10V, V_{DS}=400V, I_D=4A, R_G=5Ω		22		ns
T_r	Turn-On Rise Time			10		ns
$T_{d(off)}$	Turn-Off DelayTime			36		ns
T_f	Turn-Off Fall Time			8		ns
T_{rr}	Body Diode Reverse Recovery Time	I_F=4A, dI/dt=100A/µs, V_{DS}=400V		245		ns
I_{rm}	Peak Reverse Recovery Current			18.6		A
Q_{rr}	Body Diode Reverse Recovery Charge			3		µC

A. The value of $R_{\theta JA}$ is measured with the device in a still air environment with T_A=25° C.
B. The power dissipation P_D is based on $T_{J(MAX)}$=150° C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.
C. Repetitive rating, pulse width limited by junction temperature $T_{J(MAX)}$=150° C, Ratings are based on low frequency and duty cycles to keep initial T_J =25° C.
D. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to case $R_{\theta JC}$ and case to ambient.
E. The static characteristics in Figures 1 to 6 are obtained using <300µs pulses, duty cycle 0.5% max.
F. These curves are based on the junction-to-case thermal impedance which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(MAX)}$=150° C. The SOA curve provides a single pulse rating.
G. L=60mH, I_{AS}=0.8A, R_G=25Ω, Starting T_J=25° C.
H. $C_{o(er)}$ is a fixed capacitance that gives the same stored energy as C_{oss} while V_{DS} is rising from 0 to 80% $V_{(BR)DSS}$.
I. $C_{o(tr)}$ is a fixed capacitance that gives the same charging time as C_{oss} while V_{DS} is rising from 0 to 80% $V_{(BR)DSS}$.

APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO MAKE CHANGES TO PRODUCT SPECIFICATIONS WITHOUT NOTICE. IT IS THE RESPONSIBILITY OF THE CUSTOMER TO EVALUATE SUITABILITY OF THE PRODUCT FOR THEIR INTENDED APPLICATION. CUSTOMER SHALL COMPLY WITH APPLICABLE LEGAL REQUIREMENTS, INCLUDING ALL APPLICABLE EXPORT CONTROL RULES, REGULATIONS AND LIMITATIONS.

AOS' products are provided subject to AOS' terms and conditions of sale which are set forth at:
http://www.aosmd.com/terms_and_conditions_of_sale

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: Break Down vs. Junction Temparature




Figure 6: Body-Diode Characteristics

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Coss stored Energy




Figure 10: Current De-rating (Note F)




Figure 11: Maximum Forward Biased Safe Operating Area for AOTF600A70L (Note F)




Figure 12: Maximum Forward Biased Safe Operating Area for AOT(B)600A70L(Note F)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 13: Normalized Maximum Transient Thermal Impedance for AOTF600A70L (Note F)






Figure 14: Normalized Maximum Transient Thermal Impedance for AOT(B)600A70L (Note F)


Gate Charge Test Circuit & Waveform




Resistive Switching Test Circuit & Waveforms



Unclamped Inductive Switching (UIS) Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.