ALPHA & OMEGA SEMICONDUCTOR

AOC2421

8V P-Channel MOSFET

General Description


The AOC2421 uses advanced trench technology to provide excellent $R_{DS(ON)}$, low gate charge and operation with gate voltages as low as 1.2V while retaining a 5V $V_{GS(MAX)}$ rating.


Product Summary


V_{DS}	-8V
I_D (at V_{GS}=-2.5V)	-2.5A
$R_{DS(ON)}$ (at V_{GS}=-2.5V)	< 60mΩ
$R_{DS(ON)}$ (at V_{GS}=-1.8V)	< 72mΩ
$R_{DS(ON)}$ (at V_{GS}=-1.5V)	< 85mΩ
$R_{DS(ON)}$ (at V_{GS}=-1.2V)	< 115mΩ
Typical ESD protection	**HBM Class 2**

Green Product

AlphaDFN 0.97x0.97A_4







Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	-8	V
Gate-Source Voltage		V_{GS}	±5	V
Source Current (DC) Note1	T_A=25°C	I_D	-2.5	A
Source Current (Pulse) Note2		I_{DM}	-25	
Power Dissipation Note1	T_A=25°C	P_D	0.6	W
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

Thermal Characteristics

Parameter		Symbol	Typ	Max	Units
Maximum Junction-to-Ambient A	t ≤ 10s	$R_{\theta JA}$	110	140	°C/W
Maximum Junction-to-Ambient A D	Steady-State		160	200	°C/W

Note 1. Mounted on minimum pad PCB

Note 2. PW <300 µs pulses, duty cycle 0.5% max

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Units
STATIC PARAMETERS						
BV_{DSS}	Drain-Source Breakdown Voltage	I_D=-250µA, V_{GS}=0V	-8			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=-8V, V_{GS}=0V			-1	µA
		T_J=55°C			-5	
I_{GSS}	Gate-Body leakage current	V_{DS}=0V, V_{GS}=±5V			±10	µA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS} I_D=-250µA	-0.2	-0.45	-0.7	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=-2.5V, I_D=-1.5A		50	62	mΩ
		T_J=125°C		63.5	79	
		V_{GS}=-1.8V, I_D=-1A		57	72	mΩ
		V_{GS}=-1.5V, I_D=-1A		65	85	mΩ
		V_{GS}=-1.2V, I_D=-1A		83	115	mΩ
g_{FS}	Forward Transconductance	V_{DS}=-5V, I_D=-1.5A		12		S
V_{SD}	Diode Forward Voltage	I_S=-1A,V_{GS}=0V		-0.6	-1	V
DYNAMIC PARAMETERS						
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=-4V, f=1MHz		752		pF
C_{oss}	Output Capacitance			178		pF
C_{rss}	Reverse Transfer Capacitance			104		pF
R_g	Gate resistance	V_{GS}=0V, V_{DS}=0V, f=1MHz		1.6		KΩ
SWITCHING PARAMETERS						
Q_g	Total Gate Charge	V_{GS}=-4.5V, V_{DS}=-4V, I_D=-1.5A		7.5	13	nC
Q_{gs}	Gate Source Charge			1.5		nC
Q_{gd}	Gate Drain Charge			1.0		nC
$t_{D(on)}$	Turn-On DelayTime	V_{GS}=-2.5V, V_{DS}=-4V, R_L=2.67Ω, R_{GEN}=3Ω		285		ns
t_r	Turn-On Rise Time			465		ns
$t_{D(off)}$	Turn-Off DelayTime			1870		ns
t_f	Turn-Off Fall Time			1900		ns
t_{rr}	Body Diode Reverse Recovery Time	I_F=-1.5A, dI/dt=100A/µs		12		ns
Q_{rr}	Body Diode Reverse Recovery Charge	I_F=-1.5A, dI/dt=100A/µs		4		nC

APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO MAKE CHANGES TO PRODUCT SPECIFICATIONS WITHOUT NOTICE. IT IS THE RESPONSIBILITY OF THE CUSTOMER TO EVALUATE SUITABILITY OF THE PRODUCT FOR THEIR INTENDED APPLICATION. CUSTOMER SHALL COMPLY WITH APPLICABLE LEGAL REQUIREMENTS, INCLUDING ALL APPLICABLE EXPORT CONTROL RULES, REGULATIONS AND LIMITATIONS.

AOS' products are provided subject to AOS' terms and conditions of sale which are set forth at:
http://www.aosmd.com/terms_and_conditions_of_sale

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)




Figure 4: On-Resistance vs. Junction Temperature (Note E)




Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)




Figure 6: Body-Diode Characteristics (Note E)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area




Figure 10: Single Pulse Power Rating Junction-to-Ambient






Figure 11: Normalized Maximum Transient Thermal Impedance


Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.