ALPHA & OMEGA SEMICONDUCTOR

AOK065V120X2

1200 V αSiC Silicon Carbide Power MOSFET

Features

- Proprietary αSiC MOSFET technology
- Low loss, fast switching speeds with low R_G
- Optimized drive voltage (V_{GS} = 15 V) for broad driver compatibility
- Robust body diode and low Qrr

Product Summary

V_{DS} @ $T_{J, max}$	1200 V
I_{DM}	85 A
$R_{DS(ON), typ}$	65 mΩ
Q_{rr}	155 nC
E_{OSS} @ 800 V	30 µJ
100% UIS Tested	


RoHS Compliant

Applications

Renewable
- EV Charger
- Solar Inverters

Industrial
- UPS
- SMPS
- Motor Drives

Pin Configuration



Ordering Part Number	Package Type	Form	Shipping Quantity
AOK065V120X2	TO-247-3L	Tube	30/Tube

Absolute Maximum Ratings

(T_A = 25°C, unless otherwise noted)

Symbol	Parameter		AOK065V120X2	Units
V_{DS}	Drain-Source Voltage		1200	V
$V_{GS, MAX}$	Gate-Source Voltage	Maximum	-8/+18	V
$V_{GS,OP,TRANS}$		Max Transient[A]	-8/+20	
$V_{GS,OP}$		Recommended Operating [B]	-5/+15	
I_D	Continuous Drain Current	T_C = 25°C	40.3	A
		T_C = 100°C	29.6	
I_{DM}	Pulsed Drain Current[C]		85	
E_{AS}	Single Pulsed Avalanche Energy[D]		250	mJ
P_D	Power Dissipation[C]		187.5	W
T_J, T_{STG}	Junction and Storage Temperature Range		-55 to 175	°C
T_L	Maximum lead temperature for soldering purpose, 1/8" from case for 5 seconds		300	°C

Thermal Characteristics

Symbol	Parameter	AOK065V120X2	Units
$R_{\theta JA}$	Maximum Junction-to-Ambient (E,F)	40	°C/W
$R_{\theta JC}$	Maximum Junction-to-Case (G)	0.8	°C/W

Electrical Characteristics

(T_A = 25°C, unless otherwise noted)

Symbol	Parameter	Conditions		Min	Typ	Max	Units
STATIC							
$V_{(BR)DSS}$	Drain-Source Breakdown Voltage	I_D=250µA, V_{GS}=0V, T_J=25°C		1200			V
		I_D=250µA, V_{GS}=0V, T_J=150°C		1200			V
I_{DSS}	Zero Gate Voltage Drain Current	V_{DS}=1200V, V_{GS}=0V				50	µA
I_{GSS}	Gate-Source Leakage Current	V_{DS}=0V, V_{GS}=+15/-5V				±100	nA
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_D=10mA		1.8	2.8	3.5	V
$R_{DS(ON)}$	Static Drain-Source On-Resistance	V_{GS}=15V, I_D=10A	T_J = 25°C		65	85	mΩ
			T_J= 150°C		90		mΩ
g_{fs}	Forward Transconductance	V_{DS}=20V, I_D=20V			12		S
V_{SD}	Diode Forward Voltage	I_S=10A,V_{GS}=-5V			4.1	5	V
DYNAMIC							
C_{iss}	Input Capacitance	V_{GS}=0V, V_{DS}=800V, f=1MHz			1716		pF
C_{oss}	Output Capacitance				71		pF
C_{rss}	Reverse Transfer Capacitance				5		pF
E_{oss}	Coss Stored Energy				30		µJ
R_G	Gate Resistance	f=1MHz			1.7		Ω
SWITCHING							
Q_g	Total Gate Charge	V_{GS}=-5/+15V, V_{DS}=800V, I_D=20A			62.3		nC
Q_{gs}	Gate Source Charge				23.1		nC
Q_{gd}	Gate Drain Charge				23.7		nC
$t_{d(on)}$	Turn-On Delay Time	V_{GS}=0V/+15V, V_{DS}=800V, I_D=20A, R_G=5Ω, L=120µH, FWD: AOK065V120X2			14.6		ns
t_r	Turn-On Rise Time				36.2		ns
$t_{d(off)}$	Turn-Off Delay Time				20.8		ns
t_f	Turn-Off Fall Time				10.2		ns
E_{on}	Turn-On Energy				325		µJ
E_{off}	Turn-Off Energy				23		µJ
E_{tot}	Total Switching Energy				348		µJ
t_{rr}	Body Diode Reverse Recovery Time	I_F=20A,dI/dt=1560A/us, V_{DS}=800V			27		ns
I_{rm}	Peak Reverse Recovery Current				10		A
Q_{rr}	Body Diode Reverse Recovery Charge				155		nC

Notes:
A. <1% duty cycle, f>1Hz
B. Device can be operated at V_{GS}=0/15V. Actual operating VGS will depend on application specifics such as parasitic inductance and dV/dt but should not exceed maximum ratings.
C. The power dissipation P_D is based on $T_{J(MAX)}$=175°C, using junction-to-case thermal resistance, and is more useful in setting the upper dissipation limit for cases where additional heatsinking is used.
D. L=5mH, I_{AS}=10A, R_G=25Ω, Starting T_J=25°C.
E. The value of $R_{\theta JA}$ is measured with the device in a still air environment with T_A=25°C.
F. The $R_{\theta JA}$ is the sum of the thermal impedance from junction to case $R_{\theta JC}$ and case to ambient.
G. The value of $R_{\theta JC}$ is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(MAX)}$=175°C.
H. The static characteristics in Figures 1 to 8 are obtained using <300ms pulses, duty cycle 0.5% max.
I. These curves are based on $R_{\theta JC}$ which is measured with the device mounted to a large heatsink, assuming a maximum junction temperature of $T_{J(MAX)}$=175°C. The SOA curve provides a single pulse rating.

Typical Electrical and Thermal Characteristics




Figure 1. On-Region Characteristics T_J = 25°C




Figure 2. On-Region Characteristics T_J = 175°C




Figure 3. On-Resistance vs. Junction Temperature




Figure 4. Normalized On-Resistance vs. Junction Temperature




Figure 5. Transfer Characteristics




Figure 6. Threshold Voltage vs. Junction Temperature

Typical Electrical and Thermal Characteristics *(Continued)*




Figure 7. Body-Diode Characteristics at 25°C




Figure 8. Body-Diode Characteristics at 175°C




Figure 9. Gate-Charge Characteristics




Figure 10. Capacitance Characteristics




Figure 11. Coss stored Energy




Figure 12. Switching Energy vs. Drain Current

Typical Electrical and Thermal Characteristics *(Continued)*




Figure 13. Switching Energy vs. Drain Current




Figure 14. Turn-On Energy and dV/dt vs. External Gate Resistance




Figure 15. Power De-rating (Note I)




Figure 16. Current De-rating (Note I)




Figure 17. Maximum Forward Biased Safe Operating Area for AOK065V120X2 (Note I)

Typical Electrical and Thermal Characteristics *(Continued)*




Figure 18. Normalized Maximum Transient Thermal Impedance for AOK065V120X2 (Note I)

Test Circuits and Waveforms




Figure 19. Gate Charge Test Circuits and Waveforms




Figure 20. Inductive Switching Test Circuit and Waveforms




Figure 21. Unclamped Inductive Switching (UIS) Test Circuit and Waveforms






Figure 22. Diode Recovery Test Circuits and Waveforms

Package Dimensions, TO-247-3L



SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	4.90	5.00	5.10	0.193	0.197	0.201
A1	2.31	2.42	2.52	0.091	0.095	0.099
A2	1.90	2.00	2.10	0.075	0.079	0.083
b	1.16	1.22	1.27	0.046	0.048	0.050
b1	1.96	2.02	2.07	0.078	0.080	0.081
b2	2.00	2.10	2.20	0.079	0.083	0.087
b3	2.96	3.02	3.07	0.117	0.119	0.121
b4	3.00	3.10	3.20	0.118	0.122	0.126
c	0.59	0.62	0.66	0.023	0.024	0.026
D	20.90	21.00	21.10	0.823	0.827	0.831
D1	16.25	16.55	16.85	0.640	0.652	0.663
D2		5.00 TYP			0.197 TYP	
D3	1.05	1.20	1.35	0.041	0.047	0.053
e		5.44 BSC			0.214 BSC	
E	15.70	15.80	15.90	0.618	0.622	0.626
E1	13.06	13.26	13.50	0.514	0.522	0.530
E2		2.50 TYP			0.098 TYP	
L	19.72	19.92	20.12	0.776	0.784	0.792
L1	---	---	4.30	---	---	0.169
Q		6.15 BSC			0.242 BSC	
Q1	5.60	5.80	6.00	0.220	0.228	0.236
ØP	3.55	3.60	3.70	0.140	0.142	0.146

RECOMMENDED LAND PATTERN




UNIT: mm

NOTE
1. PAKCAGE BODY SIZES EXCLUDE MOLD FLASH AND GATE BURRS.
   MOLD FLASH AT THE NON-LEAD SIDES SHOULD BE LESS THAN 6 MILS EACH.
2. CONTROLLING DIMENSION IS MILLIMETER.
   CONVERTED INCH DIMENSIONS ARE NOT NECESSARILY EXACT.

Part Marking

AOK065V120X2
TO-247-3L



LEGAL DISCLAIMER

Applications or uses as critical components in life support devices or systems are not authorized. Alpha and Omega Semiconductor does not assume any liability arising out of such applications or uses of its products. AOS reserves the right to make changes to product specifications without notice. It is the responsibility of the customer to evaluate suitability of the product for their intended application. Customer shall comply with applicable legal requirements, including all applicable export control rules, regulations and limitations.

AOS's products are provided subject to AOS's terms and conditions of sale which are set forth at:
http://www.aosmd.com/terms_and_conditions_of_sale

LIFE SUPPORT POLICY

ALPHA AND OMEGA SEMICONDUCTOR PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.

2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.