ALPHA & OMEGA SEMICONDUCTOR

AOK30B120D2

1200V, 30A Alpha IGBT™ with Diode

General Description

- Latest AlphaIGBT (αIGBT) technology
- Low turn-off switching loss due to fast turn-off time
- Very smooth turn-off current waveforms reduce EMI
- Better thermal management
- High surge current capability
- Minimal gate spike due to high input capacitance

Applications

- Induction Cooking
- Rice Cookers
- Microwave Ovens
- Other soft switching applications


Product Summary

V_{CE}	1200V
I_C (T_C=100°C)	30A
$V_{CE(sat)}$ (T_C=25°C)	1.77V


RoHS Compliant

Top View

TO-247



AOK30B120D2



Orderable Part Number	Package Type	Form	Minimum Order Quantity
AOK30B120D2	TO247	Tube	240

Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	AOK30B120D2	Units
Collector-Emitter Voltage		V_{CE}	1200	V
Gate-Emitter Voltage		V_{GE}	±30	V
Continuous Collector Current	T_C=25°C	I_C	60	A
	T_C=100°C		30	
Pulsed Collector Current, Limited by T_{Jmax}		I_{Cpulse}	120	A
Non repetitive peak collector current[A]		I_{CSM}	200	A
Turn off SOA, $V_{CE} \leqslant$ 600V, Limited by T_{Jmax}		I_{LM}	120	A
Continuous Diode Forward Current	T_C=25°C	I_F	60	A
	T_C=100°C		30	
Diode Pulsed Current, Limited by T_{Jmax}		I_{Fpulse}	120	A
Power Dissipation	T_C=25°C	P_D	340	W
	T_C=100°C		170	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 175	°C
Maximum lead temperature for soldering purpose, 1/8" from case for 5 seconds		T_L	300	°C

Thermal Characteristics

Parameter	Symbol	AOK30B120D2	Units
Maximum Junction-to-Ambient	$R_{\theta JA}$	40	°C/W
Maximum IGBT Junction-to-Case	$R_{\theta JC}$	0.44	°C/W
Maximum Diode Junction-to-Case	$R_{\theta JC}$	1.20	°C/W

Note A: Capacitor charging saturation current limited by T_{jmax}<175°C and t_p<3µs

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions		Min	Typ	Max	Units
STATIC PARAMETERS							
BV_{CES}	Collector-Emitter Breakdown Voltage	I_C=1mA, V_{GE}=0V, T_J=25°C		1200	-	-	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	V_{GE}=15V, I_C=30A	T_J=25°C	-	1.77	2.2	V
			T_J=125°C	-	2.2	-	
			T_J=175°C	-	2.43	-	
V_F	Diode Forward Voltage	V_{GE}=0V, I_C=30A	T_J=25°C	-	1.5	1.8	V
			T_J=125°C	-	1.6	-	
			T_J=175°C	-	1.62	-	
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	V_{CE}=5V, I_C=1mA		-	5.2	-	V
I_{CES}	Zero Gate Voltage Collector Current	V_{CE}=1200V, V_{GE}=0V	T_J=25°C	-	-	10	µA
			T_J=125°C	-	-	800	
			T_J=175°C	-	-	8000	
I_{GES}	Gate-Emitter leakage current	V_{CE}=0V, V_{GE}=±30V		-	-	±100	nA
g_{FS}	Forward Transconductance	V_{CE}=20V, I_C=30A		-	28	-	S
DYNAMIC PARAMETERS							
C_{ies}	Input Capacitance	V_{GE}=0V, V_{CE}=25V, f=1MHz		-	1900	-	pF
C_{oes}	Output Capacitance			-	109	-	pF
C_{res}	Reverse Transfer Capacitance			-	32	-	pF
Q_g	Total Gate Charge	V_{GE}=15V, V_{CE}=960V, I_C=30A		-	67	-	nC
Q_{ge}	Gate to Emitter Charge			-	16	-	nC
Q_{gc}	Gate to Collector Charge			-	32	-	nC
R_g	Gate resistance	V_{GE}=0V, V_{CE}=0V, f=1MHz		-	1.85	-	Ω
SWITCHING PARAMETERS, (Load Inductive, T_J=25°C)							
$t_{D(off)}$	Turn-Off Delay Time	T_J=25°C V_{GE}=15V, V_{CE}=600V, I_C=30A, R_G=10Ω, Parasitic Inductance=150nH		-	115	-	ns
t_f	Turn-Off Fall Time			-	130	-	ns
E_{off}	Turn-Off Energy			-	1.28	-	mJ
SWITCHING PARAMETERS, (Load Inductive, T_J=175°C)							
$t_{D(off)}$	Turn-Off Delay Time	T_J=175°C V_{GE}=15V, V_{CE}=600V, I_C=30A, R_G=10Ω, Parasitic Inductance=150nH		-	140	-	ns
t_f	Turn-Off Fall Time			-	200	-	ns
E_{off}	Turn-Off Energy			-	2.15	-	mJ

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: Output Characteristic (T_j=25°C)




Fig 2: Output Characteristic (T_j=175°C)




Fig 3: Transfer Characteristic




Fig 4: Diode Characteristic




Fig 5: Collector-Emitter Saturation Voltage vs. Junction Temperature




Figure 6: $V_{GE(TH)}$ vs. T_j

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 7: Gate-Charge Characteristics




Fig 8: Capacitance Characteristic




Fig 9: Forward Bias Safe Operating Area
(T_C=25C,V_{GE}=15V)




Fig 10: Power Disspation as a Function of Case




Fig 11: Current De-rating

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 12: Switching Time vs. I_C
(T_j=175°C,V_{GE}=15V,V_{CE}=600V,R_g=10Ω)




Figure 13: Switching Time vs. R_g
(T_j=175°C,V_{GE}=15V,V_{CE}=600V,I_C=30A)




Figure 14: Switching Time vs.T_j
(V_{GE}=15V,V_{CE}=600V,I_C=30A,R_g=10Ω)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 15: Switching Loss vs. I_C
(T_j=175°C,V_{GE}=15V,V_{CE}=600V,R_g=10Ω)




Figure 16: Switching Loss vs. R_g
(T_j=175°C,V_{GE}=15V,V_{CE}=600V,I_C=30A)




Figure 17: Switching Loss vs. T_j
(V_{GE}=15V,V_{CE}=600V,I_C=30A,R_g=10Ω)




Figure 18: Switching Loss vs. V_{CE}
(T_j=175°C,V_{GE}=15V,I_C=30A,R_g=10Ω)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 19: Diode Reverse Leakage Current vs. Junction Temperature




Fig 20: Diode Forward voltage vs. Junction Temperature




Figure 21: Normalized Maximum Transient Thermal Impedance for IGBT






Figure 22: Normalized Maximum Transient Thermal Impedance for Diode


Gate Charge Test Circuit & Waveform



Inductive Switching Test Circuit & Waveforms



Diode Recovery Test Circuit & Waveforms



ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.