AOKS40B65H2AL

650V, 40A AlphaIGBT™

General Description

- Latest AlphaIGBT (αIGBT) Technology
- 650V Breakdown Voltage
- High Efficient Turn-On di/dt Controllability
- Very High Switching Speed
- Low Turn-Off Switching Loss and Softness
- Very Good EMI Behavior

Applications


- PFC Circuits
- Very High Switching Frequency Applications

Product Summary


V_{CE}	650V
I_C (T_C=100°C)	40A
$V_{CE(sat)}$ (T_J=25°C)	2.05V

Green Product

TO-247



AOKS40B65H2AL



Orderable Part Number	Package Type	Form	Minimum Order Quantity
AOKS40B65H2AL	TO247	Tube	240

Absolute Maximum Ratings T_A=25°C unless otherwise noted

Parameter		Symbol	AOKS40B65H2AL	Units
Collector-Emitter Voltage		V_{CE}	650	V
Gate-Emitter Voltage		V_{GE}	±30	V
Continuous Collector Current	T_C=25°C	I_C	80	A
	T_C=100°C		40	
Pulsed Collector Current, Limited by T_{Jmax}		I_{CM}	120	A
Turn off SOA, V_{CE}≤650V, Limited by T_{Jmax}		I_{LM}	60	A
Power Dissipation	T_C=25°C	P_D	260	W
	T_C=100°C		105	
Junction and Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C
Maximum lead temperature for soldering purpose, 1/8" from case for 5 seconds		T_L	300	°C

Thermal Characteristics

Parameter	Symbol	AOKS40B65H2AL	Units
Maximum Junction-to-Ambient	$R_{\theta JA}$	40	°C/W
Maximum IGBT Junction-to-Case	$R_{\theta JC}$	0.48	°C/W

Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions		Min	Typ	Max	Units
STATIC PARAMETERS							
BV_{CES}	Collector-Emitter Breakdown Voltage	I_C=1mA, V_{GE}=0V, T_J=25°C		650	-	-	V
$V_{CE(sat)}$	Collector-Emitter Saturation Voltage	V_{GE}=15V, I_C=40A	T_J=25°C	-	2.05	2.6	V
			T_J=125°C	-	2.57	-	
			T_J=150°C	-	2.71	-	
$V_{GE(th)}$	Gate-Emitter Threshold Voltage	V_{CE}=5V, I_C=1mA		-	4.7	-	V
I_{CES}	Zero Gate Voltage Collector Current	V_{CE}=650V, V_{GE}=0V	T_J=25°C	-	-	10	µA
			T_J=125°C	-	-	500	
			T_J=150°C	-	-	5000	
I_{GES}	Gate-Emitter leakage current	V_{CE}=0V, V_{GE}=±30V		-	-	±100	nA
g_{FS}	Forward Transconductance	V_{CE}=20V, I_C=40A		-	24	-	S
DYNAMIC PARAMETERS							
C_{ies}	Input Capacitance	V_{GE}=0V, V_{CC}=25V, f=1MHz		-	1275	-	pF
C_{oes}	Output Capacitance			-	88	-	pF
C_{res}	Reverse Transfer Capacitance			-	44	-	pF
Q_g	Total Gate Charge	V_{GE}=15V, V_{CC}=520V, I_C=40A		-	61	-	nC
Q_{ge}	Gate to Emitter Charge			-	18	-	nC
Q_{gc}	Gate to Collector Charge			-	27	-	nC
R_g	Gate resistance	V_{GE}=0V, V_{CC}=0V, f=1MHz		-	11	-	Ω
SWITCHING PARAMETERS, (Load Inductive, T_J=25°C)							
$T_{d(on)}$	Turn-On DelayTime	T_J=25°C V_{GE}=15V, V_{CC}=400V, I_C=40A, R_G=7.5Ω Eon and Etotal include diode (AOK40B65H2AL) reverse recovery		-	30	-	ns
T_r	Turn-On Rise Time			-	30	-	ns
$T_{d(off)}$	Turn-Off Delay Time			-	117	-	ns
T_f	Turn-Off Fall Time			-	16	-	ns
E_{on}	Turn-On Energy			-	1.17	-	mJ
E_{off}	Turn-Off Energy			-	0.54	-	mJ
E_{total}	Total Switching Energy			-	1.71	-	mJ
SWITCHING PARAMETERS, (Load Inductive, T_J=150°C)							
$T_{d(on)}$	Turn-On DelayTime	T_J=150°C V_{GE}=15V, V_{CC}=400V, I_C=40A, R_G=7.5Ω Eon and Etotal include diode (AOK40B65H2AL) reverse recovery		-	29	-	ns
T_r	Turn-On Rise Time			-	35	-	ns
$T_{d(off)}$	Turn-Off Delay Time			-	133	-	ns
T_f	Turn-Off Fall Time			-	18	-	ns
E_{on}	Turn-On Energy			-	1.27	-	mJ
E_{off}	Turn-Off Energy			-	0.78	-	mJ
E_{total}	Total Switching Energy			-	2.06	-	mJ

APPLICATIONS OR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN,FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 1: Output Characteristic (T_j=25°C)




Figure 2: Output Characteristic (T_j=150°C)




Figure 3: Transfer Characteristic




Figure 4: Collector-Emitter Saturation Voltage vs. Junction Temperature




Figure 5: $V_{GE(TH)}$ vs. T_j

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 6: Gate-Charge Characteristics




Figure 7: Capacitance Characteristic




Figure 8: Forward Bias Safe Operating Area
(T_C=25°C, V_{GE}=15V)




Figure 9: Power Disspation as a Function of Case




Figure 10: Current De-rating




Figure 11: Switching Time vs.T_J
(V_{GE}=15V, V_{CE}=400V, I_C=40A, R_g=7.5Ω)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 12: Switching Time vs. I_C
(T_j=150°C, V_{GE}=15V, V_{CE}=400V, R_g=7.5Ω)




Figure 13: Switching Time vs. R_g
(T_j=150°C, V_{GE}=15V, V_{CE}=400V, I_C=40A)




Figure 14: Switching Loss vs. I_C
(T_j=150°C, V_{GE}=15V, V_{CE}=400V, R_g=7.5Ω)




Figure 15: Switching Loss vs. R_g
(T_j=150°C, V_{GE}=15V, V_{CE}=400V, I_C=40A)




Figure 16: Switching Loss vs. T_j
(V_{GE}=15V, V_{CE}=400V, I_C=40A, R_g=7.5Ω)




Figure 17: Switching Loss vs. V_{CE}
(T_j=150°C, V_{GE}=15V, I_C=40A, R_g=7.5Ω)

TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 18: Normalized Maximum Transient Thermal Impedance for IGBT




Figure A: Gate Charge Test Circuit & Waveforms




Figure B: Inductive Switching Test Circuit & Waveforms

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.