1A LOW NOISE CMOS LDO REGULATOR WITH ENABLE AP2114

General Description

The AP2114 is CMOS process low dropout linear regulator with enable function, the regulator delivers a guaranteed 1A (Min) continuous load current.

The AP2114 features low power consumption.

The AP2114 is available in 1.2V, 1.5V, 1.8V, 2.5V and 3.3V regulator output and 0.8V to 5V adjustable output, and available in excellent output accuracy ±1.5%, it is also available in an excellent load regulation and line regulation performance.

The AP2114 is available in standard packages of SOT-223, TO-252-2 (1), TO-252-2 (3), TO-252-2 (4), TO-263-3, SOIC-8 and PSOP-8.

Features

- Output Voltage Accuracy: ±1.5%
- Output Current: 1A (Min)
- Fold-back Short Current Protection: 50mA
- Low Dropout Voltage (3.3V): 450mV (Typ) @I_{OUT}=1A
- Stable with 4.7μF Flexible Cap: Ceramic, Tantalum and Aluminum Electrolytic
- Excellent Line Regulation: 0.02%/V (Typ), 0.1%/V (Max) @ I_{OUT}=30mA
- Excellent Load Regulation: 0.2%A (Typ) @ I_{OUT}=1mA to 1A
- Low Quiescent Current: 60μA (1.2V/1.5V/1.8V /2.5V/ADJ)
- Low Output Noise: 30μV_{RMS}
- PSRR: 68dB @ Freq=1KHz (1.2V/1.5V/1.8V /ADJ)
- OTSD Protection
- Operating Temperature Range: -40°C to 85°C
- ESD: MM 400V, HBM 4000V

Applications

- LCD Monitor
- LCD TV
- STB



Figure 1. Package Types of AP2114

Pin Configuration



Figure 2. Pin Configuration of AP2114 (Top View)

Pin Descriptions

Pin Number				Pin Name	Function
SOT-223 (H), TO-263-3, TO-252-2 (1) (D) TO-252-2 (3) (D) TO-252-2 (4) (D)	SOT-223 (HA), TO-252-2 (1) (DA) TO-252-2 (3) (DA) TO-252-2 (4) (DA)	SOIC-8, PSOP-8 (Fixed)	SOIC-8, PSOP-8 (ADJ)		
1	2	1, 3, 5, 6, 7	2, 3, 5, 7	GND	Ground
2	3	2	8	VOUT	Regulated Output
3	1	4	1	VIN	Input Voltage Pin
		8	4	EN	Chip Enable, H–Normal Work, L– Shutdown Output
			6	ADJ	Adjust Output

Functional Block Diagram



A(B){C}
A: SOT-223(H), TO-263-3, TO-252-2(1)/(3)/(4)(D)
B: SOIC-8, PSOP-8
C: SOT-223(HA), TO-252-2(1)/(3)/(4)(DA)

For Fixed Versions

Functional Block Diagram (Continued)



For ADJ Version

Figure 3. Functional Block Diagram of AP2114

1A LOW NOISE CMOS LDO REGULATOR WITH ENABLE AP2114

Ordering Information



Package	Temperature Range	Output Voltage	Part Number	Marking ID	Packing Type
SOT-223	-40 to 85°C	1.2V (H)	AP2114H-1.2TRG1	GH12C	Tape & Reel
		1.5V (H)	AP2114H-1.5TRG1	GH16G	Tape & Reel
		1.8V (H)	AP2114H-1.8TRG1	GH12D	Tape & Reel
		2.5V (H)	AP2114H-2.5TRG1	GH14C	Tape & Reel
		3.3V (H)	AP2114H-3.3TRG1	GH12E	Tape & Reel
SOT-223	-40 to 85°C	1.2V (HA)	AP2114HA-1.2TRG1	GH13B	Tape & Reel
		1.5V (HA)	AP2114HA-1.5TRG1	GH16H	Tape & Reel
		1.8V (HA)	AP2114HA-1.8TRG1	GH14D	Tape & Reel
		2.5V (HA)	AP2114HA-2.5TRG1	GH14E	Tape & Reel
		3.3V (HA)	AP2114HA-3.3TRG1	GH14F	Tape & Reel
TO-252-2 (1)/ TO-252-2 (3)/ TO-252-2 (4)	-40 to 85°C	1.2V (D)	AP2114D-1.2TRG1	AP2114D-1.2G1	Tape & Reel
		1.5V (D)	AP2114D-1.5TRG1	AP2114D-1.5G1	Tape & Reel
		1.8V (D)	AP2114D-1.8TRG1	AP2114D-1.8G1	Tape & Reel
		2.5V (D)	AP2114D-2.5TRG1	AP2114D-2.5G1	Tape & Reel
		3.3V (D)	AP2114D-3.3TRG1	AP2114D-3.3G1	Tape & Reel
TO-252-2 (1)/ TO-252-2 (3)/ TO-252-2 (4)	-40 to 85°C	1.2V (DA)	AP2114DA-1.2TRG1	AP2114DA-1.2G1	Tape & Reel
		1.5V (DA)	AP2114DA-1.5TRG1	AP2114DA-1.5G1	Tape & Reel
		1.8V (DA)	AP2114DA-1.8TRG1	AP2114DA-1.8G1	Tape & Reel
		2.5V (DA)	AP2114DA-2.5TRG1	AP2114DA-2.5G1	Tape & Reel
		3.3V (DA)	AP2114DA-3.3TRG1	AP2114DA-3.3G1	Tape & Reel
TO-263-3	-40 to 85°C	1.2V	AP2114S-1.2TRG1	AP2114S-1.2G1	Tape & Reel
		1.5V	AP2114S-1.5TRG1	AP2114S-1.5G1	Tape & Reel
		1.8V	AP2114S-1.8TRG1	AP2114S-1.8G1	Tape & Reel
		2.5V	AP2114S-2.5TRG1	AP2114S-2.5G1	Tape & Reel
		3.3V	AP2114S-3.3TRG1	AP2114S-3.3G1	Tape & Reel
SOIC-8	-40 to 85°C	1.2V	AP2114M-1.2TRG1	2114M-1.2G1	Tape & Reel
		1.5V	AP2114M-1.5TRG1	2114M-1.5G1	Tape & Reel
		1.8V	AP2114M-1.8TRG1	2114M-1.8G1	Tape & Reel
		2.5V	AP2114M-2.5TRG1	2114M-2.5G1	Tape & Reel
		3.3V	AP2114M-3.3TRG1	2114M-3.3G1	Tape & Reel
		ADJ	AP2114M-ADJG1	2114M-ADJG1	Tube
			AP2114M-ADJTRG1	2114M-ADJG1	Tape & Reel

Ordering Information (Continued)

Package	Temperature Range	Output Voltage	Part Number	Marking ID	Packing Type
PSOP-8	-40 to 85°C	1.2V	AP2114MP-1.2TRG1	2114MP-1.2G1	Tape & Reel
		1.5V	AP2114MP-1.5TRG1	2114MP-1.5G1	Tape & Reel
		1.8V	AP2114MP-1.8TRG1	2114MP-1.8G1	Tape & Reel
		2.5V	AP2114MP-2.5TRG1	2114MP-2.5G1	Tape & Reel
		3.3V	AP2114MP-3.3TRG1	2114MP-3.3G1	Tape & Reel
		ADJ	AP2114MP-ADJG1	2114MP-ADJG1	Tube
			AP2114MP-ADJTRG1	2114MP-ADJG1	Tape & Reel

BCD Semiconductor's Pb-free products, as designated with "G1" suffix in the part number, are RoHS compliant and Green.

Absolute Maximum Ratings (Note 1)

Parameter	Symbol	Value		Unit
Power Supply Voltage	V_{IN}	6.5		V
Operating Junction Temperature Range	T_J	150		ºC
Storage Temperature Range	T_{STG}	-65 to 150		ºC
Lead Temperature (Soldering, 10sec)	T_{LEAD}	260		ºC
Thermal Resistance （Junction to Ambient）(No Heatsink)	θ_{JA}	SOIC-8	144	°C/W
		PSOP-8	143	
		SOT-223	128	
		TO-252-2 (1)/ TO-252-2 (3)/ TO-252-2 (4)	90	
		TO-263-3	73	
ESD (Machine Model)		400		V
ESD (Human Body Model)		4000		V

Note 1: Stresses greater than those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “Recommended Operating Conditions” is not implied. Exposure to “Absolute Maximum Ratings” for extended periods may affect device reliability.

Recommended Operating Conditions

Parameter	Symbol	Min	Max	Unit
Supply Voltage	V_{IN}	2.5	6.0	V
Operating Ambient Temperature Range	T_A	-40	85	°C

Electrical Characteristics

AP2114-1.2 Electrical Characteristics (Note 2)

(V_{IN}=2.5V, C_{IN}=4.7μF (Ceramic), C_{OUT}=4.7μF (Ceramic), Typical T_A= 25°C, **Bold** typeface applies over -40°C≤T_A≤85°C ranges, unless otherwise specified (Note 3))

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Output Voltage	V_{OUT}	V_{IN} =2.5V, 1mA ≤ I_{OUT} ≤ 30mA		V_{OUT} ×98.5%	1.2	V_{OUT} ×101.5%	V
Input Voltage	V_{IN}					6.0	V
Maximum Output Current	$I_{OUT(MAX)}$	V_{IN}=2.5V, V_{OUT}=1.182V to 1.218V		1			A
Load Regulation	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle I_{OUT}}$	V_{IN}=2.5V, 1mA ≤ I_{OUT} ≤1A			0.2	1	%/A
Line Regulation	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle V_{IN}}$	2.5V≤V_{IN}≤6V, I_{OUT}=30mA		-0.1	0.02	0.1	%/V
Dropout Voltage	V_{DROP}	I_{OUT}=1.0A			1200	1300	mV
Quiescent Current	I_Q	V_{IN}=2.5V, I_{OUT}=0mA			60	75	μA
Power Supply Rejection Ratio	PSRR	Ripple 1Vp-p V_{IN}=2.5V, I_{OUT}=100mA	f=100Hz		68		dB
			f=1KHz		68		
Output Voltage Temperature Coefficient	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle T}$	I_{OUT}=30mA, T_A =-40°C to 85°C			**±30**		ppm/°C
Short Current Limit	I_{SHORT}	V_{OUT}=0V			50		mA
RMS Output Noise	V_{NOISE}	10Hz ≤ f ≤100kHz (No Load)			30		μV_{RMS}
V_{EN} High Voltage	V_{IH}	Enable logic high, regulator on		1.5			V
V_{EN} Low Voltage	V_{IL}	Enable logic low, regulator off				0.4	
Standby Current	I_{STD}	V_{IN}=2.5V, V_{EN} in OFF mode			0.01	1.0	μA
Start-up Time	t_S	No Load			20		μs
EN Pull Down Resistor	R_{PD}				3.0		MΩ
V_{OUT} Discharge Resistor	R_{DCHG}	Set EN pin at Low			60		Ω
Thermal Shutdown Temperature	T_{OTSD}				160		°C
Thermal Shutdown Hysteresis	T_{HYOTSD}				25		
Thermal Resistance (Junction to Case)	θ_{JC}	SOIC-8			74.6		°C/W
		PSOP-8			43.7		
		SOT-223			50.9		
		TO-252-2 (1) /(3) /(4)			35		
		TO-263-3			22		

Note 2: To prevent the Short Circuit Current protection feature from being prematurely activated, the input voltage must be applied before a current source load is applied.
Note 3: Production testing at T_A=25°C. Over temperature specifications guaranteed by design only.

Electrical Characteristics (Continued)

AP2114-1.5 Electrical Characteristics (Note 2)

(V_{IN}=2.5V, C_{IN}=4.7μF (Ceramic), C_{OUT}=4.7μF (Ceramic), Typical T_A= 25°C, **Bold** typeface applies over -40°C≤T_A≤85°C ranges, unless otherwise specified (Note 3))

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Output Voltage	V_{OUT}	V_{IN} =2.5V, 1mA ≤ I_{OUT} ≤ 30mA	V_{OUT} ×98.5%	1.5	V_{OUT} ×101.5%	V
Input Voltage	V_{IN}				6.0	V
Maximum Output Current	$I_{OUT(MAX)}$	V_{IN}=2.5V, V_{OUT}=1.478V to 1.523V	1			A
Load Regulation	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle I_{OUT}}$	V_{IN}=2.5V, 1mA ≤ I_{OUT} ≤1A		0.2	1	%/A
Line Regulation	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle V_{IN}}$	2.5V≤V_{IN}≤6V, I_{OUT}=30mA	-0.1	0.02	0.1	%/V
Dropout Voltage	V_{DROP}	I_{OUT}=1.0A		800	1000	mV
Quiescent Current	I_Q	V_{IN}=2.5V, I_{OUT}=0mA		60	75	μA
Power Supply Rejection Ratio	PSRR	Ripple 1Vp-p, V_{IN}=2.5V, I_{OUT}=100mA, f=100Hz		68		dB
		Ripple 1Vp-p, V_{IN}=2.5V, I_{OUT}=100mA, f=1KHz		68		dB
Output Voltage Temperature Coefficient	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle T}$	I_{OUT}=30mA, T_A =-40°C to 85°C		**±30**		ppm/°C
Short Current Limit	I_{SHORT}	V_{OUT}=0V		50		mA
RMS Output Noise	V_{NOISE}	10Hz ≤ f ≤100kHz (No Load)		30		μV_{RMS}
V_{EN} High Voltage	V_{IH}	Enable logic high, regulator on	1.5			V
V_{EN} Low Voltage	V_{IL}	Enable logic low, regulator off			0.4	V
Standby Current	I_{STD}	V_{IN}=2.5V, V_{EN} in OFF mode		0.01	1.0	μA
Start-up Time	t_S	No Load		20		μs
EN Pull Down Resistor	R_{PD}			3.0		MΩ
V_{OUT} Discharge Resistor	R_{DCHG}	Set EN pin at Low		60		Ω
Thermal Shutdown Temperature	T_{OTSD}			160		°C
Thermal Shutdown Hysteresis	T_{HYOTSD}			25		°C
Thermal Resistance (Junction to Case)	θ_{JC}	SOIC-8		74.6		°C/W
		PSOP-8		43.7		°C/W
		SOT-223		50.9		°C/W
		TO-252-2 (1) /(3) /(4)		35		°C/W
		TO-263-3		22		°C/W

Note 2: To prevent the Short Circuit Current protection feature from being prematurely activated, the input voltage must be applied before a current source load is applied.
Note 3: Production testing at T_A=25°C. Over temperature specifications guaranteed by design only.

Electrical Characteristics (Continued)

AP2114-1.8 Electrical Characteristics (Note 2)

(V_{IN}=2.8V, C_{IN}=4.7μF (Ceramic), C_{OUT}=4.7μF (Ceramic), Typical T_A= 25°C, **Bold** typeface applies over -40°C≤T_A≤85°C ranges, unless otherwise specified (Note 3))

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Output Voltage	V_{OUT}	V_{IN}=2.8V, 1mA ≤ I_{OUT} ≤ 30mA		V_{OUT} ×98.5%	1.8	V_{OUT} ×101.5%	V
Maximum Output Current	$I_{OUT(MAX)}$	V_{IN}=2.8V, V_{OUT}=1.773V to 1.827V		1.0			A
Load Regulation	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle I_{OUT}}$	V_{IN}=2.8V, 1mA ≤ I_{OUT} ≤1A			0.2	1.0	%/A
Line Regulation	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle V_{IN}}$	2.8V≤V_{IN}≤6V, I_{OUT}=30mA		-0.1	0.02	0.1	%/V
Dropout Voltage	V_{DROP}	I_{OUT}=1.0A			500	700	mV
Quiescent Current	I_Q	V_{IN}=2.8V, I_{OUT}=0mA			60	75	μA
Power Supply Rejection Ratio	PSRR	Ripple 1Vp-p V_{IN}=2.8V, I_{OUT}=100mA	f=100Hz		68		dB
			f=1KHz		68		
Output Voltage Temperature Coefficient	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle T}$	I_{OUT}=30mA, T_A =-40°C to 85°C			**±30**		ppm/°C
Short Current Limit	I_{SHORT}	V_{OUT}=0V			50		mA
RMS Output Noise	V_{NOISE}	10Hz ≤ f ≤100kHz (No load)			30		μV_{RMS}
V_{EN} High Voltage	V_{IH}	Enable logic high, regulator on		1.5			V
V_{EN} Low Voltage	V_{IL}	Enable logic low, regulator off				0.4	
Standby Current	I_{STD}	V_{IN}=2.8V, V_{EN} in OFF mode			0.01	1.0	μA
Start-up Time	t_S	No Load			20		μs
EN Pull Down Resistor	R_{PD}				3.0		MΩ
V_{OUT} Discharge Resistor	R_{DCHG}	Set EN pin at Low			60		Ω
Thermal Shutdown Temperature	T_{OTSD}				160		°C
Thermal Shutdown Hysteresis	T_{HYOTSD}				25		
Thermal Resistance (Junction to Case)	θ_{JC}	SOIC-8			74.6		°C /W
		PSOP-8			43.7		
		SOT-223			50.9		
		TO-252-2 (1) /(3) /(4)			35		
		TO-263-3			22		

Note 2: To prevent the Short Circuit Current protection feature from being prematurely activated, the input voltage must be applied before a current source load is applied.
Note 3: Production testing at T_A=25°C. Over temperature specifications guaranteed by design only.

Electrical Characteristics (Continued)

AP2114-2.5 Electrical Characteristics (Note 2)

(V_{IN}=3.5V, C_{IN}=4.7μF (Ceramic), C_{OUT}=4.7μF (Ceramic), Typical T_A= 25°C, **Bold** typeface applies over -40°C≤T_A≤85°C ranges, unless otherwise specified (Note 3))

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Output Voltage	V_{OUT}	V_{IN}=3.5V, 1mA ≤ I_{OUT} ≤ 30mA		V_{OUT} ×98.5%	2.5	V_{OUT} ×101.5%	V
Maximum Output Current	$I_{OUT(MAX)}$	V_{IN}=3.5V, V_{OUT}=2.463V to 2.537V		1.0			A
Load Regulation	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle I_{OUT}}$	Vout=2.5V, V_{IN}=Vout+1V 1mA ≤ I_{OUT} ≤1A			0.2	1.0	%/A
Line Regulation	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle V_{IN}}$	3.5V≤V_{IN}≤6V, I_{OUT}=30mA		-0.1	0.02	0.1	%/V
Dropout Voltage	V_{DROP}	I_{OUT} =1A			450	750	mV
Quiescent Current	I_Q	V_{IN}=3.5V, I_{OUT}=0mA			60	80	μA
Power Supply Rejection Ratio	PSRR	Ripple 1Vp-p V_{IN}=3.5V, I_{OUT}=100mA	f=100Hz		65		dB
			f=1KHz		65		
Output Voltage Temperature Coefficient	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle T}$	I_{OUT}=30mA			**±30**		ppm/°C
Short Current Limit	I_{SHORT}	V_{OUT}=0V			50		mA
RMS Output Noise	V_{NOISE}	10Hz ≤ f ≤100kHz			30		μV_{RMS}
V_{EN} High Voltage	V_{IH}	Enable logic high, regulator on		1.5			V
V_{EN} Low Voltage	V_{IL}	Enable logic low, regulator off				0.4	
Standby Current	I_{STD}	V_{IN}=3.5V, V_{EN} in OFF mode			0.01	1.0	μA
Start-up Time	t_S	No Load			20		μs
EN Pull Down Resistor	R_{PD}				3.0		MΩ
V_{OUT} Discharge Resistor	R_{DCHG}	Set EN pin at Low			60		Ω
Thermal Shutdown Temperature	T_{OTSD}				160		°C
Thermal Shutdown Hysteresis	T_{HYOTSD}				25		
Thermal Resistance (Junction to Case)	θ_{JC}	SOIC-8			74.6		°C /W
		PSOP-8			43.7		
		SOT-223			50.9		
		TO-252-2 (1) /(3) /(4)			35		
		TO-263-3			22		

Note 2: To prevent the Short Circuit Current protection feature from being prematurely activated, the input voltage must be applied before a current source load is applied.
Note 3: Production testing at T_A=25°C. Over temperature specifications guaranteed by design only.

Electrical Characteristics (Continued)

AP2114-3.3 Electrical Characteristics (Note 2)

(V_{IN}=4.3V, C_{IN}=4.7μF (Ceramic), C_{OUT}=4.7μF (Ceramic), Typical T_A= 25°C, **Bold** typeface applies over -40°C≤T_A≤85°C ranges, unless otherwise specified (Note 3))

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Output Voltage	V_{OUT}	V_{IN}=4.3V, 1mA ≤ I_{OUT} ≤ 30mA		V_{OUT} ×98.5%	3.3	V_{OUT} ×101.5%	V
Maximum Output Current	$I_{OUT(MAX)}$	V_{IN} =4.3V, V_{OUT}=3.25V to 3.35V		1.0			A
Load Regulation	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle I_{OUT}}$	V_{IN}=4.3V, 1mA ≤ I_{OUT} ≤1A			0.2	1.0	%/A
Line Regulation	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle V_{IN}}$	4.3V≤V_{IN}≤6V, I_{OUT}=30mA		-0.1	0.02	0.1	%/V
Dropout Voltage	V_{DROP}	I_{OUT}=1A			450	750	mV
Quiescent Current	I_Q	V_{IN}=4.3V, I_{OUT}=0mA			65	90	μA
Power Supply Rejection Ratio	PSRR	Ripple 1Vp-p V_{IN}=4.3V, I_{OUT}=100mA	f=100Hz		65		dB
			f=1KHz		65		
Output Voltage Temperature Coefficient	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle T}$	I_{OUT}=30mA			**±30**		ppm/°C
Short Current Limit	I_{SHORT}	V_{OUT}=0V			50		mA
RMS Output Noise	V_{NOISE}	10Hz ≤ f ≤100kHz (No load)			30		μV_{RMS}
V_{EN} High Voltage	V_{IH}	Enable logic high, regulator on		1.5			V
V_{EN} Low Voltage	V_{IL}	Enable logic low, regulator off				0.4	
Standby Current	I_{STD}	V_{IN}=4.3V, V_{EN} in OFF mode			0.01	1.0	μA
Start-up Time	t_S	No Load			20		μs
EN Pull Down Resistor	R_{PD}				3.0		MΩ
V_{OUT} Discharge Resistor	R_{DCHG}	Set EN pin at Low			60		Ω
Thermal Shutdown Temperature	T_{OTSD}				160		°C
Thermal Shutdown Hysteresis	T_{HYOTSD}				25		
Thermal Resistance (Junction to Case)	θ_{JC}	SOIC-8			74.6		°C/W
		PSOP-8			43.7		
		SOT-223			50.9		
		TO-252-2 (1) /(3) /(4)			35		
		TO-263-3			22		

Note 2: To prevent the Short Circuit Current protection feature from being prematurely activated, the input voltage must be applied before a current source load is applied.
Note 3: Production testing at T_A=25°C. Over temperature specifications guaranteed by design only.

Electrical Characteristics (Continued)

AP2114-ADJ Electrical Characteristics (Note 2)

(V_{IN}=2.5V, C_{IN}=4.7μF (Ceramic), C_{OUT}=4.7μF (Ceramic), Typical T_A= 25°C, **Bold** typeface applies over -40°C≤T_A≤85°C ranges, unless otherwise specified (Note 3))

Parameter	Symbol	Test Conditions		Min	Typ	Max	Unit
Reference Voltage	V_{REF}	V_{IN}=2.5V, 1mA ≤ I_{OUT} ≤ 30mA		V_{REF} ×98.5%	0.8	V_{REF} ×101.5%	V
Input Voltage	V_{IN}					6.0	V
Maximum Output Current	$I_{OUT(MAX)}$	V_{IN}=2.5V, V_{OUT}= 0.788V to 0.812V		1			A
Load Regulation	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle I_{OUT}}$	V_{IN}=2.5V, 1mA ≤ I_{OUT} ≤1A			0.2	1	%/A
Line Regulation	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle V_{IN}}$	2.5V≤V_{IN}≤6V, I_{OUT}=30mA		-0.1	0.02	0.1	%/V
Quiescent Current	I_Q	V_{IN}=2.5V, I_{OUT}=0mA			60	75	μA
Power Supply Rejection Ratio	PSRR	Ripple 1Vp-p V_{IN}=2.5V, I_{OUT}=100mA	f=100Hz		68		dB
			f=1KHz		68		
Output Voltage Temperature Coefficient	$\frac{\triangle V_{OUT}/V_{OUT}}{\triangle T}$	I_{OUT}=30mA, T_A =-40°C to 85°C			**±30**		ppm/°C
Short Current Limit	I_{SHORT}	V_{OUT}=0V			50		mA
RMS Output Noise	V_{NOISE}	10Hz ≤ f ≤100kHz (No Load)			30		μV_{RMS}
V_{EN} High Voltage	V_{IH}	Enable logic high, regulator on		1.5			V
V_{EN} Low Voltage	V_{IL}	Enable logic low, regulator off				0.4	
Standby Current	I_{STD}	V_{IN}=2.5V, V_{EN} in OFF mode			0.01	1.0	μA
Start-up Time	t_S	No Load			20		μs
EN Pull Down Resistor	R_{PD}				3.0		MΩ
V_{OUT} Discharge Resistor	R_{DCHG}	Set EN pin at Low			60		Ω
Thermal Shutdown Temperature	T_{OTSD}				160		°C
Thermal Shutdown Hysteresis	T_{HYOTSD}				25		
Thermal Resistance (Junction to Case)	θ_{JC}	SOIC-8			74.6		°C/W
		PSOP-8			43.7		

Note 2: To prevent the Short Circuit Current protection feature from being prematurely activated, the input voltage must be applied before a current source load is applied.
Note 3: Production testing at T_A=25°C. Over temperature specifications guaranteed by design only.

Typical Performance Characteristics



Figure 4. Ground Current vs. Output Current



Figure 5. Ground Current vs. Output Current



Figure 6. Ground Current vs. Output Current



Figure 7. Ground Current vs. Output Current

Typical Performance Characteristics (Continued)



Figure 8. Quiescent Current vs. Temperature



Figure 9. Quiescent Current vs. Temperature



Figure 10. Quiescent Current vs. Temperature



Figure 11. Quiescent Current vs. Temperature

Typical Performance Characteristics (Continued)



Figure 12. Quiescent Current vs. Input Voltage



Figure 13. Quiescent Current vs. Input Voltage



Figure 14. Quiescent Current vs. Input Voltage



Figure 15. Quiescent Current vs. Input Voltage

Typical Performance Characteristics (Continued)



Figure 16. Output Voltage vs. Temperature



Figure 17. Output Voltage vs. Temperature



Figure 18. Output Voltage vs. Temperature



Figure 19. Output Voltage vs. Temperature

Typical Performance Characteristics (Continued)



Figure 20. Output Voltage vs. Input Voltage



Figure 21. Output Voltage vs. Input Voltage



Figure 22. Output Voltage vs. Input Voltage



Figure 23. Output Voltage vs. Input Voltage

Typical Performance Characteristics (Continued)



Figure 24. Output Voltage vs. Output Current



Figure 25. Output Voltage vs. Output Current



Figure 26. Output Voltage vs. Output Current



Figure 27. Output Voltage vs. Output Current

Typical Performance Characteristics (Continued)



Figure 28. Output Voltage vs. Output Current



Figure 29. Output Voltage vs. Output Current



Figure 30. Dropout Voltage vs. Output Current



Figure 31. Dropout Voltage vs. Output Current

Typical Performance Characteristics (Continued)



Figure 32. Dropout Voltage vs. Output Current



Figure 33. Max. Output Current vs. Input Voltage



Figure 34. Max. Output Current vs. Input Voltage



Figure 35. Max. Output Current vs. Input Voltage

Typical Performance Characteristics (Continued)



Figure 36. Max. Output Current vs. Input Voltage



Figure 37. Max. Output Current vs. Input Voltage

Note 4: Considering power dissipation and thermal behavior, we suggest provide enough design margins in application design which are no less than 30% at least.



Figure 38. Output Short Current vs. Temperature



Figure 39. Output Short Current vs. Temperature

Typical Performance Characteristics (Continued)



Figure 40. Output Short Current vs. Temperature



Figure 41. Output Short Current vs. Temperature



Figure 42. PSRR vs. Frequency



Figure 43. PSRR vs. Frequency

Typical Performance Characteristics (Continued)



Figure 44. PSRR vs. Frequency



Figure 45. PSRR vs. Frequency



Figure 46. Load Transient

Typical Application





Figure 47. Typical Application of AP2114

Mechanical Dimensions

SOT-223 **Unit: mm(inch)**



Mechanical Dimensions (Continued)

TO-252-2 (1) **Unit: mm(inch)**



Mechanical Dimensions (Continued)

TO-252-2 (3) **Unit: mm(inch)**



Mechanical Dimensions (Continued)

TO-252-2 (4) **Unit: mm(inch)**



Mechanical Dimensions (Continued)

TO-263-3 **Unit: mm(inch)**



Mechanical Dimensions (Continued)

SOIC-8 **Unit: mm(inch)**



Note: Eject hole, oriented hole and mold mark is optional.

Mechanical Dimensions (Continued)

PSOP-8 **Unit: mm(inch)**



Note: Eject hole, oriented hole and mold mark is optional.



BCD Semiconductor Manufacturing Limited

http://www.bcdsemi.com

IMPORTANT NOTICE

BCD Semiconductor Manufacturing Limited reserves the right to make changes without further notice to any products or specifications herein. BCD Semiconductor Manufacturing Limited does not assume any responsibility for use of any its products for any particular purpose, nor does BCD Semiconductor Manufacturing Limited assume any liability arising out of the application or use of any its products or circuits. BCD Semiconductor Manufacturing Limited does not convey any license under its patent rights or other rights nor the rights of others.

MAIN SITE

- Headquarters
BCD Semiconductor Manufacturing Limited
No. 1600, Zi Xing Road, Shanghai ZiZhu Science-based Industrial Park, 200241, China
Tel: +86-21-24162266, Fax: +86-21-24162277

- Wafer Fab
Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd.
800 Yi Shan Road, Shanghai 200233, China
Tel: +86-21-6485 1491, Fax: +86-21-5450 0008

REGIONAL SALES OFFICE

Shenzhen Office
Shanghai SIM-BCD Semiconductor Manufacturing Co., Ltd., Shenzhen Office
Unit A Room 1203, Skyworth Bldg., Gaoxin Ave.1.S., Nanshan District, Shenzhen, China
Tel: +86-755-8826 7951
Fax: +86-755-8826 7865

Taiwan Office
BCD Semiconductor (Taiwan) Company Limited
4F, 298-1, Rui Guang Road, Nei-Hu District, Taipei, Taiwan
Tel: +886-2-2656 2808
Fax: +886-2-2656 2806

USA Office
BCD Semiconductor Corp.
30920 Huntwood Ave. Hayward, CA 94544, USA
Tel : +1-510-324-2988
Fax: +1-510-324-2788

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.