PEAK 3A CMOS LDO REGULATOR WITH ENABLE AND POWER-GOOD

Description

The AP2132A is a positive voltage regulator IC fabricated by CMOS process. The IC consists of a voltage reference, an error amplifier, a power transistor, a resistor network for setting output voltage, a current-limit circuit for current protection, and a chip-enable circuit.

The AP2132A has features of large current, low-dropout voltage, high output-voltage accuracy and low input voltage. The AP2132A provides a power-good (PG) signal to indicate if the voltage level of V_{OUT} reaches 92% of its rating value. And it operates with a V_{IN} as low as 1.4V and V_{CTRL} voltage 5V with output voltage programmable as low as 0.6V.

The AP2132A is available in 1.8V fixed output voltage version and adjustable output voltage version. The fixed version integrates the adjust resistors. It is also available in an adjustable version, which can set the output voltage with external resistor. If the pin of adjustable output voltage is to ground, it will switch to fixed output voltage.

The AP2132A is available in the PSOP-8 package.

Features

- Adjustable Output: 0.6V to 3.0V
- Low-Dropout Voltage: 300mV at I_{OUT} = 2A, V_{OUT} = 1.2V
- Overcurrent and Overtemperature Protection
- Enable Pin
- PSOP-8 Package with Thermal Pad
- Maximum Output Current: 3A (Peak)
- High Output-Voltage Accuracy: 2%
- V_{OUT} Power-Good Signal
- Excellent Line/Load Regulation
- **Lead-Free Finish; RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **For automotive applications requiring specific change control (i.e. parts qualified to AEC-Q100/101/104/200, PPAP capable, and manufactured in IATF 16949 certified facilities), please contact us or your local Diodes representative. https://www.diodes.com/quality/product-definitions/**

Pin Assignments

(Top View)



PSOP-8

Applications

- Notebooks

Notes:
1. EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant. All applicable RoHS exemptions applied.
2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Typical Applications Circuit



$$V_{OUT} = \frac{0.6(R1+R2)}{R2} \quad (V)$$

Adjustable Version



Fixed Version

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Pin Descriptions

Pin Number	Pin Name	Function
1	PG	Assert high once V_{OUT} reaches 92% of its rating voltage
2	EN	Enable input
3	VIN	Input voltage
4	VCTRL	Input voltage for controlling circuit
5	NC	Not connected
6	VOUT	Regulated output voltage
7	ADJ	Adjust output: when connected to ground, the output voltage is set by internal resistors; when external feedback resistors are connected, the output voltage will be V_{OUT} = 0.6V×(R1+R2)/R2.
8	GND	Ground

Functional Block Diagram



© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Absolute Maximum Ratings (Note 4)

Symbol	Parameter	Rating	Unit
V_{IN} V_{CTRL}	Input Voltage Input Voltage for Controlling Circuit	6.0	V
V_{EN}	Enable Input Voltage	-0.3 to 6.0	V
θ_{JA}	Thermal Resistance (No Heatsink)	130	°C/W
T_J	Operating Junction Temperature	+150	°C
T_{STG}	Storage Temperature Range	-65 to +150	°C
T_{LEAD}	Lead Temperature (Soldering, 10sec)	+260	°C
—	ESD (Machine Model)	200	V
—	ESD (Human Body Model)	2000	V

Note 4: Stresses greater than those listed under *Absolute Maximum Ratings* can cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to *Absolute Maximum Ratings* for extended periods can affect device reliability.

Recommended Operating Conditions

Symbol	Parameter	Min	Max	Unit
V_{IN}	Input Voltage	1.4	5.5	V
V_{CTRL}	Input Voltage for Controlling Circuit	4.5	5.5	V
T_A	Operating Ambient Temperature Range	-40	+85	°C

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Electrical Characteristics (@V_{IN} = V_{OUT}+0.5V, V_{CTRL} = V_{EN} = 5V, T_A = +25°C, C_{IN} = C_{OUT} = 10µF, C_{CTRL} = 1µF, I_{OUT} = 10mA, Bold typeface applies over -40°C ≤ T_A ≤ +85°C, unless otherwise specified.)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{OUT}	Output Voltage	V_{IN} = V_{OUT}+0.5V, I_{OUT} = 10mA	V_{OUT} × 98%	—	V_{OUT} × 102%	V
V_{IN}	Input Voltage	—	1.4	—	5.5	V
I_{LIMIT}	Current Limit	V_{IN}–V_{OUT} = 1V	3	—	—	A
V_{RLOAD}	Load Regulation	V_{IN} = V_{OUT}+0.5V, 10mA ≤ I_{OUT} ≤ 2A	—	10	—	mV
V_{RLINE}	Line Regulation	V_{OUT}+0.5V ≤ V_{IN} ≤ 5V, I_{OUT} = 10mA	—	2	—	mV
V_{DROP}	Dropout Voltage	I_{OUT} = 500mA	—	80	120	mV
		I_{OUT} = 1A	—	150	200	mV
		I_{OUT} = 2A	—	300	450	mV
I_{SUPPLY}	Supply Current	V_{IN} = V_{OUT}+0.5V, I_{OUT} = 0	—	300	—	µA
I_{CTRLH}	V_{CTRL} Current	V_{IN} = V_{OUT}+0.5V, V_{CTRL} = V_{EN} = 5V	—	250	500	µA
I_{CTRLL}		V_{IN} = V_{OUT}+0.5V, V_{CTRL} = 5V, V_{EN} = 0	—	0.1	1.0	µA
PSRR	Power-Supply Rejection Ratio	Ripple 0.5Vp-p, V_{IN} = V_{OUT}+1V, f = 100Hz	—	60	—	dB
		Ripple 0.5Vp-p, V_{IN} = V_{OUT}+1V, f = 1kHz	—	60	—	dB
$\frac{\Delta V_{OUT}}{V_{OUT} \times \Delta T}$	Output Voltage Temperature Coefficient	I_{OUT} = 10mA, -40°C ≤ T_A ≤ +85°C	—	±100	—	ppm/°C
V_{REF}	Reference Voltage	Adjust Short to V_{OUT}	0.588	0.6	0.612	V
—	Enable “High” Voltage	Enable Input Voltage “High”	1.5	—	—	V
—	Enable “Low” Voltage	Enable Input Voltage “Low”	—	—	0.4	V
OTSD	Thermal Shutdown	—	—	+165	—	°C
—	Thermal Shutdown Hysteresis	—	—	+20	—	°C
V_{THPG}	V_{OUT} Power-Good Voltage	—	—	92	—	%
—	V_{PG} Hysteresis	—	—	7	—	%
—	Adjust Pin Threshold	—	—	200	—	mV
θ_{JC}	Thermal Resistance (Junction to Case)	PSOP-8	—	40	—	°C/W

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Performance Characteristics

Supply Current vs. Output Current



Supply Current vs. Case Temperature



Enable High/Low Voltage vs. Case Temperature



Supply Current vs. Input Voltage



Output Voltage vs. Case Temperature



Output Voltage vs. Output Current



© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Performance Characteristics (continued)

Output Voltage vs. Input Voltage



Dropout Voltage vs. Output Current



Dropout Voltage vs. Case Temperature



Short Current vs. Case Temperature



PSRR vs. Frequency



V_{IN} Startup Waveform (V_{CTRL}=V_{EN}=5V, V_{IN}=0 to 2.2V, No Load)



Time 80μs/div

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Performance Characteristics (continued)

V_{EN} Startup Waveform
(V_{CTRL}=5V, V_{EN}=0 to 5V, V_{IN}=2.2V, No Load)



Time 80μs/div

V_{CTRL} Startup and Shutdown Waveform
(V_{CTRL}=0 to 5V, V_{EN}=5V, V_{IN}=2.2V, No Load)



Time 80μs/div

Load Transient
(V_{CTRL}=V_{EN}=5V, V_{IN}=2.2V, I_{OUT}=0 to 2A)



Time 80μs/div

Line Transient
(V_{CTRL}=V_{EN}=5V, C_{IN}=C_{CTRL}=1μF, C_{OUT}=10μF, V_{IN}=2.2V to 3.2V, I_{OUT}=10mA)



Time 80μs/div

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Ordering Information



Part Number	Package	Temperature Range	Version Description	Marking ID	Packing	
					Qty.	Carrier
AP2132AMP-1.8TRG1	PSOP-8	-40°C to +85°C	Each fixed output version integrates ADJ version	2132A-1.8G1	4000	Tape & Reel

Marking Information

(Top View)



= Logo
2132A-1.8G1 = Marking ID
YWW = Year and Work Week of Mold Operation
(Y = Year (ex: 4 = 2024))
(WW = Week (01 to 53))
A = Assembly Site Code
XX = Last Two Digits of Wafer Lot No.

Part Number	Package	Marking ID
AP2132AMP-1.8TRG1	PSOP-8	2132A-1.8G1

Mechanical Data

- Moisture Sensitivity: Level 1 Per J-STD-020
- Terminals: Finish - Matte Tin Plated Leads, Solderable per MIL-STD-202, Method 208 e3
- Weight: 0.075 grams (Approximate)

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Package Outline Dimensions (All dimensions in mm(inch).)

Please see http://www.diodes.com/package-outlines.html for the latest version.

PSOP-8



Note: Eject hole, oriented hole and mold mark is optional.

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.

PSOP-8



Dimensions	Z (mm)/(inch)	G (mm)/(inch)	X (mm)/(inch)	Y (mm)/(inch)	X1 (mm)/(inch)	Y1 (mm)/(inch)	E (mm)/(inch)
Value	6.900/0.272	3.900/0.154	0.650/0.026	1.500/0.059	3.600/0.142	2.700/0.106	1.270/0.050

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

IMPORTANT NOTICE

1. DIODES INCORPORATED (Diodes) AND ITS SUBSIDIARIES MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes' products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes' products. Diodes' products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of Diodes' products for their intended applications, (c) ensuring their applications, which incorporate Diodes' products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.

3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes' websites, harmless against all damages and liabilities.

4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes' website) under this document.

5. Diodes' products are provided subject to Diodes' Standard Terms and Conditions of Sale (https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.

6. Diodes' products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes' products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.

7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.

8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.

9. This Notice may be periodically updated with the most recent version available at https://www.diodes.com/about/company/terms-and-conditions/important-notice

The Diodes logo is a registered trademark of Diodes Incorporated in the United States and other countries.
All other trademarks are the property of their respective owners.
© 2024 Diodes Incorporated. All Rights Reserved.

www.diodes.com

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.