WIDE INPUT VOLTAGE RANGE, 50mA ULDO REGULATOR

Description

The DIODES™ AP7384 series is a positive voltage regulator IC.

The AP7384 has features of wide input voltage range, high accuracy, low dropout voltage, current limit and ultra-low quiescent current which make it ideal for use in various USB and portable devices.

The IC consists of a voltage reference, an error amplifier, a resistor network for setting output voltage, a current limit circuit for current protection, and a chip enable circuit.

The AP7384 has 2.8V, 3.3V, 5V and 7V fixed voltage version.

The AP7384 is available in space-saving SOT89, SOT23 and TO92 (Ammo Packing) packages.

Features


- Wide Input Voltage Range: Up to 40V
- Low Dropout Voltage: V_{DROP} = 500mV@I_{OUT} = 50mA @ V_{OUT} = 3.3V
- Low Ground Current
- High Output Voltage Accuracy
- Compatible with Low ESR Ceramic Capacitor
- Excellent Line/Load Regulation
- Thermal Shutdown Function
- Short Current Protection Function
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **For automotive applications requiring specific change control (i.e. parts qualified to AEC-Q100/101/104/200, PPAP capable, and manufactured in IATF 16949 certified facilities), please contact us or your local Diodes representative. https://www.diodes.com/quality/product-definitions/**

Applications

- E-meters
- Battery-powered equipments
- Laptop, palmtops, notebook computers
- Portable information appliances


Pin Assignments

(Top View)




SOT89

(Top View)



TO92 (Ammo Packing)

(Top View)




SOT23

NOT RECOMMENDED FOR NEW DESIGN

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

© 2022 Copyright Diodes Incorporated. All Rights Reserved.

Typical Applications Circuit



Pin Descriptions

Pin Number			Pin Name	Function
TO92 (Ammo Packing)	SOT89	SOT23		
3	3	1	VIN	Input voltage
2	2	3	GND	Ground
1	1	2	VOUT	Regulated output voltage

Absolute Maximum Ratings

Symbol	Parameter	Rating		Unit
V_{IN}	Supply Input Voltage	45		V
I_{OUT}	Output Current	50		mA
T_{LEAD}	Lead Temperature (Soldering, 10sec)	+260		°C
T_J	Operating Junction Temperature	+150		°C
θ_{JA}	Thermal Resistance	SOT89	125	°C/W
		TO92 (Ammo Packing)	165	
		SOT23	166	
T_{STG}	Storage Temperature Range	-65 to +150		°C
CDM	ESD (Change Device Model)	2000		V
HBM	ESD (Human Body Model)	4000		V

NOT RECOMMENDED FOR NEW DESIGN

Recommended Operating Conditions

Symbol	Parameter	Min	Max	Unit
V_{IN}	Supply Input Voltage	3.3	40	V
T_J	Operating Junction Temperature	-40	+125	°C

© 2022 Copyright Diodes Incorporated. All Rights Reserved.

Electrical Characteristics

(T_J = +25°C, I_{OUT} = 1mA, C_{IN} = 1.0µF, C_{OUT} = 2.2µF, V_{IN} = V_{OUT} + 2V, **Bold** typeface applies over -40°C ≤ T_J ≤ +125°C, unless otherwise specified.)


Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V_{OUT}	Output Voltage	Variation from Specified V_{OUT}	V_{OUT} x 98%	—	V_{OUT} x 102%	V
V_{IN}	Input Voltage	—	3.3	—	40	V
I_{LIMIT}	Current Limit	V_{OUT} = 98% x V_{OUT}, V_{IN} = V_{OUT} + 2V	50	—	—	mA
$\Delta V_{OUT}/\Delta V_{IN}$	Line Regulation	V_{OUT}+2V ≤ V_{IN} ≤ 40V, I_{OUT} = 10mA	—	0.05	—	%/V
$\Delta V_{OUT}/V_{OUT}$	Load Regulation	1mA ≤ I_{OUT} ≤ 50mA	—	0.5	—	%
V_{DROP}	Dropout Voltage	I_{OUT} = 50mA @ V_{OUT} = 3.3V	—	500	—	mV
I_{GND}	Ground Current	I_{OUT} = 0A	—	2.5	—	µA
		I_{OUT} = 50mA	—	25	—	
$\Delta V_{OUT}/(V_{OUT} x \Delta T)$	Output Voltage Temperature Coefficient	I_{OUT} = 100µA, -40°C ≤ T_J ≤ +125°C	—	±100	—	ppm/°C
T_{OTSD}	Thermal Shutdown Temperature	—	—	+160	—	°C
T_{HYOTSD}	Thermal Shutdown Hysteresis	—	—	+20	—	°C
PSRR	Power Supply Rejection Ratio	I_{OUT} = 1mA, V_{OUT} = 3.3V	—	60	—	dB

NOT RECOMMENDED FOR NEW DESIGN


© 2022 Copyright Diodes Incorporated. All Rights Reserved.

Performance Characteristics


Output Voltage vs. Input Voltage @-40°C




Output Voltage vs. Input Voltage @+25°C




Output Voltage vs. Input Voltage @+85°C




Output Voltage vs. Output Current



Output Voltage vs. Temperature



Output Voltage vs. Output Current




NOT RECOMMENDED FOR NEW DESIGN


© 2022 Copyright Diodes Incorporated. All Rights Reserved.

Performance Characteristics (continued)


Dropout Voltage vs. Output Current




Dropout Voltage vs. Temperature




I_{GND} vs. Input Voltage



I_{GND} vs. Output Current




I_{GND} vs Temperature



Load Transient

C_{IN}=1µF, C_{OUT}=2.2µF, V_{IN}=V_{OUT}+2V, I_{OUT}=0 to 50mA



NOT RECOMMENDED FOR NEW DESIGN

© 2022 Copyright Diodes Incorporated. All Rights Reserved.

Ordering Information

AP7384 - X X - X


Output Voltage	Package	Packing
28 : 2.8V 33 : 3.3V 50 : 5.0V 70 : 7.0V	V : TO92 (Ammo Packing) Y : SOT89 SA : SOT23	7/13 : Tape & Reel A : Ammo

Part Number	Package Code	Package	Packing		Part Number Suffix
			Quantity	Carrier	
AP7384-28V-A	V	TO92 (Ammo Packing)	2000	Ammo	-A
AP7384-33V-A	V	TO92 (Ammo Packing)	2000	Ammo	-A
AP7384-50V-A	V	TO92 (Ammo Packing)	2000	Ammo	-A
AP7384-70V-A	V	TO92 (Ammo Packing)	2000	Ammo	-A
AP7384-28Y-13	Y	SOT89	2500	Tape & Reel	-13
AP7384-33Y-13	Y	SOT89	2500	Tape & Reel	-13
AP7384-50Y-13	Y	SOT89	2500	Tape & Reel	-13
AP7384-70Y-13	Y	SOT89	2500	Tape & Reel	-13
AP7384-28SA-7	SA	SOT23	3000	Tape & Reel	-7
AP7384-33SA-7	SA	SOT23	3000	Tape & Reel	-7
AP7384-50SA-7	SA	SOT23	3000	Tape & Reel	-7
AP7384-70SA-7	SA	SOT23	3000	Tape & Reel	-7

Marking Information

(1) SOT89

(Top View)



XXX : Identification Code
Y : Year : 0 to 9
W : Week : A to Z : 1 to 26 Week;
a to z : 27 to 52 Week;
z Represents 52 and 53 Week
X : Internal Code


Part Number	Package	Identification Code
AP7384-28Y-13	SOT89	F4A
AP7384-33Y-13	SOT89	F4B
AP7384-50Y-13	SOT89	F4C
AP7384-70Y-13	SOT89	F4D

NOT RECOMMENDED FOR NEW DESIGN

© 2022 Copyright Diodes Incorporated. All Rights Reserved.


Marking Information (continued)

(2) TO92 (Ammo Packing)



Part Number	Package	Identification Code
AP7384-28V-A	TO92 (Ammo Packing)	7384-28
AP7384-33V-A	TO92 (Ammo Packing)	7384-33
AP7384-50V-A	TO92 (Ammo Packing)	7384-50
AP7384-70V-A	TO92 (Ammo Packing)	7384-70

(3) SOT23



Part Number	Package	Identification Code
AP7384-28SA-7	SOT23	F4A
AP7384-33SA-7	SOT23	F4B
AP7384-50SA-7	SOT23	F4C
AP7384-70SA-7	SOT23	F4D


NOT RECOMMENDED FOR NEW DESIGN

© 2022 Copyright Diodes Incorporated. All Rights Reserved.

Package Outline Dimensions (All dimensions in mm.)

Please see http://www.diodes.com/package-outlines.html for the latest version.

(1) Package Type: SOT89




NOT RECOMMENDED FOR NEW DESIGN

© 2022 Copyright Diodes Incorporated. All Rights Reserved.

Package Outline Dimensions (continued. All dimensions in mm.)

Please see http://www.diodes.com/package-outlines.html for the latest version.

(2) TO92 (Ammo Packing)




NOT RECOMMENDED FOR NEW DESIGN

© 2022 Copyright Diodes Incorporated. All Rights Reserved.

Package Outline Dimensions (continued. All dimensions in mm.)

Please see http://www.diodes.com/package-outlines.html for the latest version.

(3) Package Type: SOT23



SOT23			
Dim	**Min**	**Max**	**Typ**
A	0.37	0.51	0.40
B	1.20	1.40	1.30
C	2.30	2.50	2.40
D	0.89	1.03	0.915
F	0.45	0.60	0.535
G	1.78	2.05	1.83
H	2.80	3.00	2.90
J	0.013	0.10	0.05
K	0.890	1.00	0.975
K1	0.903	1.10	1.025
L	0.45	0.61	0.55
L1	0.25	0.55	0.40
M	0.085	0.150	0.110
a	0°	8°	--
All Dimensions in mm			


NOT RECOMMENDED FOR NEW DESIGN

© 2022 Copyright Diodes Incorporated. All Rights Reserved.

Suggested Pad Layout


Please see http://www.diodes.com/package-outlines.html for the latest version.

(1) Package Type: SOT89



Dimensions	Z (mm)/(inch)	X (mm)/(inch)	X1 (mm)/(inch)	X2 (mm)/(inch)	Y (mm)/(inch)	Y1 (mm)/(inch)	E (mm)/(inch)
Value	4.600/0.181	0.550/0.022	1.850/0.073	0.800/0.031	1.300/0.051	1.475/0.058	1.500/0.059

(2) Package Type: SOT23



Dimensions	Value (in mm)
C	2.0
X	0.8
X1	1.35
Y	0.9
Y1	2.9

NOT RECOMMENDED FOR NEW DESIGN

© 2022 Copyright Diodes Incorporated. All Rights Reserved.

IMPORTANT NOTICE

1. DIODES INCORPORATED (Diodes) AND ITS SUBSIDIARIES MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes' products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes' products. Diodes' products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of Diodes' products for their intended applications, (c) ensuring their applications, which incorporate Diodes' products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.

3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes' websites, harmless against all damages and liabilities.

4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes' website) under this document.

5. Diodes' products are provided subject to Diodes' Standard Terms and Conditions of Sale (https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.

6. Diodes' products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes' products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.

7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.

8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.

9. This Notice may be periodically updated with the most recent version available at https://www.diodes.com/about/company/terms-and-conditions/important-notice

The Diodes logo is a registered trademark of Diodes Incorporated in the United States and other countries.
DIODES is a trademark of Diodes Incorporated in the United States and other countries.
All other trademarks are the property of their respective owners.
© 2022 Diodes Incorporated. All Rights Reserved.

www.diodes.com

NOT RECOMMENDED FOR NEW DESIGN

© 2022 Copyright Diodes Incorporated. All Rights Reserved.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.