ART700FH; ART700FHS; ART700FHG

Power LDMOS transistor

AMPLEON

Rev. 4 — 5 February 2024 **Product data sheet**

1. Product profile

1.1 General description

Based on Advanced Rugged Technology (ART), this 700 W LDMOS RF power transistor has been designed to cover a wide range of applications for ISM, broadcast and non cellular communications. The unmatched transistor has a frequency range of 1 MHz to 450 MHz.

Table 1. Application information

Test signal	f	V_{DS}	P_L	G_p	η_D
	(MHz)	(V)	(W)	(dB)	(%)
CW pulsed [1][2]	108	50	700	27	81.5
CW pulsed [1][2]	108	55	800	28.5	80
CW [1]	108	55	800	27.5	79.5

[1] Production circuit.

[2] t_p = 100 μs; δ = 10 %.

1.2 Features and benefits







- High breakdown voltage enables class E operation at V_{DS} = 48 V
- Suitable for V_{DS} = 50 and 55 V
- Qualified up to a maximum of V_{DS} = 55 V
- Characterized from 30 V to 55 V to support a wide range of applications
- Integrated dual sided ESD protection enables class C operation and complete switch off of the transistor
- Excellent ruggedness with no device degradation
- High efficiency
- Excellent thermal stability
- Designed for broadband operation
- For RoHS compliance see the product details on the Ampleon website

1.3 Applications

- Industrial, scientific and medical applications
  - Plasma generators
  - MRI systems
  - CO_2 lasers
  - Particle accelerators
- Broadcast
  - FM radio
  - VHF TV
- Communications
  - Non cellular communications
  - UHF radar

2. Pinning information

Table 2. Pinning

Pin	Description	Simplified outline	Graphic symbol
ART700FH (SOT1214A)			
1	drain1		
2	drain2		
3	gate1		
4	gate2		
5	source [1]		
ART700FHS (SOT1214B)			
1	drain1		
2	drain2		
3	gate1		
4	gate2		
5	source [1]		
ART700FHG (SOT1214C)			
1	drain1		
2	drain2		
3	gate1		
4	gate2		
5	source [1]		

[1] Connected to flange.

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.

3. Ordering information

Table 3. Ordering information

Package name	Orderable part number	12NC	Packing description	Min. orderable quantity (pieces)
SOT1214A	ART700FHU	9349 604 89112	Tray; 20-fold; non-dry pack	60
SOT1214B	ART700FHSU	9349 605 47112	Tray; 20-fold; non-dry pack	60
SOT1214C	ART700FHGJ	9349 605 48118	TR13; 100-fold; 44 mm; non-dry pack	100

4. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	drain-source voltage		-	177	V
V_{GS}	gate-source voltage		–9	+13	V
T_{stg}	storage temperature		–65	+150	°C
T_j	junction temperature	[1]	-	225	°C

[1] Continuous use at maximum temperature will affect the reliability, for details refer to the online MTF calculator.

5. Thermal characteristics

Table 5. Thermal characteristics


Symbol	Parameter	Conditions	Typ	Unit
$R_{th(j-c)}$	thermal resistance from junction to case	T_j = 120 °C [1][2]	0.175	K/W
$Z_{th(j-c)}$	transient thermal impedance from junction to case	T_j = 120 °C; t_p = 100 μs; δ = 10 % [3]	0.052	K/W

[1] T_j is the junction temperature.

[2] $R_{th(j-c)}$ is measured under RF conditions.

[3] See Figure 1.

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.



(1) δ = 1 %
(2) δ = 2 %
(3) δ = 5 %
(4) δ = 10 %
(5) δ = 20 %
(6) δ = 50 %
(7) δ = 100 % (DC)

Fig 1. Transient thermal impedance from junction to case as a function of pulse duration

6. Characteristics

Table 6. DC characteristics

T_j = 25 °C; per section unless otherwise specified.


Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$V_{(BR)DSS}$	drain-source breakdown voltage	V_{GS} = 0 V; I_D = 2.8 mA	177	191	-	V
$V_{GS(th)}$	gate-source threshold voltage	V_{DS} = 20 V; I_D = 275 mA	1.5	2.1	2.5	V
I_{DSS}	drain leakage current	V_{GS} = 0 V; V_{DS} = 50 V	-	-	1.4	μA
I_{DSX}	drain cut-off current	V_{GS} = $V_{GS(th)}$ + 3.75 V; V_{DS} = 20 V	-	40	-	A
I_{GSS}	gate leakage current	V_{GS} = 13 V; V_{DS} = 0 V	-	-	140	nA
$R_{DS(on)}$	drain-source on-state resistance	V_{GS} = $V_{GS(th)}$ + 3.75 V; I_D = 9.625 A	-	0.171	-	Ω

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.

Table 7. AC characteristics

T_j = 25 °C; per section unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
C_{rs}	feedback capacitance	V_{GS} = 0 V; f = 1 MHz				
		V_{DS} = 50 V	-	1.04	-	pF
		V_{DS} = 55 V	-	1.00	-	pF
C_{iss}	input capacitance	V_{GS} = 0 V; f = 1 MHz				
		V_{DS} = 50 V	-	312	-	pF
		V_{DS} = 55 V	-	312	-	pF
C_{oss}	output capacitance	V_{GS} = 0 V; f = 1 MHz				
		V_{DS} = 50 V	-	97	-	pF
		V_{DS} = 55 V	-	93	-	pF



V_{GS} = 0 V; f = 1 MHz

Fig 2. Output capacitance as a function of drain-source voltage; typical values per section

Table 8. RF characteristics

Test signal: pulsed RF; t_p = 100 µs; δ = 10 %; f = 108 MHz; RF performance at V_{DS} = 55 V; I_{Dq} = 25 mA per section; T_{case} = 25 °C; unless otherwise specified; in a class-AB production test circuit.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
G_p	power gain	P_L = 800 W	26.8	28.6	-	dB
RL_{in}	input return loss	P_L = 800 W	-	−32.7	-	dB
η_D	drain efficiency	P_L = 800 W	73.0	77.6	-	%

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.

7. Test information

7.1 Ruggedness in class-AB operation

The ART700FH, ART700FHS and ART700FHG are capable of withstanding a load mismatch corresponding to VSWR ≥ 65 : 1 through all phases under the following conditions: P_L = 700 W pulsed at V_{DS} = 50 V and P_L = 800 W pulsed at V_{DS} = 55 V; I_{Dq} = 50 mA per section; t_p = 100 μs; δ = 10 %; f = 108 MHz.

7.2 Impedance information





Fig 3. Definition of transistor impedance

Table 9. Typical push-pull impedance
Simulated Z_i and Z_L device impedance.

f	Z_i	Z_L	P_L
(MHz)	(Ω)	(Ω)	(W)
V_{DS} = 50 V			
108	4.75 – j17.00	6.60 + j1.10	700
V_{DS} = 55 V			
108	4.75 – j17.00	6.95 + j1.30	800

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.

7.3 Test circuit



Printed-Circuit Board (PCB): RO4350B; ε_r = 3.48 F/m; thickness = 0.762 mm.

See Table 10 for a list of components.

Fig 4. Component layout

Table 10. List of components

For test circuit see Figure 4.

Component	Description	Value	Remarks
C1	multilayer ceramic chip capacitor	510 pF [1]	
C2, C3	multilayer ceramic chip capacitor	62 pF [1]	
C4	multilayer ceramic chip capacitor	160 pF [1]	
C5, C6, C22, C23	multilayer ceramic chip capacitor	820 pF [1]	
C7, C8	multilayer ceramic chip capacitor	4.7 μF, 50 V	Murata: GRM32ER71H475KA88L
C9, C10	multilayer ceramic chip capacitor	36 pF [1]	
C11, C12, C13, C14	multilayer ceramic chip capacitor	56 pF [1]	
C15	multilayer ceramic chip capacitor	43 pF [1]	
C16	multilayer ceramic chip capacitor	47 pF [1]	
C17, C18, C19, C20	multilayer ceramic chip capacitor	62 pF [1]	
C21	multilayer ceramic chip capacitor	220 pF [1]	
C24, C25	multilayer ceramic chip capacitor	4.7 μF, 100 V	TDK: C5750X7R2A475KT/A
C26, C27	electrolytic capacitor	1500 μF, 80 V	radial leaded
L1, L3	1 mm copper wire	5 turn, D = 4 mm	
L2, L4	1 mm copper wire	3 turn, D = 4 mm	
R1, R2	chip resistor	4.7 kΩ	SMD 1206

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.


Table 10. List of components *…continued*
For test circuit see Figure 4.

Component	Description	Value	Remarks
R3, R4, R5, R6	chip resistor	20 Ω	SMD 1206
R7, R8	chip resistor	0.01 Ω	Vishay: WSHP2818
T1, T2, T3, T4	hand formable coax	50 Ω, 160 mm	SUCOFORM 141

[1] AVX type 800B or capacitor of same quality.


7.4 Graphical data

7.4.1 1-Tone CW pulsed



V_{DS} = 55 V; I_{Dq} = 50 mA per section; f = 108 MHz; t_p = 100 μs; δ = 10 %.

Fig 5. Power gain and drain efficiency as function of output power; typical values




V_{DS} = 55 V; I_{Dq} = 50 mA per section; f = 108 MHz; t_p = 100 μs; δ = 10 %.

(1) $P_{L(1dB)}$ = 58.95 dBm (785 W)

(2) $P_{L(3dB)}$ = 59.32 dBm (855 W)

Fig 6. Output power as a function of input power; typical values


All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.



V_{DS} = 55 V; f = 108 MHz; t_p = 100 μs; δ = 10 %.

(1) I_{Dq} = 25 mA per section
(2) I_{Dq} = 50 mA per section
(3) I_{Dq} = 100 mA per section
(4) I_{Dq} = 200 mA per section
(5) I_{Dq} = 300 mA per section
(6) I_{Dq} = 600 mA per section
(7) I_{Dq} = 1200 mA per section

Fig 7. Power gain as a function of output power; typical values




V_{DS} = 55 V; f = 108 MHz; t_p = 100 μs; δ = 10 %.

(1) I_{Dq} = 25 mA per section
(2) I_{Dq} = 50 mA per section
(3) I_{Dq} = 100 mA per section
(4) I_{Dq} = 200 mA per section
(5) I_{Dq} = 300 mA per section
(6) I_{Dq} = 600 mA per section
(7) I_{Dq} = 1200 mA per section

Fig 8. Drain efficiency as a function of output power; typical values


All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.



I_{Dq} = 50 mA per section; f = 108 MHz; t_p = 100 μs; δ = 10 %.

(1) V_{DS} = 55 V
(2) V_{DS} = 50 V
(3) V_{DS} = 45 V
(4) V_{DS} = 40 V
(5) V_{DS} = 35 V
(6) V_{DS} = 30 V

Fig 9. Power gain as a function of output power; typical values




I_{Dq} = 50 mA per section; f = 108 MHz; t_p = 100 μs; δ = 10 %.

(1) V_{DS} = 55 V
(2) V_{DS} = 50 V
(3) V_{DS} = 45 V
(4) V_{DS} = 40 V
(5) V_{DS} = 35 V
(6) V_{DS} = 30 V

Fig 10. Drain efficiency as a function of output power; typical values


All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.

7.4.2 1-Tone CW



V_{DS} = 55 V; I_{Dq} = 50 mA per section; f = 108 MHz.

Fig 11. Power gain and drain efficiency as function of output power; typical values




V_{DS} = 55 V; I_{Dq} = 50 mA per section; f = 108 MHz.

(1) $P_{L(1dB)}$ = 58.81 dBm (760 W)

(2) $P_{L(3dB)}$ = 59.16 dBm (825 W)

Fig 12. Output power as a function of input power; typical values



V_{DS} = 55 V; f = 108 MHz.

(1) I_{Dq} = 25 mA per section

(2) I_{Dq} = 50 mA per section

(3) I_{Dq} = 100 mA per section


(4) I_{Dq} = 200 mA per section

(5) I_{Dq} = 300 mA per section

(6) I_{Dq} = 600 mA per section

(7) I_{Dq} = 1200 mA per section

Fig 13. Power gain as a function of output power; typical values



V_{DS} = 55 V; f = 108 MHz.

(1) I_{Dq} = 25 mA per section

(2) I_{Dq} = 50 mA per section

(3) I_{Dq} = 100 mA per section

(4) I_{Dq} = 200 mA per section


(5) I_{Dq} = 300 mA per section

(6) I_{Dq} = 600 mA per section

(7) I_{Dq} = 1200 mA per section

Fig 14. Drain efficiency as a function of output power; typical values


All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.



I_{Dq} = 50 mA per section; f = 108 MHz.

(1) V_{DS} = 55 V
(2) V_{DS} = 50 V
(3) V_{DS} = 45 V
(4) V_{DS} = 40 V
(5) V_{DS} = 35 V
(6) V_{DS} = 30 V

Fig 15. Power gain as a function of output power; typical values



I_{Dq} = 50 mA per section; f = 108 MHz.


(1) V_{DS} = 55 V
(2) V_{DS} = 50 V
(3) V_{DS} = 45 V
(4) V_{DS} = 40 V
(5) V_{DS} = 35 V
(6) V_{DS} = 30 V

Fig 16. Drain efficiency as a function of output power; typical values

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.

8. Package outline

Flanged ceramic package; 2 mounting holes; 4 leads **SOT1214A**



Dimensions

Unit[1]		A	b	c	D	D_1	e	E	E_1	F	H	H_1	p	Q[2]	q	U_1	U_2	w_1	w_2	w_3
mm	max	4.72	6.17	0.15	20.02	19.96		9.53	9.50	1.14	19.94		3.38	1.70		34.16	9.91			
	nom						8.21					14.24			27.94			0.25	0.51	0.25
	min	3.43	5.92	0.08	19.61	19.66		9.27	9.29	0.89	18.92		3.12	1.45		33.91	9.65			
inches	max	0.187	0.243	0.006	0.788	0.786		0.375	0.374	0.045	0.785		0.133	0.067		1.345	0.39			
	nom						0.323					0.56			1.10			0.01	0.02	0.01
	min	0.135	0.233	0.003	0.772	0.774		0.365	0.366	0.035	0.745		0.123	0.057		1.335	0.38			

Note
1. millimeter dimensions are derived from the original inch dimensions.
2. dimension is measured 0.030 inch (0.76 mm) from body.


sot1214a_po

Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1214A						~~12-08-16~~ 12-10-10

Fig 17. Package outline SOT1214A

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.

Earless flanged ceramic package; 4 leads **SOT1214B**



Dimensions

Unit(1)		A	b	c	D	D_1	e	E	E_1	F	H	H_1	Q(2)	U_1	U_2	w_2	w_3
mm	max	4.72	6.17	0.15	20.02	19.96		9.53	9.50	1.14	19.94		1.70	20.70	9.91		
	nom						8.21					14.24				0.51	0.25
	min	3.43	5.92	0.08	19.61	19.66		9.27	9.29	0.89	18.92		1.45	20.45	9.65		
inches	max	0.187	0.243	0.006	0.788	0.786		0.375	0.374	0.045	0.785		0.067	0.815	0.39		
	nom						0.323					0.56				0.02	0.01
	min	0.135	0.233	0.003	0.772	0.774		0.365	0.366	0.035	0.745		0.057	0.805	0.38		

Note
1. millimeter dimensions are derived from the original inch dimensions.
2. dimension is measured 0.030 inch (0.76 mm) from body.


sot1214b_po

Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1214B						~~12-10-10~~ 14-03-27

Fig 18. Package outline SOT1214B

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.

Earless flanged LDMOST ceramic package; 4 leads **SOT1214C**



Dimensions (mm are the original dimensions)

Unit		A	b	c	D	D_1	e	E	E_1	F	H	H_1	L_p	Q	U_1	U_2	v	w_2	w_3	y	α
mm	max	4.72	6.17	0.15	20.02	19.96		9.53	9.50	1.14	14.3		1.38	0.195	20.70	9.91				0.15	7°
	nom						8.21					14.24					0.25	0.51	0.25		
	min	3.43	5.92	0.08	19.61	19.66		9.27	9.29	0.89	14.1		0.98	0.055	20.45	9.65					0°

sot1214c_po

Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1214C						~~13-11-21~~ 13-12-02

Fig 19. Package outline SOT1214C

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.

9. Handling information

CAUTION



This device is sensitive to ElectroStatic Discharge (ESD). Observe precautions for handling electrostatic sensitive devices.

Such precautions are described in the *ANSI/ESD S20.20*, *IEC/ST 61340-5*, *JESD625-A* or equivalent standards.

Table 11. ESD sensitivity

ESD model	Class
Charged Device Model (CDM); According to ANSI/ESDA/JEDEC standard JS-002	C2A [1]
Human Body Model (HBM); According to ANSI/ESDA/JEDEC standard JS-001	2 [2]

[1] CDM classificationC2A is granted to any part that passes after exposure to an ESD pulse of 500 V.

[2] HBM classification 2 is granted to any part that passes after exposure to an ESD pulse of 2000 V.

10. Abbreviations

Table 12. Abbreviations

Acronym	Description
CW	Continuous Wave
ESD	ElectroStatic Discharge
FM	Frequency Modulation
ISM	Industrial, Scientific and Medical
LDMOS	Laterally Diffused Metal-Oxide Semiconductor
MRI	Magnetic Resonance Imaging
MTF	Median Time to Failure
RoHS	Restriction of Hazardous Substances
SMD	Surface Mounted Device
UHF	Ultra High Frequency
VHF	Very High Frequency
VSWR	Voltage Standing Wave Ratio

11. Revision history

Table 13. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
ART700FH_700FHS_700FHG v.4	20240205	Product data sheet	-	ART700FH_700FHS_700FHG v.3
Modifications:	• Table 10 on page 7: changed value R3, R4, R5, R6			
ART700FH_700FHS_700FHG v.3	20221118	Product data sheet	-	ART700FH_700FHS_700FHG v.2
ART700FH_700FHS_700FHG v.2	20220708	Product data sheet	-	ART700FH v.1
ART700FH v.1	20210924	Product data sheet	-	-

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2024. All rights reserved.

12. Legal information

12.1 Data sheet status

Document status[1][2]	Product status[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.ampleon.com.

12.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Ampleon does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Ampleon sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Ampleon and its customer, unless Ampleon and customer have explicitly agreed otherwise in writing. An agreement according to which the functions and qualities of Ampleon products exceed those described in the Product data sheet is invalid.

12.3 Disclaimers

Maturity — After the relevant product(s) have passed the Release Gate in Ampleon's release process, Ampleon will confirm the final version in writing.

Limited warranty and liability — Ampleon uses its best efforts to keep the information in this document accurate and reliable. However, Ampleon gives no representations or warranties, expressed or implied, as to the accuracy or completeness of such information and assumes no liability for the consequences of the use of such information. Ampleon is not liable for content provided by an external information source.

In no event and irrespective of the legal basis (contract, tort (including negligence) statutory liability, misrepresentation, indemnity or any other area of law) shall Ampleon be liable for any indirect, incidental, punitive, special or consequential damages (including but without limitation loss of profit or revenue, loss of use or loss of production, loss of data, cost of capital, cost of substitute goods, property damage external to the Ampleon products and any damage, expenditure or loss arising out of such damage, business interruption, costs related to the removal or replacement of any products or rework charges) or any of the foregoing suffered by any third party.

Notwithstanding any damages that customer might incur for any reason whatsoever, Ampleon's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Ampleon.

Right to make changes — Ampleon reserves the right to change information including but without limitation specifications and product descriptions published in this document at any time and without notice. This document supersedes and replaces all information regarding these products supplied prior to the publication hereof.

Suitability for use — Ampleon products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Ampleon product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Insofar as a customer or another party nevertheless uses Ampleon products unlawfully for such purposes, Ampleon and its suppliers are not liable for any damages.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Ampleon makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Ampleon products, and Ampleon is not liable for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Ampleon product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers shall provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Ampleon is not liable related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for and shall do all necessary testing for the customer's applications and products using Ampleon products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Ampleon is not liable in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not guaranteed. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Ampleon products are sold subject to the general terms and conditions of commercial sale, as published at http://www.ampleon.com/terms, unless otherwise agreed in a valid written individual agreement. In the event of signing an individual agreement the terms and conditions of the respective agreement shall apply. Ampleon hereby expressly objects to and rejects the validity of customer's terms and conditions regarding the purchase of Ampleon products by customer.

All information provided in this document is subject to legal disclaimers.

© Ampleon Netherlands B.V. 2024. All rights reserved.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Ampleon product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Ampleon is not liable for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer breaches this and uses the products for design and use in automotive applications in accordance with automotive specifications and standards, (a) Ampleon gives no warranty, representation or other guarantees of any kind with respect to such automotive applications, use and specifications, and (b) such use is solely and exclusively at customer's own risk, and (c) customer fully indemnifies Ampleon against any and all liability, damages or failed product claims, including against third parties, arising out of customer's design and use of the product for automotive applications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

12.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

13. Contact information

For more information, please visit: **http://www.ampleon.com**

For sales office addresses, please visit: **http://www.ampleon.com/sales**

All information provided in this document is subject to legal disclaimers.

© Ampleon Netherlands B.V. 2024. All rights reserved.

14. Contents

1 Product profile 1
1.1 General description 1
1.2 Features and benefits 1
1.3 Applications 2
2 Pinning information 2
3 Ordering information 3
4 Limiting values 3
5 Thermal characteristics 3
6 Characteristics 4
7 Test information 6
7.1 Ruggedness in class-AB operation 6
7.2 Impedance information 6
7.3 Test circuit 7
7.4 Graphical data 8
7.4.1 1-Tone CW pulsed 8
7.4.2 1-Tone CW 11
8 Package outline 13
9 Handling information 16
10 Abbreviations 16
11 Revision history 16
12 Legal information 17
12.1 Data sheet status 17
12.2 Definitions 17
12.3 Disclaimers 17
12.4 Trademarks 18
13 Contact information 18
14 Contents 19

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© Ampleon Netherlands B.V. 2024. All rights reserved.

For more information, please visit: http://www.ampleon.com
For sales office addresses, please visit: http://www.ampleon.com/sales

Date of release: 5 February 2024
Document identifier: ART2K0FE_2K0FES_2K0FEG

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.