Description

The AS78XXA series are three-terminal positive voltage regulators designed for a wide variety of applications including local, on-card regulation.

The AS78XXA are complete with internal current limiting, thermal shutdown protection, and safe-area compensation which make them virtually immune from output overload. If adequate heat sinking is provided, these regulators can deliver output currents of up to 1A.

The AS78XXA are available in TO-220-3, TO-220-3 (2), TO-252-2 (5), TO252 (Type CJ) and TO-263-2 packages.

Applications

- High-efficiency linear regulators
- Post regulation for switching supplies
- Microprocessor power supplies
- Motherboards
- Telecommunication.

Features


- Output Current up to 1A
- Fixed Output Voltages of 5V, 12V, 15V
- Output Voltage Accuracy of ±4% over the Full Temperature Range
- Internal Short-Circuit Current Limiting
- Internal Thermal Overload Protection
- Output Transistor Safe-Area Protection
- Low Load Regulation
- Stable Performance in High Temperature
- Lead-Free Packages: TO-220-3, TO-220-3 (2)
  - **Totally Lead-Free; RoHS Compliant (Notes 1 & 3)**
- Available in “Green” Packages: TO-220-3, TO-220-3 (2), and TO-263-2
  - **Lead-Free Finish; RoHS Compliant (Notes 2 & 3)**
  - **Halogen and Antimony Free. “Green” Device (Note 4)**
- Lead-Free Packages, Available in “Green” Molding Compound: TO-252-2 (5), TO252 (Type CJ)
  - **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 3)**
  - **Halogen and Antimony Free. “Green” Device (Note 4)**
- **For automotive applications requiring specific change control (i.e. parts qualified to AEC-Q100/101/104/200, PPAP capable, and manufactured in IATF 16949 certified facilities), please contact us or your local Diodes representative. https://www.diodes.com/quality/product-definitions/**

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
2. EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant. All applicable RoHS exemptions applied.
3. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated’s definitions of Halogen- and Antimony-free, "Green" and Lead-free.
4. Halogen- and Antimony-free "Green” products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

© 2024 Copyright Diodes Incorporated. All Rights Reserved.


Pin Assignments

(Front View)




TO-220-3 (Option 1)

(Front View)




TO-220-3 (Option 2)

(Front View)




TO-220-3 (2)

(Front View)




TO-263-2

(Top View)



TO-252-2 (5)


(Top View)



TO252 (Type CJ)

© 2024 Copyright Diodes Incorporated. All Rights Reserved.


Typical Applications Circuit



Pin Descriptions

Pin Number	Pin Name	Function
1	INPUT	Voltage Input
2	GND	Ground
3	OUTPUT	Voltage Output

Functional Block Diagram



© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Absolute Maximum Ratings (Note 5)

Symbol	Parameter		Rating	Unit
V_{IN}	Input Voltage		36	V
T_{LEAD}	Lead Temperature (Soldering, 10sec)		+260	°C
P_D	Power Dissipation		Internally Limited	W
T_J	Operating Junction Temperature		+150	°C
T_{STG}	Storage Temperature Range		-65 to +150	°C
θ_{JA}	Thermal Resistance	TO-220-3 TO-220-3 (2)	60	°C/W
		TO-252-2 (5) TO252 (Type CJ)	100	
		TO-263-2	50	
ESD	ESD (Human Body Model)		6000	V
ESD	ESD (Machine Model)		500	V

Note: 5. Stresses greater than those listed under *Absolute Maximum Ratings* can cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under *Recommended Operating Conditions* is not implied. Exposure to *Absolute Maximum Ratings* for extended periods can affect device reliability.

Recommended Operating Conditions

Symbol	Parameter		Min	Max	Unit
V_{IN}	Input Voltage	AS7805A	—	25	V
		AS7812A	—	32	
		AS7815A	—	32	
T_J	Operating Junction Temperature Range		-40	+125	°C

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Electrical Characteristics

AS7805A (@ V_{IN} = 10V, I_{OUT} = 1A, T_J = -40 to +125°C, unless otherwise specified.)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{OUT}	Output Voltage	T_J = +25°C	4.9	5	5.1	V
		I_{OUT} = 5mA to 1A, V_{IN} = 7.5V to 20V $P_D \leq$ 15W	4.8	—	5.2	
V_{RLINE}	Line Regulation	V_{IN} = 7.5V to 20V I_{OUT} = 500mA, T_J = +25°C	—	25	50	mV
V_{RLOAD}	Load Regulation	V_{IN} = 10V, I_{OUT} = 5mA to 1A T_J = +25°C	—	20	50	mV
I_Q	Quiescent Current	V_{IN} = 10V, I_{OUT} = 0	—	3.2	6	mA
ΔI_Q	Quiescent Current Change	V_{IN} = 8V to 25V, I_{OUT} = 500mA T_J = +25°C	—	0.3	0.8	mA
		I_{OUT} = 5mA to 1A, T_J = +25°C	—	0.08	0.5	
PSRR	Ripple Rejection	V_{IN} = 8V to 18V, f = 120Hz I_{OUT} = 500mA	—	70	—	dB
V_{DROP}	Dropout Voltage	ΔV_{OUT} = 1%, I_{OUT} = 1A T_J = +25°C	—	2	—	V
N_O	Output Noise Voltage	f = 10Hz to 100kHz, T_A = +25°C	—	10	—	μV/V_O
R_O	Output Resistance	f = 1kHz	—	10	—	mΩ
I_{SC}	Short-Circuit Current	V_{IN} = 35V, T_A = +25°C	—	0.05	—	A
I_{PK}	Peak Output Current	V_{IN} = 10V, T_J = +25°C	—	2.2	—	A
$\Delta V_{OUT}/\Delta T$	Output Voltage Temperature Coefficient	—	—	0.4	—	mV/°C
$(\Delta V_{OUT}/V_{OUT})/\Delta T$		—	—	80	—	ppm/°C
θ_{JC}	Thermal Resistance	TO-220-3/TO-220-3 (2)	—	9	—	°C/W
		TO-252-2 (5)/TO252 (Type CJ)	—	16	—	
		TO-263-2	—	6	—	

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Electrical Characteristics (continued)

AS7812A (@ V_{IN} = 19V, I_{OUT} = 1A, T_J = -40 to +125°C, unless otherwise specified.)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{OUT}	Output Voltage	T_J = +25°C	11.75	12	12.25	V
		I_{OUT} = 5mA to 1A, V_{IN} = 14.8V to 27V $P_D \leq$ 15W	11.5	—	12.5	
V_{RLINE}	Line Regulation	V_{IN} = 14.8V to 27V I_{OUT} = 500mA, T_J = +25°C	—	25	120	mV
V_{RLOAD}	Load Regulation	V_{IN} = 19V, I_{OUT} = 5mA to 1A T_J = +25°C	—	40	120	mV
I_Q	Quiescent Current	V_{IN} = 19V, I_{OUT} = 0	—	3.4	6	mA
ΔI_Q	Quiescent Current Change	V_{IN} = 14.8V to 30V, I_{OUT} = 500mA T_J = +25°C	—	0.3	0.8	mA
		I_{OUT} = 5mA to 1A, T_J = +25°C	—	0.08	0.5	
PSRR	Ripple Rejection	V_{IN} = 15V to 25V, f = 120Hz I_{OUT} = 500mA	—	60	—	dB
V_{DROP}	Dropout Voltage	ΔV_{OUT} = 1%, I_{OUT} = 1A T_J = +25°C	—	2	—	V
N_O	Output Noise Voltage	f = 10Hz to 100kHz, T_A = +25°C	—	10	—	μV/V_O
R_O	Output Resistance	f = 1kHz	—	11	—	mΩ
I_{SC}	Short-Circuit Current	V_{IN} = 35V, T_A = +25°C	—	0.2	—	A
I_{PK}	Peak Output Current	V_{IN} = 18V, T_J = +25°C	—	2.2	—	A
$\Delta V_{OUT}/\Delta T$	Output Voltage Temperature Coefficient	—	—	0.96	—	mV/°C
$(\Delta V_{OUT}/V_{OUT})/\Delta T$		—	—	80	—	ppm/°C
θ_{JC}	Thermal Resistance	TO-220-3/TO-220-3 (2)	—	9	—	°C/W
		TO-252-2 (5)/TO252 (Type CJ)	—	16	—	

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Electrical Characteristics (continued)


AS7815A (@ V_{IN} = 23V, I_{OUT} = 1A, T_J = -40 to +125°C, unless otherwise specified.)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
V_{OUT}	Output Voltage	T_J = +25°C	14.7	15	15.3	V
		I_{OUT} = 5mA to 1A, V_{IN} = 17.9V to 30V $P_D \leq$ 15W	14.4	—	15.6	
V_{RLINE}	Line Regulation	V_{IN} = 17.9V to 30V I_{OUT} = 500mA, T_J = +25°C	—	35	150	mV
V_{RLOAD}	Load Regulation	V_{IN} = 23V, I_{OUT} = 5mA to 1A T_J = +25°C	—	70	150	mV
I_Q	Quiescent Current	V_{IN} = 23V, I_{OUT} = 0	—	3.4	6	mA
ΔI_Q	Quiescent Current Change	V_{IN} = 17.9V to 30V, I_{OUT} = 500mA T_J = +25°C	—	0.3	0.8	mA
		I_{OUT} = 5mA to 1A, T_J = +25°C	—	0.08	0.5	
PSRR	Ripple Rejection	V_{IN} = 18.5V to 28.5V, f = 120Hz I_{OUT} = 500mA	—	58	—	dB
V_{DROP}	Dropout Voltage	ΔV_{OUT} = 1%, I_{OUT} = 1A, T_J = +25°C	—	2	—	V
N_O	Output Noise Voltage	f = 10Hz to 100kHz, T_A = +25°C	—	10	—	$\mu V/V_O$
R_O	Output Resistance	f = 1kHz	—	11	—	mΩ
I_{SC}	Short-Circuit Current	V_{IN} = 35V, T_A = +25°C	—	0.2	—	A
I_{PK}	Peak Output Current	V_{IN} = 21V, T_J = +25°C	—	2.2	—	A
$\Delta V_{OUT}/\Delta T$	Output Voltage Temperature Coefficient	—	—	1.2	—	mV/°C
$(\Delta V_{OUT}/V_{OUT})/\Delta T$		—	—	80	—	ppm/°C
θ_{JC}	Thermal Resistance	TO-220-3/TO-220-3 (2)	—	9	—	°C/W
		TO-252-2 (5)/TO252 (Type CJ)	—	16	—	


© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Performance Characteristics


Peak Output Current vs. Input/Output Differential Voltage




Output Voltage vs. Junction Temperature




Output Voltage vs. Output Current




Output Voltage vs. Input Voltage



Quiescent Current vs. Junction Temperature




Ripple Rejection vs. Frequency




© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Performance Characteristics (continued)


Dropout Voltage vs. Junction Temperature




Power Dissipation vs. Junction Temperature



Line Transient
(Conditions: I_{OUT} = 500mA, C_{OUT} = 0.1µF)




Load Transient
(Conditions: V_{IN} = 10V, C_{IN} = 0.33µF, C_{OUT} = 0.1µF)



© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Ordering Information



Orderable Part Number	Package (Note 6)	Output Voltage (V)	RoHS Compliant Lead Free/ Green	Marking ID	Packing	
					Qty.	Carrier
AS7805ADTR-E1	TO-252-2 (5) TO252 (Type CJ)	5	Green	AS7805AD-E1	2500	Tape & Reel
AS7805ADTR-G1		5	Green	AS7805AD-G1	2500	Tape & Reel
AS7805AT-E1	TO-220-3 TO-220-3 (2)	5	Green	AS7805AT-E1	1000	Tube
AS7805ASTR-G1	TO-263-2	5	Green	AS7805AS-G1	800	Tape & Reel

Orderable Part Number	Package (Note 6)	Output Voltage (V)	RoHS Compliant Lead Free/ Green	Marking ID	Packing	
					Qty.	Carrier
AS7812ADTR-G1	TO-252-2 (5) TO252 (Type CJ)	12	Green	AS7812AD-G1	2500	Tape & Reel
AS7812AT-E1	TO-220-3 TO-220-3 (2)	12	Lead Free	AS7812AT-E1	1000	Tube
AS7815ADTR-G1	TO-252-2 (5) TO252 (Type CJ)	15	Green	AS7815AD-G1	2500	Tape & Reel
AS7815AT-E1	TO-220-3 TO-220-3 (2)	15	Lead Free	AS7815AT-E1	1000	Tube


Note: 6. For packaging details, go to our website at: https://www.diodes.com/design/support/packaging/diodes-packaging/.

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Marking Information


(1) TO-220-3/TO-220-3 (2)

(Front View)



First and Second Lines: Logo and Marking ID
(See *Ordering Information*)
Third Line: Date Code
Y: Year
WW: Work Week of Molding
A: Assembly House Code
XX: Internal Code


(2) TO252 (Type CJ)/TO-252-2 (5)



First and Second Lines: Logo and Marking ID
(See *Ordering Information*)
Third Line: Date Code
Y: Year
WW: Work Week of Molding
A: Assembly House Code
XX: Internal Code

(3) TO-263-2

(Top View)




First and Second Lines: Logo and Marking ID
(See *Ordering Information*)
Third line: Date Code
Y: Year
WW: Work Week of Molding
A: Assembly House Code
XX: 7th and8th Digits of Batch No.


© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Package Outline Dimensions (All dimensions in mm(inch).)

Please see http://www.diodes.com/package-outlines.html for the latest version.

(1) Package Type: TO-220-3






© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Package Outline Dimensions (continued) (All dimensions in mm(inch).)

Please see http://www.diodes.com/package-outlines.html for the latest version.

(2) Package Type: TO-220-3 (2)




© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Package Outline Dimensions (continued) (All dimensions in mm(inch).)

Please see http://www.diodes.com/package-outlines.html for the latest version.

(3) Package Type: TO-252-2 (5)




© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Package Outline Dimensions (continued) (All dimensions in mm(inch).)


Please see http://www.diodes.com/package-outlines.html for the latest version.

(4) Package Type: TO252 (Type CJ)



TO252 (Type CJ)			
Dim	Min	Max	Typ
A	2.200	2.400	--
A1	0.000	0.127	--
b	0.635	0.770	--
b3	5.100	5.460	--
c	0.460	0.580	--
D	6.000	6.200	--
D2	5.250 REF		
E	6.500	6.700	--
E2	4.830 REF		
e	2.186	2.386	--
h	0.000	0.300	--
H	9.712	10.312	--
L	1.400	1.700	--
L1	2.900 REF		
L2	0.600	1.000	--
L3	1.600 REF		
Ø	1.100	1.300	--
θ	0°	8°	--
All Dimensions in mm			

(5) Package Type: TO-263-2




© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.

(1) Package Type: TO252 (Type CJ)




Dimensions	Z (mm)/(inch)	X1 (mm)/(inch)	X2 = Y2 (mm)/(inch)	Y1 (mm)/(inch)	G (mm)/(inch)	E1 (mm)/(inch)
Value	11.600/0.457	1.500/0.059	7.000/0.276	2.500/0.098	2.100/0.083	2.300/0.091

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Suggested Pad Layout (continued)

Please see http://www.diodes.com/package-outlines.html for the latest version.

(2) Package Type: TO-252-2 (5)




Dimensions	Z (mm)/(inch)	X1 (mm)/(inch)	X2 = Y2 (mm)/(inch)	Y1 (mm)/(inch)	G (mm)/(inch)	E1 (mm)/(inch)
Value	11.600/0.457	1.500/0.059	7.000/0.276	2.500/0.098	2.100/0.083	2.300/0.091

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

Suggested Pad Layout (continued)

Please see http://www.diodes.com/package-outlines.html for the latest version.

(3) Package Type: TO-263-2



Dimensions	Z (mm)/(inch)	X1 (mm)/(inch)	X2 (mm)/(inch)	X3 (mm)/(inch)
Value	16.760/0.660	1.200/0.047	8.540/0.336	10.540/0.415
Dimensions	Y1 (mm)/(inch)	Y2 (mm)/(inch)	Y3 (mm)/(inch)	E (mm)/(inch)
Value	3.830/0.151	8.560/0.337	3.000/0.118	5.080/0.200

Mechanical Data

- Moisture Sensitivity: Level 3 per J-STD-020
- Terminals: Finish—Matte Tin Plated Leads, Solderable per MIL-STD-202, Method 208 e3
- Weight:
  - TO-252-2 (5)/TO252 (Type CJ): 0.312 grams (Approximate)
  - TO-220-3/TO-220-3 (2): 1.925 grams (Approximate)
  - TO-263-2: 1.412 grams (Approximate)

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

IMPORTANT NOTICE

1. DIODES INCORPORATED (Diodes) AND ITS SUBSIDIARIES MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes' products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes' products. Diodes' products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of Diodes' products for their intended applications, (c) ensuring their applications, which incorporate Diodes' products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.

3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes' websites, harmless against all damages and liabilities.

4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes' website) under this document.

5. Diodes' products are provided subject to Diodes' Standard Terms and Conditions of Sale (https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.

6. Diodes' products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes' products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.

7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.

8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.

9. This Notice may be periodically updated with the most recent version available at https://www.diodes.com/about/company/terms-and-conditions/important-notice

The Diodes logo is a registered trademark of Diodes Incorporated in the United States and other countries.
All other trademarks are the property of their respective owners.
© 2024 Diodes Incorporated. All Rights Reserved.

www.diodes.com

© 2024 Copyright Diodes Incorporated. All Rights Reserved.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.