Ordering number : ENA1479A

ATP102

P-Channel Power MOSFET
−30V, −40A, 18.5mΩ, Single ATPAK

ON Semiconductor®
http://onsemi.com

Features

- Low ON-resistance
- Slim package
- Halogen free compliance
- Large current
- 4.5V drive
- Protection diode in

Specifications

Absolute Maximum Ratings at Ta=25°C


Parameter	Symbol	Conditions	Ratings	Unit
Drain-to-Source Voltage	V_{DSS}		−30	V
Gate-to-Source Voltage	V_{GSS}		±20	V
Drain Current (DC)	I_D		−40	A
Drain Current (PW≤10μs)	I_{DP}	PW≤10μs, duty cycle≤1%	−120	A
Allowable Power Dissipation	P_D	Tc=25°C	40	W
Channel Temperature	Tch		150	°C
Storage Temperature	Tstg		−55 to +150	°C
Avalanche Energy (Single Pulse) *1	E_{AS}		58	mJ
Avalanche Current *2	I_{AV}		20	A

Note :*1 V_{DD}=10V, L=200μH, I_{AV}=20A
*2 L≤200μH, Single pulse

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Package Dimensions


unit : mm (typ)
7057-001




Product & Package Information

- Package : ATPAK
- JEITA, JEDEC : -
- Minimum Packing Quantity : 3,000 pcs./reel


Packing Type: TL



Marking




Electrical Connection



Electrical Characteristics at Ta=25°C


Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	I_D=−1mA, V_{GS}=0V	−30			V
Zero-Gate Voltage Drain Current	I_{DSS}	V_{DS}=−30V, V_{GS}=0V			−1	μA
Gate-to-Source Leakage Current	I_{GSS}	V_{GS}=±16V, V_{DS}=0V			±10	μA
Cutoff Voltage	V_{GS}(off)	V_{DS}=−10V, I_D=−1mA	−1.2		−2.6	V
Forward Transfer Admittance	| yfs |	V_{DS}=−10V, I_D=−20A		29		S
Static Drain-to-Source On-State Resistance	R_{DS}(on)1	I_D=−20A, V_{GS}=−10V		14	18.5	mΩ
	R_{DS}(on)2	I_D=−10A, V_{GS}=−4.5V		22	31	mΩ
Input Capacitance	Ciss	V_{DS}=−10V, f=1MHz		1490		pF
Output Capacitance	Coss			360		pF
Reverse Transfer Capacitance	Crss			270		pF
Turn-ON Delay Time	t_d(on)	See specified Test Circuit.		11		ns
Rise Time	t_r			135		ns
Turn-OFF Delay Time	t_d(off)			135		ns
Fall Time	t_f			185		ns
Total Gate Charge	Qg	V_{DS}=−15V, V_{GS}=−10V, I_D=−40A		34		nC
Gate-to-Source Charge	Qgs			4.2		nC
Gate-to-Drain “Miller” Charge	Qgd			11.5		nC
Diode Forward Voltage	V_{SD}	I_S=−40A, V_{GS}=0V		−0.99	−1.5	V


Switching Time Test Circuit





Ordering Information


Device	Package	Shipping	memo
ATP102-TL-H	ATPAK	3,000pcs./reel	Pb Free and Halogen Free



ID -- VDS
Drain Current, ID – A
Drain-to-Source Voltage, VDS – V
IT14687
–4.0V
–4.5V
–6.0V
–8.0V
–10.0V
–16.0V
VGS= –3.5V
Tc=25°C
Single pulse



ID -- VGS
Drain Current, ID – A
Gate-to-Source Voltage, VGS – V
IT14688
VDS= –10V
Single pulse
Tc= –25°C
75°C
25°C
25°C
Tc=75°C
–25°C



RDS(on) -- VGS
Static Drain-to-Source
On-State Resistance, RDS(on) – mΩ
Gate-to-Source Voltage, VGS – V
IT14689
Tc=25°C
Single pulse
ID= –10A
–20A



RDS(on) -- Tc
Static Drain-to-Source
On-State Resistance, RDS(on) – mΩ
Case Temperature, Tc – °C
IT14690
Single pulse
VGS= –4.5V, ID= –10A
VGS= –10V, ID= –20A



| yfs | -- ID
Forward Transfer Admittance, | yfs | – S
Drain Current, ID – A
IT14691
VDS= –10V
Single pulse
25°C
Tc= –25°C
75°C



IS -- VSD
Source Current, IS – A
Diode Forward Voltage, VSD – V
IT14692
VGS=0V
Single pulse
Tc=75°C
25°C
–25°C



SW Time -- ID
Switching Time, SW Time – ns
Drain Current, ID – A
IT14693
VDD= –15V
VGS= –10V
td(off)
tf
tr
td(on)


Ciss, Coss, Crss -- VDS
Ciss, Coss, Crss – pF
Drain-to-Source Voltage, VDS – V
IT14694
f=1MHz
Ciss
Coss
Crss


VGS – Qg
VDS= –15V
ID= –40A
Gate-to-Source Voltage, VGS – V
Total Gate Charge, Qg – nC
IT14695


A S O
IDP= –120A
PW≤10μs
10μs
100μs
ID= –40A
1ms
10ms
100ms
DC operation
Operation in this area is limited by RDS(on).
Tc=25°C
Single pulse
Drain Current, ID – A
Drain-to-Source Voltage, VDS – V
IT14696


PD -- Tc
Allowable Power Dissipation, PD – W
Case Temperature, Tc – °C
IT14697


EAS -- Ta
Avalanche Energy derating factor – %
Ambient Temperature, Ta – °C
IT10478


Taping Specification

ATP102-TL-H

1. Packing Format (TL)

Package Name	Carrier Tape Type	Maximum Number of devices contained (pcs)			Packing format	
		Reel	Inner box	Outer box	INNER BOX SD-C-18	OUTER BOX SD-A-18
ATPAK	ATP	3,000	3,000	15,000	1 reels contained Dimensions:mm (external) 340×340×28	5 inner boxes contained Dimensions:mm (external) 355×355×165


Packing method



Reel label


Reel label, Inner box label

(unit:mm)



Outer box label

It is a label at the time of factory shipments. The form of a label may change in physical distribution process.




NOTE (1)

The LEAD FREE ※ description shows that the surface treatment of the terminal is lead free.


Label	JEITA Phase
LEAD FREE 3	JEITA Phase 3A
LEAD FREE 4	JEITA Phase 3

2. Taping configuration

2-1. Carrier tape size (unit:mm)




2-2. Device placement direction




The one erectrode terminals on feed hole side····TL

Outline Drawing

ATP102-TL-H



Land Pattern Example



Note on usage : Since the ATP102 is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.