1. Product profile

1.1 General description

A 35 W extremely rugged LDMOS power transistor for broadcast and industrial applications in the HF to 600 MHz band.

Table 1. Application information

Test signal	f	V_{DS}	P_L	G_p	η_D
	(MHz)	(V)	(W)	(dB)	(%)
pulsed RF	108	50	35	27	75
CW	63.86	50	35	29.4	75.6
	127.72	50	35	26.8	75.7

1.2 Features and benefits





- Easy power control
- Integrated double sided ESD protection
- Excellent ruggedness
- High efficiency
- Excellent thermal stability
- Designed for broadband operation (HF to 600 MHz)
- Compliant to Directive 2002/95/EC, regarding Restriction of Hazardous Substances (RoHS)

1.3 Applications

- Industrial, scientific and medical applications
- Broadcast transmitter applications

2. Pinning information

Table 2. Pinning

Pin	Description	Simplified outline	Graphic symbol
BLP05H635XR (SOT1223-2)			
1	gate 2		
2	gate 1		
3	drain 1		
4	drain 2		
5	source [1]		
BLP05H635XRG (SOT1224-2)			
1	gate 2		
2	gate 1		
3	drain 1		
4	drain 2		
5	source [1]		

[1] Connected to flange.

3. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
BLP05H635XR	HSOP4F	plastic, heatsink small outline package; 4 leads (flat)	SOT1223-2
BLP05H635XRG	HSOP4F	plastic, heatsink small outline package; 4 leads	SOT1224-2

4. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	drain-source voltage		-	135	V
V_{GS}	gate-source voltage		–6	+11	V
T_{stg}	storage temperature		–65	+150	°C
T_j	junction temperature	[1]	-	225	°C

[1] Continuous use at maximum temperature will affect the reliability, for details refer to the online MTF calculator.

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.

5. Thermal characteristics


Table 5. Thermal characteristics

Symbol	Parameter	Conditions	Typ	Unit
$R_{th(j-c)}$	thermal resistance from junction to case	T_j = 115 °C [1][2]	2.0	K/W
$Z_{th(j-c)}$	transient thermal impedance from junction to case	T_j = 150 °C; t_p = 100 µs; δ = 20 % [3]	0.68	K/W

[1] T_j is the junction temperature.

[2] $R_{th(j-c)}$ is measured under RF conditions.

[3] See Figure 1.



(1) δ = 1 %
(2) δ = 2 %
(3) δ = 5 %
(4) δ = 10 %
(5) δ = 20 %
(6) δ = 50 %
(7) δ = 100 % (DC)

Fig 1. Transient thermal impedance from junction to case as a function of pulse duration

6. Characteristics

Table 6. DC characteristics

T_j = 25 °C; per section unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$V_{(BR)DSS}$	drain-source breakdown voltage	V_{GS} = 0 V; I_D = 0.125 mA	135	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	V_{DS} = 10 V; I_D = 12.5 mA	1.25	1.8	2.25	V
V_{GSq}	gate-source quiescent voltage	V_{DS} = 50 V; I_D = 10 mA	-	1.7	-	V
I_{DSS}	drain leakage current	V_{GS} = 0 V; V_{DS} = 50 V	-	-	1.4	µA

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.

Table 6. DC characteristics *...continued*

T_j = 25 °C; per section unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
I_{DSX}	drain cut-off current	$V_{GS} = V_{GS(th)} + 3.75$ V; $V_{DS} = 10$ V	-	1.8	-	A
I_{GSS}	gate leakage current	$V_{GS} = 11$ V; $V_{DS} = 0$ V	-	-	140	nA
$R_{DS(on)}$	drain-source on-state resistance	$V_{GS} = V_{GS(th)} + 3.75$ V; $I_D = 437.5$ mA	-	3.2	-	Ω

Table 7. AC characteristics


T_j = 25 °C; per section unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
C_{rs}	feedback capacitance	$V_{GS} = 0$ V; $V_{DS} = 50$ V; f = 1 MHz	-	0.12	-	pF
C_{iss}	input capacitance	$V_{GS} = 0$ V; $V_{DS} = 50$ V; f = 1 MHz	-	16.2	-	pF
C_{oss}	output capacitance	$V_{GS} = 0$ V; $V_{DS} = 50$ V; f = 1 MHz	-	6.4	-	pF

Table 8. RF characteristics

Test signal: pulsed RF; t_p = 100 μs; δ = 20 %; f = 108 MHz; RF performance at V_{DS} = 50 V; I_{Dq} = 10 mA; T_{case} = 25 °C; unless otherwise specified; in a class-AB production test circuit.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
G_p	power gain	P_L = 35 W	25.5	27	-	dB
RL_{in}	input return loss	P_L = 35 W	-	−25	-	dB
η_D	drain efficiency	P_L = 35 W	71	75	-	%



V_{GS} = 0 V; f = 1 MHz.

Fig 2. Output capacitance as a function of drain-source voltage; typical values per section

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.

7. Test information

7.1 Ruggedness in class-AB operation

The BLP05H635XR and BLP05H635XRG are capable of withstanding a load mismatch corresponding to VSWR > 65 : 1 through all phases under the following conditions: V_{DS} = 50 V; I_{Dq} = 20 mA; P_L = 35 W pulsed; f = 108 MHz.

7.2 Impedance information




Fig 3. Definition of transistor impedance

Table 9. Typical push-pull impedance

Simulated Z_i and Z_L device impedance; impedance info at V_{DS} = 50 V and P_L = 35 W.

f	Z_i	Z_L
(MHz)	(Ω)	(Ω)
108	46.6 – j282.0	100.6 + j26.9

7.3 UIS avalanche energy

Table 10. Typical avalanche data per section

T_{amb} = 25 °C; typical test data; test jig without water cooling.

I_{AS}	E_{AS}
(A)	(J)
1.0	0.08
1.25	0.05
1.5	0.04

For information see application note *AN10273*.

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.





Fig 4. Non-repetitive avalanche energy as a function of single pulse avalanche current; typical values

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.

7.4 Test circuit



Printed-Circuit Board (PCB): RF-35; ε_r = 3.5 F/m; thickness = 0.765 mm; thickness copper plating = 35 μm.

See Table 11 for a list of components.

Fig 5. Component layout for class-AB production test circuit

Table 11. List of components

For test circuit see Figure 5.


Component	Description	Value	Remarks
C1, C7	multilayer ceramic chip capacitor	470 pF	ATC 800B
C2	multilayer ceramic chip capacitor	120 pF	ATC 800B
C3	multilayer ceramic chip capacitor	390 pF	ATC 800B
C5	multilayer ceramic chip capacitor	1 μF, 50 V	GRM32RR71H105KA01L
C6, C13	multilayer ceramic chip capacitor	820 pF	ATC 800B
C8, C9	multilayer ceramic chip capacitor	39 pF	ATC 100A
C10	multilayer ceramic chip capacitor	27 pF	ATC 800B
C11	multilayer ceramic chip capacitor	4.7 μF, 100 V	C5750X7RA475KT/A
C12	multilayer ceramic chip capacitor	100 nF	GRM188R72A104KA35D
C14	multilayer ceramic chip capacitor	15 pF	ATC 800B
C15	electrolytic capacitor	2200 μF, 63 V	Vishay
L1	wire inductor	169 nH	Coilcraft:132-12SMG
L2	wire inductor	90 nH	Coilcraft:132-9SMG
R1, R2	resistor	10 Ω	SMD 1206
R3	resistor	4.64 kΩ	SMD 0805
R4	shunt resistor	50 mΩ	Ohmite: FC4L110R050FER
R5	resistor	7.5 Ω, 0.6 W	SMD 1206

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.

7.5 Graphical data


The following figures are measured in a class-AB production test circuit.

7.5.1 1-Tone CW pulsed



V_{DS} = 50 V; I_{Dq} = 10 mA; f = 108 MHz; t_p = 100 μs; δ = 20 %.

Fig 6. Power gain and drain efficiency as function of output power; typical values




V_{DS} = 50 V; I_{Dq} = 10 mA; f = 108 MHz; t_p = 100 μs; δ = 20 %.

(1) $P_{L(1dB)}$ = 45.5 dBm (35.2 W) at P_i = 18.6 dBm

(2) $P_{L(3dB)}$ = 46.0 dBm (39.4 W) at P_i = 21.1 dBm

Fig 7. Output power as a function of input power; typical values


All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.



V_{DS} = 50 V; f = 108 MHz; t_p = 100 μs; δ = 20 %.

(1) I_{Dq} = 5 mA
(2) I_{Dq} = 10 mA
(3) I_{Dq} = 20 mA
(4) I_{Dq} = 50 mA
(5) I_{Dq} = 100 mA
(6) I_{Dq} = 200 mA

Fig 8. Power gain as a function of output power; typical values




V_{DS} = 50 V; f = 108 MHz; t_p = 100 μs; δ = 20 %.

(1) I_{Dq} = 5 mA
(2) I_{Dq} = 10 mA
(3) I_{Dq} = 20 mA
(4) I_{Dq} = 50 mA
(5) I_{Dq} = 100 mA
(6) I_{Dq} = 200 mA

Fig 9. Drain efficiency as a function of output power; typical values


All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.



I_{Dq} = 10 mA; f = 108 MHz; t_p = 100 μs; δ = 20 %.

(1) V_{DS} = 50 V
(2) V_{DS} = 45 V
(3) V_{DS} = 40 V
(4) V_{DS} = 35 V
(5) V_{DS} = 30 V
(6) V_{DS} = 25 V
(7) V_{DS} = 20 V

Fig 10. Power gain as a function of output power; typical values



I_{Dq} = 10 mA; f = 108 MHz; t_p = 100 μs; δ = 20 %.


(1) V_{DS} = 50 V
(2) V_{DS} = 45 V
(3) V_{DS} = 40 V
(4) V_{DS} = 35 V
(5) V_{DS} = 30 V
(6) V_{DS} = 25 V
(7) V_{DS} = 20 V

Fig 11. Drain efficiency as a function of output power; typical values

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.

8. Package outline

HSOP4F: plastic, heatsink small outline package; 4 leads(flat) **SOT1223-2**



Q_1	v	w	y
1.62			0.1
1.57	0.25	0.25	
1.52			

Dimensions (mm are the original dimensions)

Unit		A	A_1	A_2	b	c	$D^{(1)}$	D_1	D_2	D_3	$E^{(1)}$	E_1	E_2	E_3	e	e_1	e_2	e_3	e_4	F	H_E
	max	3.9	0.2	3.65	3.90	0.27	20.62	19.00	16.05	20.44	10.01	8.18	5.89	9.83							16.16
mm	nom		0.1	3.60	3.85	0.22	20.57	18.95	16.00	20.39	9.96	8.13	5.84	9.78	8.85	8.45	9.55	2.97	4.07	0.4	15.96
	min		0	3.55	3.80	0.17	20.52	18.90	15.95	20.34	9.91	8.08	5.79	9.73							15.76

Note
1. Package body dimensions “D and “E do not include mold and metal protrusions. Allowable protrusion is 0.25 mm per side.
2. Lead width dimension “b does not include dambar protrusions. Allowable dambar protrusion is 0.25 mm in total per lead.


sot1223-2_po

Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1223-2						~~15-01-12~~ 15-06-04

Fig 12. Package outline SOT1223-2 (HSOP4F)

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.

HSOP4: plastic, heatsink small outline package; 4 leads **SOT1224-2**



H_E	L_p	Q	v	w	y	θ
13.5	1.10	2.07			0.1	7°
13.2	0.95	2.02	0.25	0.25		3°
12.9	0.80	1.97				0°

Dimensions (mm are the original dimensions)

Unit		A	A_1	A_2	A_3	A_4	b	c	$D^{(1)}$	D_1	D_2	D_3	$E^{(1)}$	E_1	E_2	E_3	e	e_1	e_2	e_3	e_4
mm	max	3.9	0.2	3.65		0.06	3.90	0.27	20.62	19.00	16.05	20.44	10.01	8.18	5.89	9.83					
	nom		0.1	3.60	0.35	0	3.85	0.22	20.57	18.95	16.00	20.39	9.96	8.13	5.84	9.78	8.85	8.45	9.55	2.97	4.07
	min		0	3.55		-0.02	3.80	0.17	20.52	18.90	15.95	20.34	9.91	8.08	5.79	9.73					

Note
1. Package body dimensions “D and “E do not include mold and metal protrusions. Allowable protrusion is 0.25 mm per side.
2. Lead width dimension “b does not include dambar protrusions. Allowable dambar protrusion is 0.25 mm in total per lead.
3. Dimension A_4 is measured with respect to bottom of the heatsink DATUM H. Positive value means that the bottom of the heatsink is higher than the bottom of the lead.

sot1224-2_po

Outline version	References				European projection	Issue date
	IEC	JEDEC	JEITA			
SOT1224-2						~~15-01-13~~ 15-06-04

Fig 13. Package outline SOT1224-2 (HSOP4F)

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.

9. Handling information

CAUTION



This device is sensitive to ElectroStatic Discharge (ESD). Observe precautions for handling electrostatic sensitive devices.

Such precautions are described in the *ANSI/ESD S20.20*, *IEC/ST 61340-5*, *JESD625-A* or equivalent standards.

10. Abbreviations

Table 12. Abbreviations

Acronym	Description
CW	Continuous Wave
ESD	ElectroStatic Discharge
HF	High Frequency
LDMOS	Laterally Diffused Metal-Oxide Semiconductor
MTF	Median Time to Failure
SMD	Surface Mounted Device
UIS	Unclamped Inductive Switching
VSWR	Voltage Standing-Wave Ratio

11. Revision history

Table 13. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
BLP05H635XR_H635XRG v.4	20160921	Product data sheet	-	BLP05H635XR v.3
Modifications:	• The document now describes both the straight lead and gull-wing versions of this product: BLP05H635XR and BLP05H635XRG respectively • Table 2 on page 2: added BLP05H635XRG data • Table 3 on page 2: added BLP05H635XRG data • Section 7.1 on page 5: added BLP05H635XRG • Figure 13 on page 12: added figure SOT1224-2			
BLP05H635XR v.3	20160108	Product data sheet	-	BLP05H635XR#2
BLP05H635XR#2	20150901	Objective data sheet	-	BLP05H635XR v.1
BLP05H635XR v.1	20150518	Objective data sheet	-	-

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.

12. Legal information

12.1 Data sheet status

Document status[1][2]	Product status[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL http://www.ampleon.com.

12.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Ampleon does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Ampleon sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Ampleon and its customer, unless Ampleon and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Ampleon product is deemed to offer functions and qualities beyond those described in the Product data sheet.

12.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Ampleon does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Ampleon takes no responsibility for the content in this document if provided by an information source outside of Ampleon.

In no event shall Ampleon be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Ampleon's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Ampleon.

Right to make changes — Ampleon reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Ampleon products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an Ampleon product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Ampleon and its suppliers accept no liability for inclusion and/or use of Ampleon products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Ampleon makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Ampleon products, and Ampleon accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Ampleon product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Ampleon does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Ampleon products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Ampleon does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Ampleon products are sold subject to the general terms and conditions of commercial sale, as published at http://www.ampleon.com/terms, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Ampleon hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Ampleon products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

All information provided in this document is subject to legal disclaimers.
© Ampleon Netherlands B.V. 2016. All rights reserved.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Ampleon product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Ampleon accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Ampleon' warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Ampleon' specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Ampleon for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Ampleon' standard warranty and Ampleon' product specifications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

12.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

Any reference or use of any 'NXP' trademark in this document or in or on the surface of Ampleon products does not result in any claim, liability or entitlement vis-à-vis the owner of this trademark. Ampleon is no longer part of the NXP group of companies and any reference to or use of the 'NXP' trademarks will be replaced by reference to or use of Ampleon's own trademarks.

13. Contact information

For more information, please visit: **http://www.ampleon.com**

For sales office addresses, please visit: **http://www.ampleon.com/sales**

All information provided in this document is subject to legal disclaimers.

© Ampleon Netherlands B.V. 2016. All rights reserved.

14. Contents

1 Product profile 1
1.1 General description 1
1.2 Features and benefits 1
1.3 Applications 1
2 Pinning information 2
3 Ordering information 2
4 Limiting values 2
5 Thermal characteristics 3
6 Characteristics 3
7 Test information 5
7.1 Ruggedness in class-AB operation 5
7.2 Impedance information 5
7.3 UIS avalanche energy 5
7.4 Test circuit 7
7.5 Graphical data 8
7.5.1 1-Tone CW pulsed 8
8 Package outline 11
9 Handling information 13
10 Abbreviations 13
11 Revision history 13
12 Legal information 14
12.1 Data sheet status 14
12.2 Definitions 14
12.3 Disclaimers 14
12.4 Trademarks 15
13 Contact information 15
14 Contents 16

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© Ampleon Netherlands B.V. 2016. All rights reserved.

For more information, please visit: http://www.ampleon.com
For sales office addresses, please visit: http://www.ampleon.com/sales

Date of release: 21 September 2016
Document identifier: BLP05H635XR_H635XRG

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.