CDM7-600LR

SURFACE MOUNT SILICON N-CHANNEL LR POWER MOSFET 7.0 AMP, 600 VOLT

UltraMOS™



DPAK CASE

Central Semiconductor™

www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CDM7-600LR is a 600 Volt N-Channel MOSFET designed for high voltage, fast switching applications such as Power Factor Correction (PFC), lighting and power inverters. This UltraMOS™ MOSFET combines high voltage capability with ultra low $r_{DS(ON)}$, low threshold voltage, and low gate charge for optimal efficiency.

MARKING: FULL PART NUMBER

APPLICATIONS:

- Power Factor Correction
- Alternative energy inverters
- Solid State Lighting (SSL)

FEATURES:

- High voltage capability (V_{DS}=600V)
- Low gate charge (Q_{gs}=3.54nC TYP)
- Ultra low $r_{DS(ON)}$ (0.48Ω TYP)

MAXIMUM RATINGS: (T_C=25°C unless otherwise noted)

	SYMBOL		UNITS
Drain-Source Voltage	V_{DS}	600	V
Gate-Source Voltage	V_{GS}	30	V
Continuous Drain Current (Steady State)	I_D	7.0	A
Maximum Pulsed Drain Current, tp=10μs	I_{DM}	28	A
Continuous Source Current (Body Diode)	I_S	7.0	A
Maximum Pulsed Source Current (Body Diode)	I_{SM}	28	A
Single Pulse Avalanche Energy (Note 1)	E_{AS}	255	mJ
Power Dissipation	P_D	60	W
Operating and Storage Junction Temperature	T_J, T_{stg}	-55 to +150	°C
Thermal Resistance	Θ_{JC}	2.08	°C/W
Thermal Resistance	Θ_{JA}	110	°C/W

Note 1: L=79mH, I_{AS}=2.4A, V_{DD}=100V, R_G=25Ω, Initial T_J=25°C

ELECTRICAL CHARACTERISTICS: (T_C=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNITS
I_{GSSF}, I_{GSSR}	V_{GS}=30V, V_{DS}=0			100	nA
I_{DSS}	V_{DS}=600V, V_{GS}=0			1.0	μA
BV_{DSS}	V_{GS}=0, I_D=250μA	600			V
$V_{GS(th)}$	V_{GS}=V_{DS}, I_D=250μA	2.0		4.0	V
V_{SD}	V_{GS}=0, I_S=7.0A			1.4	V
$r_{DS(ON)}$	V_{GS}=10V, I_D=3.5A		0.48	0.58	Ω
C_{rss}	V_{DS}=100V, V_{GS}=0, f=1.0MHz		6.7		pF
C_{iss}	V_{DS}=100V, V_{GS}=0, f=1.0MHz		450		pF
C_{oss}	V_{DS}=100V, V_{GS}=0, f=1.0MHz		29		pF

CDM7-600LR


SURFACE MOUNT SILICON
N-CHANNEL
LR POWER MOSFET
7.0 AMP, 600 VOLT

ELECTRICAL CHARACTERISTICS - Continued: (T_C=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	TYP	UNITS
$Q_{g(tot)}$	V_{DS}=480V, V_{GS}=10V, I_D=7.0A (Note 2)	22.9	nC
Q_{gs}	V_{DS}=480V, V_{GS}=10V, I_D=7.0A (Note 2)	3.54	nC
Q_{gd}	V_{DS}=480V, V_{GS}=10V, I_D=7.0A (Note 2)	13.2	nC
$t_{d(on)}$	V_{DD}=300V, V_{GS}=10V, I_D=7.0A, R_G=24Ω (Note 2)	10.3	ns
t_r	V_{DD}=300V, V_{GS}=10V, I_D=7.0A, R_G=24Ω (Note 2)	32.6	ns
$t_{d(off)}$	V_{DD}=300V, V_{GS}=10V, I_D=7.0A, R_G=24Ω (Note 2)	72.2	ns
t_f	V_{DD}=300V, V_{GS}=10V, I_D=7.0A, R_G=24Ω (Note 2)	28.9	ns
t_{rr}	V_{GS}=0, I_S=7.0A, di/dt=100A/μs (Note 2)	430	ns
Q_{rr}	V_{GS}=0, I_S=7.0A, di/dt=100A/μs (Note 2)	3.2	μC

Note 2: Pulse Width ≤ 300μs, Duty Cycle ≤ 2%


DPAK CASE - MECHANICAL OUTLINE



DIMENSIONS				
	INCHES		MILLIMETERS	
SYMBOL	MIN	MAX	MIN	MAX
A	0.083	0.108	2.10	2.75
B	0.016	0.035	0.40	0.89
C	0.035	0.063	0.89	1.60
D	0.203	0.228	5.15	5.79
E	0.020	-	0.51	-
F	0.016	0.024	0.40	0.60
G	0.061		1.55	
H	0.248	0.268	6.30	6.81
J	0.195	0.217	4.95	5.50
K	0.209	0.245	5.30	6.22
L	0.033		0.83	
M	0.090	0.115	2.30	2.91
N	0.012	0.045	0.30	1.14
P	0.180		4.60	
R	0.090		2.30	

DPAK(REV:R2)

PIN CONFIGURATION



LEAD CODE:
1) Gate
2) Drain
3) Source
4) Drain
Pin 2 is common to the tab (4)

MARKING: FULL PART NUMBER


R5 (22-August 2023)

CDM7-600LR


SURFACE MOUNT SILICON
N-CHANNEL
LR POWER MOSFET
7.0 AMP, 600 VOLT

TYPICAL ELECTRICAL CHARACTERISTICS


Output Characteristics




Drain Source On Resistance




Capacitance



Transfer Characteristics



Power Derating



R5 (22-August 2023)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centralsemi.com

Worldwide Field Representatives:
www.centralsemi.com/wwreps

Worldwide Distributors:
www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.