CMPDM7002A
CMPDM7002AG*

SURFACE MOUNT SILICON N-CHANNEL ENHANCEMENT-MODE MOSFET



SOT-23 CASE

* Device is ***Halogen Free*** by design

Central Semiconductor Corp.

www.centralsemi.com

DESCRIPTION:

The CENTRAL SEMICONDUCTOR CMPDM7002A and CMPDM7002AG are special versions of the 2N7002 enhancement-mode N-Channel MOSFET manufactured by the N-Channel DMOS Process, designed for high speed pulsed amplifier and driver applications. These special devices offer low $r_{DS(ON)}$ and low $V_{DS\ (ON)}$.

MARKING CODES: CMPDM7002A: C702A
CMPDM7002AG*: 702G

MAXIMUM RATINGS: (T_A=25°C)	**SYMBOL**		**UNITS**
Drain-Source Voltage	V_{DS}	60	V
Drain-Gate Voltage	V_{DG}	60	V
Gate-Source Voltage	V_{GS}	40	V
Continuous Drain Current	I_D	280	mA
Continuous Source Current (Body Diode)	I_S	280	mA
Maximum Pulsed Drain Current	I_{DM}	1.5	A
Maximum Pulsed Source Current	I_{SM}	1.5	A
Power Dissipation	P_D	350	mW
Operating and Storage Junction Temperature	T_J, T_{stg}	-65 to +150	°C
Thermal Resistance	Θ_{JA}	357	°C/W

ELECTRICAL CHARACTERISTICS: (T_A=25°C unless otherwise noted)

SYMBOL	**TEST CONDITIONS**	**MIN**	**MAX**	**UNITS**
I_{GSSF}, I_{GSSR}	V_{GS}=20V, V_{DS}=0		100	nA
I_{DSS}	V_{DS}=60V, V_{GS}=0		1.0	μA
I_{DSS}	V_{DS}=60V, V_{GS}=0, T_J=125°C		500	μA
$I_{D(ON)}$	V_{GS}=10V, V_{DS}=10V	500		mA
BV_{DSS}	V_{GS}=0, I_D=10μA	60		V
$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=250μA	1.0	2.5	V
$V_{DS(ON)}$	V_{GS}=10V, I_D=500mA		1.0	V
$V_{DS(ON)}$	V_{GS}=5.0V, I_D=50mA		0.15	V
V_{SD}	V_{GS}=0, I_S=400mA		1.2	V
$r_{DS(ON)}$	V_{GS}=10V, I_D=500mA		2.0	Ω
$r_{DS(ON)}$	V_{GS}=10V, I_D=500mA, T_J=125°C		3.5	Ω
$r_{DS(ON)}$	V_{GS}=5.0V, I_D=50mA		3.0	Ω
$r_{DS(ON)}$	V_{GS}=5.0V, I_D=50mA, T_J=125°C		5.0	Ω
g_{FS}	V_{DS}=10V, I_D=200mA	80		mS
C_{rss}	V_{DS}=25V, V_{GS}=0, f=1.0MHz		5.0	pF
C_{iss}	V_{DS}=25V, V_{GS}=0, f=1.0MHz		50	pF
C_{oss}	V_{DS}=25V, V_{GS}=0, f=1.0MHz		25	pF

R5 (9-February 2015)


CMPDM7002A
CMPDM7002AG*

SURFACE MOUNT SILICON
N-CHANNEL
ENHANCEMENT-MODE
MOSFET

ELECTRICAL CHARACTERISTICS - Continued: (T_A=25°C unless otherwise noted)

SYMBOL	TEST CONDITIONS	TYP	MAX	UNITS
$Q_{g(tot)}$	V_{DS}=30V, V_{GS}=4.5V, I_D=100mA	0.592		nC
Q_{gs}	V_{DS}=30V, V_{GS}=4.5V, I_D=100mA	0.196		nC
Q_{gd}	V_{DS}=30V, V_{GS}=4.5V, I_D=100mA	0.148		nC
t_{on}, t_{off}	V_{DD}=30V, V_{GS}=10V, I_D=200mA, R_G=25Ω, R_L=150Ω		20	ns

SOT-23 CASE - MECHANICAL OUTLINE



DIMENSIONS				
	INCHES		MILLIMETERS	
SYMBOL	MIN	MAX	MIN	MAX
A	0.003	0.007	0.08	0.18
B	0.006	-	0.15	-
C	-	0.005	-	0.13
D	0.035	0.043	0.89	1.09
E	0.110	0.120	2.80	3.05
F	0.075		1.90	
G	0.037		0.95	
H	0.047	0.055	1.19	1.40
I	0.083	0.098	2.10	2.49
J	0.014	0.020	0.35	0.50

SOT-23 (REV: R3)

LEAD CODE:
1) Gate
2) Source
3) Drain

MARKING CODES:
CMPDM7002A: C702A
CMPDM7002AG*: 702G
* Device is ***Halogen Free*** by design


R5 (9-February 2015)

CMPDM7002A
CMPDM7002AG*


SURFACE MOUNT SILICON N-CHANNEL ENHANCEMENT-MODE MOSFET

TYPICAL ELECTRICAL CHARACTERISTICS


Output Characteristics




Transfer Characteristics




Capacitance



Drain Source On Resistance



Power Derating



R5 (9-February 2015)

OUTSTANDING SUPPORT AND SUPERIOR SERVICES

PRODUCT SUPPORT

Central's operations team provides the highest level of support to insure product is delivered on-time.

- Supply management (Customer portals)
- Inventory bonding
- Consolidated shipping options
- Custom bar coding for shipments
- Custom product packing

DESIGNER SUPPORT/SERVICES

Central's applications engineering team is ready to discuss your design challenges. Just ask.

- Free quick ship samples (2nd day air)
- Online technical data and parametric search
- SPICE models
- Custom electrical curves
- Environmental regulation compliance
- Customer specific screening
- Up-screening capabilities
- Special wafer diffusions
- PbSn plating options
- Package details
- Application notes
- Application and design sample kits
- Custom product and package development

REQUESTING PRODUCT PLATING

1. If requesting Tin/Lead plated devices, add the suffix " TIN/LEAD" to the part number when ordering (example: 2N2222A TIN/LEAD).
2. If requesting Lead (Pb) Free plated devices, add the suffix " PBFREE" to the part number when ordering (example: 2N2222A PBFREE).

CONTACT US

Corporate Headquarters & Customer Support Team

Central Semiconductor Corp.
145 Adams Avenue
Hauppauge, NY 11788 USA
Main Tel: (631) 435-1110
Main Fax: (631) 435-1824
Support Team Fax: (631) 435-3388
www.centralsemi.com

Worldwide Field Representatives:
www.centralsemi.com/wwreps

Worldwide Distributors:
www.centralsemi.com/wwdistributors

For the latest version of Central Semiconductor's **LIMITATIONS AND DAMAGES DISCLAIMER**, which is part of Central's Standard Terms and Conditions of sale, visit: www.centralsemi.com/terms

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.