THE DGTD65T15H2TF IS NOT RECOMMENDED FOR NEW DESIGNS. PLEASE CONTACT US.

Green

DGTD65T15H2TF

650V FIELD STOP IGBT IN ITO220AB

Description

The DGTD65T15H2TF is produced using advanced Field Stop Trench IGBT Technology, which provides high performance, excellent quality, and high ruggedness.

Applications


- Motor drives

Features


- High Ruggedness for Motor Control
- $V_{CE(sat)}$ Positive Temperature Coefficient
- Very Soft, Fast Recovery Anti-Parallel Diode
- Low EMI
- Maximum Junction Temperature +175°C
- **Lead-Free Finish; RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **For automotive applications requiring specific change control (i.e. parts qualified to AEC-Q100/101/104/200, PPAP capable, and manufactured in IATF 16949 certified facilities), please contact us or your local Diodes representative.**
  https://www.diodes.com/quality/product-definitions/

Mechanical Data

- Package: ITO220AB
- Package Material: Molded Plastic. "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Terminals: Finish—Matte Tin Plated Leads. Solderable per MIL-STD-202, Method 208 (e3)
- Weight: 1.9 grams (Approximate)



ITO220AB (Type MC)



Device Symbol

Ordering Information (Note 4)

Orderable Part Number	Package	Marking	Packing	
			Qty.	Carrier
DGTD65T15H2TF	ITO220AB (Type MC)	DGTD65T15H2	1000	Box in Tubes (Note 5)

Notes:
1. EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant. All applicable RoHS exemptions applied.
2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. For packaging details, go to our website at https://www.diodes.com/design/support/packaging/diodes-packaging/.
5. 50 devices per tube.

Marking Information



= Manufacturer's Marking
DGTD65T15H2 = Product Type Marking Code
YY = Year (ex: 26 = 2026)
LLLLL = Lot Code
WW = Week (01 to 53)

NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

Absolute Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

Characteristic		Symbol	Value	Unit
Collector-Emitter Voltage		V_{CE}	650	V
DC Collector Current, Limited by T_{jmax}	T_C = 25°C	I_C	30	A
	T_C = 100°C		15	A
Pulsed Collector Current, t_p Limited by T_{jmax}		I_{Cpuls}	60	A
Diode Forward Current Limited by T_{jmax}	T_C = 25°C	I_F	30	A
	T_C = 100°C		15	A
Diode Pulsed Current, t_p Limited by T_{jmax}		I_{Fpuls}	60	A
Gate-Emitter Voltage		V_{GE}	±20	V
Short-Circuit Withstand Time $V_{CC} \leq$ 360V, V_{GE} = 15V, T_j = 150°C		t_{SC}	5	µs

Thermal Characteristics (@T_A = +25°C, unless otherwise specified.)


Characteristic		Symbol	Value	Unit
Power Dissipation Linear Derating Factor (Note 7)	T_C = 25°C	P_D	48	W
	T_C = 100°C		24	
Thermal Resistance, Junction to Ambient (Note 6)		$R_{\theta JA}$	62	°C/W
Thermal Resistance, Junction to Case for IBGT (Note 7)		$R_{\theta JC}$	3.0	
Thermal Resistance, Junction to Case for Diode (Note 7)		$R_{\theta JC}$	5.0	
Operating Temperature		T_j	-40 to 175	°C
Storage Temperature Range		T_{STG}	-55 to 150	

Notes: 6. For a device mounted in a socket in still air conditions. Collector lead length 10mm.
7. For a device mounted on a Force Cooled Aluminium Heatsink 80mm x 80mm x 60mm.


NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.


Thermal Characteristics and Derating Information




Transient Thermal Impedance




Transient Thermal Impedance




Derating Curve



Derating Curve



Transient Thermal Impedance



Case Temperature-Collector Current

NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

Electrical Characteristics (@T_J = +25°C, unless otherwise specified.)

Parameter		Symbol	Min	Typ	Max	Unit	Condition
STATIC CHARACTERISTICS							
Collector-Emitter Breakdown Voltage		BV_{CES}	650	—	—	V	I_C = 2mA, V_{GE} = 0V
Collector-Emitter Saturation Voltage	T_j = 25°C	$V_{CE(sat)}$	—	1.65	2.00	V	I_C = 15A, V_{GE} = 15V
	T_j = 175°C		—	1.90	—		
Diode Forward Voltage	T_j = 25°C	V_F	—	1.85	2.30	V	V_{GE} = 0V, I_F = 15A
	T_j = 175°C		—	1.95	—		
Gate-Emitter Threshold Voltage		$V_{GE(th)}$	4.5	5.5	6.5	V	V_{CE} = V_{GE}, I_C = 0.5mA
Zero Gate Voltage Collector Current		I_{CES}	—	—	20	μA	V_{CE} = 650V, V_{GE} = 0V, T_j = 25°C
Gate-Emitter Leakage Current		I_{GES}	—	—	±100	nA	V_{GE} = 20V, V_{CE} = 0V
DYNAMIC CHARACTERISTICS							
Total Gate Charge		Q_g	—	61	—	nC	V_{CE} = 520V, I_C = 15A, V_{GE} = 15V
Gate-Emitter Charge		Q_{ge}	—	11	—		
Gate-Collector Charge		Q_{gc}	—	35	—		
Input Capacitance		C_{ies}	—	1129	—	pF	V_{CE} = 25V, V_{GE} = 0V, f = 1MHz
Reverse Transfer Capacitance		C_{res}	—	57	—		
Output Capacitance		C_{oes}	—	31	—		
SWITCHING CHARACTERISTICS							
Turn-On Delay Time		$t_{d(on)}$	—	19	—	ns	V_{GE} = 15V, V_{CC} = 400V, I_C = 15A, R_G = 10Ω, Inductive Load, T_j = 25°C
Rise Time		t_r	—	27	—		
Turn-Off Delay Time		$t_{d(off)}$	—	128	—		
Fall Time		t_f	—	32	—		
Turn-On Switching Energy		E_{on}	—	270	—	μJ	
Turn-Off Switching Energy		E_{off}	—	86	—		
Total Switching Energy		E_{ts}	—	356	—		
Turn-On Delay Time		$t_{d(on)}$	—	17	—	ns	V_{GE} = 15V, V_{CC} = 400V, I_C = 15A, R_G = 10Ω, Inductive Load, T_j = 175°C
Rise Time		t_r	—	29	—		
Turn-Off Delay Time		$t_{d(off)}$	—	150	—		
Fall Time		t_f	—	130	—		
Turn-On Switching Energy		E_{on}	—	342	—	μJ	
Turn-Off Switching Energy		E_{off}	—	288	—		
Total Switching Energy		E_{ts}	—	630	—		
Reverse-Recovery Time		t_{rr}	—	150	—	ns	I_F = 15A, di_F/dt = 200A/μs, T_j = 25°C
Reverse-Recovery Current		I_{rr}	—	5.2	—	A	
Reverse-Recovery Charge		Q_{rr}	—	390	—	nC	
Reverse-Recovery Time		t_{rr}	—	207	—	ns	I_F = 15A, di_F/dt = 200A/μs, T_j = 175°C
Reverse-Recovery Current		I_{rr}	—	6.1	—	A	
Reverse-Recovery Charge		Q_{rr}	—	631	—	nC	

NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

Typical Performance Characteristics (@T_A = +25°C, unless otherwise specified.)




Fig.1 Typical Output Characteristics(T_J=25℃)




Fig.2 Typical Output Characteristics(T_J=175℃)




Fig.3 Typical Transfer Characteristics




Fig.4 Typical Collector-Emitter Saturation Voltage -Junction Temperature




Fig.5 Diode Forward Characteristics




Fig.6 Diode Forward-Junction Temperature

NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

Typical Performance Characteristics (@T_A = +25°C, unless otherwise specified.) (continued)




Fig.7 Threshold Voltage-Junction Temperature




Fig.8 Typical Capacitance




Fig.9 Typical Gate Charge




Fig.10 Typical Turn on-Collector Current




Fig.11 Typical Turn off-Collector Current




Fig.12 Switching Loss-Collector Current

NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

Typical Performance Characteristics (@T_A = +25°C, unless otherwise specified.) (continued)




Fig.13 Turn on Characteristics-Gate Resistance




Fig.14 Turn off Characteristics-Gate Resistance




Fig.15 Switching Loss-Gate Resistance




Fig.16 Turn on Characteristics-Junction Temperature




Fig.17 Turn off Characteristics-Junction Temperature




Fig.18 Switching Loss-Junction Temperature


NOT RECOMMENDED FOR NEW DESIGN


© 2026 Copyright Diodes Incorporated. All Rights Reserved.

Package Outline Dimensions

Please see http://www.diodes.com/package-outlines.html for the latest version.

ITO220AB (Type MC)





ITO220AB (Type MC)			
Dim	**Min**	**Max**	**Typ**
A	4.30	4.80	--
A1	2.50	3.10	--
A2	2.30	2.90	--
b	0.50	1.00	--
b1	0.95	1.70	--
c	0.40	0.80	--
D	14.50	16.40	--
H1	6.20	7.20	--
E	9.60	10.40	--
e	--	--	2.54
e1	--	--	5.08
L	12.20	14.20	--
L1	2.90	4.70	--
P	3.00	3.40	--
Q	2.40	3.50	--
All Dimensions in mm			

NOT RECOMMENDED FOR NEW DESIGN

Note: For high-voltage applications, the appropriate industry sector guidelines should be considered with regards to creepage and clearance distances between device terminals and PCB tracking.

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

IMPORTANT NOTICE

1. DIODES INCORPORATED (Diodes) AND ITS SUBSIDIARIES MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes' products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes' products. Diodes' products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of Diodes' products for their intended applications, (c) ensuring their applications, which incorporate Diodes' products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.

3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes' websites, harmless against all damages and liabilities.

4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes' website) under this document.

5. Diodes' products are provided subject to Diodes' Standard Terms and Conditions of Sale (https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.

6. Diodes' products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes' products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.

7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.

8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.

9. This Notice may be periodically updated with the most recent version available at https://www.diodes.com/about/company/terms-and-conditions/important-notice

The Diodes logo is a registered trademark of Diodes Incorporated in the United States and other countries.
All other trademarks are the property of their respective owners.
© 2026 Diodes Incorporated. All Rights Reserved.

www.diodes.com

NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.