DMN3024LK3

30V TO252 (DPAK) N-CHANNEL ENHANCEMENT MODE MOSFET

Please click here to visit our online spice models database.

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)}$	I_D T_A = 25°C
30V	24mΩ @ V_{GS}= 10V	14.4A
	39mΩ @ V_{GS}= 4.5V	11.6A

Features and Benefits

- Low on-resistance
- Fast switching speed
- Low gate drive
- "Green" component and RoHS compliant (Note 1)

Description and Applications

This new generation MOSFET has been designed to minimize the on-state resistance ($R_{DS(on)}$) and yet maintain superior switching performance, making it ideal for high efficiency power management applications.


- Backlighting
- DC-DC Converters
- Power management functions

Mechanical Data


- Case: TO-252 (DPAK)
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0 (Note 1)
- Moisture Sensitivity: Level 1 per J-STD-020D
- Terminals Connections: See Diagram
- Terminals: Matte Tin Finish annealed over Copper leadframe. Solderable per MIL-STD-202, Method 208
- Marking Information: See Below
- Ordering Information: See Below
- Weight: 0.33 grams (approximate)



TOP VIEW



PIN OUT -TOP VIEW



Equivalent Circuit

Ordering Information (Note 1)

Product	Marking	Reel size (inches)	Tape width (mm)	Quantity per reel
DMN3024LK3-13	N3024L	13	16	2,500

Note: 1. Diodes, Inc. defines "Green" products as those which are Eu RoHS compliant and contain no halogens or antimony compounds; further information about Diodes Inc.'s "Green" Policy can be found on our website. For packaging details, go to our website.

Marking Information



= Manufacturer's Marking
N3024L = Product Type Marking Code
YYWW = Date Code Marking
YY = Year (ex: 09 = 2009)
WW = Week (01-52)

© Diodes Incorporated

Maximum Ratings @T_A = 25°C unless otherwise specified

Characteristic			Symbol	Value	Unit
Drain-Source voltage			V_{DSS}	30	V
Gate-Source voltage			V_{GS}	±20	V
Continuous Drain current	V_{GS} = 10V	(Note 3)	I_D	14.4	A
		T_A=70°C (Note 3)		12.0	
		(Note 2)		9.78	
Pulsed Drain current	V_{GS}= 10V	(Note 4)	I_{DM}	46.5	A
Continuous Source current (Body diode)		(Note 3)	I_S	12	A
Pulsed Source current (Body diode)		(Note 4)	I_{SM}	46.5	A


Thermal Characteristics @T_A = 25°C unless otherwise specified

Characteristic		Symbol	Value	Unit
Power dissipation Linear derating factor	(Note 2)	P_D	4.1 32.5	W mW/°C
	(Note 3)		8.9 71.4	
	(Note 5)		2.17 17.4	
Thermal Resistance, Junction to Ambient	(Note 2)	$R_{\theta JA}$	30.8	°C/W
	(Note 3)		14.0	
	(Note 5)		57.6	
Thermal Resistance, Junction to Lead	(Note 6)	$R_{\theta JL}$	2.24	
Operating and storage temperature range		T_J, T_{STG}	-55 to 150	°C


Notes:
2. For a device surface mounted on 50mm x 50mm x 1.6mm FR4 PCB with high coverage of single sided 2oz copper, in still air conditions; the device is measured when operating in a steady-state condition.
3. Same as note 2, except the device is measured at t ≤ 10 sec.
4. Same as note 2, except the device is pulsed with D = 0.02 and pulse width 300 µs. The pulse current is limited by the maximum junction temperature.
5. For a device surface mounted on 25mm x 25mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions; the device is measured when operating in a steady-state condition.
6. Thermal resistance from junction to solder-point (at the end of the drain lead).

© Diodes Incorporated


Thermal Characteristics




Safe Operating Area




Safe Operating Area




Transient Thermal Impedance



Transient Thermal Impedance



Pulse Power Dissipation



Derating Curve

© Diodes Incorporated


Electrical Characteristics @T_A = 25°C unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	30	—	—	V	I_D = 250μA, V_{GS}= 0V
Zero Gate Voltage Drain Current	I_{DSS}	—	—	0.5	μA	V_{DS}= 30V, V_{GS}= 0V
Gate-Source Leakage	I_{GSS}	—	—	±100	nA	V_{GS}= ±20V, V_{DS}= 0V
ON CHARACTERISTICS						
Gate Threshold Voltage	$V_{GS(th)}$	1.0	—	3.0	V	I_D= 250μA, V_{DS}= V_{GS}
Static Drain-Source On-Resistance (Note 7)	$R_{DS\ (ON)}$	—	—	0.024	Ω	V_{GS}= 10V, I_D= 7.0A
				0.039		V_{GS}= 4.5V, I_D= 6.0A
Forward Transconductance (Notes 7 & 8)	g_{fs}	—	16.5	—	S	V_{DS}= 15V, I_D= 7.0A
Diode Forward Voltage (Note 7)	V_{SD}	—	0.82	1.2	V	I_S= 1.7A, V_{GS}= 0V
Reverse recovery time (Note 8)	t_{rr}		12	—	ns	I_S= 2.2A, di/dt= 100A/μs
Reverse recovery charge (Note 8)	Q_{rr}	—	4.8	—	nC	
DYNAMIC CHARACTERISTICS (Note 8)						
Input Capacitance	C_{iss}	—	608	—	pF	V_{DS}= 15V, V_{GS}= 0V f= 1MHz
Output Capacitance	C_{oss}	—	132	—	pF	
Reverse Transfer Capacitance	C_{rss}	—	71	—	pF	
Total Gate Charge	Q_g	—	12.9	—	nC	V_{DS}= 15V, V_{GS}= 10V I_D= 7A
Gate-Source Charge	Q_{gs}	—	2.5	—	nC	
Gate-Drain Charge	Q_{gd}	—	2.5	—	nC	
Turn-On Delay Time (Note 9)	$t_{D(on)}$	—	2.9	—	ns	V_{DD}= 15V, V_{GS}= 10V I_D= 1A, $R_G \cong$ 6.0Ω
Turn-On Rise Time (Note 9)	t_r	—	3.3	—	ns	
Turn-Off Delay Time (Note 9)	$t_{D(off)}$	—	16	—	ns	
Turn-Off Fall Time (Note 9)	t_f	—	8	—	ns	


Notes:
7. Measured under pulsed conditions. Pulse width ≤ 300μs; duty cycle ≤ 2%
8. For design aid only, not subject to production testing.
9. Switching characteristics are independent of operating junction temperatures.

© Diodes Incorporated


Typical Characteristics




Output Characteristics




Output Characteristics




Typical Transfer Characteristics



Normalised Curves v Temperature




On-Resistance v Drain Current




Source-Drain Diode Forward Voltage

© Diodes Incorporated

Typical Characteristics - continued




Capacitance v Drain-Source Voltage




Gate-Source Voltage v Gate Charge


Test Circuits




Basic gate charge waveform



Gate charge test circuit




Switching time waveforms



Switching time test circuit

© Diodes Incorporated


Package Outline Dimensions



DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min	Max	Min	Max		Min	Max	Min	Max
A	0.086	0.094	2.18	2.39	**e**	0.090 BSC		2.29 BSC	
A1	-	0.005	-	0.127	**H**	0.370	0.410	9.40	10.41
b	0.020	0.035	0.508	0.89	**L**	0.055	0.070	1.40	1.78
b2	0.030	0.045	0.762	1.14	**L1**	0.108 REF		2.74 REF	
b3	0.205	0.215	5.21	5.46	**L2**	0.020 BSC		0.508 BSC	
c	0.018	0.024	0.457	0.61	**L3**	0.035	0.065	0.89	1.65
c2	0.018	0.023	0.457	0.584	**L4**	0.025	0.040	0.635	1.016
D	0.213	0.245	5.41	6.22	**L5**	0.045	0.060	1.14	1.52
D1	0.205	-	5.21	-	**θ1°**	0°	10°	0°	10°
E	0.250	0.265	6.35	6.73	**θ°**	0°	15°	0°	15°
E1	0.170	-	4.32	-	-	-	-	-	-

© Diodes Incorporated

Suggested Pad Layout



IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2009, Diodes Incorporated

www.diodes.com

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.