60V N-CHANNEL ENHANCEMENT MODE MOSFET

Product Summary

$V_{(BR)DSS}$	$R_{DS(on)}$	I_D T_A = +25°C
60V	66mΩ @ V_{GS} = 10V	5.0A
	97mΩ @ V_{GS} = 4.5V	4.1A

Features and Benefits

- Low on-resistance
- Fast switching speed
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**
- **PPAP Capable (Note 4)**

Description and Applications


This MOSFET is designed to minimize the on-state resistance and yet maintain superior switching performance, making it ideal for high efficiency power management applications.

- Motor Control
- Backlighting
- DC-DC Converters
- Power Management Functions


Mechanical Data

- Case: SO-8
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals Connections: See Diagram Below
- Terminals: Finish – Tin Finish Annealed over Copper Leadframe. Solderable per MIL-STD-202, Method 208 e3
- Weight: 0.074 grams (Approximate)


SO-8



Top View



Top View



Equivalent Circuit


Ordering Information (Notes 4 & 5)

Part Number	Compliance	Case	Packaging
DMN6066SSS-13	Commercial	SO-8	2,500/Tape & Reel
DMN6066SSSQ-13	Automotive	SO-8	2,500/Tape & Reel

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
2. See http://www.diodes.com/quality/lead_free.html for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. Automotive products are AEC-Q101 qualified and are PPAP capable. Automotive, AEC-Q101 and standard products are electrically and thermally the same, except where specified. For more information, please refer to http://www.diodes.com/quality/product_grade_definitions/.
5. For packaging details, go to our website at http://www.diodes.com/products/packages.html.

Marking Information

SO-8



= Manufacturer's Marking
N6066SS = Product Type Marking Code
YYWW = Date Code Marking
YY = Year (ex: 09 = 2009)
WW = Week (01 - 53)

© Diodes Incorporated

Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

Characteristic			Symbol	Value	Unit
Drain-Source Voltage			V_{DSS}	60	V
Gate-Source Voltage		(Note 6)	V_{GS}	±20	V
Single Pulsed Avalanche Energy		(Note 11)	E_{AS}	37.5	mJ
Single Pulsed Avalanche Current		(Note 11)	I_{AS}	5.0	A
Continuous Drain Current	V_{GS} = 10V	(Note 8)	I_D	5.0	A
		T_A = +70°C (Note 8)		4.0	
		(Note 7)		3.7	
Pulsed Drain Current	V_{GS} = 10V	(Note 9)	I_{DM}	23	A
Continuous Source Current (Body diode)		(Note 8)	I_S	4.0	A
Pulsed Source Current (Body diode)		(Note 9)	I_{SM}	23	A


Thermal Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic		Symbol	Value	Unit
Power Dissipation	(Note 7)	P_D	1.56	W
Linear Derating Factor			12.5	mW/°C
	(Note 8)		2.81	W
			22.5	mW/°C
Thermal Resistance, Junction to Ambient	(Note 7)	$R_{\theta JA}$	80.0	°C/W
	(Note 8)		44.5	
Thermal Resistance, Junction to Lead	(Note 10)	$R_{\theta JL}$	37.0	°C/W
Operating and Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C


Notes:
6. AEC-Q101 V_{GS} maximum is ±16V.
7. For a device surface mounted on 25mm x 25mm x 1.6mm FR4 PCB with high coverage of single sided 1oz copper, in still air conditions; the device is measured when operating in a steady-state condition.
8. Same as note (7), except the device is measured at t ≤ 10 sec.
9. Same as note (7), except the device is pulsed with D= 0.02 and pulse width 300 µs. The pulse current is limited by the maximum junction temperature.
10. Thermal resistance from junction to solder-point (at the end of the drain lead).
11. UIS in production with L = 3.0mH, I_{AS} = 5.0A, R_G = 25Ω, V_{DD}=50V, starting T_J = +25°C.

© Diodes Incorporated


Thermal Characteristics




Safe Operating Area



Derating Curve



Transient Thermal Impedance



Pulse Power Dissipation

© Diodes Incorporated


Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV_{DSS}	60	—	—	V	I_D = 250µA, V_{GS} = 0V
Zero Gate Voltage Drain Current	I_{DSS}	—	—	0.5	µA	V_{DS} = 60V, V_{GS} = 0V
Gate-Source Leakage	I_{GSS}	—	—	±100	nA	V_{GS} = ±20V, V_{DS} = 0V
ON CHARACTERISTICS						
Gate Threshold Voltage	$V_{GS(th)}$	1.0	—	3.0	V	I_D = 250µA, V_{DS} = V_{GS}
Static Drain-Source On-Resistance (Note 12)	$R_{DS\ (ON)}$	—	0.048	0.066	Ω	V_{GS} = 10V, I_D = 4.5A
			0.068	0.097		V_{GS} = 4.5V, I_D = 3.5A
Forward Transconductance (Notes 12 & 13)	g_{fs}	—	19.2	—	S	V_{DS} = 15V, I_D = 6A
Diode Forward Voltage (Note 12)	V_{SD}	—	0.89	1.15	V	I_S = 4.5A, V_{GS} = 0V
Reverse Recovery Time (Note 13)	t_{rr}		23	—	ns	I_S = 2.4A, di/dt = 100A/µs
Reverse Recovery Charge (Note 13)	Q_{rr}	—	19.7	—	nC	
DYNAMIC CHARACTERISTICS (Note 13)						
Input Capacitance	C_{iss}	—	502	—	pF	V_{DS} = 30V, V_{GS} = 0V f = 1MHz
Output Capacitance	C_{oss}	—	45.7	—	pF	
Reverse Transfer Capacitance	C_{rss}	—	27.1	—	pF	
Total Gate Charge (Note 14)	Q_g	—	5.4	—	nC	V_{GS} = 4.5V
Total Gate Charge (Note 14)	Q_g	—	10.3	—	nC	V_{GS} = 10V V_{DS} = 30V I_D = 4.5A
Gate-Source Charge (Note 14)	Q_{gs}	—	1.7	—	nC	
Gate-Drain Charge (Note 14)	Q_{gd}	—	3.2	—	nC	
Turn-On Delay Time (Note 14)	$t_{D(on)}$	—	2.7	—	ns	V_{DD} = 30V, V_{GS} = 10V I_D = 1A, $R_G \cong 6.0\Omega$
Turn-On Rise Time (Note 14)	t_r	—	2.4	—	ns	
Turn-Off Delay Time (Note 14)	$t_{D(off)}$	—	14.7	—	ns	
Turn-Off Fall Time (Note 14)	t_f	—	5.4	—	ns	


Notes:
12. Measured under pulsed conditions. Pulse width ≤ 300µs; duty cycle ≤ 2%.
13. For design aid only, not subject to production testing.
14. Switching characteristics are independent of operating junction temperatures.

© Diodes Incorporated


Typical Characteristics




Output Characteristics




Output Characteristics




Typical Transfer Characteristics



Normalised Curves v Temperature




On-Resistance v Drain Current




Source-Drain Diode Forward Voltage

© Diodes Incorporated


Typical Characteristics (continued)



Capacitance v Drain-Source Voltage




Gate-Source Voltage v Gate Charge




Single-Pulsed Avalanche Rating

© Diodes Incorporated


Test Circuits




Basic gate charge waveform



Gate charge test circuit



Switching time waveforms




Switching time test circuit

© Diodes Incorporated

Package Outline Dimensions


Please see AP02002 at http://www.diodes.com/datasheets/ap02002.pdf for the latest version.



SO-8		
Dim	**Min**	**Max**
A	-	1.75
A1	0.10	0.20
A2	1.30	1.50
A3	0.15	0.25
b	0.3	0.5
D	4.85	4.95
E	5.90	6.10
E1	3.85	3.95
e	1.27 Typ	
h	-	0.35
L	0.62	0.82
θ	0°	8°
All Dimensions in mm		

Suggested Pad Layout

Please see AP02001 at http://www.diodes.com/datasheets/ap02001.pdf for the latest version.



Dimensions	Value (in mm)
X	0.60
Y	1.55
C1	5.4
C2	1.27

© Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

   1. are intended to implant into the body, or
   2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2015, Diodes Incorporated

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.