Product Summary

BV_{DSS}	$R_{DS(ON)}$ Max	I_D T_A = +25°C
-20V	78mΩ @ V_{GS} = -8V	-3.4A
	100mΩ @ V_{GS} = -4.5V	-3.0A

Description

This new generation MOSFET is designed to minimize the footprint in handheld and mobile application. It can be used to replace many small signals MOSFET with as really small footprint.

Applications

- Battery Management
- Load Switch
- Battery Protection
- Handheld and Mobile Application

Features and Benefits


- Low Q_g & Q_{gd}
- Small Footprint
- Low Profile 0.225mm Height
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**

Mechanical Data


- Case: X4-DSN1006-3
- Terminal Connections: See Diagram Below
- Moisture Sensitivity: Level 1 per J-STD-020
- Backside Lamination: A Protective Polymer Film
- Terminals: Finish — NiPdAu.or NiAu Solderable per MIL-STD-202, Method 208 e4



X4-DSN1006-3 (Type B)



Top View



Equivalent Circuit

Ordering Information (Note 4)

Part Number	Case	Packaging
DMP2079LCA3-7	X4-DSN1006-3 (Type B)	10k/Tape & Reel

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. For packaging details, go to our website at https://www.diodes.com/design/support/packaging/diodes-packaging/.

Marking Information



R = Product Type Marking Code
YM = Date Code Marking
Y or $\overline{Y}$ = Year (ex: G = 2019)
M or $\overline{M}$ = Month (ex: 9 = September)

Date Code Key

Year	2018	2019	2020	2021	2022	2023	2024	2025	2026
Code	F	G	H	I	J	K	L	M	N

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

© Diodes Incorporated

Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

Characteristic			Symbol	Value	Unit
Drain-Source Voltage			V_{DSS}	-20	V
Gate-Source Voltage			V_{GSS}	-12	V
Continuous Drain Current (Note 5) V_{GS} = -8V	Steady State	T_A = +25°C T_A = +70°C	I_D	-3.4 -2.7	A
Continuous Drain Current (Note 5) V_{GS} = -4.5V	Steady State	T_A = +25°C T_A = +70°C	I_D	-3.0 -2.4	A
Pulsed Drain Current (Note 6)			I_{DM}	-13	A
Human Body Model (HBM)			$V_{(ESD)}$	4	kV

Thermal Characteristics

Characteristic	Symbol	Value	Unit
Power Dissipation (Note 7)	P_D	0.81	W
Thermal Resistance, Junction to Ambient @T_A = +25°C (Note 7)	$R_{\theta JA}$	155.4	°C/W
Power Dissipation (Note 5)	P_D	1.4	W
Thermal Resistance, Junction to Ambient @T_A = +25°C (Note 5)	$R_{\theta JA}$	90.4	°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150	°C

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 8)						
Drain-Source Breakdown Voltage	BV_{DSS}	-20	—	—	V	V_{GS} = 0V, I_D = -250µA
Zero Gate Voltage Drain Current T_J = +25°C	I_{DSS}	—	—	-100	nA	V_{DS} = -16V, V_{GS} = 0V
Gate-Source Leakage	I_{GSS}	—	—	-50	nA	V_{GS} = -12V, V_{DS} = 0V
ON CHARACTERISTICS (Note 8)						
Gate Threshold Voltage	$V_{GS(TH)}$	-0.7	-0.9	-1.2	V	V_{DS} = V_{GS}, I_D = -250µA
Static Drain-Source On-Resistance	$R_{DS(ON)}$	—	64	78	mΩ	V_{GS} = -8V, I_D = -0.5A
		—	77	100		V_{GS} = -4.5V, I_D = -0.5A
		—	113	165		V_{GS} = -2.5V, I_D = -0.5A
		—	188	600		V_{GS} = -1.8V, I_D = -0.1A
Diode Forward Voltage	V_{SD}	—	-0.7	-1.0	V	V_{GS} = 0V, I_S = -0.5A
Reverse Recovery Charge	Q_{RR}	—	1.3	—	nC	V_{DD} = -10V, I_F = -1A, di/dt = 100A/µs
Reverse Recovery Time	t_{RR}	—	7.7	—	ns	
DYNAMIC CHARACTERISTICS (Note 9)						
Input Capacitance	C_{iss}	—	152	—	pF	V_{DS} = -10V, V_{GS} = 0V, f = 1MHz
Output Capacitance	C_{oss}	—	78	—		
Reverse Transfer Capacitance	C_{rss}	—	4.3	—		
Series Gate Resistance	R_G	—	21	—	Ω	f = 1MHz, V_{GS} = 0V, V_{DS} = 0V
Total Gate Charge	Q_g	—	1.1	—	nC	V_{GS} = -4.5V, V_{DS} = -10V, I_D = -0.5A
Gate-Source Charge	Q_{gs}	—	0.2	—		
Gate-Drain Charge	Q_{gd}	—	0.2	—		
Gate Charge at V_{TH}	$Q_{g(th)}$	—	3.6	—		
Turn-On Delay Time	$t_{D(ON)}$	—	4.1	—	ns	V_{DS} = -10V, V_{GS} = -4.5V, R_G = 2Ω, I_D = -0.5A
Turn-On Rise Time	t_R	—	5.6	—		
Turn-Off Delay Time	$t_{D(OFF)}$	—	9.5	—		
Turn-Off Fall Time	t_F	—	4.6	—		

Notes:
5. Device mounted on FR-4 material with 1-inch^2 (6.45-cm^2), 2-oz. (0.071-mm thick) Cu.
6. Repetitive rating, pulse width limited by junction temperature.
7. Device mounted on FR-4 PCB with minimum recommended pad layout, single sided.
8. Short duration pulse test used to minimize self-heating effect.
9. Guaranteed by design. Not subject to production testing.

© Diodes Incorporated




Figure 1. Typical Output Characteristic




Figure 2. Typical Transfer Characteristic




Figure 3. Typical On-Resistance vs. Drain Current and Gate Voltage




Figure 4. Typical Transfer Characteristic




Figure 5. Typical On-Resistance vs. Drain Current and Junction Temperature




Figure 6. On-Resistance Variation with Junction Temperature

© Diodes Incorporated




Figure 7. On-Resistance Variation with Junction Temperature




Figure 8. Gate Threshold Variation vs. Junction Temperature




Figure 9. Diode Forward Voltage vs. Current




Figure 10. Gate Charge




Figure 11. SOA, Safe Operation Area

© Diodes Incorporated




Figure 12. Single Pulse Maximum Power Dissipation





Figure 13. Transient Thermal Resistance

© Diodes Incorporated

Package Outline Dimensions

Please see http://www.diodes.com/package-outlines.html for the latest version.

X4-DSN1006-3 (Type B)




X4-DSN1006-3 (Type B)			
Dim	**Min**	**Max**	**Typ**
A	0.20	0.25	0.225
A4	0.18	0.22	0.20
b	0.14	0.16	0.15
b2	0.49	0.51	0.50
D	0.56	0.64	0.60
E	0.96	1.04	1.00
e	--	--	0.35
e1	--	--	0.65
k	--	--	0.325
L	0.24	0.26	0.25
La	0.24	0.26	0.25
All Dimensions in mm			

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.

X4-DSN1006-3 (Type B)



Dimensions	Value (in mm)
G	0.40
G1	0.20
X	0.15
X1	0.50
Y	0.25
Y1	0.90

© Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or

2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2019, Diodes Incorporated

www.diodes.com

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.