Ordering number : EN6666B

5LP01S

P-Channel Small Signal MOSFET
−50V, −0.07A, 23Ω, Single SMCP

ON Semiconductor®
http://onsemi.com

Features

- Low ON-resistance
- Ultrahigh-speed switching
- 2.5V drive

Specifications

Absolute Maximum Ratings at Ta=25°C


Parameter	Symbol	Conditions	Ratings	Unit
Drain-to-Source Voltage	V_{DSS}		−50	V
Gate-to-Source Voltage	V_{GSS}		±10	V
Drain Current (DC)	I_D		−0.07	A
Drain Current (Pulse)	I_{DP}	PW≤10μs, duty cycle≤1%	−0.28	A
Allowable Power Dissipation	P_D		0.15	W
Channel Temperature	Tch		150	°C
Storage Temperature	Tstg		−55 to +150	°C

This product is designed to "ESD immunity < 200V*", so please take care when handling.
* Machine Model

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

Package Dimensions


unit : mm (typ)
7027-004




Product & Package Information

- Package : SMCP
- JEITA, JEDEC : SC-75, SOT-416
- Minimum Packing Quantity : 3,000 pcs./reel


Packing Type: TL



Marking




Electrical Connection



Electrical Characteristics at Ta=25°C


Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain-to-Source Breakdown Voltage	$V_{(BR)DSS}$	I_D= −1mA, V_{GS}=0V	−50			V
Zero-Gate Voltage Drain Current	I_{DSS}	V_{DS}= −50V, V_{GS}=0V			−1	μA
Gate-to-Source Leakage Current	I_{GSS}	V_{GS}=±8V, V_{DS}=0V			±10	μA
Cutoff Voltage	V_{GS}(off)	V_{DS}= −10V, I_D= −100μA	−0.4		−1.4	V
Forward Transfer Admittance	| yfs |	V_{DS}= −10V, I_D= −40mA	70	100		mS
Static Drain-to-Source On-State Resistance	R_{DS}(on)1	I_D= −40mA, V_{GS}= −4V		18	23	Ω
	R_{DS}(on)2	I_D= −20mA, V_{GS}= −2.5V		20	28	Ω
	R_{DS}(on)3	I_D= −5mA, V_{GS}= −1.5V		30	60	Ω
Input Capacitance	Ciss	V_{DS}= −10V, f=1MHz		7.4		pF
Output Capacitance	Coss			4.2		pF
Reverse Transfer Capacitance	Crss			1.3		pF
Turn-ON Delay Time	t_{d}(on)	See specified Test Circuit.		20		ns
Rise Time	t_r			35		ns
Turn-OFF Delay Time	t_{d}(off)			160		ns
Fall Time	t_f			150		ns
Total Gate Charge	Qg	V_{DS}= −10V, V_{GS}= −10V, I_D= −70mA		1.40		nC
Gate-to-Source Charge	Qgs			0.16		nC
Gate-to-Drain “Miller” Charge	Qgd			0.23		nC
Diode Forward Voltage	V_{SD}	I_S= −70mA, V_{GS}=0V		−0.85	−1.2	V


Switching Time Test Circuit





Ordering Information


Device	Package	Shipping	memo
5LP01S-TL-E	SMCP	3,000pcs./reel	Pb Free



ID – VDS
Drain Current, ID – A
Drain-to-Source Voltage, VDS – V
IT00090
–4.0V
–6.0V
–3.0V
–2.5V
–3.5V
–2.0V
VGS= –1.5V



ID – VGS
Drain Current, ID – A
Gate-to-Source Voltage, VGS – V
IT00091
VDS= –10V
Ta= –25°C
25°C
75°C



RDS(on) – VGS
Static Drain-to-Source On-State Resistance, RDS(on) – Ω
Gate-to-Source Voltage, VGS – V
IT00092
Ta=25°C
–40mA
ID= –20mA



RDS(on) – ID
Static Drain-to-Source On-State Resistance, RDS(on) – Ω
Drain Current, ID – A
IT00093
VGS= –4V
Ta=75°C
25°C
–25°C



RDS(on) – ID
Static Drain-to-Source On-State Resistance, RDS(on) – Ω
Drain Current, ID – A
IT00094
VGS= –2.5V
Ta=75°C
25°C
–25°C



RDS(on) – ID
Static Drain-to-Source On-State Resistance, RDS(on) – Ω
Drain Current, ID – A
IT00095
VGS= –1.5V
Ta=75°C
25°C
–25°C



RDS(on) – Ta
Static Drain-to-Source On-State Resistance, RDS(on) – Ω
Ambient Temperature, Ta – °C
IT00096
ID= –20mA, VGS= –2.5V
ID= –40mA, VGS= –4.0V



| yfs | – ID
Forward Transfer Admittance, | yfs | – S
Drain Current, ID – A
IT00097
VDS= –10V
Ta= –25°C
75°C
25°C


IS – VSD
VGS=0V
Source Current, IS – A
Ta=75°C
25°C
–25°C
Diode Forward Voltage, VSD – V
IT00098


SW Time – ID
VDD= –25V
VGS = –4V
Switching Time, SW Time – ns
tf
td(off)
tr
td(on)
Drain Current, ID – A
IT00099


Ciss, Coss, Crss – VDS
f=1MHz
Ciss, Coss, Crss – pF
Ciss
Coss
Crss
Drain-to-Source Voltage, VDS – V
IT00100


VGS – Qg
VDS= –10V
ID= –70mA
Gate-to-Source Voltage, VGS – V
Total Gate Charge, Qg – nC
IT00101


PD – Ta
Allowable Power Dissipation, PD – W
Ambient Temperature, Ta – °C
IT02381


Embossed Taping Specification

5LP01S-TL-E

1. Packing Format

Package Name	Carrier Tape Type	Maximum Number of devices contained (pcs)			Packing format	
		Reel	Inner box	Outer box	Inner BOX (C-1)	Outer BOX (A-7)
SMCP	SMCP	3,000	15,000	90,000	5 reels contained Dimensions:mm (external) 183×72×185	6 inner boxes contained Dimensions:mm (external) 440×195×210


Packing method



Reel label


Reel label, Inner box label

(unit:mm)



Outer box label

It is a label at the time of factory shipments. The form of a label may change in physical distribution process.




NOTE (1)
The LEAD FREE ※ description shows that the surface treatment of the terminal is lead free.


Label	JEITA Phase
••••••••••	JEITA Phase 3

2. Taping configuration

2-1. Carrier tape size (unit:mm)




2-2. Device placement direction




Those with one electrode terminal on the feed hole side·····TL

Outline Drawing

5LP01S-TL-E



Land Pattern Example



Note on usage : Since the 5LP01S is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC). SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.