International
IOR Rectifier

IRG8P50N120KDPbF
IRG8P50N120KD-EPbF


Insulated Gate Bipolar Transistor with Ultrafast Soft Recovery Diode

V_{CES} = 1200V


I_C = 50A, T_C =100°C

$t_{SC} \geq$ 10µs, $T_{J(max)}$ = 150°C


$V_{CE(ON)}$ typ. = 1.7V @ I_C = 35A



n-channel



IRG8P50N120KDPbF
TO-247AC



IRG8P50N120KD-EPbF
TO-247AD

G	C	E
Gate	Collector	Emitter

Applications

- Industrial Motor Drive
- UPS
- Solar Inverters
- Welding

Features	→	Benefits
Benchmark Low $V_{CE(ON)}$		High Efficiency in a Motor Drive Applications
10µs Short Circuit SOA		Increases margin for short circuit protection scheme
Positive $V_{CE(ON)}$ Temperature Coefficient		Excellent Current Sharing in Parallel Operation
Square RBSOA and high I_{LM} rating		Rugged Transient Performance
Lead-Free, RoHS compliant		Environmentally friendly

Base part number	Package Type	Standard Pack		Orderable Part Number
		Form	Quantity	
IRG8P50N120KDPbF	TO-247AC	Tube	25	IRG8P50N120KDPbF
IRG8P50N120KD-EPbF	TO-247AD	Tube	25	IRG8P50N120KD-EPbF

Absolute Maximum Ratings

	Parameter	Max.	Units
V_{CES}	Collector-to-Emitter Voltage	1200	V
I_C @ T_C = 25°C	Continuous Collector Current	80	A
I_C @ T_C = 100°C	Continuous Collector Current	50	
I_{CM}	Pulse Collector Current (see fig. 2)	105	
I_{LM}	Clamped Inductive Load Current (see fig. 3)①	140	
I_F @ T_C = 25°C	Diode Continuous Forward Current	45	
I_F @ T_C = 100°C	Diode Continuous Forward Current	25	
I_{FM}	Diode Maximum Forward Current ⑤	140	
V_{GE}	Continuous Gate-to-Emitter Voltage	±30	V
P_D @ T_C = 25°C	Maximum Power Dissipation	350	W
P_D @ T_C = 100°C	Maximum Power Dissipation	140	
T_J T_{STG}	Operating Junction and Storage Temperature Range	-40 to +150	C
	Soldering Temperature, for 10 sec.	300 (0.063 in. (1.6mm) from case)	
	Mounting Torque, 6-32 or M3 Screw	10 lbf·in (1.1 N·m)	

Thermal Resistance

	Parameter	Min.	Typ.	Max.	Units
$R_{\theta JC}$ (IGBT)	Thermal Resistance Junction-to-Case-(each IGBT) ②	—	—	0.36	°C/W
$R_{\theta JC}$ (Diode)	Thermal Resistance Junction-to-Case-(each Diode) ②	—	—	0.83	
$R_{\theta CS}$	Thermal Resistance, Case-to-Sink (flat, greased surface)	—	0.24	—	
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (typical socket mount)	—	40	—	

© 2014 International Rectifier

Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(BR)CES}$	Collector-to-Emitter Breakdown Voltage	1200	—	—	V	V_{GE} = 0V, I_C = 250µA ③
$\Delta V_{(BR)CES}/\Delta T_J$	Temperature Coeff. of Breakdown Voltage	—	0.93	—	V/°C	V_{GE} = 0V, I_C = 2mA (25°C-150°C)
$V_{CE(on)}$	Collector-to-Emitter Saturation Voltage	—	1.7	2.0	V	I_C = 35A, V_{GE} = 15V, T_J = 25°C
		—	2.0	—		I_C = 35A, V_{GE} = 15V, T_J = 150°C
$V_{GE(th)}$	Gate Threshold Voltage	5.0	—	6.5	V	V_{CE} = V_{GE}, I_C = 1.4mA
$\Delta V_{GE(th)}/\Delta T_J$	Threshold Voltage Temperature Coeff.	—	-16	—	mV/°C	V_{CE} = V_{GE}, I_C = 1.4mA (25°C-150°C)
gfe	Forward Transconductance	—	20	—	S	V_{CE} = 50V, I_C = 35A, PW = 20µs
I_{CES}	Collector-to-Emitter Leakage Current	—	1	35	µA	V_{GE} = 0V, V_{CE} = 1200V
		—	1.2	—	mA	V_{GE} = 0V, V_{CE} = 1200V, T_J = 150°C
I_{GES}	Gate-to-Emitter Leakage Current	—	—	±300	nA	V_{GE} = ±30V
V_F	Diode Forward Voltage Drop	—	2.1	2.7	V	I_F = 35A
		—	2.4	—		I_F = 35A, T_J = 150°C

Switching Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max④	Units	Conditions
Q_g	Total Gate Charge (turn-on)	—	210	315	nC	I_C = 35A
Q_{ge}	Gate-to-Emitter Charge (turn-on)	—	10	15		V_{GE} = 15V
Q_{gc}	Gate-to-Collector Charge (turn-on)	—	135	205		V_{CC} = 600V
E_{on}	Turn-On Switching Loss	—	2.3	—	mJ	I_C = 35A, V_{CC} = 600V, V_{GE}=15V R_G = 5Ω, T_J = 25°C Energy losses include tail & diode reverse recovery ⑥
E_{off}	Turn-Off Switching Loss	—	1.9	—		
E_{total}	Total Switching Loss	—	4.2	—		
$t_{d(on)}$	Turn-On delay time	—	35	—	ns	
t_r	Rise time	—	25	—		
$t_{d(off)}$	Turn-Off delay time	—	190	—		
t_f	Fall time	—	105	—		
E_{on}	Turn-On Switching Loss	—	3.8	—	mJ	I_C = 35A, V_{CC} = 600V, V_{GE}=15V R_G = 5Ω, T_J = 150°C Energy losses include tail & diode reverse recovery ⑥
E_{off}	Turn-Off Switching Loss	—	3.9	—		
E_{total}	Total Switching Loss	—	7.7	—		
$t_{d(on)}$	Turn-On delay time	—	30	—	ns	
t_r	Rise time	—	25	—		
$t_{d(off)}$	Turn-Off delay time	—	270	—		
t_f	Fall time	—	140	—		
C_{ies}	Input Capacitance	—	3300	—	pF	V_{GE} = 0V
C_{oes}	Output Capacitance	—	200	—		V_{CC} = 30V
C_{res}	Reverse Transfer Capacitance	—	105	—		f = 1.0Mhz
RBSOA	Reverse Bias Safe Operating Area	FULL SQUARE				T_J = 150°C, I_C = 140A V_{CC} = 960V, Vp ≤ 1200V V_{GE} = +20V to 0V
SCSOA	Short Circuit Safe Operating Area	10	—	—	µs	T_J = 150°C,V_{CC} = 600V, Vp ≤ 1200V V_{GE} = +15V to 0V
Erec	Reverse Recovery Energy of the Diode	—	0.52	—	mJ	T_J = 150°C
t_{rr}	Diode Reverse Recovery Time	—	170	—	ns	V_{CC} = 600V, I_F = 35A
I_{rr}	Peak Reverse Recovery Current	—	22	—	A	V_{GE} = 15V, Rg = 5Ω

Notes:

① V_{CC} = 80% (V_{CES}), V_{GE} = 20V.

② R_θ is measured at T_J of approximately 90°C.

③ Refer to AN-1086 for guidelines for measuring $V_{(BR)CES}$ safely.

④ Maximum limits are based on statistical sample size characterization.

⑤ Pulse width limited by max. junction temperature.

⑥ Values influenced by parasitic L and C in measurement.

 © 2014 International Rectifier




Fig. 1 - Typical Load Current vs. Frequency
(Load Current = I_{RMS} of fundamental)




Fig. 2 - Forward SOA
T_C = 25°C; T_J ≤ 150°C; V_{GE} = 15V




Fig. 3 - Reverse Bias SOA
T_J = 150°C; V_{GE} = 20V




Fig. 4 -Typ. IGBT Output Characteristics
T_J = 25°C; tp = 20µs




Fig. 5 - Typ. IGBT Saturation Voltage
V_{GE} = 15V; tp = 20µs

 © 2014 International Rectifier




Fig. 6 - Typ. Transfer Characteristics
V_{CE} = 50V; tp = 20µs




Fig. 7 - Typical Gate Charge vs. V_{GE}
I_{CE} = 35A




Fig. 8 - Typ. Energy Loss vs. I_C
V_{CE} = 600V, R_G = 5.0Ω; V_{GE} = 15V




Fig. 9 - Typ. Switching Time vs. I_C
T_J = 150°C; V_{CE} = 600V, R_G = 5.0Ω; V_{GE} = 15V




Fig. 10 - Typ. Energy Loss vs. R_G
V_{CE} = 600V, I_{CE} = 35A; V_{GE} = 15V




Fig. 11 - Typ. Switching Time vs. R_G
T_J = 150°C; V_{CE} = 600V, I_{CE} = 35A; V_{GE} = 15V

 © 2014 International Rectifier




Fig. 12 - Typ. I_{RR} vs. di/dt




Fig. 13 - Typ. Diode E_{RR} vs. I_F
T_J = 150°C




Fig. 14 - Typ. Diode Forward Voltage Drop Characteristics

 © 2014 International Rectifier




Fig. 15 - Maximum Transient Thermal Impedance, Junction-to-Case (IGBT)




Fig. 16 - Maximum Transient Thermal Impedance, Junction-to-Case (DIODE)

 © 2014 International Rectifier




Fig.C.T.1 - Gate Charge Circuit (turn-off)




Fig.C.T.2 - RBSOA Circuit




Fig.C.T.3 - S.C. SOA Circuit




Fig.C.T.4 - Switching Loss Circuit
(Board Stray Inductance 180nH)




Fig.C.T.5 - BVCES Filter Circuit

 © 2014 International Rectifier





Fig. WF1 - Typ. S.C. Waveform
@ T_J = 150°C using Fig. CT.3

 © 2014 International Rectifier

TO-247AC Package Outline

Dimensions are shown in millimeters (inches)



NOTES:

1. DIMENSIONING AND TOLERANCING AS PER ASME Y14.5M 1994.
2. DIMENSIONS ARE SHOWN IN INCHES.
3. CONTOUR OF SLOT OPTIONAL.
4. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005" (0.127) PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
5. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS D1 & E1.
6. LEAD FINISH UNCONTROLLED IN L1.
7. øP TO HAVE A MAXIMUM DRAFT ANGLE OF 1.5 ° TO THE TOP OF THE PART WITH A MAXIMUM HOLE DIAMETER OF .154 INCH.
8. OUTLINE CONFORMS TO JEDEC OUTLINE TO-247AC .

SYMBOL	DIMENSIONS				NOTES
	INCHES		MILLIMETERS		
	MIN.	MAX.	MIN.	MAX.	
A	.183	.209	4.65	5.31	
A1	.087	.102	2.21	2.59	
A2	.059	.098	1.50	2.49	
b	.039	.055	0.99	1.40	
b1	.039	.053	0.99	1.35	
b2	.065	.094	1.65	2.39	
b3	.065	.092	1.65	2.34	
b4	.102	.135	2.59	3.43	
b5	.102	.133	2.59	3.38	
c	.015	.035	0.38	0.89	
c1	.015	.033	0.38	0.84	
D	.776	.815	19.71	20.70	4
D1	.515	–	13.08	–	5
D2	.020	.053	0.51	1.35	
E	.602	.625	15.29	15.87	4
E1	.530	–	13.46	–	
E2	.178	.216	4.52	5.49	
e	.215 BSC		5.46 BSC		
øk	.010		0.25		
L	.559	.634	14.20	16.10	
L1	.146	.169	3.71	4.29	
øP	.140	.144	3.56	3.66	
øP1	–	.291	–	7.39	
Q	.209	.224	5.31	5.69	
S	.217 BSC		5.51 BSC		

LEAD ASSIGNMENTS

HEXFET

1.– GATE
2.– DRAIN
3.– SOURCE
4.– DRAIN

IGBTs, CoPACK

1.– GATE
2.– COLLECTOR
3.– EMITTER
4.– COLLECTOR

DIODES


1.– ANODE/OPEN
2.– CATHODE
3.– ANODE

TO-247AC Part Marking Information

Notes: This part marking information applies to devices produced after 02/26/2001

EXAMPLE: THIS IS AN IRFPE30
WITH ASSEMBLY
LOT CODE 5657
ASSEMBLED ON WW 35, 2001
IN THE ASSEMBLY LINE "H"

Note: "P" in assembly line position
indicates "Lead-Free"




TO-247AC package is not recommended for Surface Mount Application.

Note: For the most current drawing please refer to IR website at http://www.irf.com/package/

 © 2014 International Rectifier

TO-247AD Package Outline

Dimensions are shown in millimeters (inches)



NOTES:

1. DIMENSIONING AND TOLERANCING AS PER ASME Y14.5M 1994.
2. DIMENSIONS ARE SHOWN IN INCHES.
3. CONTOUR OF SLOT OPTIONAL.
4. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005" (0.127) PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
5. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS D1 & E1.
6. LEAD FINISH UNCONTROLLED IN L1.
7. øP TO HAVE A MAXIMUM DRAFT ANGLE OF 1.5 ° TO THE TOP OF THE PART WITH A MAXIMUM HOLE DIAMETER OF .154 INCH.
8. OUTLINE CONFORMS TO JEDEC OUTLINE TO-247AD.

SYMBOL	DIMENSIONS				NOTES
	INCHES		MILLIMETERS		
	MIN.	MAX.	MIN.	MAX.	
A	.183	.209	4.65	5.31	
A1	.087	.102	2.21	2.59	
A2	.059	.098	1.50	2.49	
b	.039	.055	0.99	1.40	
b1	.039	.053	0.99	1.35	
b2	.065	.094	1.65	2.39	
b3	.065	.092	1.65	2.34	
b4	.102	.135	2.59	3.43	
b5	.102	.133	2.59	3.38	
c	.015	.035	0.38	0.89	
c1	.015	.033	0.38	0.84	
D	.776	.815	19.71	20.70	4
D1	.515	–	13.08	–	5
D2	.020	.053	0.51	1.35	
E	.602	.625	15.29	15.87	4
E1	.530	–	13.46	–	
E2	.178	.216	4.52	5.49	
e	.215 BSC		5.46 BSC		
øk	.010		0.25		
L	.780	.827	19.57	21.00	
L1	.146	.169	3.71	4.29	
øP	.140	.144	3.56	3.66	
øP1	–	.291	–	7.39	
Q	.209	.224	5.31	5.69	
S	.217 BSC		5.51 BSC		

LEAD ASSIGNMENTS

HEXFET

1.– GATE
2.– DRAIN
3.– SOURCE
4.– DRAIN

IGBTs, CoPACK

1.– GATE
2.– COLLECTOR
3.– EMITTER
4.– COLLECTOR


DIODES

1.– ANODE/OPEN
2.– CATHODE
3.– ANODE

TO-247AD Part Marking Information

EXAMPLE: THIS IS AN IRGP30B120KD-E
WITH ASSEMBLY
LOT CODE 5657
ASSEMBLED ON WW 35, 2000
IN THE ASSEMBLY LINE "H"

Note: "P" in assembly line position
indicates "Lead-Free"



TO-247AD package is not recommended for Surface Mount Application.

Note: For the most current drawing please refer to IR website at http://www.irf.com/package/

 © 2014 International Rectifier

Qualification Information†

Qualification Level	Industrial† (per JEDEC JESD47F) ††	
Moisture Sensitivity Level	TO-247AC	N/A
	TO-247AD	N/A
RoHS Compliant	Yes	

† Qualification standards can be found at International Rectifier's web site: http://www.irf.com/product-info/reliability/

†† Applicable version of JEDEC standard at the time of product release.

 © 2014 International Rectifier

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.