IRGP4266PbF
IRGP4266-EPbF


Insulated Gate Bipolar Transistor

V_{CES} = 650V


I_C = 90A, T_C =100°C

$t_{SC} \geq$ 5.5µs, $T_{J(max)}$ = 175°C


$V_{CE(ON)}$ typ. = 1.7V @ I_C = 75A



n-channel



IRGP4266PbF
TO-247AC



IRGP4266-EPbF
TO-247AD

G	C	E
Gate	Collector	Emitter

Applications
- Industrial Motor Drive
- Inverters
- UPS
- Welding

Features	→	Benefits
Low $V_{CE(ON)}$ and switching Losses		High efficiency in a wide range of applications and switching frequencies
Square RBSOA and Maximum Junction Temperature 175°C		Improved reliability due to rugged hard switching performance and higher power capability
Positive $V_{CE\ (ON)}$ Temperature Coefficient		Excellent current sharing in parallel operation
5.5µs short circuit SOA		Enables short circuit protection scheme
Lead-Free, RoHS compliant		Environmentally friendly

Base part number	Package Type	Standard Pack		Orderable Part Number
		Form	Quantity	
IRGP4266PbF	TO-247AC	Tube	25	IRGP4266PbF
IRGP4266-EPbF	TO-247AD	Tube	25	IRGP4266-EPbF

Absolute Maximum Ratings

	Parameter	Max.	Units
V_{CES}	Collector-to-Emitter Voltage	650	V
I_C @ T_C = 25°C	Continuous Collector Current	140	A
I_C @ T_C = 100°C	Continuous Collector Current	90	
I_{CM}	Pulse Collector Current, V_{GE}=20V	300	
I_{LM}	Clamped Inductive Load Current, V_{GE}=20V ①	300	
V_{GE}	Continuous Gate-to-Emitter Voltage	±20	V
P_D @ T_C = 25°C	Maximum Power Dissipation	455	W
P_D @ T_C = 100°C	Maximum Power Dissipation	230	
T_J T_{STG}	Operating Junction and Storage Temperature Range	-40 to +175	°C
	Soldering Temperature, for 10 sec.	300 (0.063 in. (1.6mm) from case)	
	Mounting Torque, 6-32 or M3 Screw	10 lbf·in (1.1 N·m)	

Thermal Resistance

	Parameter	Min.	Typ.	Max.	Units
$R_{\theta JC}$	Thermal Resistance Junction-to-Case ②	–––	–––	0.33	°C/W
$R_{\theta CS}$	Thermal Resistance, Case-to-Sink (flat, greased surface)	–––	0.24	–––	
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient (typical socket mount)	–––	40	–––	

 © 2014 International Rectifier

Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions
$V_{(BR)CES}$	Collector-to-Emitter Breakdown Voltage	650	—	—	V	V_{GE} = 0V, I_C = 100µA ③
$\Delta V_{(BR)CES}/\Delta T_J$	Temperature Coeff. of Breakdown Voltage	—	570	—	mV/°C	V_{GE} = 0V, I_C = 1.0mA (25°C-175°C)
$V_{CE(on)}$	Collector-to-Emitter Saturation Voltage	—	1.7	2.1	V	I_C = 75A, V_{GE} = 15V, T_J = 25°C
		—	2.1	—		I_C = 75A, V_{GE} = 15V, T_J = 175°C
$V_{GE(th)}$	Gate Threshold Voltage	5.5	—	7.7	V	V_{CE} = V_{GE}, I_C = 2.1mA
$\Delta V_{GE(th)}/\Delta TJ$	Threshold Voltage temp. coefficient	—	-22	—	mV/°C	V_{CE}=V_{GE}, I_C = 2.1mA (25°C - 175°C)
gfe	Forward Transconductance	—	43	—	S	V_{CE} = 50V, I_C = 75A, PW = 20µs
I_{CES}	Collector-to-Emitter Leakage Current	—	1.0	25	µA	V_{GE} = 0V, V_{CE} = 650V
		—	1.1	—	mA	V_{GE} = 0V, V_{CE} = 650V, T_J = 175°C
I_{GES}	Gate-to-Emitter Leakage Current	—	—	±100	nA	V_{GE} = ±20V

Switching Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.④	Units	Conditions
Q_g	Total Gate Charge (turn-on)	—	140	210	nC	I_C = 75A
Q_{ge}	Gate-to-Emitter Charge (turn-on)	—	40	60		V_{GE} = 15V
Q_{gc}	Gate-to-Collector Charge (turn-on)	—	60	90		V_{CC} = 400V
E_{on}	Turn-On Switching Loss	—	3.2	4.2	mJ	I_C = 75A, V_{CC} = 400V, V_{GE} = 15V
E_{off}	Turn-Off Switching Loss	—	1.7	2.6		R_G = 10Ω, L = 200µH, T_J = 25°C
E_{total}	Total Switching Loss	—	4.9	6.8		Energy losses include tail & diode
$t_{d(on)}$	Turn-On delay time	—	80	95	ns	reverse recovery ⑤⑥
t_r	Rise time	—	85	105		
$t_{d(off)}$	Turn-Off delay time	—	200	220		
t_f	Fall time	—	40	55		
E_{on}	Turn-On Switching Loss	—	4.6	—	mJ	I_C = 75A, V_{CC} = 400V, V_{GE}=15V
E_{off}	Turn-Off Switching Loss	—	2.4	—		R_G=10Ω, L=200µH,T_J = 175°C
E_{total}	Total Switching Loss	—	7.0	—		Energy losses include tail & diode
$t_{d(on)}$	Turn-On delay time	—	60	—	ns	reverse recovery ⑤⑥
t_r	Rise time	—	95	—		
$t_{d(off)}$	Turn-Off delay time	—	205	—		
t_f	Fall time	—	60	—		
C_{ies}	Input Capacitance	—	4300	—	pF	V_{GE} = 0V
C_{oes}	Output Capacitance	—	230	—		V_{CC} = 30V
C_{res}	Reverse Transfer Capacitance	—	120	—		f = 1.0Mhz
RBSOA	Reverse Bias Safe Operating Area	FULL SQUARE				T_J = 175°C, I_C = 300A V_{CC} = 520V, Vp ≤ 650V Rg = 50Ω, V_{GE} = +20V to 0V
SCSOA	Short Circuit Safe Operating Area	5.5	—	—	µs	T_J = 150°C,V_{CC} = 400V, Vp ≤600V Rg = 50Ω, V_{GE} = +15V to 0V

Notes:

① V_{CC} = 80% (V_{CES}), V_{GE} = 20V, L = 50µH, R_G = 50Ω.
② R_θ is measured at T_J of approximately 90°C.
③ Refer to AN-1086 for guidelines for measuring $V_{(BR)CES}$ safely.
④ Maximum limits are based on statistical sample size characterization.
⑤ Pulse width limited by max. junction temperature.
⑥ Values influenced by parasitic L and C in measurement.

 © 2014 International Rectifier




Fig. 1 - Typical Load Current vs. Frequency
(Load Current= I_{RMS} of fundamental)




Fig. 2 - Maximum DC Collector Current vs. Case Temperature




Fig. 3 - Power Dissipation vs. Case Temperature




Fig. 4 - Forward SOA




Fig. 5 - Reverse Bias SOA
T_J = 175°C; V_{GE} = 20V

 © 2014 International Rectifier




Fig. 6 - Typ. IGBT Output Characteristics
T_J = -40°C; tp = 20µs




Fig. 7 - Typ. IGBT Output Characteristics
T_J = 25°C; tp = 20µs




Fig. 8 - Typ. IGBT Output Characteristics
T_J = 175°C; tp = 20µs




Fig. 9 - Typical V_{CE} vs. V_{GE}
T_J = -40°C




Fig. 10 - Typical V_{CE} vs. V_{GE}
T_J = 25°C




Fig. 11 - Typical V_{CE} vs. V_{GE}
T_J = 175°C

 © 2014 International Rectifier




Fig. 12 - Typ. Transfer Characteristics
V_{CE} = 50V; tp = 20µs




Fig. 13 - Typ. Energy Loss vs. I_C
T_J = 175°C; L = 200µH; V_{CE} = 400V, R_G = 10Ω; V_{GE} = 15V




Fig. 14 - Typ. Switching Time vs. I_C
T_J = 175°C; L = 200µH; V_{CE} = 400V, R_G = 10Ω; V_{GE} = 15V




Fig. 15 - Typ. Energy Loss vs. R_G
T_J = 175°C; L = 200µH; V_{CE} = 400V, I_{CE} = 75A; V_{GE} = 15V




Fig. 16 - Typ. Switching Time vs. R_G
T_J = 175°C; L = 200µH; V_{CE} = 400V, I_{CE} = 75A; V_{GE} = 15V




Fig. 17 - V_{GE} vs. Short Circuit Time
V_{CC} = 400V; T_C = 150°C

 © 2014 International Rectifier




Fig. 18 - Typ. Capacitance vs. V_{CE}




Fig. 19 - Typical Gate Charge vs. V_{GE}




Fig 20. Maximum Transient Thermal Impedance, Junction-to-Case

 © 2014 International Rectifier




Fig.C.T.1 - Gate Charge Circuit (turn-off)




Fig.C.T.2 - RBSOA Circuit




Fig.C.T.3 - S.C. SOA Circuit





Fig.C.T.4 - Switching Loss Circuit



Resistive Load

Fig.C.T.5 - Resistive Load Circuit




Fig.C.T.6 - BVCES Filter Circuit

 © 2014 International Rectifier




Fig. WF1 - Typ. Turn-off Loss Waveform
@ T_J = 175°C using Fig. CT.3




Fig. WF2 - Typ. Turn-on Loss Waveform
@ T_J = 175°C using Fig. CT.4





Fig. WF3 - Typ. S.C. Waveform
@ T_J = 150°C using Fig. CT.3

 © 2014 International Rectifier

TO-247AC Package Outline

Dimensions are shown in millimeters (inches)



NOTES:

1. DIMENSIONING AND TOLERANCING AS PER ASME Y14.5M 1994.
2. DIMENSIONS ARE SHOWN IN INCHES.
3. CONTOUR OF SLOT OPTIONAL.
4. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005" (0.127) PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
5. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS D1 & E1.
6. LEAD FINISH UNCONTROLLED IN L1.
7. øP TO HAVE A MAXIMUM DRAFT ANGLE OF 1.5 ° TO THE TOP OF THE PART WITH A MAXIMUM HOLE DIAMETER OF .154 INCH.
8. OUTLINE CONFORMS TO JEDEC OUTLINE TO-247AC .

SYMBOL	DIMENSIONS				NOTES
	INCHES		MILLIMETERS		
	MIN.	MAX.	MIN.	MAX.	
A	.183	.209	4.65	5.31	
A1	.087	.102	2.21	2.59	
A2	.059	.098	1.50	2.49	
b	.039	.055	0.99	1.40	
b1	.039	.053	0.99	1.35	
b2	.065	.094	1.65	2.39	
b3	.065	.092	1.65	2.34	
b4	.102	.135	2.59	3.43	
b5	.102	.133	2.59	3.38	
c	.015	.035	0.38	0.89	
c1	.015	.033	0.38	0.84	
D	.776	.815	19.71	20.70	4
D1	.515	–	13.08	–	5
D2	.020	.053	0.51	1.35	
E	.602	.625	15.29	15.87	4
E1	.530	–	13.46	–	
E2	.178	.216	4.52	5.49	
e	.215 BSC		5.46 BSC		
øk	.010		0.25		
L	.559	.634	14.20	16.10	
L1	.146	.169	3.71	4.29	
øP	.140	.144	3.56	3.66	
øP1	–	.291	–	7.39	
Q	.209	.224	5.31	5.69	
S	.217 BSC		5.51 BSC		

LEAD ASSIGNMENTS

HEXFET

1.– GATE
2.– DRAIN
3.– SOURCE
4.– DRAIN

IGBTs, CoPACK

1.– GATE
2.– COLLECTOR
3.– EMITTER
4.– COLLECTOR

DIODES


1.– ANODE/OPEN
2.– CATHODE
3.– ANODE

TO-247AC Part Marking Information

Notes: This part marking information applies to devices produced after 02/26/2001

EXAMPLE: THIS IS AN IRFPE30
WITH ASSEMBLY
LOT CODE 5657
ASSEMBLED ON WW 35, 2001
IN THE ASSEMBLY LINE "H"

Note: "P" in assembly line position
indicates "Lead-Free"




TO-247AC package is not recommended for Surface Mount Application.


Note: For the most current drawing please refer to IR website at http://www.irf.com/package/


 © 2014 International Rectifier


TO-247AD Package Outline

Dimensions are shown in millimeters (inches)









NOTES:

1. DIMENSIONING AND TOLERANCING AS PER ASME Y14.5M 1994.
2. DIMENSIONS ARE SHOWN IN INCHES.
3. CONTOUR OF SLOT OPTIONAL.
4. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005" (0.127) PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
5. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS D1 & E1.
6. LEAD FINISH UNCONTROLLED IN L1.
7. øP TO HAVE A MAXIMUM DRAFT ANGLE OF 1.5 ° TO THE TOP OF THE PART WITH A MAXIMUM HOLE DIAMETER OF .154 INCH.
8. OUTLINE CONFORMS TO JEDEC OUTLINE TO-247AD.

SYMBOL	DIMENSIONS				NOTES
	INCHES		MILLIMETERS		
	MIN.	MAX.	MIN.	MAX.	
A	.183	.209	4.65	5.31	
A1	.087	.102	2.21	2.59	
A2	.059	.098	1.50	2.49	
b	.039	.055	0.99	1.40	
b1	.039	.053	0.99	1.35	
b2	.065	.094	1.65	2.39	
b3	.065	.092	1.65	2.34	
b4	.102	.135	2.59	3.43	
b5	.102	.133	2.59	3.38	
c	.015	.035	0.38	0.89	
c1	.015	.033	0.38	0.84	
D	.776	.815	19.71	20.70	4
D1	.515	–	13.08	–	5
D2	.020	.053	0.51	1.35	
E	.602	.625	15.29	15.87	4
E1	.530	–	13.46	–	
E2	.178	.216	4.52	5.49	
e	.215 BSC		5.46 BSC		
øk	.010		0.25		
L	.780	.827	19.57	21.00	
L1	.146	.169	3.71	4.29	
øP	.140	.144	3.56	3.66	
øP1	–	.291	–	7.39	
Q	.209	.224	5.31	5.69	
S	.217 BSC		5.51 BSC		

LEAD ASSIGNMENTS

HEXFET

1.– GATE
2.– DRAIN
3.– SOURCE
4.– DRAIN

IGBTs, CoPACK

1.– GATE
2.– COLLECTOR
3.– EMITTER
4.– COLLECTOR


DIODES

1.– ANODE/OPEN
2.– CATHODE
3.– ANODE

TO-247AD Part Marking Information

EXAMPLE: THIS IS AN IRGP30B120KD-E
WITH ASSEMBLY
LOT CODE 5657
ASSEMBLED ON WW 35, 2000
IN THE ASSEMBLY LINE "H"

Note: "P" in assembly line position
indicates "Lead-Free"



TO-247AD package is not recommended for Surface Mount Application.

Note: For the most current drawing please refer to IR website at http://www.irf.com/package/

 © 2014 International Rectifier

Qualification Information†

Qualification Level	Industrial† (per JEDEC JESD47F) ††	
Moisture Sensitivity Level	TO-247AC	N/A
	TO-247AD	
RoHS Compliant	Yes	

† Qualification standards can be found at International Rectifier's web site: http://www.irf.com/product-info/reliability/

†† Applicable version of JEDEC standard at the time of product release.

Revision History

Date	Comments
8/22/2014	• Updated I_C vs. T_C graph Fig.2 to match page1 spec data on page 3.
	• Updated package outline on page 9.

International
IOR Rectifier

IR WORLD HEADQUARTERS: 101 N. Sepulveda Blvd., El Segundo, California 90245, USA
To contact International Rectifier, please visit http://www.irf.com/whoto-call/

 © 2014 International Rectifier

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.