
International
IOR Rectifier

PD - 95644A

IRGB6B60KPbF
IRGS6B60KPbF
IRGSL6B60KPbF

INSULATED GATE BIPOLAR TRANSISTOR



n-channel

V_{CES} = 600V

I_C = 7.0A, T_C=100°C

t_{sc} > 10µs, T_J=150°C


$V_{CE(on)}$ typ. = 1.8V

Features

- Low VCE (on) Non Punch Through IGBT Technology.
- 10µs Short Circuit Capability.
- Square RBSOA.
- Positive VCE (on) Temperature Coefficient.
- Lead-Free.

Benefits

- Benchmark Efficiency for Motor Control.
- Rugged Transient Performance.
- Low EMI.
- Excellent Current Sharing in Parallel Operation.



TO-220AB	D^2Pak	TO-262
IRGB6B60K	IRGS6B60K	IRGSL6B60K

Absolute Maximum Ratings

	Parameter	Max.	Units
V_{CES}	Collector-to-Emitter Voltage	600	V
I_C @ T_C = 25°C	Continuous Collector Current	13	A
I_C @ T_C = 100°C	Continuous Collector Current	7.0	
I_{CM}	Pulsed Collector Current	26	
I_{LM}	Clamped Inductive Load Current ①	26	
V_{GE}	Gate-to-Emitter Voltage	± 20	V
P_D @ T_C = 25°C	Maximum Power Dissipation	90	W
P_D @ T_C = 100°C	Maximum Power Dissipation	36	
T_J	Operating Junction and	-55 to +150	°C
T_{STG}	Storage Temperature Range		
	Soldering Temperature, for 10 sec.	300 (0.063 in. (1.6mm) from case)	

Thermal Resistance

	Parameter	Min.	Typ.	Max.	Units
$R_{\theta JC}$	Junction-to-Case - IGBT	—	—	1.4	°C/W
$R_{\theta CS}$	Case-to-Sink, flat, greased surface	—	0.50	—	
$R_{\theta JA}$	Junction-to-Ambient, typical socket mount②	—	—	62	
$R_{\theta JA}$	Junction-to-Ambient (PCB Mount, steady state)③	—	—	40	
Wt	Weight	—	1.44	—	g

Electrical Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions	Ref.Fig.
$V_{(BR)CES}$	Collector-to-Emitter Breakdown Voltage	600	—	—	V	V_{GE} = 0V, I_C = 500µA	
$\Delta V_{(BR)CES}/\Delta T_J$	Temperature Coeff. of Breakdown Voltage	—	0.3	—	V/°C	V_{GE} = 0V, I_C = 1.0mA, (25°C-150°C)	
$V_{CE(on)}$	Collector-to-Emitter Saturation Voltage	1.5	1.80	2.20	V	I_C = 5.0A, V_{GE} = 15V	5, 6,7
		—	2.20	2.50		I_C = 5.0A,V_{GE} = 15V, T_J = 150°C	8,9,10
$V_{GE(th)}$	Gate Threshold Voltage	3.5	4.5	5.5	V	V_{CE} = V_{GE}, I_C = 250µA	8,9,10
$\Delta V_{GE(th)}/\Delta T_J$	Temperature Coeff. of Threshold Voltage	—	-10	—	mV/°C	V_{CE} = V_{GE}, I_C = 1.0mA, (25°C-150°C)	11
g_{fe}	Forward Transconductance	—	3.0	—	S	V_{CE} = 50V, I_C = 5.0A, PW=80µs	
I_{CES}	Zero Gate Voltage Collector Current	—	1.0	150	µA	V_{GE} = 0V, V_{CE} = 600V	
		—	200	500		V_{GE} = 0V, V_{CE} = 600V, T_J = 150°C	
I_{GES}	Gate-to-Emitter Leakage Current	—	—	±100	nA	V_{GE} = ±20V	

Switching Characteristics @ T_J = 25°C (unless otherwise specified)

	Parameter	Min.	Typ.	Max.	Units	Conditions	Ref.Fig.
Qg	Total Gate Charge (turn-on)	—	18.2	—		I_C = 5.0A	17
Qge	Gate - Emitter Charge (turn-on)	—	1.9	—	nC	V_{CC} = 400V	CT1
Qgc	Gate - Collector Charge (turn-on)	—	9.2	—		V_{GE} = 15V	
E_{on}	Turn-On Switching Loss	—	110	210	µJ	I_C = 5.0A, V_{CC} = 400V	CT4
E_{off}	Turn-Off Switching Loss	—	135	245		V_{GE} = 15V,R_G = 100Ω, L =1.4mH	
E_{tot}	Total Switching Loss	—	245	455		Ls = 150nH T_J = 25°C ④	
$t_{d(on)}$	Turn-On Delay Time	—	25	34		I_C = 5.0A, V_{CC} = 400V	CT4
t_r	Rise Time	—	17	26		V_{GE} = 15V, R_G = 100Ω L =1.4mH	
$t_{d(off)}$	Turn-Off Delay Time	—	215	230	ns	Ls = 150nH, T_J = 25°C	
t_f	Fall Time	—	13.2	22			
E_{on}	Turn-On Switching Loss	—	150	260		I_C = 5.0A, V_{CC} = 400V	CT4
E_{off}	Turn-Off Switching Loss	—	190	300	µJ	V_{GE} = 15V,R_G = 100Ω, L =1.4mH	12,14
E_{tot}	Total Switching Loss	—	340	560		Ls = 150nH T_J = 150°C ④	WF1WF2
$t_{d(on)}$	Turn-On Delay Time	—	28	37		I_C = 5.0A, V_{CC} = 400V	13, 15
t_r	Rise Time	—	17	26		V_{GE} = 15V, R_G = 100Ω L =1.4mH	CT4
$t_{d(off)}$	Turn-Off Delay Time	—	240	255	ns	Ls = 150nH, T_J = 150°C	WF1
t_f	Fall Time	—	18	27			WF2
C_{ies}	Input Capacitance	—	290	—		V_{GE} = 0V	
C_{oes}	Output Capacitance	—	34	—	pF	V_{CC} = 30V	16
C_{res}	Reverse Transfer Capacitance	—	10	—		f = 1.0MHz	
RBSOA	Reverse Bias Safe Operting Area	FULL SQUARE				T_J = 150°C, I_C = 26A, Vp =600V	4
						V_{CC} = 500V, V_{GE} =+15V to 0V,R_G = 100Ω	CT2
SCSOA	Short Circuit Safe Operting Area	10	—	—	µs	T_J = 150°C, Vp =600V, R_G = 100Ω	CT3
						V_{CC} = 360V, V_{GE} = +15V to 0V	WF3

Note ① to ④ are on page 13




Fig. 1 - Maximum DC Collector Current vs. Case Temperature




Fig. 2 - Power Dissipation vs. Case Temperature




Fig. 3 - Forward SOA
T_C = 25°C; $T_J \leq$ 150°C




Fig. 4 - Reverse Bias SOA
T_J = 150°C; V_{GE} =15V




Fig. 5 - Typ. IGBT Output Characteristics
T_J = -40°C; tp = 80µs




Fig. 6 - Typ. IGBT Output Characteristics
T_J = 25°C; tp = 80µs




Fig. 7 - Typ. IGBT Output Characteristics
T_J = 150°C; tp = 80µs




Fig. 8 - Typical V_{CE} vs. V_{GE}
T_J = -40°C




Fig. 9 - Typical V_{CE} vs. V_{GE}
T_J = 25°C




Fig. 10 - Typical V_{CE} vs. V_{GE}
T_J = 150°C




Fig. 11 - Typ. Transfer Characteristics
V_{CE} = 50V; tp = 10µs




Fig. 12 - Typ. Energy Loss vs. I_C
T_J = 150°C; L=1.4mH; V_{CE}= 400V
R_G= 100Ω; V_{GE}= 15V




Fig. 13 - Typ. Switching Time vs. I_C
T_J = 150°C; L=1.4mH; V_{CE}= 400V
R_G= 100Ω; V_{GE}= 15V




Fig. 14 - Typ. Energy Loss vs. R_G
T_J = 150°C; L=1.4mH; V_{CE}= 400V
I_{CE}= 5.0A; V_{GE}= 15V




Fig. 15 - Typ. Switching Time vs. R_G
T_J = 150°C; L=1.4mH; V_{CE}= 400V
I_{CE}= 5.0A; V_{GE}= 15V




Fig. 16- Typ. Capacitance vs. V_{CE}
V_{GE}= 0V; f = 1MHz




Fig. 17 - Typical Gate Charge vs. V_{GE}
I_{CE} = 5.0A; L = 600µH




Fig 18. Maximum Transient Thermal Impedance, Junction-to-Case (IGBT)




Fig.C.T.1 - Gate Charge Circuit (turn-off)




Fig.C.T.2 - RBSOA Circuit




Fig.C.T.3 - S.C.SOA Circuit




Fig.C.T.4 - Switching Loss Circuit




Fig.C.T.5 - Resistive Load Circuit




Fig. WF1- Typ. Turn-off Loss Waveform
@ T_J = 150°C using Fig. CT.4




Fig. WF2- Typ. Turn-on Loss Waveform
@ T_J = 150°C using Fig. CT.4






Fig. WF3- Typ. S.C Waveform
@ T_C = 150°C using Fig. CT.3

TO-220AB Package Outline

Dimensions are shown in millimeters (inches)





NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5 M- 1994.
2. DIMENSIONS ARE SHOWN IN INCHES [MILLIMETERS].
3. LEAD DIMENSION AND FINISH UNCONTROLLED IN L1.
4. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED .005" (0.127) PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
5. DIMENSION b1 & c1 APPLY TO BASE METAL ONLY.
6. CONTROLLING DIMENSION : INCHES.
7. THERMAL PAD CONTOUR OPTIONAL WITHIN DIMENSIONS E,H1,D2 & E1
8. DIMENSION E2 X H1 DEFINE A ZONE WHERE STAMPING AND SINGULATION IRREGULARITIES ARE ALLOWED.

SYMBOL	DIMENSIONS				NOTES
	MILLIMETERS		INCHES		
	MIN.	MAX.	MIN.	MAX.	
A	3.56	4.82	.140	.190	
A1	0.51	1.40	.020	.055	
A2	2.04	2.92	.080	.115	
b	0.38	1.01	.015	.040	
b1	0.38	0.96	.015	.038	5
b2	1.15	1.77	.045	.070	
b3	1.15	1.73	.045	.068	
c	0.36	0.61	.014	.024	
c1	0.36	0.56	.014	.022	5
D	14.22	16.51	.560	.650	4
D1	8.38	9.02	.330	.355	
D2	12.19	12.88	.480	.507	7
E	9.66	10.66	.380	.420	4,7
E1	8.38	8.89	.330	.350	7
e	2.54 BSC		.100 BSC		
e1	5.08		.200 BSC		
H1	5.85	6.55	.230	.270	7,8
L	12.70	14.73	.500	.580	
L1	-	6.35	-	.250	3
øP	3.54	4.08	.139	.161	
Q	2.54	3.42	.100	.135	
ø	90°-93°		90°-93°		

LEAD ASSIGNMENTS

HEXFET

1.- GATE
2.- DRAIN
3.- SOURCE

IGBTs, CoPACK

1.- GATE
2.- COLLECTOR
3.- EMITTER


DIODES

1.- ANODE/OPEN
2.- CATHODE
3.- ANODE

TO-220AB Part Marking Information


EXAMPLE: THIS IS AN IRF1010
LOT CODE 1789
ASSEMBLED ON WW 19, 1997
IN THE ASSEMBLY LINE "C"

Note: "P" in assembly line position indicates "Lead-Free"



D²Pak Package Outline

Dimensions are shown in millimeters (inches)



SYMBOL	DIMENSIONS				NOTES
	MILLIMETERS		INCHES		
	MIN.	MAX.	MIN.	MAX.	
A	4.06	4.83	.160	.190	
A1		0.127		.005	
b	0.51	0.99	.020	.039	
b1	0.51	0.89	.020	.035	4
b2	1.14	1.40	.045	.055	
c	0.43	0.63	.017	.025	
c1	0.38	0.74	.015	.029	4
c2	1.14	1.40	.045	.055	
D	8.51	9.65	.335	.380	3
D1	5.33		.210		
E	9.65	10.67	.380	.420	3
E1	6.22		.245		
e	2.54 BSC		.100 BSC		
L	14.61	15.88	.575	.625	
L1	1.78	2.79	.070	.110	
L2		1.65		.065	
L3	1.27	1.78	.050	.070	
L4	0.25 BSC		.010 BSC		
m	17.78		.700		
m1	8.89		.350		
n	11.43		.450		
o	2.08		.082		
p	3.81		.150		
θ	90°	93°	90°	93°	

LEAD ASSIGNMENTS

HEXFET	IGBTs, CoPACK	DIODES
1.– GATE	1.– GATE	1.– ANODE *
2.– DRAIN	2.– COLLECTOR	2.– CATHODE
3.– SOURCE	3.– EMITTER	3.– ANODE

* PART DEPENDENT.


NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M–1994
2. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
3. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.127 [.005"] PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY.
4. DIMENSION b1 AND c1 APPLY TO BASE METAL ONLY.
5. CONTROLLING DIMENSION: INCH.


D²Pak Part Marking Information

EXAMPLE: THIS IS AN IRF530S WITH
LOT CODE 8024
ASSEMBLED ON WW 02, 2000
IN THE ASSEMBLY LINE "L"

Note: "P" in assembly line position indicates "Lead-Free"




OR



TO-262 Package Outline

Dimensions are shown in millimeters (inches)



SYMBOL	DIMENSIONS				NOTES
	MILLIMETERS		INCHES		
	MIN.	MAX.	MIN.	MAX.	
A	4.06	4.83	.160	.190	
A1	2.03	2.92	.080	.115	
b	0.51	0.99	.020	.039	
b1	0.51	0.89	.020	.035	4
b2	1.14	1.40	.045	.055	
c	0.38	0.63	.015	.025	4
c1	1.14	1.40	.045	.055	
c2	0.43	.063	.017	.029	
D	8.51	9.65	.335	.380	3
D1	5.33		.210		
E	9.65	10.67	.380	.420	3
E1	6.22		.245		
e	2.54 BSC		.100 BSC		
L	13.46	14.09	.530	.555	
L1	3.56	3.71	.140	.146	
L2		1.65		.065	

LEAD ASSIGNMENTS


HEXFET	IGBT
1.– GATE	1 – GATE
2.– DRAIN	2 – COLLECTOR
3.– SOURCE	3 – EMITTER
4.– DRAIN	

NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M–1994
2. DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
3. DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.127 [.005"] PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY.
4. DIMENSION b1 AND c1 APPLY TO BASE METAL ONLY.
5. CONTROLLING DIMENSION: INCH.


TO-262 Part Marking Information

EXAMPLE: THIS IS AN IRL3103L
LOT CODE 1789
ASSEMBLED ON WW 19, 1997
IN THE ASSEMBLY LINE "C"

Note: "P" in assembly line position indicates "Lead-Free"





OR



D²Pak Tape & Reel Information

Dimensions are shown in millimeters (inches)





Notes:

① V_{CC}= 80% (V_{CES}), V_{GE} =15V, L = 28µH, R_G = 22Ω

② This is only applied to TO-220AB package

③ This is applied to D²Pak, when mounted on 1" square PCB (FR-4 or G-10 Material).
For recommended footprint and soldering techniques refer to application note #AN-994.

④ Energy losses include "tail" and diode reverse recovery, using Diode HF03D060ACE.

TO-220 package is not recommended for Surface Mount Application

Data and specifications subject to change without notice.
This product has been designed and qualified for Industrial market.
Qualification Standards can be found on IR's Web site.

International
IOR Rectifier

IR WORLD HEADQUARTERS: 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105
TAC Fax: (310) 252-7903
Visit us at www.irf.com for sales contact information. 11/04

Note: For the most current drawings please refer to the IR website at:
http://www.irf.com/package/

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.