MIC5365/6

High-Performance Single 150 mA LDO

Features

- 2.5V to 5.5V Input Voltage Range
- 150 mA Guaranteed Output Current
- Stable with 1 µF Ceramic Output Capacitors
- Low Dropout Voltage (155 mV at 150 mA)
- Excellent Load/Line Transient Response
- Low Quiescent Current: 29 µA
- High PSRR: 70 dB
- Output Discharge Circuit: MIC5366
- High Output Accuracy
  - ±2% Initial Accuracy
- Thermal Shutdown and Current-Limit Protection
- Tiny 1 mm × 1 mm UDFN, SC-70-5, and Thin SOT23-5 Packages

Applications

- Mobile Phones
- Digital Cameras
- GPS Devices, PMPs, PDAs, and Handhelds
- Portable Electronics

General Description

The MIC5365/6 are advanced general-purpose linear regulators offering high power supply rejection (PSRR) in an ultra-small 1 mm × 1 mm package. The MIC5366 includes an auto-discharge feature that is activated when the enable pin is low. The MIC5365/6 are capable of sourcing 150 mA output current and offer high PSRR, making them ideal solutions for any portable electronic application.


Ideal for battery-powered applications, the MIC5365/6 offer 2% initial accuracy, low dropout voltage (155 mV @ 150 mA) and low ground current (typically 29 µA). The MIC5365/6 can also be put into a zero-off-mode current state, drawing virtually no current when disabled.

The MIC5365/6 are available in several advanced packages, including a lead-free (RoHS-compliant) 1 mm × 1 mm UDFN occupying only 1 mm^2 of PCB area, a 75% reduction in board area compared to SC-70 and 2 mm × 2 mm UDFN packages. They are also available in a thin SOT23-5 package.


The MIC5365/6 have an operating junction temperature range of -40°C to 125°C.

Package Types

MIC5365/6
4-Lead UDFN (MT)




MIC5365/6
5-Lead TSOT23-5 (D5)
5-Lead SC-70 (C5)




© 2021-2026 Microchip Technology Inc. and its subsidiaries

Typical Application Circuit



Functional Block Diagrams



© 2021-2026 Microchip Technology Inc. and its subsidiaries

1.0 ELECTRICAL CHARACTERISTICS

Absolute Maximum Ratings †

Supply Voltage (V_{IN}) ..... 0V to +6V
Enable Voltage (V_{EN}) ..... 0V to V_{IN}
Power Dissipation (P_D), Note 1 ..... Internally Limited
ESD Rating, Note 2 ..... 2 kV

Operating Ratings ‡

Supply Voltage (V_{IN}) ..... +2.5V to +5.5V
Enable Voltage (V_{EN}) ..... 0V to V_{IN}

† Notice: Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only and functional operation of the device at those or any other conditions above those indicated in the operational sections of this specification is not intended. Exposure to maximum rating conditions for extended periods may affect device reliability.

‡ Notice: The device is not guaranteed to function outside its operating ratings.

Note 1: The maximum allowable power dissipation of any T_A (ambient temperature) is $P_{D(MAX)} = (T_{J(MAX)} - T_A)/\theta_{JA}$. Exceeding the maximum allowable power dissipation will result in excessive die temperature, and the regulator will go into thermal shutdown.

2: Devices are ESD sensitive. Handling precautions are recommended. Human body model, 1.5 kΩ in series with 100 pF.

TABLE 1-1: ELECTRICAL CHARACTERISTICS

Electrical Characteristics: $V_{IN} = V_{EN} = V_{OUT} + 1V$; $C_{IN} = C_{OUT} = 1\ \mu F$; $I_{OUT} = 100\ \mu A$; $T_A = +25°C$; **Bold** values are valid for -40°C to +125°C unless noted. **(Note 1)**.						
Parameters	**Symbol**	**Min.**	**Typ.**	**Max.**	**Units**	**Conditions**
Output Voltage Accuracy	V_{OUT}	-2.0	—	+2.0	%	Variation from nominal V_{OUT}
		-3.0	—	**+3.0**		Variation from nominal V_{OUT}; -40°C to +125°C
Line Regulation	$\Delta V_{OUT}/V_{OUT}$	—	0.02	**0.3**	%	$V_{IN} = V_{OUT}$ +1V to 5.5V; $I_{OUT} = 100\ \mu A$
Load Regulation	$\Delta V_{OUT}/V_{OUT}$	—	0.3	1	%	$I_{OUT} = 100\ \mu A$ to 150 mA
Dropout Voltage	V_{DO}	—	55	**110**	mV	$I_{OUT} = 50$ mA; $V_{OUT} \geq 2.8V$
		—	155	**310**		$I_{OUT} = 150$ mA; $V_{OUT} \geq 2.8V$
		—	60	**135**		$I_{OUT} = 50$ mA; $V_{OUT} < 2.8V$
		—	180	**380**		$I_{OUT} = 150$ mA; $V_{OUT} < 2.8V$
Ground Pin Current	I_{GND}	—	29	**39**	µA	$I_{OUT} = 0$ mA
Ground Pin Current in Shutdown	I_{SHDN}	—	0.05	1	µA	$V_{EN} \leq 0.2V$
Ripple Rejection	PSRR	—	80	—	dB	f = up to 1 kHz; $C_{OUT} = 1\ \mu F$
		—	65	—		f = 1 kHz to 10 kHz, $C_{OUT} = 1\ \mu f$
Current Limit	I_{LIM}	200	325	550	mA	$V_{OUT} = 0V$
Output Voltage Noise	e_N	—	200	—	μV_{RMS}	$C_{OUT} = 1\mu F$, 10 Hz to 100 kHz
Auto-Discharge NFET Resistance	R_{DSCG}	—	30	—	Ω	MIC5366 Only; $V_{EN} = 0V$; $V_{IN} = 3.6V$, $I_{OUT} = -3$ mA
Enable Inputs						
Enable Input Voltage	V_{IL}	—	—	**0.2**	V	Logic Low
	V_{IH}	**1.2**	—	—		Logic High

© 2021-2026 Microchip Technology Inc. and its subsidiaries

TABLE 1-1: ELECTRICAL CHARACTERISTICS (CONTINUED)

Electrical Characteristics: $V_{IN} = V_{EN} = V_{OUT} + 1V$; $C_{IN} = C_{OUT} = 1\ \mu F$; $I_{OUT} = 100\ \mu A$; $T_A = +25°C$; **Bold** values are valid for -40°C to +125°C unless noted. **(Note 1)**.						
Parameters	**Symbol**	**Min.**	**Typ.**	**Max.**	**Units**	**Conditions**
Enable Input Current	I_{IL}	—	0.01	**1**	µA	$V_{IL} \le 0.2V$
	I_{IH}	—	0.01	**1**		$V_{IH} \ge 1.2V$
Turn-On Time	t_{ON}	—	50	**125**	µs	$C_{OUT} = 1\ \mu F$; $I_{OUT} = 150\ mA$

Note 1: Specification for packaged product only.

TABLE 1-2: TEMPERATURE SPECIFICATIONS

Parameters	**Symbol**	**Min.**	**Typ.**	**Max.**	**Units**	**Conditions**
Temperature Ranges						
Maximum Junction Temperature Range	$T_{J(MAX)}$	-40	—	+150	°C	Note 1
Storage Temperature Range	T_S	-65	—	+150	°C	—
Lead Temperature	—	—	—	+260	°C	Soldering, 3 sec.
Junction Temperature	T_J	-40	—	+125	°C	—
Package Thermal Resistances						
Thermal Resistance, UDFN-4	θ_{JA}	—	240	—	°C/W	—
Thermal Resistance, TSOT23-5		—	253	—		
Thermal Resistance, SC-70-5		—	256.5	—		

Note 1: The maximum allowable power dissipation is a function of ambient temperature, the maximum allowable junction temperature and the thermal resistance from junction to air (i.e., T_A, T_J, θ_{JA}). Exceeding the maximum allowable power dissipation will cause the device operating junction temperature to exceed the maximum +125°C rating. Sustained junction temperatures above +125°C can impact the device reliability.

© 2021-2026 Microchip Technology Inc. and its subsidiaries

2.0 TYPICAL PERFORMANCE CURVES

Note: The graphs and tables provided following this note are a statistical summary based on a limited number of samples and are provided for informational purposes only. The performance characteristics listed herein are not tested or guaranteed. In some graphs or tables, the data presented may be outside the specified operating range (e.g., outside specified power supply range) and therefore outside the warranted range.




FIGURE 2-1: *Power Supply Rejection Ratio.*




FIGURE 2-4: *Ground Current vs. Supply Voltage.*




FIGURE 2-2: *Dropout Voltage vs. Load Current.*




FIGURE 2-5: *Ground Current vs. Load Current.*




FIGURE 2-3: *Dropout Voltage vs. Temperature.*




FIGURE 2-6: *Ground Current vs. Temperature.*

© 2021-2026 Microchip Technology Inc. and its subsidiaries




FIGURE 2-7: *Output Voltage vs. Load Current.*




FIGURE 2-10: *Current Limit vs. Supply Voltage.*




FIGURE 2-8: *Output Voltage vs. Supply Voltage.*




FIGURE 2-11: *Output Noise Spectral Density.*




FIGURE 2-9: *Output Voltage vs. Temperature.*




FIGURE 2-12: *Enable Turn-On.*

© 2021-2026 Microchip Technology Inc. and its subsidiaries




FIGURE 2-13: *Enable Turn-On.*




FIGURE 2-16: *Line Transient.*




FIGURE 2-14: *Load Transient.*




FIGURE 2-17: *MIC5366 Auto Discharge (No Load).*




FIGURE 2-15: *Load Transient.*

© 2021-2026 Microchip Technology Inc. and its subsidiaries

3.0 PIN DESCRIPTIONS

The descriptions of the pins are listed in Table 3-1.

TABLE 3-1: PIN FUNCTION TABLE

Pin Number	Pin Name UDFN-4	Pin Name TSOT23-5	Pin Name SC70-5	Description
1	VOUT	—	—	Output Voltage
1	—	VIN	VIN	Supply Input
2	GND	GND	GND	Ground
3	EN	EN	EN	Enable Input: Active-high. High = ON; Low = OFF. Do not leave floating.
4	VIN	—	—	Supply Input
4	—	NC	NC	No Connect. Not internally connected.
5	—	VOUT	VOUT	Output Voltage
EP	HS Pad	N/A	N/A	Exposed heat sink pad

© 2021-2026 Microchip Technology Inc. and its subsidiaries

4.0 APPLICATION INFORMATION

MIC5365 and MIC5366 are low noise 150 mA LDOs. The MIC5366 includes an auto-discharge circuit that is switched on when the regulator is disabled through the enable pin. The MIC5365/6 regulators are fully protected from damage due to fault conditions, offering linear current limiting and thermal shutdown.

4.1 Input Capacitor

The MIC5365/6 are high-performance, high-bandwidth devices. An 1 µF input capacitor from input to ground is required to ensure stability. Low-ESR ceramic capacitors provide optimal performance while minimizing space requirements. Additional high-frequency capacitors, such as small valued NPO dielectric type capacitors, help filter out high-frequency noise and are recommended in RF-based circuits. X5R or X7R dielectrics are recommended for the input capacitor. Y5V dielectrics lose most of their capacitance over temperature and are therefore, not recommended.

4.2 Output Capacitor

The MIC5365/6 require an output capacitor of 1 µF or greater to maintain stability. The design is optimized for use with low-ESR ceramic chip capacitors. High-ESR capacitors may cause high-frequency oscillation. The output capacitor can be increased, but performance has been optimized for a 1 µF ceramic output capacitor and does not improve significantly with larger capacitance.

X7R/X5R dielectric-type ceramic capacitors are recommended because of their temperature performance. X7R type capacitors change capacitance by 15% over their operating temperature range and are the most stable type of ceramic capacitors. Z5U and Y5V dielectric capacitors change value by as much as 50% and 60%, respectively, over their operating temperature ranges. To use a ceramic chip capacitor with Y5V dielectric, the value must be much higher than an X7R ceramic capacitor to ensure the same minimum capacitance over the equivalent operating temperature range.

4.3 No-Load Stability

Unlike many other voltage regulators, the MIC5365/6 will remain stable and in regulation with no load. This is especially important in CMOS RAM to keep applications alive.

4.4 Enable/Shutdown

The MIC5365/6 comes with an active-high enable pin that allows the regulator to be disabled. Forcing the enable pin low disables the regulator and sends it into a “zero” off-mode current state. In this state, current consumed by the regulator goes nearly to zero. Forcing the enable pin high enables the output voltage. The active-high enable pin uses CMOS technology and the enable pin cannot be left floating; a floating enable pin may cause an indeterminate state on the output.

4.5 Thermal Considerations

The MIC5365/6 are designed to provide 150 mA of continuous current in a very small package. The maximum ambient operating temperature can be calculated based on the output current and the voltage drop across the device. For example if the input voltage is 3.6V, the output voltage is 2.8V, and the output current = 150 mA. The actual power dissipation of the regulator circuit can be determined using the equation Equation 4-1:

EQUATION 4-1:

$$P_D = (V_{IN} - V_{OUT})I_{OUT} + V_{IN} \times I_{GND}$$

Because this device uses CMOS and the ground current is typically <100 µA over the load range, the power dissipation contributed by the ground current is <1% and can be ignored for the calculation in Equation 4-2:

EQUATION 4-2:

$$P_D = (3.6V - 2.8V) \times 150mA$$

$$P_D = 0.120W$$

To determine the maximum ambient operating temperature of the package, use the junction-to-ambient thermal resistance of the device and the following basic formula in Equation 4-3:

EQUATION 4-3:

$$P_{D(MAX)} = \left(\frac{T_{J(MAX)} - T_A}{\theta_{JA}}\right)$$

Where:

$T_{J(MAX)}$ = 125°C

θ_{JA} = 240°C/W (UDFN Package)
256.5°C/W (SC-70-5 Package)
235°C/W (TSOT23-5 Package)

© 2021-2026 Microchip Technology Inc. and its subsidiaries

Substituting P_D for $P_{D(MAX)}$ and solving for the ambient operating temperature provides the maximum operating conditions for the regulator circuit. The junction-to-ambient thermal resistance for the minimum footprint is 250°C/W.

The maximum power dissipation must not be exceeded for proper operation.

For example, when operating the MIC5365-2.8YMT at an input voltage of 3.6V and 150 mA loads at each output with a minimum footprint layout, the maximum ambient operating temperature, $T_{A,}$ can be determined using Equation 4-4:

EQUATION 4-4:

$$0.120W = (125°C - T_A)/(250°C/\mathrm{W})$$

$$T_A = 95°C$$


Therefore, the maximum ambient operating temperature of 95°C is allowed in a 1 mm × 1 mm UDFN package. For a full discussion of heat sinking and thermal effects of voltage regulators, refer to the "Regulator Thermals" section of Designing with Low-Dropout Voltage Regulators handbook.

© 2021-2026 Microchip Technology Inc. and its subsidiaries


5.0 PACKAGING INFORMATION

5.1 Package Marking Information


4-Lead UDFN*




Example




5-Lead SC70-5*
5-Lead TSOT23-5*
(front)



Example
(front)



5-Lead SC70-5*
5-Lead TSOT23-5*
(back)



Example
(back)



Legend:	XX...X	Product code or customer-specific information
	Y	Year code (last digit of calendar year)
	YY	Year code (last 2 digits of calendar year)
	WW	Week code (week of January 1 is week ‘01’)
	NNN	Alphanumeric traceability code
	(e3)	Pb-free JEDEC® designator for Matte Tin (Sn)
	*	This package is Pb-free. The Pb-free JEDEC designator ((e3)) can be found on the outer packaging for this package.
	●, ▲, ▼	Pin one index is identified by a dot, delta up, or delta down (triangle mark).
Note:		In the event the full Microchip part number cannot be marked on one line, it will be carried over to the next line, thus limiting the number of available characters for customer-specific information. Package may or may not include the corporate logo.
		Underbar (_) and/or Overbar (¯) symbol may not be to scale.

TABLE 5-1: PACKAGE MARKING CODES FOR MIC5365/6

Part Number	Output Voltage	Marking Codes
MIC5365-1.0YMT	1.0V	5C
MIC5365-1.2YMT	1.2V	54
MIC5365-1.3YMT	1.3V	55
MIC5365-1.5YMT	1.5V	5F
MIC5365-1.8YMT	1.8V	5G
MIC5365-2.0YMT	2.0V	5H
MIC5365-2.5YMT	2.5V	5J
MIC5365-2.6YMT	2.6V	5K
MIC5365-2.7YMT	2.7V	5L
MIC5365-2.8YMT	2.8V	5M
MIC5365-2.85YMT	2.85V	5N
MIC5365-2.9YMT	2.9V	5O
MIC5365-3.0YMT	3.0V	5P
MIC5365-3.3YMT	3.3V	5S
MIC5365-1.0YC5	1.0V	65C
MIC5365-1.2YC5	1.2V	654
MIC5365-1.3YC5	1.3V	655
MIC5365-1.5YC5	1.5V	65F
MIC5365-1.8YC5	1.8V	65G
MIC5365-2.0YC5	2.0V	65H
MIC5365-2.5YC5	2.5V	65J
MIC5365-2.6YC5	2.6V	65K
MIC5365-2.7YC5	2.7V	65L
MIC5365-2.8YC5	2.8V	65M
MIC5365-2.85YC5	2.85V	65N
MIC5365-2.9YC5	2.9V	65O
MIC5365-3.0YC5	3.0V	65P
MIC5365-3.3YC5	3.3V	65S
MIC5365-1.2YD5	1.2V	645
MIC5365-1.8YD5	1.8V	6G5
MIC5365-2.8YD5	2.8V	6M5
MIC5365-2.85YD5	2.85V	6N5
MIC5365-3.3YD5	3.3V	6S5
MIC5366-1.0YMT	1.0V	6C
MIC5366-1.2YMT	1.2V	64
MIC5366-1.3YMT	1.3V	65
MIC5366-1.5YMT	1.5V	6F
MIC5366-1.8YMT	1.8V	6G
MIC5366-2.0YMT	2.0V	6H
MIC5366-2.5YMT	2.5V	6J
MIC5366-2.6YMT	2.6V	6K
MIC5366-2.7YMT	2.7V	6L
MIC5366-2.8YMT	2.8V	6M

© 2021-2026 Microchip Technology Inc. and its subsidiaries


TABLE 5-1: PACKAGE MARKING CODES FOR MIC5365/6 (CONTINUED)

Part Number	Output Voltage	Marking Codes
MIC5366-2.85YMT	2.85V	6N
MIC5366-2.9YMT	2.9V	6O
MIC5366-3.0YMT	3.0V	6P
MIC5366-3.3YMT	3.3V	6S
MIC5366-1.0YC5	1.0V	66C
MIC5366-1.2YC5	1.2V	664
MIC5366-1.3YC5	1.3V	665
MIC5366-1.5YC5	1.5V	66F
MIC5366-1.8YC5	1.8V	66G
MIC5366-2.0YC5	2.0V	66H
MIC5366-2.5YC5	2.5V	66J
MIC5366-2.6YC5	2.6V	66K
MIC5366-2.7YC5	2.7V	66L
MIC5366-2.8YC5	2.8V	66M
MIC5366-2.85YC5	2.85V	66N
MIC5366-2.9YC5	2.9V	66O
MIC5366-3.0YC5	3.0V	66P
MIC5366-3.3YC5	3.3V	66S

© 2021-2026 Microchip Technology Inc. and its subsidiaries

4-Lead Ultra Thin Plastic Dual Flat, No Lead Package (HCA) - 1x1 mm Body [UDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging




Microchip Technology Drawing C04-1149 Rev A Sheet 1 of 2

© 2021-2026 Microchip Technology Inc. and its subsidiaries

4-Lead Ultra Thin Plastic Dual Flat, No Lead Package (HCA) - 1x1 mm Body [UDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Terminals	N		4	
Pitch	e		0.65 BSC	
Overall Height	A	0.50	0.55	0.60
Standoff	A1	0.00	0.02	0.05
Terminal Thickness	A3		0.152 REF	
Overall Length	D		1.00 BSC	
Exposed Pad Length	D2	0.45	0.50	0.55
Overall Width	E		1.00 BSC	
Exposed Pad Width	E2	0.45	0.50	0.55
Terminal Width	b	0.175	0.225	0.275
Terminal Length	L	0.20	0.25	0.30

Notes:

1. Pin 1 visual index feature may vary, but must be located within the hatched area.
2. Package is saw singulated
3. Dimensioning and tolerancing per ASME Y14.5M

   BSC: Basic Dimension. Theoretically exact value shown without tolerances.


   REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-1149 Rev A Sheet 2 of 2

© 2021-2026 Microchip Technology Inc. and its subsidiaries

4-Lead Ultra Thin Plastic Dual Flat, No Lead Package (HCA) - 1x1 mm Body [UDFN]

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		0.65 BSC	
Center Pad Width	X2			0.48
Center Pad Length	Y2			0.48
Contact Pad Spacing	C		0.90	
Contact Pad Width (X4)	X1			0.25
Contact Pad Length (X3)	Y1			0.40
Terminal 1 Pad Length	Y3			0.47
Contact Pad Chamfer (X3)	CH		0.18	
Thermal Via Diameter	V		0.30	

Notes:


1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
2. For best soldering results, thermal vias, if used, should be filled or tented to avoid solder loss during reflow process

Microchip Technology Drawing C04-3149 Rev A


© 2021-2026 Microchip Technology Inc. and its subsidiaries

5-Lead Plastic Thin Small Outline Transistor (D5A) [TSOT]
Micrel Legacy Package TSOT-5LD-PL-1

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



TOP VIEW




SIDE VIEW

Microchip Technology Drawing C04-1179 Rev A Sheet 1 of 2

5-Lead Plastic Thin Small Outline Transistor (D5A) [TSOT]
Micrel Legacy Package TSOT-5LD-PL-1

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



VIEW A-A
SHEET 1

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Leads	N		5	
Pitch	e		0.95 BSC	
Outside lead pitch	e1		1.90 BSC	
Overall Height	A	-	-	1.00
Molded Package Thickness	A2	0.84	0.87	0.90
Standoff	A1	0.00	-	0.10
Overall Width	E		2.80 BSC	
Molded Package Width	E1		1.60 BSC	
Overall Length	D		2.90 BSC	
Foot Length	L	0.30	0.40	0.50
Footprint	L1		0.60 REF	
Foot Angle	ϕ	0°	-	4°
Lead Thickness	c		0.127 REF	
Lead Width	b	0.30	-	0.50

Notes:


1. Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.25mm per side.
2. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.
   REF: Reference Dimension, usually without tolerance, for information purposes only.

Microchip Technology Drawing C04-1179 Rev A Sheet 1 of 2

© 2021-2026 Microchip Technology Inc. and its subsidiaries

5-Lead Plastic Thin Small Outline Transistor (D5A) [TSOT]
Micrel Legacy Package TSOT-5LD-PL-1

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		0.95 BSC	
Contact Pad Spacing	C		2.60	
Contact Pad Width (X5)	X1			0.60
Contact Pad Length (X5)	Y1			1.10
Contact Pad to Center Pad (X2)	G	0.20		

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M


   BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing C04-3179 Rev A


© 2021-2026 Microchip Technology Inc. and its subsidiaries

5-Lead Plastic Small Outline Transistor (D3A) [SC70] Micrel Legacy Package: YC


Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



TOP VIEW



SIDE VIEW




END VIEW

Microchip Technology Drawing C04-01132 Rev A Sheet 1 of 2

© 2021-2026 Microchip Technology Inc. and its subsidiaries

5-Lead Plastic Small Outline Transistor (D3A) [SC70] Micrel Legacy Package: YC

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Number of Pins	N		5	
Pitch	e		0.65 BSC	
Overall Height	A	0.80	0.95	1.10
Standoff	A1	0.00	0.05	0.10
Molded Package Thickness	A2	0.80	0.90	1.00
Overall Length	D	1.80	2.00	2.25
Overall Width	E	1.80	2.10	2.40
Molded Package Width	E1	1.15	1.25	1.35
Terminal Width	b	0.15	-	0.30
Terminal Length	L	0.21	-	0.46
Lead Thickness	c	0.08	-	0.30

Notes:

1. The Pin 1 visual index feature may vary, but it must be located within the hatched area.
2. Dimensions D and E1 do not include mold flash or protrusions. Mold flash or protrusions shall not exceed 0.15mm per side.
3. Dimensioning and tolerancing per ASME Y14.5M

BSC: Basic Dimension. Theoretically exact value shown without tolerances.


REF: Reference Dimension, usually without tolerances, for information purposes only.

Microchip Technology Drawing C04-01132 Rev A Sheet 2 of 2

© 2021-2026 Microchip Technology Inc. and its subsidiaries

5-Lead Plastic Small Outline Transistor (D3A) [SC70] Micrel Legacy Package: YC

Note: For the most current package drawings, please see the Microchip Packaging Specification located at http://www.microchip.com/packaging



RECOMMENDED LAND PATTERN

Units		MILLIMETERS		
Dimension Limits		MIN	NOM	MAX
Contact Pitch	E		0.65 BSC	
Contact Pad Spacing	C		1.90	
Contact Pad Width	X			0.42
Contact Pad Length	Y			0.77
Distance Between Pads	G	1.13		
Distance Between Pads	Gx	0.23		

Notes:

1. Dimensioning and tolerancing per ASME Y14.5M
   BSC: Basic Dimension. Theoretically exact value shown without tolerances.

Microchip Technology Drawing No. C04-03132 Rev A

© 2021-2026 Microchip Technology Inc. and its subsidiaries

APPENDIX A: REVISION HISTORY

Revision C (November 2026)

- Removed T5 Tape and Reel options from the Product Identification System.

Revision B (April 2026)

- Corrected typos in Functional Block Diagrams and Table 5-1.
- Updated TDFN references to UDFN instead throughout document.
- Updated **Section 5.1 "Package Marking Information"** with markings on back of TSOT option.
- Updated Package Drawings in **Section 5.0 "Packaging Information"**.
- Fixed voltage option details throughout Product Identification System page.

Revision A (October 2021)

- Converted Micrel document MIC5365/6 to Microchip data sheet DS20006605A.
- Minor text changes throughout.
- Evaluation Board Schematic and BOM sections from original data sheet moved to the part's Evaluation Board User Guide.

© 2021-2026 Microchip Technology Inc. and its subsidiaries

PRODUCT IDENTIFICATION SYSTEM

To order or obtain information, e.g., on pricing or delivery, contact your local Microchip representative or sales office.

PART NO.	-XXX	X	XX	-XX
Device	Voltage	Junction Temperature Range	Package	Media Type

Device:	MIC5365: High-Performance Single 150 mA LDO MIC5366: High-Performance Single 150 mA LDO with Output Discharge Circuit	
Voltage Options	1.0 = 1.0V 1.2 = 1.2V 1.3 = 1.3V 1.5 = 1.5V 1.8 = 1.8V 2.0 = 2.0V 2.5 = 2.5V 2.6 = 2.6V 2.7 = 2.7V 2.8 = 2.8V 2.85 = 2.85V 2.9 = 2.9V 3.0 = 3.0V 3.3 = 3.3V	
Junction Temperature Range:	Y =	-40°C to +125°C (RoHS Compliant)
Package:	MT =	4-Lead 1 mm x 1 mm UDFN Package (Pb-Free) (MIC5365/6)
	C5 =	5-Lead SC-70 Package (Pb-Free) (MIC5365/6)
	D5 =	5-Lead TSOT-23 Package (Pb-Free) (MIC5365 Only)
Media Type:	TR =	3,000/Reel (for package options C5 and D5 only)
	TR =	5,000/Reel (for package option MT only)
	TZ =	10,000/Reel (for package option MT only)

Examples:

a) MIC5365-2.8YC5-TR	High-Performance Single 150 mA LDO, 2.8V, -40°C to +125°C, 5-Lead SC-70-5 Package, 3,000/Reel
b) MIC5365-2.85YMT-TZ	High-Performance Single 150 mA LDO, 2.85V, -40°C to +125°C, 4-Lead UDFN Package, 10,000/Reel
c) MIC5366-2.7YC5-TR	High-Performance Single 150 mA LDO, 2.7V, -40°C to +125°C, 5-Lead SC-70-5 Package, 3,000/Reel
d) MIC5366-2.9YMT-TZ	High-Performance Single 150 mA LDO, 2.9V, -40°C to +125°C, 4-Lead UDFN Package, 10,000/Reel

Note 1: Tape and Reel identifier only appears in the catalog part number description. This identifier is used for ordering purposes and is not printed on the device package. Check with your Microchip Sales Office for package availability with the Tape and Reel option.

© 2021-2026 Microchip Technology Inc. and its subsidiaries

Microchip Information

Trademarks

The “Microchip” name and logo, the “M” logo, and other names, logos, and brands are registered and unregistered trademarks of Microchip Technology Incorporated or its affiliates and/or subsidiaries in the United States and/or other countries (“Microchip Trademarks”). Information regarding Microchip Trademarks can be found at https://www.microchip.com/en-us/about/legal-information/microchip-trademarks.

Legal Notice

This publication and the information herein may be used only with Microchip products, including to design, test, and integrate Microchip products with your application. Use of this information in any other manner violates these terms. Information regarding device applications is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. Contact your local Microchip sales office for additional support or, obtain additional support at www.microchip.com/en-us/support/design-help/client-support-services.

THIS INFORMATION IS PROVIDED BY MICROCHIP "AS IS". MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION INCLUDING BUT NOT LIMITED TO ANY IMPLIED WARRANTIES OF NON-INFRINGEMENT, MERCHANTABILITY, AND FITNESS FOR A PARTICULAR PURPOSE, OR WARRANTIES RELATED TO ITS CONDITION, QUALITY, OR PERFORMANCE.

IN NO EVENT WILL MICROCHIP BE LIABLE FOR ANY INDIRECT, SPECIAL, PUNITIVE, INCIDENTAL, OR CONSEQUENTIAL LOSS, DAMAGE, COST, OR EXPENSE OF ANY KIND WHATSOEVER RELATED TO THE INFORMATION OR ITS USE, HOWEVER CAUSED, EVEN IF MICROCHIP HAS BEEN ADVISED OF THE POSSIBILITY OR THE DAMAGES ARE FORESEEABLE. TO THE FULLEST EXTENT ALLOWED BY LAW, MICROCHIP'S TOTAL LIABILITY ON ALL CLAIMS IN ANY WAY RELATED TO THE INFORMATION OR ITS USE WILL NOT EXCEED THE AMOUNT OF FEES, IF ANY, THAT YOU HAVE PAID DIRECTLY TO MICROCHIP FOR THE INFORMATION.

Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

Microchip Devices Code Protection Feature

Note the following details of the code protection feature on Microchip products:

- Microchip products meet the specifications contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is secure when used in the intended manner, within operating specifications, and under normal conditions.
- Microchip values and aggressively protects its intellectual property rights. Attempts to breach the code protection features of Microchip product is strictly prohibited and may violate the Digital Millennium Copyright Act.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of its code. Code protection does not mean that we are guaranteeing the product is “unbreakable”. Code protection is constantly evolving. Microchip is committed to continuously improving the code protection features of our products.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.