MOSFET - Power, Single N-Channel, Source Down DualCool 33, WDFN9

40 V, 1.3 mΩ, 207 A

NTTFSSCH1D3N04XL


$V_{(BR)DSS}$	$R_{DS(ON)}$ MAX	I_D MAX
40 V	1.3 mΩ @ 10 V	207 A
	1.7 mΩ @ 4.5 V	

Features


- Excellent Thermal Conduction by Advanced Source−Down Center Gate Dual−Cooling Package Technology (3.3x3.3mm)
- Low $R_{DS(on)}$ to Minimize Conduction Loss
- Low QRR with Soft Recovery to Minimize ERR Loss and Voltage Spike
- Low Q_G and Capacitance to Minimize Driving and Switching Losses
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

Applications

- High Switching Frequency DC−DC Conversion
- Synchronous Rectifier



N−CHANNEL MOSFET



WDFN9
CASE 511BX


MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Parameter		Symbol	Value	Unit
Drain−to−Source Voltage		V_{DSS}	40	V
Gate−to−Source Voltage	DC	V_{GS}	±20	V
Continuous Drain Current	T_C = 25°C	I_D	207	A
	T_C = 100°C		146	
Power Dissipation	T_C = 25°C	P_D	107	W
Pulsed Drain Current	T_C = 25°C, t_p = 100 μs	I_{DM}	812	A
Operating Junction and Storage Temperature Range		T_J, T_{stg}	−55 to +175	°C
Continuous Source−Drain Current (Body Diode)		I_S	184	A
Single Pulse Avalanche Energy (I_{PK} = 52 A)		E_{AS}	135	mJ
Lead Temperature for Soldering Purposes (1/8″ from case for 10 s)		T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. The entire application environment impacts the thermal resistance values shown, they are not constants and are valid for the particular conditions noted.
2. Surface−mounted on FR4 board using a 1 in^2 pad size, 1 oz Cu pad.
3. E_{AS} of 135 mJ is based on started T_J = 25°C, I_{AS} = 52 A, V_{DD} = 32 V, V_{GS} = 10 V, 100% avalanche tested.

MARKING DIAGRAM



1D3 = Specific Device Code
A = Assembly Location
YW = Assembly Start Week
ZZ = Assembly Lot Number

ORDERING INFORMATION

See detailed ordering and shipping information on page 3 of this data sheet.

© Semiconductor Components Industries, LLC, 2023

THERMAL RESISTANCE RATINGS

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction−to−Case (Bottom)	$R_{\theta JCB}$	1.4	°C/W
Thermal Resistance, Junction−to−Case (Top)	$R_{\theta JCT}$	1.2	
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	60	

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain−to−Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 1 mA	40			V
Drain−to−Source Breakdown Voltage Temperature Coefficient	$\Delta V_{(BR)DSS}/\Delta T_J$	I_D = 1 mA, Referenced to 25°C		17		mV/°C
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 40 V, T_J = 25°C			10	μA
		V_{DS} = 40 V, T_J = 125°C			100	
Gate−to−Source Leakage Current	I_{GSS}	V_{DS} = 0 V, V_{GS} = 20 V			100	nA
ON CHARACTERISTICS						
Drain−to−Source On Resistance	$R_{DS(ON)}$	V_{GS} = 10 V, I_D = 24 A		1.0	1.3	mΩ
		V_{GS} = 6 V, I_D = 24 A		1.1	1.4	
		V_{GS} = 4.5 V, I_D = 19 A		1.4	1.7	
Gate Threshold Voltage	$V_{GS(TH)}$	V_{GS} = V_{DS}, I_D = 120 μA	1.3		2.2	V
Gate Threshold Voltage Temperature Coefficient	$\Delta V_{GS(TH)}/\Delta T_J$	V_{GS} = V_{DS}, I_D = 120 μA		−5		mV/°C
Forward Transconductance	g_{FS}	V_{DS} = 5 V, I_D = 24 A		123		S
CHARGES, CAPACITANCES & GATE RESISTANCE						
Input Capacitance	C_{ISS}	V_{GS} = 0 V, V_{DS} = 20 V, f = 1 MHz		3480		pF
Output Capacitance	C_{OSS}			920		
Reverse Transfer Capacitance	C_{RSS}			32		
Output Charge	Q_{OSS}			35		nC
Total Gate Charge	$Q_{G(TOT)}$	V_{GS} = 4.5 V, V_{DD} = 20 V; I_D = 24 A		21		
		V_{GS} = 6 V, V_{DD} = 20 V; I_D = 24 A		28		
		V_{GS} = 10 V, V_{DD} = 20 V; I_D = 24 A		47		
Threshold Gate Charge	$Q_{G(TH)}$			5.7		
Gate−to−Source Charge	Q_{GS}			10		
Gate−to−Drain Charge	Q_{GD}			3.4		
Gate Plateau Voltage	V_{GP}			2.9		V
Gate Resistance	R_G	f = 1 MHz		0.6		Ω
SWITCHING CHARACTERISTICS						
Turn−On Delay Time	$t_{d(ON)}$	Resistive Load, V_{GS} = 0/10 V, V_{DD} = 20 V, I_D = 24 A, R_G = 2.5 Ω		18		ns
Rise Time	t_r			5		
Turn−Off Delay Time	$t_{d(OFF)}$			43		
Fall Time	t_f			4		
SOURCE−TO−DRAIN DIODE CHARACTERISTICS						
Forward Diode Voltage	V_{SD}	V_{GS} = 0 V, I_S = 24 A, T_J = 25°C		0.79	1.2	V
		V_{GS} = 0 V, I_S = 24 A, T_J = 125°C		0.65		

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise specified)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
SOURCE−TO−DRAIN DIODE CHARACTERISTICS						
Reverse Recovery Time	t_{RR}	V_{GS} = 0 V, I_S = 24 A, dI/dt = 1000 A/μs, V_{DD} = 20 V		17		ns
Charge Time	t_a			10		
Discharge Time	t_b			7		
Reverse Recovery Charge	Q_{RR}			84		nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

ORDERING INFORMATION

Device	Marking	Package	Shipping†
NTTFSSCH1D3N04XL	1D3	WDFN9 (Pb−Free)	5000 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS




Figure 1. On−Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On−Resistance vs. Gate Voltage




Figure 4. On−Resistance vs. Drain Current




Figure 5. Normalized ON Resistance vs. Junction Temperature




Figure 6. Drain Leakage Current vs. Drain Voltage

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS




Figure 7. Capacitance Characteristics




Figure 8. Gate Charge Characteristics




Figure 9. Resistive Switching Time Variation vs. Gate Resistance




Figure 10. Diode Forward Characteristics




Figure 11. Safe Operating Area (SOA)




Figure 12. Avalanche Current vs. Pulse Time (UIS)

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS




Figure 13. Gate Threshold Voltage vs. Junction Temperature




Figure 14. IDM vs. Pulse Width






Figure 15. Transient Thermal Response

Share Feedback
Your Opinion Matters




WDFN−9 3.30x3.30x0.58, 0.65P
CASE 511BX
ISSUE C


DATE 25 SEP 2026



TOP VIEW




FRONT VIEW



BOTTOM VIEW

UNIT IN MILLIMETERS			
DIM	MIN	NOM	MAX
A	0.53	0.58	0.63
A1	0.00	–	0.05
A3		0.20 REF	
b	0.25	0.30	0.35
b1	0.37	0.42	0.47
D		3.30 BSC	
D2	2.31	2.41	2.51
D3	1.58	1.68	1.78
D4	0.35	0.45	0.55
D5	0.25	0.35	0.45
D6	2.10	2.20	2.30
D7	2.31	2.41	2.51
D8		0.55 REF	
e		0.65 BSC	
E		3.30 BSC	
E2	0.84	0.94	1.04
E3	0.20	0.25	0.30


DIM	MIN	NOM	MAX
E4	1.50	1.60	1.70
E5	0.25	0.35	0.40
E6		0.60 REF	
E7	2.10	2.20	2.30
k		0.75 REF	
k1		0.45 REF	
L	0.73	0.83	0.93
L1	0.10	0.20	0.30
L2	0.35	0.45	0.55
L4	0.40	0.50	0.60
TOLERANCE FORM & POSITION			
aaa		0.10	
bbb		0.10	
ccc		0.10	
ddd		0.05	
eee		0.08	



DETAIL A
SCALE: 3:1

NOTES:


1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2018.
2. CONTROLLING DIMENSION: MILLIMETERS
3. COPLANARITY APPLIES TO THE EXPOSED PADS AS WELL AS THE TERMINALS.
4. DIMENSIONS D1, D2, E1 AND E2 DO NOT INCLUDE MOLD FLASH.
5. SEATING PLANE IS DEFINED BY THE TERMINALS. "A1" IS DEFINED AS THE DISTANCE FROM THE SEATING PLANE TO THE LOWEST POINT ON THE PACKAGE BODY.



RECOMMENDED MOUNTING FOOTPRINT

*For additional information on our Pb-Free Strategy and Soldering details, please download the onsemi Soldering and Mounting Techniques reference manual, SOLDERRM/D.

GENERIC MARKING DIAGRAM*



XXX = Specific Device Code
A = Assembly Location
Y = Year
W = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON34932H**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.	
DESCRIPTION:	**WDFN−9 3.30x3.30x0.58, 0.65P**		**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.