UNIKC Semiconductor


RoHS Compliant

P3203CMG


N-Channel Enhancement Mode MOSFET

PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
30V	32mΩ @V_{GS} = 4.5V	6A



SOT-23



ABSOLUTE MAXIMUM RATINGS (T_A = 25 °C Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		V_{DS}	30	V
Gate-Source Voltage		V_{GS}	±12	
Continuous Drain Current	T_A = 25 °C	I_D	6	A
	T_A = 70 °C		5	
Pulsed Drain Current[1]		I_{DM}	30	
Power Dissipation	T_A = 25 °C	P_D	1.25	W
	T_A = 70 °C		0.8	
Operating Junction & Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Ambient[3]	$R_{\theta JA}$		100	°C / W

[1]Pulse width limited by maximum junction temperature.

[2]Limited only by maximum temperature allowed.

UNIKC Semiconductor

RoHS Compliant

P3203CMG

N-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS (T_J = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D = 250μA	30			V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250μA	0.45	0.7	1.2	
Gate-Body Leakage	I_{GSS}	V_{DS} = 0V, V_{GS} = ±16V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 16V, V_{GS} = 0V			1	μA
		V_{DS} = 10V, V_{GS} = 0V , T_J = 55 °C			10	
On-State Drain Current[1]	$I_{D(ON)}$	V_{DS} = 5V, V_{GS} = 4.5V	30			A
Drain-Source On-State Resistance[1]	$R_{DS(ON)}$	V_{GS} = 2.5V, I_D = 4A		32	50	mΩ
		V_{GS} = 4.5V, I_D = 5A		24	32	
		V_{GS} = 10V, I_D = 6A		22	28	
Forward Transconductance[1]	g_{fs}	V_{DS} = 5V, I_D = 5A		33		S
DYNAMIC						
Input Capacitance	C_{iss}	V_{GS} = 0V, V_{DS} = 15V, f = 1MHz		620		pF
Output Capacitance	C_{oss}			69		
Reverse Transfer Capacitance	C_{rss}			62		
Total Gate Charge[2]	Q_g	V_{DS} = 0.5$V_{(BR)DSS}$, V_{GS} = 4.5V, I_D = 5A		8		nC
Gate-Source Charge[2]	Q_{gs}			1.5		
Gate-Drain Charge[2]	Q_{gd}			3		
Turn-On Delay Time[2]	$t_{d(on)}$	V_{DS} = 15V, I_D ≅ 5A, V_{GS} = 4.5V, R_{GS} = 6Ω		4.5		nS
Rise Time[2]	t_r			4		
Turn-Off Delay Time[2]	$t_{d(off)}$			37		
Fall Time[2]	t_f			6		
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICE (T_J = 25 ˚C)						
Continuous Current	I_S				1	A
Forward Voltage[1]	V_{SD}	I_F = 1.3A, V_{GS} = 0V			1.3	V
Reverse Recovery Time	t_{rr}	I_F = 6A, dI_F/dt = 100 A/μs		10.5		nS
Reverse Recovery Charge	Q_{rr}			2.1		μC

[1]Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

[2]Independent of operating temperature.


UNIKC Semiconductor

RoHS Compliant


P3203CMG

N-Channel Enhancement Mode MOSFET


Output Characteristics




Transfer Characteristics




On-Resistance VS Temperature




Capacitance Characteristic



Gate charge Characteristics



Source-Drain Diode Forward Voltage




UNIKC Semiconductor

RoHS Compliant


P3203CMG

N-Channel Enhancement Mode MOSFET


Safe Operating Area



Single Pulse Maximum Power Dissipation



Transient Thermal Response Curve



UNIKC Semiconductor

RoHS Compliant


P3203CMG

N-Channel Enhancement Mode MOSFET

Package Dimension

SOT-23-3 MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A		1.05		H	0.1		0.2
B	2.4		3	I	0.3		0.6
C	1.4		1.73				
D	2.7		3.1				
E	1		1.31				
F	0		0.15				
G	0.3		0.5				



ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.