UNIKC Semiconductor


RoHS Compliant

PA102FMG


P-Channel Enhancement Mode MOSFET

PRODUCT SUMMARY

$V_{(BR)DSS}$	$R_{DS(ON)}$	I_D
-20V	118mΩ @V_{GS} = -4.5V	-3A



SOT-23



ABSOLUTE MAXIMUM RATINGS (T_A = 25 °C Unless Otherwise Noted)

PARAMETERS/TEST CONDITIONS		SYMBOL	LIMITS	UNITS
Drain-Source Voltage		V_{DS}	-20	V
Gate-Source Voltage		V_{GS}	±12	
Continuous Drain Current	T_A = 25 °C	I_D	-3	A
	T_A = 70 °C		-2.1	
Pulsed Drain Current[1]		I_{DM}	-10	
Power Dissipation	T_A = 25 °C	P_D	1.38	W
	T_A = 70 °C		0.88	
Operating Junction & Storage Temperature Range		T_J, T_{STG}	-55 to 150	°C

THERMAL RESISTANCE RATINGS

THERMAL RESISTANCE	SYMBOL	TYPICAL	MAXIMUM	UNITS
Junction-to-Ambient	$R_{\theta JA}$		90	°C / W

[1]Pulse width limited by maximum junction temperature.

[2]Duty cycle ≦ 1%

UNIKC Semiconductor

RoHS Compliant

PA102FMG

P-Channel Enhancement Mode MOSFET

ELECTRICAL CHARACTERISTICS (T_J = 25 °C, Unless Otherwise Noted)

PARAMETER	SYMBOL	TEST CONDITIONS	LIMITS			UNIT
			MIN	TYP	MAX	
STATIC						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D = -250μA	-20			V
Gate Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = -250μA	-0.45	-0.8	-1.2	
Gate-Body Leakage	I_{GSS}	V_{DS} = 0V, V_{GS} = ±12V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = -16V, V_{GS} = 0V			-1	μA
		V_{DS} = -16V, V_{GS} = 0V , T_J = 125 °C			-10	
On-State Drain Current[1]	$I_{D(ON)}$	V_{DS} = -5V, V_{GS} = -4.5V	-10			A
Drain-Source On-State Resistance[1]	$R_{DS(ON)}$	V_{GS} = -2.5V, I_D = -1A		150	215	mΩ
		V_{GS} = -4.5V, I_D = -2A		98	118	
		V_{GS} = -10V, I_D = -2A		72	85	
Forward Transconductance[1]	g_{fs}	V_{DS} = -5V, I_D = -2A		16		S
DYNAMIC						
Input Capacitance	C_{iss}	V_{GS} = 0V, V_{DS} = -6V, f = 1MHz		430		pF
Output Capacitance	C_{oss}			235		
Reverse Transfer Capacitance	C_{rss}			95		
Total Gate Charge[2]	Q_g	V_{DS} = 0.5$V_{(BR)DSS}$, V_{GS} = -4.5V, I_D = -2A		7.6	10	nC
Gate-Source Charge[2]	Q_{gs}			3.2		
Gate-Drain Charge[2]	Q_{gd}			2		
Turn-On Delay Time[2]	$t_{d(on)}$	V_{DD} = -10V, I_D ≅ -1A, V_{GS} = -4.5V, R_G = 6Ω		11	22	nS
Rise Time[2]	t_r			32	55	
Turn-Off Delay Time[2]	$t_{d(off)}$			38	68	
Fall Time[2]	t_f			32	55	
SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICE (T_J = 25 ˚C)						
Continuous Current	I_S				-1.6	A
Forward Voltage[1]	V_{SD}	I_F = -2A, V_{GS} = 0V			-1.2	V


[1]Pulse test : Pulse Width ≤ 300 μsec, Duty Cycle ≤ 2%.

[2]Independent of operating temperature.


PA102FMG

P-Channel Enhancement Mode MOSFET


On-Region Characteristics




Transfer Characteristics




Threshold Voltage vs. Junction Temperature




On-Resistance Variation with Drain Current and Gate Voltage



On-Resistance Variation with Gate-to-Source Voltage



On-Resistance Variation with Temperature





UNIKC Semiconductor


RoHS Compliant


PA102FMG


P-Channel Enhancement Mode MOSFET











UNIKC Semiconductor

RoHS Compliant


PA102FMG

P-Channel Enhancement Mode MOSFET

Package Dimension

SOT-23-3 MECHANICAL DATA

Dimension	mm			Dimension	mm		
	Min.	Typ.	Max.		Min.	Typ.	Max.
A		1.05		H	0.1		0.2
B	2.4		3	I	0.3		0.6
C	1.4		1.73				
D	2.7		3.1				
E	1		1.31				
F	0		0.15				
G	0.3		0.5				



ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.