# TP2640

## P-Channel Enhancement-Mode Vertical DMOS FET

### Features

- –2V Maximum Low Threshold
- High Input Impedance
- Low Input Capacitance
- Fast Switching Speeds
- Low On-Resistance
- Free from Secondary Breakdown
- Low Input and Output Leakage

### Applications

- Logic-Level Interfaces (Ideal for TTL and CMOS)
- Solid State Relays
- Battery-Operated Systems
- Photovoltaic Drives
- Analog Switches
- General Purpose Line Drivers
- Telecommunication Switches


### General Description

The TP2640 is a low-threshold, Enhancement-mode (normally-off) transistor that uses an advanced vertical DMOS structure and a well-proven silicon gate manufacturing process. This combination produces a device with the power handling capabilities of bipolar transistors and the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, this device is free from thermal runaway and thermally induced secondary breakdown.


Microchip's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

### Package Type

**3-lead TO-92**
(Top view)




**8-lead SOIC**
(Top view)




See Table 3-1 and Table 3-2 for pin information.

© 2020 Microchip Technology Inc.

## 1.0 ELECTRICAL CHARACTERISTICS

### Absolute Maximum Ratings†

Drain-to-Source Voltage ..... $BV_{DSS}$
Drain-to-Gate Voltage ..... $BV_{DGS}$
Gate-to-Source Voltage ..... ±20V
Operating Ambient Temperature, $T_A$ ..... –55°C to +150°C
Storage Temperature, $T_S$ ..... –55°C to +150°C

**† Notice:** Stresses above those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only, and functional operation of the device at those or any other conditions above those indicated in the operational sections of this specification is not intended. Exposure to maximum rating conditions for extended periods may affect device reliability.

## DC ELECTRICAL CHARACTERISTICS

**Electrical Specifications:** $T_A$ = 25°C unless otherwise specified. All DC parameters are 100% tested at 25°C unless otherwise stated. Pulse test: 300 µs pulse, 2% duty cycle.

| Parameter | Sym. | Min. | Typ. | Max. | Unit | Conditions |
|---|---|---|---|---|---|---|
| Drain-to-Source Breakdown Voltage | $BV_{DSS}$ | –400 | — | — | V | $V_{GS}$ = 0V, $I_D$ = –2 mA |
| Gate Threshold Voltage | $V_{GS(th)}$ | –0.8 | — | –2 | V | $V_{GS}$ = $V_{DS}$, $I_D$ = –1 mA |
| Change in $V_{GS(th)}$ with Temperature | $\Delta V_{GS(th)}$ | — | — | 5 | mV/°C | $V_{GS}$ = $V_{DS}$, $I_D$ = –1 mA (**Note 1**) |
| Gate Body Leakage Current | $I_{GSS}$ | — | — | –100 | nA | $V_{GS}$ = ±20V, $V_{DS}$ = 0V |
| Zero-Gate Voltage Drain Current | $I_{DSS}$ | — | — | –1 | µA | $V_{GS}$ = 0V, $V_{DS}$ = –100V |
| | | | | –10 | mA | $V_{GS}$ = 0V, $V_{DS}$ = Maximum rating |
| | | | | –1 | mA | $V_{DS}$ = 0.8 Maximum rating, $V_{GS}$ = 0V, $T_A$ = 125°C (**Note 1**) |
| On-State Drain Current | $I_{D(ON)}$ | –0.7 | — | — | A | $V_{GS}$ = –10V, $V_{DS}$ = –25V |
| Static Drain-to-Source On-State Resistance | $R_{DS(ON)}$ | — | 12 | 15 | Ω | $V_{GS}$ = –2.5V, $I_D$ = –20 mA |
| | | | 11 | 15 | Ω | $V_{GS}$ = –4.5V, $I_D$ = –150 mA |
| | | | 11 | 15 | Ω | $V_{GS}$ = –10V, $I_D$ = –300 mA |
| Change in $R_{DS(ON)}$ with Temperature | $\Delta R_{DS(ON)}$ | — | — | 0.75 | %/°C | $V_{GS}$ = –10V, $I_D$ = –300 mA (**Note 1**) |

**Note 1:** Specification is obtained by characterization and is not 100% tested.


© 2020 Microchip Technology Inc.

## AC ELECTRICAL CHARACTERISTICS

**Electrical Specifications:** $T_A$ = 25°C unless otherwise specified. Specification is obtained by characterization and is not 100% tested.

| Parameter | Sym. | Min. | Typ. | Max. | Unit | Conditions |
|---|---|---|---|---|---|---|
| Forward Transconductance | $G_{FS}$ | 200 | — | — | mmho | $V_{DS}$ = –25V, $I_D$ = –300 mA |
| Input Capacitance | $C_{ISS}$ | — | — | 300 | pF | $V_{GS}$ = 0V, $V_{DS}$ = –25V, f = 1 MHz |
| Common-Source Output Capacitance | $C_{OSS}$ | — | — | 50 | pF | |
| Reverse Transfer Capacitance | $C_{RSS}$ | — | — | 12 | pF | |
| Turn-On Delay Time | $t_{d(ON)}$ | — | — | 10 | ns | $V_{DD}$ = –25V, $I_D$ = –300 mA, $R_{GEN}$ = 25Ω |
| Rise Time | $t_r$ | — | — | 15 | ns | |
| Turn-Off Delay Time | $t_{d(OFF)}$ | — | — | 60 | ns | |
| Fall Time | $t_f$ | — | — | 40 | ns | |
| **DIODE PARAMETER** | | | | | | |
| Diode Forward Voltage Drop | $V_{SD}$ | — | — | 1.8 | V | $V_{GS}$ = 0V, $I_{DS}$ = –200 mA (**Note 1**) |
| Reverse Recovery Time | $t_{rr}$ | — | 300 | — | ns | $V_{GS}$ = 0V, $I_{DS}$ = –200 mA |

**Note 1:** Unless otherwise stated, all DC parameters are 100% tested at 25°C. Pulse test: 300 µs pulse, 2% duty cycle

## TEMPERATURE SPECIFICATIONS

| Parameter | Sym. | Min. | Typ. | Max. | Unit | Conditions |
|---|---|---|---|---|---|---|
| **TEMPERATURE RANGE** | | | | | | |
| Operating Ambient Temperature | $T_A$ | –55 | — | +150 | °C | |
| Storage Temperature | $T_S$ | –55 | — | +150 | °C | |
| **PACKAGE THERMAL RESISTANCE** | | | | | | |
| 3-lead TO-92 | $\theta_{JA}$ | — | 132 | — | °C/W | |
| 8-lead SOIC | $\theta_{JA}$ | — | 101 | — | °C/W | |

## THERMAL CHARACTERISTICS

| Package | $I_D$ (**Note 1**) (Continuous) (mA) | $I_D$ (Pulsed) (mA) | Power Dissipation at $T_A$ = 25°C (W) | $I_{DR}$ (**Note 1**) (mA) | $I_{DRM}$ (mA) |
|---|---|---|---|---|---|
| 3-lead TO-92 | –180 | –800 | 1 | –180 | –800 |
| 8-lead SOIC | –86 | –600 | 0.74 (**Note 2**) | –86 | –600 |

**Note 1:** $I_D$ (continuous) is limited by maximum $T_J$.

**2:** Mounted on an FR board, 25 mm x 25 mm x 1.57 mm

© 2020 Microchip Technology Inc.

## 2.0 TYPICAL PERFORMANCE CURVES

**Note:** The graphs and tables provided following this note are a statistical summary based on a limited number of samples and are provided for informational purposes only. The performance characteristics listed herein are not tested or guaranteed. In some graphs or tables, the data presented may be outside the specified operating range (e.g. outside specified power supply range) and therefore outside the warranted range.





***FIGURE 2-1:*** *$BV_{DSS}$ Variation with Temperature.*





***FIGURE 2-2:*** *Transfer Characteristics.*





***FIGURE 2-3:*** *Capacitance vs. Drain-to-Source Voltage.*





***FIGURE 2-4:*** *On-Resistance vs. Drain Current.*





***FIGURE 2-5:*** *$V_{GS(th)}$ and $R_{DS}$ Variation with Temperature.*





***FIGURE 2-6:*** *Gate Drive Dynamic Characteristics.*


© 2020 Microchip Technology Inc.





***FIGURE 2-7:*** *Output Characteristics.*





***FIGURE 2-10:*** *Saturation Characteristics.*





***FIGURE 2-8:*** *Transconductance vs. Drain Current.*





***FIGURE 2-11:*** *Power Dissipation vs. Temperature.*





***FIGURE 2-9:*** *Maximum Rated Safe Operating Area.*





***FIGURE 2-12:*** *Thermal Response Characteristics.*

## 3.0 PIN DESCRIPTION

The details on the pins of TP2640 TO-92 and SOT-89 packages are listed in Table 3-1 and Table 3-2, respectively. Refer to **Package Type** for the location of pins.

**TABLE 3-1: 3-LEAD TO-92 PIN FUNCTION TABLE**

| Pin Number | Pin Name | Description |
|---|---|---|
| 1 | Source | Source |
| 2 | Gate | Gate |
| 3 | Drain | Drain |

**TABLE 3-2: 8-LEAD SOIC PIN FUNCTION TABLE**

| Pin Number | Pin Name | Description |
|---|---|---|
| 1 | N/C | No Connection |
| 2 | N/C | No Connection |
| 3 | Source | Source |
| 4 | Gate | Gate |
| 5 | Drain | Drain |
| 6 | Drain | Drain |
| 7 | Drain | Drain |
| 8 | Drain | Drain |


© 2020 Microchip Technology Inc.

## 4.0 FUNCTIONAL DESCRIPTION

Figure 4-1 illustrates the switching waveforms and test circuit for TP2640.





***FIGURE 4-1:*** *Switching Waveforms and Test Circuit.*


**TABLE 4-1: PRODUCT SUMMARY**

| $BV_{DSS}/BV_{DGS}$ (V) | $R_{DS(ON)}$ (Maximum) (Ω) | $I_{D(ON)}$ (Minimum) (A) | $V_{GS(th)}$ (Maximum) (V) |
|---|---|---|---|
| –400 | 15 | –2 | –0.7 |


## 5.0 PACKAGING INFORMATION

### 5.1 Package Marking Information


3-lead TO-92





Example




8-lead SOIC




Example





| | | |
|---|---|---|
| **Legend:** | XX...X | Product Code or Customer-specific information |
| | Y | Year code (last digit of calendar year) |
| | YY | Year code (last 2 digits of calendar year) |
| | WW | Week code (week of January 1 is week ‘01’) |
| | NNN | Alphanumeric traceability code |
| | (e3) | Pb-free JEDEC® designator for Matte Tin (Sn) |
| | * | This package is Pb-free. The Pb-free JEDEC designator ((e3)) can be found on the outer packaging for this package. |

**Note**: In the event the full Microchip part number cannot be marked on one line, it will be carried over to the next line, thus limiting the number of available characters for product code or customer-specific information. Package may or not include the corporate logo.


© 2020 Microchip Technology Inc.

## 3-Lead TO-92 Package Outline (L/LL/N3)





Note: For the most current package drawings, see the Microchip Packaging Specification at www.microchip.com/packaging.

| Symbol | | A | b | c | D | E | E1 | e | e1 | L |
|---|---|---|---|---|---|---|---|---|---|---|
| Dimensions (inches) | MIN | .170 | .014† | .014† | .175 | .125 | .080 | .095 | .045 | .500 |
| | NOM | - | - | - | - | - | - | - | - | - |
| | MAX | .210 | .022† | .022† | .205 | .165 | .105 | .105 | .055 | .610* |

*JEDEC Registration TO-92.*
** This dimension is not specified in the JEDEC drawing.*
*† This dimension differs from the JEDEC drawing.*
***Drawings not to scale.***

## 8-Lead SOIC (Narrow Body) Package Outline (LG/TG)

***4.90x3.90mm body, 1.75mm height (max), 1.27mm pitch***




Note: For the most current package drawings, see the Microchip Packaging Specification at www.microchip.com/packaging.

***Note:***

1. *This chamfer feature is optional. A Pin 1 identifier must be located in the index area indicated. The Pin 1 identifier can be: a molded mark/identifier; an embedded metal marker; or a printed indicator.*

| Symbol | | A | A1 | A2 | b | D | E | E1 | e | h | L | L1 | L2 | θ | θ1 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Dimension (mm) | MIN | 1.35* | 0.10 | 1.25 | 0.31 | 4.80* | 5.80* | 3.80* | 1.27 BSC | 0.25 | 0.40 | 1.04 REF | 0.25 BSC | 0° | 5° |
| | NOM | - | - | - | - | 4.90 | 6.00 | 3.90 | | - | - | | | - | - |
| | MAX | 1.75 | 0.25 | 1.65* | 0.51 | 5.00* | 6.20* | 4.00* | | 0.50 | 1.27 | | | 8° | 15° |

*JEDEC Registration MS-012, Variation AA, Issue E, Sept. 2005.*

** This dimension is not specified in the JEDEC drawing.*

***Drawings are not to scale.***


© 2020 Microchip Technology Inc.

# APPENDIX A: REVISION HISTORY

## Revision A (July 2020)

- Converted Supertex Doc# DSFP-TP2640 to Microchip DS20006372A
- Changed the package marking format
- Updated the quantity of the 8-lead SOIC LG package from 2500/Reel to 3300/Reel to align it with the actual BQM
- Removed the P002, P003, P005, P013, P014 media types for the 3-lead TO-92 N3 package
- Made minor text changes throughout the document

## PRODUCT IDENTIFICATION SYSTEM

To order or obtain information, e.g., on pricing or delivery, contact your local Microchip representative or sales office.

| PART NO. | XX | - | X | - | X |
|---|---|---|---|---|---|
| Device | Package Options | | Environmental | | Media Type |

| | | | |
|---|---|---|---|
| Device: | TP2640 | = | P-Channel Enhancement-Mode Vertical DMOS FET |
| Packages: | N3 | = | 3-lead TO-92 |
| | LG | = | 8-lead SOIC |
| Environmental: | G | = | Lead (Pb)-free/RoHS-compliant Package |
| Media Types: | (blank) | = | 1000/Bag for an N3 Package |
| | (blank) | = | 3300/Reel for an LG Package |

**Examples:**

a) TP2640N3-G: P-Channel Enhancement-Mode Vertical DMOS FET, 3-lead TO-92, 1000/Bag

b) TP2640LG-G: P-Channel Enhancement-Mode Vertical DMOS FET, 8-lead SOIC, 3000/Reel


© 2020 Microchip Technology Inc.

**Note the following details of the code protection feature on Microchip devices:**

- Microchip products meet the specification contained in their particular Microchip Data Sheet.
- Microchip believes that its family of products is one of the most secure families of its kind on the market today, when used in the intended manner and under normal conditions.
- There are dishonest and possibly illegal methods used to breach the code protection feature. All of these methods, to our knowledge, require using the Microchip products in a manner outside the operating specifications contained in Microchip's Data Sheets. Most likely, the person doing so is engaged in theft of intellectual property.
- Microchip is willing to work with the customer who is concerned about the integrity of their code.
- Neither Microchip nor any other semiconductor manufacturer can guarantee the security of their code. Code protection does not mean that we are guaranteeing the product as "unbreakable."

Code protection is constantly evolving. We at Microchip are committed to continuously improving the code protection features of our products. Attempts to break Microchip's code protection feature may be a violation of the Digital Millennium Copyright Act. If such acts allow unauthorized access to your software or other copyrighted work, you may have a right to sue for relief under that Act.

Information contained in this publication regarding device applications and the like is provided only for your convenience and may be superseded by updates. It is your responsibility to ensure that your application meets with your specifications. MICROCHIP MAKES NO REPRESENTATIONS OR WARRANTIES OF ANY KIND WHETHER EXPRESS OR IMPLIED, WRITTEN OR ORAL, STATUTORY OR OTHERWISE, RELATED TO THE INFORMATION, INCLUDING BUT NOT LIMITED TO ITS CONDITION, QUALITY, PERFORMANCE, MERCHANTABILITY OR FITNESS FOR PURPOSE**.** Microchip disclaims all liability arising from this information and its use. Use of Microchip devices in life support and/or safety applications is entirely at the buyer's risk, and the buyer agrees to defend, indemnify and hold harmless Microchip from any and all damages, claims, suits, or expenses resulting from such use. No licenses are conveyed, implicitly or otherwise, under any Microchip intellectual property rights unless otherwise stated.

**Trademarks**

The Microchip name and logo, the Microchip logo, Adaptec, AnyRate, AVR, AVR logo, AVR Freaks, BesTime, BitCloud, chipKIT, chipKIT logo, CryptoMemory, CryptoRF, dsPIC, FlashFlex, flexPWR, HELDO, IGLOO, JukeBlox, KeeLoq, Kleer, LANCheck, LinkMD, maXStylus, maXTouch, MediaLB, megaAVR, Microsemi, Microsemi logo, MOST, MOST logo, MPLAB, OptoLyzer, PackeTime, PIC, picoPower, PICSTART, PIC32 logo, PolarFire, Prochip Designer, QTouch, SAM-BA, SenGenuity, SpyNIC, SST, SST Logo, SuperFlash, Symmetricom, SyncServer, Tachyon, TempTrackr, TimeSource, tinyAVR, UNI/O, Vectron, and XMEGA are registered trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

APT, ClockWorks, The Embedded Control Solutions Company, EtherSynch, FlashTec, Hyper Speed Control, HyperLight Load, IntelliMOS, Libero, motorBench, mTouch, Powermite 3, Precision Edge, ProASIC, ProASIC Plus, ProASIC Plus logo, Quiet-Wire, SmartFusion, SyncWorld, Temux, TimeCesium, TimeHub, TimePictra, TimeProvider, Vite, WinPath, and ZL are registered trademarks of Microchip Technology Incorporated in the U.S.A.

Adjacent Key Suppression, AKS, Analog-for-the-Digital Age, Any Capacitor, AnyIn, AnyOut, BlueSky, BodyCom, CodeGuard, CryptoAuthentication, CryptoAutomotive, CryptoCompanion, CryptoController, dsPICDEM, dsPICDEM.net, Dynamic Average Matching, DAM, ECAN, EtherGREEN, In-Circuit Serial Programming, ICSP, INICnet, Inter-Chip Connectivity, JitterBlocker, KleerNet, KleerNet logo, memBrain, Mindi, MiWi, MPASM, MPF, MPLAB Certified logo, MPLIB, MPLINK, MultiTRAK, NetDetach, Omniscient Code Generation, PICDEM, PICDEM.net, PICkit, PICtail, PowerSmart, PureSilicon, QMatrix, REAL ICE, Ripple Blocker, SAM-ICE, Serial Quad I/O, SMART-I.S., SQI, SuperSwitcher, SuperSwitcher II, Total Endurance, TSHARC, USBCheck, VariSense, ViewSpan, WiperLock, Wireless DNA, and ZENA are trademarks of Microchip Technology Incorporated in the U.S.A. and other countries.

SQTP is a service mark of Microchip Technology Incorporated in the U.S.A.

The Adaptec logo, Frequency on Demand, Silicon Storage Technology, and Symmcom are registered trademarks of Microchip Technology Inc. in other countries.

GestIC is a registered trademark of Microchip Technology Germany II GmbH & Co. KG, a subsidiary of Microchip Technology Inc., in other countries.

All other trademarks mentioned herein are property of their respective companies.

© 2020, Microchip Technology Incorporated, All Rights Reserved.

ISBN: 978-1-5224-6451-8

*For information regarding Microchip's Quality Management Systems, please visit www.microchip.com/quality.*

# Worldwide Sales and Service


## AMERICAS

**Corporate Office**
2355 West Chandler Blvd.
Chandler, AZ 85224-6199
Tel: 480-792-7200
Fax: 480-792-7277
Technical Support:
http://www.microchip.com/support
Web Address:
www.microchip.com

**Atlanta**
Duluth, GA
Tel: 678-957-9614
Fax: 678-957-1455

**Austin, TX**
Tel: 512-257-3370

**Boston**
Westborough, MA
Tel: 774-760-0087
Fax: 774-760-0088

**Chicago**
Itasca, IL
Tel: 630-285-0071
Fax: 630-285-0075

**Dallas**
Addison, TX
Tel: 972-818-7423
Fax: 972-818-2924

**Detroit**
Novi, MI
Tel: 248-848-4000

**Houston, TX**
Tel: 281-894-5983

**Indianapolis**
Noblesville, IN
Tel: 317-773-8323
Fax: 317-773-5453
Tel: 317-536-2380

**Los Angeles**
Mission Viejo, CA
Tel: 949-462-9523
Fax: 949-462-9608
Tel: 951-273-7800

**Raleigh, NC**
Tel: 919-844-7510

**New York, NY**
Tel: 631-435-6000

**San Jose, CA**
Tel: 408-735-9110
Tel: 408-436-4270

**Canada - Toronto**
Tel: 905-695-1980
Fax: 905-695-2078

## ASIA/PACIFIC

**Australia - Sydney**
Tel: 61-2-9868-6733

**China - Beijing**
Tel: 86-10-8569-7000

**China - Chengdu**
Tel: 86-28-8665-5511

**China - Chongqing**
Tel: 86-23-8980-9588

**China - Dongguan**
Tel: 86-769-8702-9880

**China - Guangzhou**
Tel: 86-20-8755-8029

**China - Hangzhou**
Tel: 86-571-8792-8115

**China - Hong Kong SAR**
Tel: 852-2943-5100

**China - Nanjing**
Tel: 86-25-8473-2460

**China - Qingdao**
Tel: 86-532-8502-7355

**China - Shanghai**
Tel: 86-21-3326-8000

**China - Shenyang**
Tel: 86-24-2334-2829

**China - Shenzhen**
Tel: 86-755-8864-2200

**China - Suzhou**
Tel: 86-186-6233-1526

**China - Wuhan**
Tel: 86-27-5980-5300

**China - Xian**
Tel: 86-29-8833-7252

**China - Xiamen**
Tel: 86-592-2388138

**China - Zhuhai**
Tel: 86-756-3210040

## ASIA/PACIFIC

**India - Bangalore**
Tel: 91-80-3090-4444

**India - New Delhi**
Tel: 91-11-4160-8631

**India - Pune**
Tel: 91-20-4121-0141

**Japan - Osaka**
Tel: 81-6-6152-7160

**Japan - Tokyo**
Tel: 81-3-6880- 3770

**Korea - Daegu**
Tel: 82-53-744-4301

**Korea - Seoul**
Tel: 82-2-554-7200

**Malaysia - Kuala Lumpur**
Tel: 60-3-7651-7906

**Malaysia - Penang**
Tel: 60-4-227-8870

**Philippines - Manila**
Tel: 63-2-634-9065

**Singapore**
Tel: 65-6334-8870

**Taiwan - Hsin Chu**
Tel: 886-3-577-8366

**Taiwan - Kaohsiung**
Tel: 886-7-213-7830

**Taiwan - Taipei**
Tel: 886-2-2508-8600

**Thailand - Bangkok**
Tel: 66-2-694-1351

**Vietnam - Ho Chi Minh**
Tel: 84-28-5448-2100

## EUROPE

**Austria - Wels**
Tel: 43-7242-2244-39
Fax: 43-7242-2244-393

**Denmark - Copenhagen**
Tel: 45-4485-5910
Fax: 45-4485-2829

**Finland - Espoo**
Tel: 358-9-4520-820

**France - Paris**
Tel: 33-1-69-53-63-20
Fax: 33-1-69-30-90-79

**Germany - Garching**
Tel: 49-8931-9700

**Germany - Haan**
Tel: 49-2129-3766400

**Germany - Heilbronn**
Tel: 49-7131-72400

**Germany - Karlsruhe**
Tel: 49-721-625370

**Germany - Munich**
Tel: 49-89-627-144-0
Fax: 49-89-627-144-44

**Germany - Rosenheim**
Tel: 49-8031-354-560

**Israel - Ra'anana**
Tel: 972-9-744-7705

**Italy - Milan**
Tel: 39-0331-742611
Fax: 39-0331-466781

**Italy - Padova**
Tel: 39-049-7625286

**Netherlands - Drunen**
Tel: 31-416-690399
Fax: 31-416-690340

**Norway - Trondheim**
Tel: 47-7288-4388

**Poland - Warsaw**
Tel: 48-22-3325737

**Romania - Bucharest**
Tel: 40-21-407-87-50

**Spain - Madrid**
Tel: 34-91-708-08-90
Fax: 34-91-708-08-91

**Sweden - Gothenberg**
Tel: 46-31-704-60-40

**Sweden - Stockholm**
Tel: 46-8-5090-4654

**UK - Wokingham**
Tel: 44-118-921-5800
Fax: 44-118-921-5820



© 2020 Microchip Technology Inc.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

# Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

### Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

**www.entegreci.com**

### Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

**Kategorilere göz atın**

### Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

**Üreticileri görün**

### Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

**Teklif isteyin**

**www.entegreci.com** | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.