
# TSM180P03CS

30V P-Channel Power MOSFET

**SOP-8**




**Pin Definition:**

1. Source
2. Source
3. Source
4. Gate
8. Drain
7. Drain
6. Drain
5. Drain

## Key Parameter Performance


| Parameter | | Value | Unit |
|---|---|---|---|
| $V_{DS}$ | | -30 | V |
| $R_{DS(on)}$ (max) | $V_{GS}$ = -10V | 18 | mΩ |
| | $V_{GS}$ = -4.5V | 30 | |
| $Q_g$ | | 14.6 | nC |

## Ordering Information

| Part No. | Package | Packing |
|---|---|---|
| TSM180P03CS RLG | SOP-8 | 2.5kpcs / 13" Reel |

**Note:** "G" denotes for Halogen- and Antimony-free as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds

## Block Diagram




P-Channel MOSFET

## Absolute Maximum Ratings (Tc=25°C unless otherwise noted)

| Parameter | | Symbol | Limit | Unit |
|---|---|---|---|---|
| Drain-Source Voltage | | $V_{DS}$ | -30 | V |
| Gate-Source Voltage | | $V_{GS}$ | ±20 | V |
| Continuous Drain Current | Tc=25ºC | $I_D$ | -10 | A |
| | Tc=100ºC | | -6.3 | A |
| Pulsed Drain Current (Note 1) | | $I_{DM}$ | -40 | A |
| Power Dissipation @ $T_C$ = 25°C | | $P_D$ | 2.5 | W |
| Operating Junction Temperature | | $T_J$ | 150 | ºC |
| Storage Temperature Range | | $T_{STG}$ | -55 to +150 | °C |

## Thermal Performance

| Parameter | Symbol | Limit | Unit |
|---|---|---|---|
| Thermal Resistance - Junction to Ambient | $R_{\Theta JA}$ | 50 | °C/W |

# TSM180P03CS

30V P-Channel Power MOSFET

Pb-Free RoHS COMPLIANT

## Electrical Specifications ($T_J$=25°C unless otherwise noted)

| Parameter | Conditions | Symbol | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| **Static** | | | | | | |
| Drain-Source Breakdown Voltage | $V_{GS}$ = 0V, $I_D$ = -250μA | $BV_{DSS}$ | -30 | -- | -- | V |
| Drain-Source On-State Resistance | $V_{GS}$ = -10V, $I_D$ = -8A | $R_{DS(ON)}$ | -- | 14 | 18 | mΩ |
| | $V_{GS}$ = -4.5V, $I_D$ = -6A | | -- | 23 | 30 | |
| Gate Threshold Voltage | $V_{DS}$ = $V_{GS}$, $I_D$ = -250μA | $V_{GS(TH)}$ | -1.2 | -1.6 | -2.5 | V |
| Zero Gate Voltage Drain Current | $V_{DS}$ = -30V, $V_{GS}$ = 0V | $I_{DSS}$ | -- | -- | -1 | μA |
| | $V_{DS}$ = -24V, $T_J$ = 125ºC | | -- | -- | -10 | |
| Gate Body Leakage | $V_{GS}$ = ±20V, $V_{DS}$ = 0V | $I_{GSS}$ | -- | -- | ±100 | nA |
| Forward Transconductance (Note 2) | $V_{DS}$ = -10V, $I_D$ = -8A | $g_{fs}$ | -- | 10.5 | -- | S |
| **Dynamic** | | | | | | |
| Total Gate Charge (Note 2,3) | $V_{DS}$ = -15V, $I_D$ = -8A, $V_{GS}$ = -4.5V | $Q_g$ | -- | 14.6 | -- | nC |
| Gate-Source Charge (Note 2,3) | | $Q_{gs}$ | -- | 4.1 | -- | |
| Gate-Drain Charge (Note 2,3) | | $Q_{gd}$ | -- | 6.3 | -- | |
| Input Capacitance | $V_{DS}$ = -15V, $V_{GS}$ = 0V, f = 1.0MHz | $C_{iss}$ | -- | 1730 | -- | pF |
| Output Capacitance | | $C_{oss}$ | -- | 180 | -- | |
| Reverse Transfer Capacitance | | $C_{rss}$ | -- | 125 | -- | |
| **Switching** | | | | | | |
| Turn-On Delay Time (Note 2,3) | $V_{DD}$ = -15V, $I_D$ = -1A, $V_{GS}$ = -10V, $R_{GEN}$ =6Ω | $t_{d(on)}$ | -- | 9 | -- | ns |
| Turn-On Rise Time (Note 2,3) | | $t_r$ | -- | 21.8 | -- | |
| Turn-Off Delay Time (Note 2,3) | | $t_{d(off)}$ | -- | 59.8 | -- | |
| Turn-Off Fall Time (Note 2,3) | | $t_f$ | -- | 14.4 | -- | |
| **Source-Drain Diode Ratings and Characteristic** | | | | | | |
| Maximum Continuous Drain-Source Diode Forward Current | Integral reverse diode in the MOSFET | $I_S$ | -- | -- | -10 | A |
| Maximum Pulse Drain-Source Diode Forward Current | | $I_{SM}$ | -- | -- | -40 | A |
| Diode-Source Forward Voltage | $V_{GS}$ = 0V, $I_S$ = -1A | $V_{SD}$ | -- | -- | -1 | V |


**Note:**

1. Pulse width limited by safe operating area
2. Pulse test: pulse width ≤300μs, duty cycle ≤2%
3. Switching time is essentially independent of operating temperature.


Pb-Free RoHS COMPLIANT

## Electrical Characteristics Curve


### Continuous Drain Current vs. $T_C$





### Gate Charge





### On-Resistance vs. Junction Temperature





### Threshold Voltage vs. Junction Temperature




### Maximum Safe Operating Area





### Normalized Thermal Transient Impedance Curve




Pb-Free RoHS COMPLIANT

## SOP-8 Mechanical Drawing




Unit: Millimeters

## Marking Diagram




**Y** = Year Code

**M** = Month Code for Halogen Free Product
(**O**=Jan, **P**=Feb, **Q**=Mar, **R**=Apl, **S**=May, **T**=Jun, **U**=Jul, **V**=Aug, **W**=Sep, **X**=Oct, **Y**=Nov, **Z**=Dec)

**L** = Lot Code

## Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

# Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

### Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

**www.entegreci.com**

### Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

**Kategorilere göz atın**

### Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

**Üreticileri görün**

### Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

**Teklif isteyin**

**www.entegreci.com** | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.