N-Channel Power MOSFET

100V, 6.5A, 95mΩ

FEATURES

- Fast switching
- Pb-free plating
- RoHS compliant
- Halogen-free mold compound

APPLICATION


- Networking
- Load Switch
- Lighting

KEY PERFORMANCE PARAMETERS			
PARAMETER		**VALUE**	**UNIT**
V_{DS}		100	V
$R_{DS(on)}$ (max)	V_{GS} = 10V	95	mΩ
	V_{GS} = 4.5V	110	
Q_g		9.3	nC

Pb-Free RoHS COMPLIANT HALOGEN FREE

SOT-223





Note: MSL 3 (Moisture Sensitivity Level) per J-STD-020

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)				
PARAMETER		**SYMBOL**	**LIMIT**	**UNIT**
Drain-Source Voltage		V_{DS}	100	V
Gate-Source Voltage		V_{GS}	±20	V
Continuous Drain Current (Note 1)	T_C = 25°C	I_D	6.5	A
	T_C = 100°C		4.1	
Pulsed Drain Current (Note 2)		I_{DM}	26	A
Total Power Dissipation @ T_C = 25°C		P_{DTOT}	9	W
Operating Junction and Storage Temperature Range		T_J, T_{STG}	- 55 to +150	°C

THERMAL PERFORMANCE			
PARAMETER	**SYMBOL**	**LIMIT**	**UNIT**
Junction to Case Thermal Resistance	$R_{\Theta JC}$	14	°C/W
Junction to Ambient Thermal Resistance	$R_{\Theta JA}$	62	°C/W

Notes: $R_{\Theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistances. The case thermal reference is defined at the solder mounting surface of the drain pins. $R_{\Theta JC}$ is guaranteed by design while $R_{\Theta CA}$ is determined by the user's board design. $R_{\Theta JA}$ shown below for single device operation on FR-4 PCB in still air

ELECTRICAL SPECIFICATIONS (T_A = 25°C unless otherwise noted)						
PARAMETER	**CONDITIONS**	**SYMBOL**	**MIN**	**TYP**	**MAX**	**UNIT**
Static (Note 3)						
Drain-Source Breakdown Voltage	V_{GS} = 0V, I_D = 250μA	BV_{DSS}	100	--	--	V
Gate Threshold Voltage	V_{DS} = V_{GS}, I_D = 250μA	$V_{GS(TH)}$	1.2	1.6	2.5	V
Gate Body Leakage	V_{GS} = ±20V, V_{DS} = 0V	I_{GSS}	--	--	±100	nA
Zero Gate Voltage Drain Current	V_{DS} = 100V, V_{GS} = 0V	I_{DSS}	--	--	1	μA
Drain-Source On-State Resistance	V_{GS} = 10V, I_D = 5A	$R_{DS(on)}$	--	80	95	mΩ
	V_{GS} = 4.5V, I_D = 3A		--	85	110	
Dynamic (Note 4)						
Total Gate Charge	V_{DS} = 48V, I_D = 5A, V_{GS} = 10V	Q_g	--	9.3	--	nC
Gate-Source Charge		Q_{gs}	--	2.1	--	
Gate-Drain Charge		Q_{gd}	--	1.8	--	
Input Capacitance	V_{DS} = 50V, V_{GS} = 0V, f = 1.0MHz	C_{iss}	--	1480	--	pF
Output Capacitance		C_{oss}	--	480	--	
Reverse Transfer Capacitance		C_{rss}	--	35	--	
Gate Resistance	f = 1MHz, open drain	R_g	--	1.3	--	Ω
Switching (Note 5)						
Turn-On Delay Time	V_{DD} = 30V, R_{GEN} = 3.3Ω, I_D = 1A, V_{GS} = 10V,	$t_{d(on)}$	--	2.9	--	ns
Turn-On Rise Time		t_r	--	9.5	--	
Turn-Off Delay Time		$t_{d(off)}$	--	18.4	--	
Turn-Off Fall Time		t_f	--	5.3	--	
Source-Drain Diode (Note 3)						
Forward On Voltage	I_S = 3.3A, V_{GS} = 0V	V_{SD}	--	--	1	V
Continuous Drain-Source Diode		I_S	--	--	6.5	A
Pulse Drain-Source Diode		I_{SM}	--	--	26	A

Notes:

1. Current limited by package
2. Pulse width limited by the maximum junction temperature
3. Pulse test: PW ≤ 300μs, duty cycle ≤ 2%
4. For DESIGN AID ONLY, not subject to production testing.
5. Switching time is essentially independent of operating temperature.

ORDERING INFORMATION

ORDERING CODE	PACKAGE	PACKING
TSM950N10CW RPG	SOT-223	2,500pcs / 13” Reel


Note:

1. Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
2. Halogen-free according to IEC 61249-2-21 definition


CHARACTERISTICS CURVES

(T_C = 25°C unless otherwise noted)


Continuous Drain Current vs. T_C




Gate Charge




On-Resistance vs. Junction Temperature




Threshold Voltage vs. Junction Temperature



Maximum Safe Operating Area




Normalized Thermal Transient Impedance Curve




PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

SOT-223



SUGGESTED PAD LAYOUT (Unit: Millimeters)



MARKING DIAGRAM



Y = Year Code

M = Month Code for Halogen Free Product

O	=Jan	**P**	=Feb	**Q**	=Mar	**R**	=Apr
S	=May	**T**	=Jun	**U**	=Jul	**V**	=Aug
W	=Sep	**X**	=Oct	**Y**	=Nov	**Z**	=Dec

L = Lot Code (1~9, A~Z)

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.