# N-Channel Enhancement-Mode Vertical DMOS FET

## Features

- Free from secondary breakdown
- Low power drive requirement
- Ease of paralleling
- Low $C_{ISS}$ and fast switching speeds
- Excellent thermal stability
- Integral source-drain diode
- High input impedance and high gain

## Applications

- Motor controls
- Converters
- Amplifiers
- Switches
- Power supply circuits
- Drivers (relays, hammers, solenoids, lamps, memories, displays, bipolar transistors, etc.)

## General Description

This enhancement-mode (normally-off) transistor utilizes a vertical DMOS structure and Supertex's well-proven, silicon-gate manufacturing process. This combination produces a device with the power handling capabilities of bipolar transistors and the high input impedance and positive temperature coefficient inherent in MOS devices. Characteristic of all MOS structures, this device is free from thermal runaway and thermally-induced secondary breakdown.

Supertex's vertical DMOS FETs are ideally suited to a wide range of switching and amplifying applications where very low threshold voltage, high breakdown voltage, high input impedance, low input capacitance, and fast switching speeds are desired.

## Ordering Information


| Part Number | Package Option | Packing |
|---|---|---|
| VN0606L-G | TO-92 | 1000/Bag |
| VN0606L-G P002 | TO-92 | 2000/Reel |
| VN0606L-G P003 | | |
| VN0606L-G P005 | | |
| VN0606L-G P013 | | |
| VN0606L-G P014 | | |

*-G denotes a lead (Pb)-free / RoHS compliant package.*
*Contact factory for Wafer / Die availablity.*
*Devices in Wafer / Die form are lead (Pb)-free / RoHS compliant.*

## Product Summary

| $BV_{DSS}/BV_{DGS}$ | $R_{DS(ON)}$ (max) | $I_{DSS}$ (min) |
|---|---|---|
| 60V | 3.0Ω | 1.5A |

## Pin Configuration




**TO-92**

## Absolute Maximum Ratings

| Parameter | Value |
|---|---|
| Drain-to-source voltage | $BV_{DSS}$ |
| Drain-to-gate voltage | $BV_{DGS}$ |
| Gate-to-source voltage | ±30V |
| Operating and storage temperature | -55°C to +150°C |

*Absolute Maximum Ratings are those values beyond which damage to the device may occur. Functional operation under these conditions is not implied. Continuous operation of the device at the absolute rating level may affect device reliability. All voltages are referenced to device ground.*

## Product Marking




YY = Year Sealed
WW = Week Sealed
_____ = "Green" Packaging

*Package may or may not include the following marks: Si or*

**TO-92**

## Typical Thermal Resistance

| Package | $\theta_{ja}$ |
|---|---|
| TO-92 | 132°C/W |

## Thermal Characteristics

| Package | $I_D$ (continuous)† | $I_D$ (pulsed) | Power Dissipation @$T_C$ = 25°C | $I_{DR}$ † | $I_{DRM}$ |
|---|---|---|---|---|---|
| TO-92 | 330mA | 1.6A | 1.0W | 330mA | 1.6A |

***Notes:***

† $I_D$ *(continuous) is limited by max rated* $T_j$ .


## Electrical Characteristics *($T_A$ = 25°C unless otherwise specified)*

| Sym | Parameter | Min | Typ | Max | Units | Conditions |
|---|---|---|---|---|---|---|
| $BV_{DSS}$ | Drain-to-source breakdown voltage | 60 | - | - | V | $V_{GS}$ = 0V, $I_D$ = 10µA |
| $V_{GS(th)}$ | Gate threshold voltage | 0.8 | - | 2.0 | V | $V_{GS}$ = $V_{DS}$, $I_D$ = 1.0mA |
| $I_{GSS}$ | Gate body leakage | - | - | 100 | nA | $V_{GS}$ = ±30V, $V_{DS}$ = 0V |
| $I_{DSS}$ | Zero gate voltage drain current | - | - | 10 | µA | $V_{GS}$ = 0V, $V_{DS}$ = 50V |
| | | - | - | 500 | | $V_{GS}$ = 0V, $V_{DS}$ = 50V, $T_A$ = 125°C |
| $I_{D(ON)}$ | On-state drain current | 1.5 | - | - | A | $V_{GS}$ = 10V, $V_{DS}$ = 10V |
| $R_{DS(ON)}$ | Static drain-to-source on-state resistance | - | - | 3.0 | Ω | $V_{GS}$ = 10V, $I_D$ = 1.0A |
| $G_{FS}$ | Forward transductance | 170 | - | - | mmho | $V_{DS}$ = 10V, $I_D$ = 500mA |
| $C_{ISS}$ | Input capacitance | - | - | 50 | pF | $V_{GS}$ = 0V, $V_{DS}$ = 25V, f = 1.0MHz |
| $C_{OSS}$ | Common source output capacitance | - | - | 25 | | |
| $C_{RSS}$ | Reverse transfer capacitance | - | - | 5.0 | | |
| $t_{(ON)}$ | Turn-on delay time | - | - | 10 | ns | $V_{DD}$ = 25V, $I_D$ = 600mA, $R_{GEN}$ = 25Ω |
| $t_{(OFF)}$ | Turn-off delay time | - | - | 10 | | |
| $V_{SD}$ | Diode forward voltage drop | - | 0.85 | - | V | $V_{GS}$ = 0V, $I_{SD}$ = 470mA |


***Notes:***

1. *All D.C. parameters 100% tested at 25°C unless otherwise stated. (Pulse test: 300µs pulse, 2% duty cycle.)*
2. *All A.C. parameters sample tested.*


## Switching Waveforms and Test Circuit




# 3-Lead TO-92 Package Outline (L)




**Front View**




**Side View**




**Bottom View**

| Symbol | | A | b | c | D | E | E1 | e | e1 | L |
|---|---|---|---|---|---|---|---|---|---|---|
| Dimensions (inches) | MIN | .170 | .014† | .014† | .175 | .125 | .080 | .095 | .045 | .500 |
| | NOM | - | - | - | - | - | - | - | - | - |
| | MAX | .210 | .022† | .022† | .205 | .165 | .105 | .105 | .055 | .610* |

*JEDEC Registration TO-92.*
** This dimension is not specified in the JEDEC drawing.*
*† This dimension differs from the JEDEC drawing.*
***Drawings not to scale.***
***Supertex Doc.#:** DSPD-3TO92N3, Version E041009.*

*(The package drawing(s) in this data sheet may not reflect the most current specifications. For the latest package outline information go to http://www.supertex.com/packaging.html.)*

**Supertex inc.** does not recommend the use of its products in life support applications, and will not knowingly sell them for use in such applications unless it receives an adequate "product liability indemnification insurance agreement." **Supertex inc.** does not assume responsibility for use of devices described, and limits its liability to the replacement of the devices determined defective due to workmanship. No responsibility is assumed for possible omissions and inaccuracies. Circuitry and specifications are subject to change without notice. For the latest product specifications refer to the **Supertex inc.** (website: http//www.supertex.com)

©2013 **Supertex inc.** All rights reserved. Unauthorized use or reproduction is prohibited.

Supertex inc.
1235 Bordeaux Drive, Sunnyvale, CA 94089
Tel: 408-222-8888
***www.supertex.com***

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

# Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

### Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

**www.entegreci.com**

### Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

**Kategorilere göz atın**

### Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

**Üreticileri görün**

### Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

**Teklif isteyin**

**www.entegreci.com** | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.