

C3M0075120J

Silicon Carbide Power MOSFET
C3M™ MOSFET Technology
N-Channel Enhancement Mode



TO-263-7



Package Types: TO-263-7
PN's: C3M0075120J

Features

- 3rd generation SiC MOSFET technology
- Low impedance package with driver source pin
- 7 mm of creepage distance between drain and source
- High blocking voltage with low on-resistance
- High-speed switching with low capacitances
- Fast intrinsic diode with low reverse recovery (Q_{rr})
- Halogen free, RoHS compliant

Wolfspeed, Inc. is in the process of rebranding its products and related materials pursuant to the entity name change from Cree, Inc. to Wolfspeed, Inc. During this transition period, products received may be marked with either the Cree name and/or logo or the Wolfspeed name and/or logo.

Typical Applications

- Renewable energy
- EV battery chargers
- High voltage DC/DC converters
- Switch mode power supplies

Benefits

- Reduce switching losses and minimize gate ringing
- Higher system efficiency
- Reduce cooling requirements
- Increase power density
- Increase system switching frequency

Key Parameters

Parameter	Symbol	Min.	Typ.	Max	Unit	Conditions	Note
Drain - Source Voltage	V_{DS}			1200	V	T_C = 25°C	
Maximum Gate - Source Voltage	$V_{GS(max)}$	-8		+19		Transient	
Operational Gate-Source Voltage	$V_{GS\ op}$		-4/15			Static	Note 1
DC Continuous Drain Current	I_D			30	A	V_{GS} = 15 V, T_C = 25 °C, T_J ≤150 °C	Fig. 19 Note 2
				19.7		V_{GS} = 15 V, T_C = 100 °C, T_J ≤150 °C	
Pulsed Drain Current	I_{DM}			80		t_{Pmax} limited by T_{jmax} V_{GS} = 15V, T_C = 25 °C	Fig. 22
Power Dissipation	P_D			113.6	W	T_C = 25 °C, T_J = 150 °C	Fig. 20
Operating Junction and Storage Temperature	T_J, T_{stg}			-55 to +150	°C		
Solder Temperature	T_L			260		According to JEDEC J-STD-020	

Note (1): Recommended turn-on gate voltage is 15V with ±5% regulation tolerance, see Application Note PRD-04814 for additional details
Note (2): Verified by design

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

Electrical Characteristics (T_C = 25 °C Unless Otherwise Specified)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Conditions	Note
Gate Threshold Voltage	$V_{GS(th)}$	1.8	2.5	3.6	V	V_{DS} = V_{GS}, I_D = 5 mA	Fig. 11
			2.2			V_{DS} = V_{GS}, I_D = 5 mA, T_J = 150 °C	
Zero Gate Voltage Drain Current	I_{DSS}		1	50	µA	V_{DS} = 1200 V, V_{GS} = 0 V	
Gate-Source Leakage Current	I_{GSS}		10	250	nA	V_{GS} = 15 V, V_{DS} = 0 V	
Drain-Source On-State Resistance	$R_{DS(on)}$		75	90	mΩ	V_{GS} = 15 V, I_D = 20 A	Fig. 4, 5, 6
			100			V_{GS} = 15 V, I_D = 20 A, T_J = 150 °C	
Transconductance	g_{fs}		12		S	V_{DS} = 20 V, I_{DS} = 20 A	Fig. 7
			13			V_{DS} = 20 V, I_{DS} = 20 A, T_J = 150 °C	
Input Capacitance	C_{iss}		1390		pF	V_{GS} = 0 V, V_{DS} = 1000 V f = 1 MHz V_{AC} = 25 mV	Fig. 17, 18
Output Capacitance	C_{oss}		58				
Reverse Transfer Capacitance	C_{rss}		2				
C_{oss} Stored Energy	E_{oss}		33		µJ		Fig. 16
Turn-On Switching Energy (Body Diode FWD)	E_{ON}		200		µJ	V_{DS} = 800 V, V_{GS} = -4 V/15 V, I_D = 20 A, $R_{G(ext)}$ = 0 Ω, L = 156 µH, T_J = 150 °C	Fig. 26, 29
Turn-Off Switching Energy (Body Diode FWD)	E_{OFF}		90				
Turn-On Delay Time	$t_{d(on)}$		7		ns	V_{DD} = 800 V, V_{GS} = -4 V/15 V I_D = 20 A, $R_{G(ext)}$ = 0 Ω, Timing Relative to V_{DS} Inductive Load	Fig. 27, 28, 29
Rise Time	t_r		15				
Turn-Off Delay Time	$t_{d(off)}$		24				
Fall Time	t_f		8				
Internal Gate Resistance	$R_{G(int)}$		9		Ω	f = 1 MHz, V_{AC} = 25 mV	
Gate to Source Charge	Q_{gs}		18		nC	V_{DS} = 800 V, V_{GS} = -4 V/15 V I_D = 20 A Per IEC60747-8-4 pg 21	Fig. 12
Gate to Drain Charge	Q_{gd}		12				
Total Gate Charge	Q_g		48				

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

Reverse Diode Characteristics (T_C = 25 °C Unless Otherwise Specified)

Parameter	Symbol	Typ.	Max.	Unit	Test Conditions	Note
Diode Forward Voltage	V_{SD}	4.5		V	V_{GS} = -4 V, I_{SD} = 10 A	Fig. 8, 9, 10
		4.0			V_{GS} = -4 V, I_{SD} = 10 A, T_J = 150 °C	
Continuous Diode Forward Current	I_S		22.4	A	V_{GS} = -4 V	
Diode Pulse Current	$I_{S,\ pulse}$	80			V_{GS} = -4 V, Pulse Width t_P Limited by T_{jmax}	
Reverse Recovery Time	t_{rr}	25		ns	V_{GS} = -4 V, I_{SD} = 20 A , V_R = 800 V dif/dt = 1925 A/µs, T_J = 25 °C	Fig. 29
Reverse Recovery Charge	Q_{rr}	109		nC		
Peak Reverse Recovery Current	I_{rrm}	11		A		

Thermal Characteristics

Parameter	Symbol	Typ.	Unit	Test Conditions	Note
Thermal Resistance from Junction to Case	$R_{\theta JC}$	1.1	°C/W		Fig. 21
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	40			

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

Typical Performance




Figure 1. Output Characteristics T_J = -55 °C




Figure 2. Output Characteristics T_J = 25 °C




Figure 3. Output Characteristics T_J = 150 °C




Figure 4. Normalized On-Resistance vs Temperature

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

Typical Performance




Figure 5. On-Resistance vs Drain Current for Various Temperatures




Figure 6. On-Resistance vs Temperature for Various Gate Voltage




Figure 7. Transfer Characteristic for Various Junction Temperatures




Figure 8. Body Diode Characteristic at -55 °C

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

Typical Performance




Figure 9. Body Diode Characteristic at 25 °C




Figure 10. Body Diode Characteristic at 150 °C




Figure 11. Threshold Voltage vs Temperature




Figure 12. Gate Charge Characteristic

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

Typical Performance




Figure 13. 3rd Quadrant Characteristic at -55 °C




Figure 14. 3rd Quadrant Characteristic at 25 °C




Figure 15. 3rd Quadrant Characteristic at 150 °C




Figure 16. Output Capacitor Stored Energy

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

Typical Performance




Figure 17. Capacitances vs Drain-Source Voltage (0-200 V)




Figure 18. Capacitances vs Drain-Source Voltage (0-1000 V)




Figure 19. Continuous Drain Current Derating vs Case Temperature




Figure 20. Maximum Power Dissipation Derating vs Case Temperature

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

Typical Performance




Figure 21. Transient Thermal Impedance (Junction - Case)




Figure 22. Safe Operating Area




Figure 23. Clamped Inductive Switching Energy vs Drain Current (V_{DD} = 600 V)




Figure 24. Clamped Inductive Switching Energy vs Drain Current (V_{DD} = 800 V)

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

Typical Performance




Figure 25. Clamped Inductive Switching Energy vs $R_{G(ext)}$




Figure 26. Clamped Inductive Switching Energy vs Temperature




Figure 27. Switching Times vs $R_{G(ext)}$




Figure 28. Switching Times Definition

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

Test Circuit Schematic





Figure 29. Clamped Inductive Switching Waveform Test Circuit

Note (3): Turn-off and Turn-on switching energy and timing values measured using SiC MOSFET body diode as shown above.

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

Package Dimensions

Package: TO-263-7L



SYMBOL	MIN (mm)	MAX (mm)
A	4.30	4.57
A1	0.00	0.25
b	0.50	0.70
b2	0.60	1.00
c	0.33	0.65
C2	1.17	1.40
D	9.025	9.125
D1	4.70	4.90
D2	7.170 REF	
D3	4.000 REF	
D4	7.000 REF	
A2	2.595 REF	
E	10.13	10.23
E1	6.50	8.60
E2	6.778	7.665
e	1.27 TYP	
H	15.043	17.313
L	2.324	2.700
L1	0.968	1.868
R	0.506 REF	
R1	0.500 REF	
θ	0°	8°
θ1	4.5°	5.5°
θ2	4°	6°
θ3	4°	6°

1	GATE
2	KELVIN
3	SOURCE
4	
5	
6	
7	
8	DRAIN

NOTE
1. ALL METAL SURFACES ARE TIN PLATED (MATTE), EXCEPT AREA OF CUT.
2. DIMENSIONING & TOLERANCING CONFORM TO ASME Y14.5M-1994.
3. ALL DIMENSIONS ARE LISTED IN MILLIMETERS. ANGLES ARE IN DEGREES.
4. PACKAGE BURR FLASH SIZE (0.5 mm) IS NOT INCLUDED IN THE DIMENSIONS

Wolfspeed


TITLE: PACKAGE OUTLINE DRAWING: TO 263-7L J

REVISION NO. 02 | A4

Date: 08/12/25 | PRD-05972 | SCALE:1:1 | SHEET 1 OF 1

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc. The information in this document is subject to change without notice.

Recommended Solder Pad Layout



Revision History

Current Revision	Date of Release	Description of Changes
B	July-2019	N/A
3	December-2023	Updated Wolfspeed branding, package drawing, package image, solder pad layout, added Rev history, Table 1 layout revised
4	December - 2024	Legal Disclaimer Updated
5	September - 2025	Package drawing updated to correct dimension D1

Related Links

- SiC MOSFET Isolated Gate Driver reference design
- SiC MOSFET Evaluation Board

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

Notes & Disclaimer

WOLFSPEED PROVIDES TECHNICAL AND RELIABILITY DATA, DESIGN RESOURCES, APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, WITH RESPECT THERETO, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, SUITABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

This document and the information contained herein are subject to change without notice. Any such change shall be evidenced by the publication of an updated version of this document by Wolfspeed. No communication from any employee or agent of Wolfspeed or any third party shall effect an amendment or modification of this document. No responsibility is assumed by Wolfspeed for any infringement of patents or other rights of third parties which may result from use of the information contained herein. No license is granted by implication or otherwise under any patent or patent rights of Wolfspeed.

The information contained in this document (excluding examples, as well as figures or values that are labeled as "typical") constitutes Wolfspeed's sole published specifications for the subject product. "Typical" parameters are the average values expected by Wolfspeed in large quantities and are provided for informational purposes only. Any examples provided herein have not been produced under conditions intended to replicate any specific end use. Product performance can and does vary due to a number of factors.

This product has not been designed or tested for use in, and is not intended for use in, any application in which failure of the product would reasonably be expected to cause death, personal injury, or property damage. For purposes of (but without limiting) the foregoing, this product is not designed, intended, or authorized for use as a critical component in equipment implanted into the human body, life-support machines, cardiac defibrillators, and similar emergency medical equipment; air traffic control systems; or equipment used in the planning, construction, maintenance, or operation of nuclear facilities. Notwithstanding any application-specific information, guidance, assistance, or support that Wolfspeed may provide, the buyer of this product is solely responsible for determining the suitability of this product for the buyer's purposes, including without limitation (1) selecting the appropriate Wolfspeed products for the buyer's application, (2) designing, validating, and testing the buyer's application, and (3) ensuring the buyer's application meets applicable standards and any other legal, regulatory, and safety-related requirements.

RoHS Compliance

The levels of RoHS restricted materials in this product are below the maximum concentration values (also referred to as the threshold limits) permitted for such substances, or are used in an exempted application, in accordance with EU Directive 2011/65/EC (RoHS2), as implemented January 2, 2013. RoHS Declarations for this product can be obtained from your Wolfspeed representative or from the Product Documentation sections of www.wolfspeed.com.

REACh Compliance

REACh substances of high concern (SVHCs) information is available for this product. Since the European Chemical Agency (ECHA) has published notice of their intent to frequently revise the SVHC listing for the foreseeable future, please contact your Wolfspeed representative to ensure you get the most up-to-date REACh SVHC Declaration. REACh banned substance information (REACh Article 67) is also available upon request.

Contact info:

4600 Silicon Drive
Durham, NC 27703 USA
Tel: +1.919.313.5300
www.wolfspeed.com/power

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
PATENT: https://www.wolfspeed.com/legal/patents

The information in this document is subject to change without notice.

© 2025 Wolfspeed, Inc. All rights reserved. Wolfspeed®, the Wolfspeed logo, and the Wolfstreak logo are registered trademarks and the Wolfspeed logo is a trademark of Wolfspeed, Inc.
The information in this document is subject to change without notice.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.