20V SOT26 N-CHANNEL ENHANCEMENT MODE MOSFET

Product Summary

$V_{(BR)DSS}$	Max $R_{DS(ON)}$	Max I_D T_A = +25°C
20V	0.040Ω @ V_{GS} = 4.5V	5.4A
	0.055Ω @ V_{GS} = 2.5V	4.6A
	0.075Ω @ V_{GS} = 1.8V	4.0A

Features and Benefits

- Low On-resistance
- Fast Switching Speed
- Low Gate Drive Capability
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**

Description and Applications


This new generation trench MOSFET from Zetex features low on-resistance achievable with low gate drive.

- DC - DC Converters
- Power Management Functions
- Disconnect Switches
- Motor Control


Mechanical Data

- Case: SOT26
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish – Matte Tin Annealed over Copper Leadframe. Solderable per MIL-STD-202, Method 208 e3
- Weight: 0.015 grams (Approximate)


SOT26



Top View



Pinout Top-view




Device Symbol

Ordering Information (Note 4)

Part Number	Reel Size (inch)	Tape Width (mm)	Quantity Per Reel
ZXMN2B03E6TA	7	8	3000

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
2. See http://www.diodes.com/quality/lead_free.html for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. For packaging details, go to our website at http://www.diodes.com/products/packages.html.

Marking Information



2B3 = Product Type Marking Code
YM = Date Code Marking
Y or $\overline{Y}$ = Year (ex: C = 2015)
M or $\overline{M}$ = Month (ex: 9 = September)

Date Code Key

Year	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025
Code	C	D	E	F	G	H	I	J	K	L	M

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

© Diodes Incorporated

Maximum Ratings (@T_A = +25°C, unless otherwise specified.)


Characteristic			Symbol	Value	Unit
Drain-Source Voltage			V_{DSS}	20	V
Gate-Source Voltage			V_{GS}	±8	V
Continuous Drain Current	V_{GS} = 4.5V	T_A = +25°C (Note 6)	I_D	5.4	A
		T_A = +70°C (Note 6)		4.3	
		T_A = +25°C (Note 5)		4.3	
Pulsed Drain Current (Note 7)			I_{DM}	26	A
Continuous Source Current (Body Diode) (Note 6)			I_S	2.8	A
Pulsed Source Current (Body Diode) (Note 7)			I_{SM}	26	A

Thermal Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Power Dissipation at T_A = +25°C (Note 5) Linear derating factor (Note 5)	P_D	1.1 8.8	W mW/°C
Power Dissipation at T_A = +25°C (Note 6) Linear derating factor (Note 6)	P_D	1.7 13.7	W mW/°C
Junction to Ambient (Note 5)	$R_{\theta JA}$	113	°C/W
Junction to Ambient (Note 6)	$R_{\theta JA}$	73	°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150	°C

Notes: 5. For a device surface mounted on 25mm x 25mm FR-4 PCB with high coverage of single sided 1oz copper, in still air conditions.
6. For a device surface mounted on FR-4 PCB measured at t≦10 secs.
7. Repetitive rating 25mm x 25mm FR-4 PCB, D = 0.02, pulse width 300µs - pulse width limited by maximum junction temperature.

Thermal Characteristics



© Diodes Incorporated


Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS						
Drain-source Breakdown Voltage	BV_{DSS}	20	—	—	V	I_D = 250μA, V_{GS} = 0V
Zero Gate Voltage Drain Current	I_{DSS}	—	—	1	μA	V_{DS} = 20V, V_{GS} = 0V
Gate-body Leakage	I_{GSS}	—	—	100	nA	V_{GS} = ±8V, V_{DS} = 0V
Diode Forward Voltage (Note 8)	V_{SD}	—	0.67	0.95	V	T_J = +25°C , I_S = 1.8A, V_{GS} = 0V
ON CHARACTERISTICS						
Gate-source Threshold Voltage	$V_{GS(th)}$	0.4	—	1.0	V	I_D = 250μA, V_{DS} = V_{GS}
Static Drain-source On-state Resistance (Note 8)	$R_{DS(ON)}$	—	—	0.040	Ω	V_{GS} = 4.5V, I_D = 4.3A
				0.055		V_{GS} = 2.5V, I_D = 3.7A
				0.075		V_{GS} = 1.8V, I_D = 3.2A
Forward Transconductance (Notes 8 & 10)	g_{fs}	—	13.5	—	S	V_{DS} = 10V, I_D = 4.3A
DYNAMIC CHARACTERISTICS (Notes 9 & 10)						
Input Capacitance	C_{iss}	—	1160	—	pF	V_{DS} = 10V, V_{GS} = 0V f = 1MHz
Output Capacitance	C_{oss}	—	210	—	pF	
Reverse Transfer Capacitance	C_{rss}	—	136	—	pF	
Total Gate Charge	Q_g	—	14.5	—	nC	V_{GS} = 4.5V, V_{DS} = 10V I_D = 4.3A
Gate-source Charge	Q_{gs}	—	2.0	—	nC	
Gate-drain Charge	Q_{gd}	—	2.8	—	nC	
Reverse Recovery Time (Note 10)	t_{rr}	—	10.8	—	ns	T_J = +25°C, I_F=2.8A, di/dt= 100A/μs
Reverse Recovery Charge (Note 10)	Q_{rr}	—	3.4	—	nC	
Turn-on Delay Time	$t_{d(on)}$	—	2.9	—	ns	V_{DD} = 10V, V_{GS} = 4.5V I_D = 1A, R_G = 6.0Ω
Turn-on Rise Time	t_r	—	6.4	—	ns	
Turn-off Delay Time	$t_{d(off)}$	—	16.0	—	ns	
Turn-off Fall Time	t_f	—	11.2	—	ns	


Notes: 8. Measured under pulsed conditions. Width=300μs. Duty cycle ≤ 2%.
9. Switching characteristics are independent of operating junction temperature.
10. For design aid only, not subject to production testing.

© Diodes Incorporated


Typical Characteristics




Output Characteristics




Output Characteristics




Typical Transfer Characteristics



Normalised Curves v Temperature




On-Resistance v Drain Current




Source-Drain Diode Forward Voltage

© Diodes Incorporated

Typical Characteristics (Cont.)




Capacitance v Drain-Source Voltage




Gate-Source Voltage v Gate Charge


Test Circuits




Basic Gate Charge Waveform



Gate Charge Test Circuit



Switching Time Waveforms




Switching Time Test Circuit

© Diodes Incorporated

Package Outline Dimensions


Please see AP02002 at http://www.diodes.com/datasheets/ap02002.pdf for the latest version.



SOT26			
Dim	**Min**	**Max**	**Typ**
A	0.35	0.50	0.38
B	1.50	1.70	1.60
C	2.70	3.00	2.80
D	—	—	0.95
H	2.90	3.10	3.00
J	0.013	0.10	0.05
K	1.00	1.30	1.10
L	0.35	0.55	0.40
M	0.10	0.20	0.15
α	0°	8°	—
All Dimensions in mm			

Suggested Pad Layout

Please see AP02001 at http://www.diodes.com/datasheets/ap02001.pdf for the latest version.



Dimensions	Value (in mm)
Z	3.20
G	1.60
X	0.55
Y	0.80
C1	2.40
C2	0.95

© Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or

2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2015, Diodes Incorporated

www.diodes.com

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.