THE ZXMP6A17GQ IS NOT RECOMMENDED FOR NEW DESIGNS.
PLEASE USE THE DMP6185SEQ.

ZXMP6A17GQ

60V P-CHANNEL ENHANCEMENT MODE MOSFET

Product Summary

BV_{DSS}	$R_{DS(on)}$	I_D T_A = +25°C
-60V	125mΩ @ V_{GS} = -10V	-4.3A
	190mΩ @ V_{GS} = -4.5V	-3.5A

Features and Benefits

- Fast Switching Speed
- Low Gate Drive
- Low Input Capacitance
- **Lead-Free Finish; RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **The ZXMP6A17GQ is suitable for automotive applications requiring specific change control; this part is AEC-Q101 qualified, PPAP capable, and manufactured in IATF 16949 certified facilities.**
  https://www.diodes.com/quality/product-definitions/

Description and Applications


This MOSFET is designed to meet the stringent requirements of automotive applications. It is qualified to AEC-Q101, supported by a PPAP and is ideal for use in:

- Motor control
- DC-DC converters
- Power-management functions
- Uninterrupted power supplies


Mechanical Data

- Package: SOT223
- Package Material: Molded Plastic, UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish—Matte Tin Annealed over Copper Leadframe. Solderable per MIL-STD-202, Method 208 e3
- Weight: 0.112 grams (Approximate)


SOT223 (Type DN)



Top View



Pinout - Top View




Equivalent Circuit

Ordering Information (Note 4)

Orderable Part Number	Package	Packing	
		Qty.	Carrier
ZXMP6A17GQTA	SOT223 (Type DN)	1000	Tape & Reel
ZXMP6A17GQTC	SOT223 (Type DN)	4000	Tape & Reel

Notes:
1. EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant. All applicable RoHS exemptions applied.
2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. For packaging details, go to our website at https://www.diodes.com/design/support/packaging/diodes-packaging/.

Marking Information



ZXMP6A17 = Product Type Marking Code
YWW = Date Code Marking
Y or Y= Year (ex: 6 = 2026)
WW or WW = Week (01 to 53)

NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

Characteristic			Symbol	Value	Unit
Drain-Source Voltage			V_{DSS}	-60	V
Gate-Source Voltage			V_{GS}	±20	V
Continuous Drain Current	V_{GS} = 10V	(Note 6)	I_D	-4.3	A
		T_A = +70°C (Note 6)		-3.5	
		(Note 5)		-3	
Pulsed Drain Current	V_{GS} = 10V	(Note 7)	I_{DM}	-13.7	A
Continuous Source Current (Body Diode)		(Note 6)	I_S	-4.3	A
Pulsed Source Current (Body Diode)		(Note 7)	I_{SM}	-13.7	A

Thermal Characteristics (@T_A = +25°C, unless otherwise specified.)


Characteristic		Symbol	Value	Unit
Power Dissipation Linear Derating Factor	(Note 5)	P_D	2 16	W
	(Note 6)		3.9 31	
Thermal Resistance, Junction to Ambient	(Note 5)	$R_{\theta JA}$	62.5	°C/W
	(Note 6)		32	
Thermal Resistance, Junction to Lead	(Note 8)	$R_{\theta JL}$	9.8	
Operating and Storage Temperature Range		T_J, T_{STG}	-55 to +150	°C

Notes:
5. For a device surface-mounted on 25mm × 25mm × 1.6mm FR4 PCB with high coverage of single-sided 2oz copper. In still air conditions, the device is measured when operating in a steady-state condition.
6. Same as Note 5 except the device is measured at t ≤ 10s.
7. Same as Note 5 except the device is pulsed with D = 0.02 and pulse width of 300µs. The pulse current is limited by the maximum junction temperature.
8. Thermal resistance from junction to solder point (at the end of the drain lead).


NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.


Thermal Characteristics




Safe Operating Area



Derating Curve



Transient Thermal Impedance



Pulse Power Dissipation

NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)


Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
OFF CHARACTERISTICS (Note 9)						
Drain-Source Breakdown Voltage	BV_{DSS}	-60	—	—	V	I_D = -250µA, V_{GS} = 0
Zero Gate Voltage Drain Current	I_{DSS}	—	—	-0.5	µA	V_{DS} = -60V, V_{GS} = 0
Gate-Source Leakage	I_{GSS}	—	—	±100	nA	V_{GS} = ±20V, V_{DS} = 0
ON CHARACTERISTICS (Note 9)						
Gate Threshold Voltage	$V_{GS(th)}$	-1	—	—	V	I_D = -250µA, V_{DS} = V_{GS}
Static Drain-Source On-Resistance	$R_{DS(on)}$	—	96	125	mΩ	V_{GS} = -10V, I_D = -2.2A
		—	120	190		V_{GS} = -4.5V, I_D = -1.8A
Forward Transconductance	g_{fs}	—	4.7	—	S	V_{DS} = -15V, I_D = -2.2A
Diode Forward Voltage	V_{SD}	—	-0.85	-0.95	V	I_S = -2A, V_{GS} = 0, T_J = +25°C
DYNAMIC CHARACTERISTICS (Note 10)						
Input Capacitance	C_{iss}	—	637	—	pF	V_{DS} = -30V, V_{GS} = 0 f = 1MHz
Output Capacitance	C_{oss}	—	70	—	pF	
Reverse Transfer Capacitance	C_{rss}	—	53	—	pF	
Total Gate Charge (V_{GS} = -4.5V)	Q_g	—	9	—	nC	V_{DS} = -30V I_D = -2.2A
Total Gate Charge (V_{GS} = -10V)	Q_g	—	17.7	—	nC	
Gate-Source Charge	Q_{gs}	—	1.6	—	nC	
Gate-Drain Charge	Q_{gd}	—	4.4	—	nC	
Turn-On Delay Time	$t_{D(on)}$	—	2.6	—	ns	V_{DD} = -30V, V_{GS} = -10V I_D = -1A, $R_G \cong 6\Omega$
Turn-On Rise Time	t_r	—	3.4	—	ns	
Turn-Off Delay Time	$t_{D(off)}$	—	26.2	—	ns	
Turn-Off Fall Time	t_f	—	11.3	—	ns	
Reverse-Recovery Time	t_{rr}	—	25.1	—	ns	I_S = -1.7A, di/dt = 100A/µs
Reverse-Recovery Charge	Q_{rr}	—	27.2	—	nC	

Notes: 9. Short duration pulse test used to minimize self-heating effect.
10. Guaranteed by design. Not subject to production testing.


NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.


Typical Characteristics




Output Characteristics




Output Characteristics




Typical Transfer Characteristics



Normalised Curves v Temperature



On-Resistance v Drain Current




Source-Drain Diode Forward Voltage


NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

Typical Characteristics (continued)




Capacitance v Drain-Source Voltage




Gate-Source Voltage v Gate Charge


Test Circuits




Basic Gate Charge Waveform



Gate Charge Test Circuit



Switching Time Waveform



Switching Time Test Circuit


NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

Package Outline Dimensions

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT223 (Type DN)




SOT223 (Type DN)			
Dim	**Min**	**Max**	**Typ**
A	--	1.70	--
A1	0.01	0.15	--
A2	1.50	1.68	1.60
b	0.60	0.80	0.70
b2	2.90	3.10	--
c	0.20	0.32	--
D	6.30	6.70	--
E	6.70	7.30	--
E1	3.30	3.70	--
e	--	--	2.30
e1	--	--	4.60
L	0.85	--	--
All Dimensions in mm			

NOT RECOMMENDED FOR NEW DESIGN

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT223 (Type DN)



Dimensions	Value (in mm)
C	2.30
C1	6.40
X	1.20
X1	3.30
Y	1.60
Y1	1.60
Y2	8.00

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

IMPORTANT NOTICE

1. DIODES INCORPORATED (Diodes) AND ITS SUBSIDIARIES MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes' products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes' products. Diodes' products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of Diodes' products for their intended applications, (c) ensuring their applications, which incorporate Diodes' products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.

3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes' websites, harmless against all damages and liabilities.

4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes' website) under this document.

5. Diodes' products are provided subject to Diodes' Standard Terms and Conditions of Sale (https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.

6. Diodes' products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes' products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.

7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.

8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.

9. This Notice may be periodically updated with the most recent version available at https://www.diodes.com/about/company/terms-and-conditions/important-notice

The Diodes logo is a registered trademark of Diodes Incorporated in the United States and other countries.
All other trademarks are the property of their respective owners.
© 2026 Diodes Incorporated. All Rights Reserved.

www.diodes.com

NOT RECOMMENDED FOR NEW DESIGN

© 2026 Copyright Diodes Incorporated. All Rights Reserved.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.