60V INPUT, 5V 15mA REGULATOR TRANSISTOR

Description

The ZXTR2105FQ monolithically integrates a transistor, zener diode and resistor to function as a linear regulator. The device regulates with a 5V nominal output at 15mA. It is designed for use in high-voltage applications where standard linear regulators cannot be used. This function is fully integrated into a SOT23 package, minimizing PCB area and reducing the number of components when compared with a multi-chip discrete solution.

This linear regulator is designed to meet the stringent requirement of automotive applications.

Applications

Supply voltage regulation for:

- 12V to 5V Rails
- 24V to 5V Rails
- Other Customized Input Rails


Features

- Series Linear Regulator Using Emitter-Follower Stage
- Input Voltage = 7V to 60V (For Regulated Output Voltage)
- Output Voltage = 5V ± 5%
- Fully Integrated into a SOT23 Package
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**
- **PPAP Capable (Note 4)**

Mechanical Data


- Case: SOT23
- Case Material: Molded Plastic "Green" Molding Compound; UL Flammability Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish - Matte Tin Plated Leads; Solderable per MIL-STD-202, Method 208 e3
- Weight: 0.008 grams (Approximate)

SOT23




Top View

ZXTR2105FQ



Internal Device Schematic



Top View Pin-Out

Pin Name	Pin Function
V_{IN}	Input Supply
GND	Power Ground
V_{OUT}	Voltage Output


Ordering Information (Note 5)

Product	Compliance	Marking	Reel Size (inches)	Tape Width (mm)	Quantity per Reel
ZXTR2105FQ-7	Automotive	2T1	7	8	3,000

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant.
2. See http://www.diodes.com/quality/lead_free.htmlfor more information about Diodes Incorporated's definitions of Halogen and Antimony free,"Green" and Lead-Free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. Automotive products are AEC-Q101 qualified and are PPAP capable. Refer to http://www.diodes.com/product_compliance_definitions.html.
5. For packaging details, go to our website at https://www.diodes.com/design/support/packaging/diodes-packaging/.

Marking Information

SOT23



2T1 = Product Type Marking Code

© Diodes Incorporated

Absolute Maximum Ratings (Voltage relative to GND, @T_A = +25°C, unless otherwise specified.)

Characteristic	Symbol	Value	Unit
Input Voltage	V_{IN}	-0.3 to 60	V
Continuous Input and Output Current	I_{IN}, I_{OUT}	320	mA
Peak Pulsed Input and Output Current	I_{IM}, I_{OM}	2	A
Maximum Voltage Applied to V_{OUT}	$V_{OUT(MAX)}$	Smaller of V_{IN}+5V or 10V	V

Maximum Current at V_{IN} = 12V (@T_A = +25°C, unless otherwise specified.)

Characteristic		Symbol	Value	Unit
Continuous Output Current	(Note 8)	I_{OUT}	89	mA
Pulsed Output Current	(Note 9)	I_{OM}	2,000	mA
	(Note 10)		890	

Thermal Characteristics

Characteristic		Symbol	Value	Unit
Power Dissipation	(Note 6)	P_D	625	mW
	(Note 7)		500	
Thermal Resistance, Junction to Ambient	(Note 6)	$R_{\theta JA}$	200	°C/W
	(Note 7)		250	
Thermal Resistance, Junction to Lead	(Note 11)	$R_{\theta JL}$	197	
Thermal Resistance, Junction to Case	(Note 11)	$R_{\theta JC}$	17	
Maximum Operating Junction and Storage Temperature Range		T_J, T_{STG}	-65 to +150	°C


ESD Ratings (Note 12)

Characteristics	Symbols	Value	Unit	JEDEC Class
Electrostatic Discharge – Human Body Model	ESD HBM	4,000	V	3A
Electrostatic Discharge – Machine Model	ESD MM	400	V	C


Notes:
6. For a device mounted with the V_{IN} lead on 25mm x 25mm 1oz copper that is on a single-sided 1.6mm FR-4 PCB; device is measured under still air conditions whilst operating in steady-state.
7. Same as Note 6, except mounted on 15mm x 15mm 1oz copper.
8. Same as Note 6, whilst operating at V_{IN}=12V. Refer to Safe Operating Area for other Input Voltages.
9. Same as Note 6, except measured with a single pulse width = 100µs and V_{IN}=12V.
10. Same as Note 6, except measured with a single pulse width = 10ms and V_{IN}=12V.
11. $R_{\theta JL}$ = Thermal resistance from junction to solder-point (at the end of the V_{IN} lead). $R_{\theta JC}$ = Thermal resistance from junction to the top of case.
12. Refer to JEDEC specification JESD22-A114 and JESD22-A115.

© Diodes Incorporated


Thermal Characteristics and Derating Information




Derating Curve




Safe Operating Area




Transient Thermal Impedance



Pulse Power Dissipation



Transient Thermal Impedance



Pulse Power Dissipation

© Diodes Incorporated

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)


Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Output Voltage (Note 13)	V_{OUT}	4.75	5.0	5.25	V	V_{IN} = 12V, I_{OUT} = 15mA
Line Regulation (Notes 13 & 14)	ΔV_{OUT}	—	33	220	mV	V_{IN} = 10V to 15V, I_{OUT} = 15mA
		—	400	700		V_{IN} = 7V to 60V, I_{OUT} = 15mA
		—	145	400		V_{IN} = 10V to 60V, I_{OUT} = 15mA
Temperature Coefficient	$\Delta V_{OUT}/\Delta T$	—	3.52	—	mV/°C	T_J = -40°C to +150°C V_{IN} = 12V, I_{OUT} = 15mA
Load Regulation (Notes 13 & 15)	ΔV_{OUT}	—	-20 -166	-130 -300	mV	I_{OUT} = 10mA to 20mA, V_{IN} = 12V I_{OUT} = 0.1mA to 50mA, V_{IN} = 12V
Minimum Value of Input Voltage Required to Maintain Line Regulation	$V_{IN(MIN)}$	7	—	—	V	—
Quiescent Current	I_Q	— —	450 4,000	800 6,700	µA	V_{IN} = 12V, I_{OUT} = 10µA V_{IN} = 60V, I_{OUT} = 10µA
Power Supply Rejection Ratio	$\Delta V_{IN}/\Delta V_{OUT}$	—	46	—	dB	C_{OUT} = 100nF, I_{OUT} = 15mA, V_{OUT} = 5V, V_{IN} = 7V to 60V,f = 100Hz

Notes: 13. Measured Under Pulsed Conditions; Pulse Width ≤ 300µs. Duty cycle ≤ 2%.

14. Line Regulation $\Delta V_{OUT} = V_{OUT}(@V_{IN} = 15V) – V_{OUT}(@V_{IN} = 10V)$
$\Delta V_{OUT} = V_{OUT}(@V_{IN} = 60V) – V_{OUT}(@V_{IN} = 7V)$
$\Delta V_{OUT} = V_{OUT}(@V_{IN} = 60V) – V_{OUT}(@V_{IN} = 10V)$

15. Load Regulation $\Delta V_{OUT} = V_{OUT}(@I_{OUT} = 20mA) – V_{OUT}(@I_{OUT} = 10mA)$
$\Delta V_{OUT} = V_{OUT}(@I_{OUT} = 50mA) – V_{OUT}(@I_{OUT} = 0.1mA)$

Typical Application Circuit




Example of a 5V regulated supply from a nominal 12V for powering a Controller IC.

Pin Functions


Pin Name	Pin Function	Notes
V_{IN}	Input Supply	Input voltage can vary from -0.3V to 60V with respect to GND; for V_{OUT} regulated then 7V ≤ V_{IN} ≤ 60V. It is recommended to connect a 1µF capacitor to GND.
GND	Power Ground	This pin should be tied to the system ground.
V_{OUT}	Voltage Output	Outputs a regulated 5V when 7V ≤ V_{IN} ≤ 60V. When V_{IN} < 7V, then V_{OUT} maximum = V_{IN} – 1V. The pin can be pulled high to a maximum of +10V with respect to GND, or +5V with respect to V_{IN}, whichever is lower. It is recommended to connect a 10µF capacitor to GND and a minimum of 10µA to be drawn from V_{OUT} to maintain regulation.

© Diodes Incorporated


Typical Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)




Line transient response




Load transient response




Line Regulation (Note 16)



Load Regulation (Note 17)



Temperature Coefficient (Note 18)



Quiescent Current


Notes: 16. Line Regulation $\Delta V_{OUT} = V_{OUT} – V_{OUT}$(@ V_{IN} = 7V, I_{OUT} = 15mA, T_J = +25°C).
17. Load Regulation $\Delta V_{OUT} = V_{OUT} – V_{OUT}$(@ V_{IN} = 12V, I_{OUT} = 0.1mA, T_J = +25°C).
18. Temperature Coefficient $\Delta V_{OUT} = V_{OUT} – V_{OUT}$(@ V_{IN} = 12V, I_{OUT} = 15mA, T_J = +25°C).

© Diodes Incorporated

Package Outline Dimensions

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT23




SOT23			
Dim	**Min**	**Max**	**Typ**
A	0.37	0.51	0.40
B	1.20	1.40	1.30
C	2.30	2.50	2.40
D	0.89	1.03	0.915
F	0.45	0.60	0.535
G	1.78	2.05	1.83
H	2.80	3.00	2.90
J	0.013	0.10	0.05
K	0.890	1.00	0.975
K1	0.903	1.10	1.025
L	0.45	0.61	0.55
L1	0.25	0.55	0.40
M	0.085	0.150	0.110
a	0°	8°	--
All Dimensions in mm			

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT23



Dimensions	Value (in mm)
C	2.0
X	0.8
X1	1.35
Y	0.9
Y1	2.9

© Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or

2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2017, Diodes Incorporated

www.diodes.com

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.