UMW SI2317A

-20V P-Channel MOSFET

1.Description

The SI2317A uses advanced trench technology to provide excellent $R_{DS(ON)}$, and low gate charge. This device is suitable for use as a load switch or in PWM applications.


2.Features


- $V_{DS(V)}$=-20V
- $R_{DS(ON)}$<40mΩ(V_{GS}=-4.5V), I_D=-4.2A
- $R_{DS(ON)}$<50mΩ(V_{GS}=-2.5V), I_D=-3.4A

3.Pinning information

Pin	Symbol	Description
1	G	GATE
2	S	SOURCE
3	D	DRAIN

SOT-23





4.Absolute Maximum Ratings T_A= 25°C


Parameter		Symbol	Maximum	Units
Drain-Source Voltage		V_{DS}	-20	V
Gate-Source Voltage		V_{GS}	±12	V
Continuous Drain Current	T_A=25°C	I_D	-4.2	A
	T_A=70°C		-3.4	
Pulsed Drain Current		I_{DM}	-10	
Power Dissipation	T_A=25°C	P_D	1.38	W
	T_A=70°C		0.8	
Thermal Resistance.Junction-to-Ambient		$R_{\theta JA}$	90	°C/W
Operating junction and storage temperature range		T_J,T_{STG}	-55 to 150	°C

5.Electrical Characteristics T_A= 25°C


Parameter	Symbol	Conditions	Min	Typ	Max	Units
Drain-Source Breakdown Voltage	V_{DSS}	I_D=-10μA, V_{GS}=0V	-20			V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=-250μA	-0.5			V
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS}=-20V, V_{GS}=0V			-1	μA
		V_{DS}=-16V,V_{GS}=0V,T_J=55°C			-10	μA
Gate-body leakage	I_{GSS}	V_{DS}=0V, V_{GS}=±12V			±100	nA
Drain-source on-state resistance	$R_{DS(ON)}$	V_{GS}=-4.5V, I_D=-4.2A			40	mΩ
		V_{GS}=-2.5V, I_D=-3.4A			50	
On-state drain curren	$I_{D(ON)}$	V_{DS}≤-5V, V_{GS}=-4.5V	-6			A
		V_{DS}≤-5V, V_{GS}=-2.5V	-3			
Forward transconductance	g_{FS}	V_{DS}=-5V, I_D=-2.8A		9		S
Input capacitance *	C_{iss}	V_{GS}=0V, V_{DS}=-15V, f=1MHz		740		pF
Output capacitance *	C_{oss}			167		
Reverse transfer capacitance *	C_{rss}			126		
Total gate charge *	Q_g	V_{DS}=-16V V_{GS}=-4.5V I_D=-4.2A		10.6		nC
Gate-source charge *	Q_{gs}			2.32		
Gate-drain charge*	Q_{gd}			3.68		
Turn - On Delay Time	$t_{D(on)}$	V_{DD}=-15V, R_L=3.6Ω I_D=-4.2A V_{GEN}=-10V, R_G=6Ω		5.9		ns
Turn - On Rise Time	t_r			3.6		ns
Turn - Off Delay Time	$t_{D(off)}$			32.4		ns
Turn - Off Fall Time	t_f			2.6		ns
Continuous source current (diode conduction) *	I_S			-1.6		A
Diode forward voltage	V_{SD}	I_S=-1.2A, V_{GS}=0V			-1.2	V

* Pulse test: PW ≤300us duty cycle≤ 2%.


6.1Typical Characterisitics




Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current



Capacitance




Gate Charge




On-Resistance vs. Junction Temperature


6.2Typical Characterisitics




Source-Drain Diode Forward Voltage




On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage




Single Pulse Power



Normalized Thermal Transient Impedance, Junction-to-Ambient

7.SOT-23 Package Outline Dimensions




DIMENSIONS (mm are the original dimensions)

Symbol	A	A1	A2	b	C	D	E	E1	e	e1	L	L1
Min	0.90	0.00	0.90	0.30	0.08	2.80	1.20	2.25	0.95	1.80	0.55	0.30
Max	1.15	0.10	1.05	0.50	0.15	3.00	1.40	2.55	TYP.	2.00	REF	0.50

Symbol	F	θ	θ1
Min	0.25	0°	2°
Max		8°	12°

8.Ordering information



yww: Batch Code

Order Code	Package	Base QTY	Delivery Mode
UMW SI2317A	SOT-23	3000	Tape and reel

9.Disclaimer

UMW reserves the right to make changes to all products, specifications. Customers should obtain the latest version of product documentation and verify the completeness and currency of the information before placing an order.

When applying our products, please do not exceed the maximum rated values, as this may affect the reliability of the entire system. Under certain conditions, any semiconductor product may experience faults or failures. Buyers are responsible for adhering to safety standards and implementing safety measures during system design, prototyping, and manufacturing when using our products to prevent potential failure risks that could lead to personal injury or property damage.

Unless explicitly stated in writing, UMW products are not intended for use in medical, life-saving, or life-sustaining applications, nor for any other applications where product failure could result in personal injury or death. If customers use or sell the product for such applications without explicit authorization, they assume all associated risks.

When reselling, applying, or exporting, please comply with export control laws and regulations of China, the United States, the United Kingdom, the European Union, and other relevant countries, regions, and international organizations.

This document and any actions by UMW do not grant any intellectual property rights, whether express or implied, by estoppel or otherwise. The product names and marks mentioned herein may be trademarks of their respective owners.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.