TP65H070G4PS

650V SuperGaN® GaN FET in TO-220 (source tab)

Description


The TP65H070G4PS 650V, 72mΩ Gallium Nitride (GaN) FET is a normally-off device. It combines a state-of-the-art high-voltage GaN HEMT with a low-voltage silicon MOSFET to offer superior performance, standard drive, ease of adoption and reliability.

The Gen IV SuperGaN® platform uses advanced epi and patented design technologies to simplify manufacturability while improving efficiency over silicon via lower gate charge, output capacitance, crossover loss, and reverse recovery charge.



Benefits

- Superior normally off architecture with D-mode GaN HEMT
- Compatible with standard silicon drivers
- Enhanced noise immunity with a 4V threshold voltage with no negative gate drive required
- Enables high-efficiency, high power density, and reliable power conversion
- Facilitates cost-effective GaN adoption reducing system size, weight, and costs

Product and Schematic Diagrams



TP65H070G4PS TO-220

	
Cascode Schematic Symbol	**Cascode Device Structure**

Features

- Ultra-fast switching Gen IV plus GaN
- JEDEC-qualified GaN technology
- Dynamic RDS(on)eff production tested
- Reduced crossover loss
- Negligible Qrr
- RoHS compliant and Halogen-free packaging

Applications

- AI datacenter and telecom power supplies
- E-mobility charging
- PV inverter
- UPS
- BESS

Specifications

V_{DS} (V)	650
$V_{DSS(TR)}$(V) maximum	800
$R_{DS(on)}$ (mΩ) maximum [1]	85
Q_{OSS} (nC) typical	78
Q_G (nC) typical	9

1. Dynamic $R_{DS(on)}$ (see Figure 17 and Figure 18)

© 2026 Renesas Electronics

Contents

1. Pin Information 3
1.1 Pin Assignments 3
1.2 Pin Descriptions 3
2. Specifications 4
2.1 Absolute Maximum Ratings 4
2.2 Thermal Specifications 4
2.3 Electrical Specifications – Forward Device 5
2.4 Electrical Specifications – Reverse Device 6
3. Typical Performance Graphs 7
4. Test Circuits and Waveforms 10
5. Package Outline Drawings 11
6. Related Information 12
7. Ordering Information 12
8. Revision History 12

Figures

Figure 1. Pin Assignments 3
Figure 2. Typical Output Characteristics, T_J = 25°C Parameter: V_{GS} 7
Figure 3. Typical Output Characteristics, T_J = 150°C Parameter: V_{GS} 7
Figure 4. Typical Transfer Characteristics V_{DS} = 10V, Parameter: T_J 7
Figure 5. Normalized On-resistance I_D = 18A, V_{GS} = 10V 7
Figure 6. Typical Capacitance V_{GS} = 0V, f = 1MHz 8
Figure 7. Typical C_{OSS} Stored Energy 8
Figure 8. Typical Q_{OSS} 8
Figure 9. Typical Gate Charge 8
Figure 10. Power Dissipation 9
Figure 11. Current Derating 9
Figure 12. Forward Characteristics of Rev. Diode 9
Figure 13. Transient Thermal Resistance 9
Figure 14. Safe Operating Area T_C = 25°C 9
Figure 15. Switching Time Test Circuit 10
Figure 16. Switching Time Waveform 10
Figure 17. Dynamic $R_{DS(on)eff}$ Test Circuit 10
Figure 18. Dynamic $R_{DS(on)eff}$ Waveform 10
Figure 19. TO-220 Package Outline Drawing 11

1. Pin Information

1.1 Pin Assignments




Figure 1. Pin Assignments

1.2 Pin Descriptions

Pin Name	Description
D	Drain.
S	Source.
G	Gate.

2. Specifications


2.1 Absolute Maximum Ratings

T_c = 25°C unless otherwise stated.

Caution: Do not operate at or near the maximum ratings listed for extended periods of time. Exposure to such conditions can adversely impact product reliability and result in failures not covered by warranty.

Symbol	Parameter	Limit Value	Unit
V_{DSS}	Drain to source voltage (T_J = -55°C to 150°C)	650	V
$V_{DSS(TR)}$	Transient drain to source voltage [1]	800	V
V_{GSS}	Gate to source voltage	+20	V
P_D	Maximum power dissipation at T_C = 25°C	96	W
I_D	Continuous drain current at T_C = 25°C	29	A
	Continuous drain current at T_C = 100°C	18.4	A
I_{DM}	Pulsed drain current (pulse width: 10µs)	120	A
T_J	Junction operating temperature	-55 to +150	°C
T_S	Storage temperature	-55 to +150	°C
T_{SOLD}	Reflow soldering temperature [2]	260	°C

1. In off-state, spike duration < 30µs, non-repetitive.
2. Reflow MSL3.



Primary Switch Voltage Stress (264 V AC)

2.2 Thermal Specifications

Symbol	Condition	Typical Value	Unit
$R_{\Theta JC}$	Junction-to-case	1	°C/W
$R_{\Theta JA}$	Junction-to-ambient [1]	62	

2.3 Electrical Specifications – Forward Device

T_J = 25°C unless otherwise stated.

Symbol	Parameter	Test Conditions	Minimum	Typical	Maximum	Unit
$V_{DSS(BL)}$	Maximum drain-source voltage	V_{GS} = 0V, I_D = 1mA	650	-	-	V
$V_{GS(th)}$	Gate threshold voltage	V_{DS} = V_{GS}, I_D = 0.7mA	3.3	4	4.8	V
$R_{DS(on)eff}$	Drain-source on-resistance [1]	V_{GS} = 10V, I_D = 18A, T_J = 25°C	-	72	85	mΩ
		V_{GS} = 10V, I_D = 18A, T_J = 150°C	-	148	-	
I_{DSS}	Drain-to-source leakage current	V_{DS} = 650V, V_{GS} = 0V, T_J = 25°C	-	1.2	12	µA
		V_{DS} = 650V, V_{GS} = 0V, T_J = 150°C	-	8	-	
I_{GSS}	Gate-to-source forward leakage current	V_{GS} = 20V	-	-	100	nA
	Gate-to-source reverse leakage current	V_{GS} = -20V	-	-	-100	
C_{ISS}	Input capacitance	V_{GS} = 0V, V_{DS} = 400V, *f* = 500kHz	-	638	-	pF
C_{OSS}	Output capacitance		-	72	-	
C_{RSS}	Reverse transfer capacitance		-	2	-	
$C_{O(er)}$	Output capacitance, energy related [2]	V_{GS} = 0V, V_{DS} = 0V to 400V	-	105	-	pF
$C_{O(tr)}$	Output capacitance, time related [3]		-	194	-	
Q_G	Total gate charge	V_{DS} = 400V, V_{GS} = 0V to 10V, I_D = 18A	-	9	-	nC
Q_{GS}	Gate-source charge		-	3.7	-	
Q_{GD}	Gate-drain charge		-	2.4	-	
Q_{OSS}	Output charge	V_{GS} = 0V, V_{DS} = 0V to 400V	-	78	-	nC
$t_{D(on)}$	Turn-on delay	V_{DS} = 400V, V_{GS} = 0V to 12V, I_D = 18A, R_G = 50Ω (see Figure 15)	-	43.4	-	ns
t_R	Rise time		-	6.2	-	
$t_{D(off)}$	Turn-off delay		-	56	-	
t_F	Fall time		-	7.2	-	

1. Dynamic $R_{DS(on)}$, 100% tested; see Figure 17 and Figure 18 for conditions.
2. Equivalent capacitance to give same stored energy from 0V to 400V.
3. Equivalent capacitance to give same charging time from 0V to 400V.

2.4 Electrical Specifications – Reverse Device

T_J = 25°C unless otherwise stated.

Symbol	Parameter	Test Conditions	Minimum	Typical	Maximum	Unit
I_S	Reverse current	V_{GS} = 0V, T_C = 100°C, ≤ 25% duty cycle	-	-	18	A
V_{SD}	Reverse voltage [1]	V_{GS} = 0V, I_S = 18A	1.6	1.9	2.2	V
		V_{GS} = 0V, I_S = 9A	1.2	1.4	1.6	

1. Includes dynamic $R_{DS(on)}$ effect.

Note: Reverse recovery charge is negligible, enabled by the LV Si FET technology

3. Typical Performance Graphs

T_C = 25°C unless otherwise stated.




Figure 2. Typical Output Characteristics, T_J = 25°C

Parameter: V_{GS}




Figure 3. Typical Output Characteristics, T_J = 150°C

Parameter: V_{GS}




Figure 4. Typical Transfer Characteristics

V_{DS} = 10V, Parameter: T_J




Figure 5. Normalized On-resistance

I_D = 18A, V_{GS} = 10V




Figure 6. Typical Capacitance

V_{GS} = 0V, f = 1MHz




Figure 7. Typical C_{OSS} Stored Energy




Figure 8. Typical Q_{OSS}




Figure 9. Typical Gate Charge

I_{DS} = 18A, V_{DS} = 400V




Figure 10. Power Dissipation




Figure 11. Current Derating

Pulse width ≤ 10µs, V_{GS} ≥ 10V




Figure 12. Forward Characteristics of Rev. Diode

$I_S = f(V_{SD})$, Parameter: T_J




Figure 13. Transient Thermal Resistance




Figure 14. Safe Operating Area T_C = 25°C

4. Test Circuits and Waveforms




Figure 15. Switching Time Test Circuit




Figure 16. Switching Time Waveform




Figure 17. Dynamic $R_{DS(on)eff}$ Test Circuit





Figure 18. Dynamic $R_{DS(on)eff}$ Waveform

5. Package Outline Drawings



SYMBOL	MILLIMETERS			INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	4.29	4.45	4.73	0.169	0.175	0.186
A1	1.09	1.31	1.40	0.043	0.052	0.055
A2	2.48	2.64	2.93	0.098	0.104	0.115
b	0.77	0.86	1.02	0.031	0.034	0.040
b1	0.70	–	0.86	0.027	–	0.034
b2	1.23	1.33	1.43	0.048	0.052	0.057
b3	1.20	–	1.37	0.047	–	0.054
c	0.35	0.40	0.47	0.014	0.016	0.019
c1	0.35	–	0.43	0.014	–	0.017
D	14.78	14.95	15.75	0.581	0.589	0.620
D1	8.38	–	9.01	0.330	–	0.355
D2	12.19	–	12.88	0.480	–	0.507
E	9.96	10.25	10.36	0.392	0.404	0.408
E1	6.86	–	8.89	0.271	–	0.350
E2	–	–	0.76	–	–	0.030
e	2.54 BSC			0.100 BSC		
e1	5.08 BSC			0.200 BSC		
H1	6.10	6.37	6.60	0.241	0.251	0.260
L	12.70	13.84	14.27	0.500	0.545	0.562
L1	3.40	3.55	3.90	0.133	0.140	0.154
øP	3.72	3.80	3.88	0.146	0.150	0.153
Q	2.60	2.80	3.00	0.102	0.110	0.119
S	15.42	15.80	16.51	0.607	0.622	0.650

Figure 19. TO-220 Package Outline Drawing

6. Related Information

All technical documents for Renesas GaN Power devices are accessible from the GaN Power Solutions page.

7. Ordering Information

Part Number	Package Description	Package Configuration
TP65H070G4PS	TO-220	Source tab

8. Revision History

Revision	Date	Description
2.01	Jun 8, 2026	Updated VSD to 25°C data.
2.00	Nov 25, 2025	Updated the document's formatting; no technical changes were completed.
1.00	Dec 4, 2023	Initial release.

IMPORTANT NOTICE AND DISCLAIMER

RENESAS ELECTRONICS CORPORATION AND ITS SUBSIDIARIES (“RENESAS”) PROVIDES TECHNICAL SPECIFICATIONS AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES “AS IS” AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR NON-INFRINGEMENT OF THIRD-PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for developers who are designing with Renesas products. You are solely responsible for (1) selecting the appropriate products for your application, (2) designing, validating, and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. Renesas grants you permission to use these resources only to develop an application that uses Renesas products. Other reproduction or use of these resources is strictly prohibited. No license is granted to any other Renesas intellectual property or to any third-party intellectual property. Renesas disclaims responsibility for, and you will fully indemnify Renesas and its representatives against, any claims, damages, costs, losses, or liabilities arising from your use of these resources. Renesas' products are provided only subject to Renesas' Terms and Conditions of Sale or other applicable terms agreed to in writing. No use of any Renesas resources expands or otherwise alters any applicable warranties or warranty disclaimers for these products.

(Disclaimer Rev.1.01)

Corporate Headquarters

TOYOSU FORESIA, 3-2-24 Toyosu,
Koto-ku, Tokyo 135-0061, Japan
www.renesas.com

Contact Information

For further information on a product, technology, the most up-to-date version of a document, or your nearest sales office, please visit www.renesas.com/contact-us/.

Trademarks

Renesas and the Renesas logo are trademarks of Renesas Electronics Corporation. All trademarks and registered trademarks are the property of their respective owners.

© 2026 Renesas Electronics Corporation. All rights reserved.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.