TOSHIBA CMOS Linear Integrated Circuit Silicon Monolithic

TCR4DG series

420 mA CMOS Low Dropout Regulator with inrush current protection circuit


1. Description

The TCR4DG series are CMOS general-purpose single-output voltage regulators with an on/off control input, featuring low dropout voltage, low output noise voltage and low inrush current.

These voltage regulators are available in fixed output voltages between 1.0 V and 4.5 V and capable of driving up to 420 mA.

They feature over-current protection, over-temperature protection, Inrush current protection circuit and Auto-discharge function.

The TCR4DG series are offered in the ultra small plastic mold package WCSP4E (0.645 mm x 0.645 mm; t 0.43 mm (max)). It has a low dropout voltage of 193 mV (3.3 V output, I_{OUT} = 420 mA) with low output noise voltage of 38 μV_{rms} (2.5 V output) and a load transient response of only $\triangle V_{OUT}$ = ±115 mV (I_{OUT} = 1 mA ⇔ 420 mA, C_{OUT} = 1.0 µF).



WCSP4E

Weight: 0.34 mg (typ.)

As small ceramic input and output capacitors can be used with the TCR4DG series, these devices are ideal for portable applications that require high-density board assembly such as cellular phones.

2. Features

- Low Drop-Out voltage
  V_{DO} = 193 mV (typ.) at 3.3 V-output, I_{OUT} = 420 mA
- Low output noise voltage
  V_{NO} = 38 μV_{rms} (typ.) at 2.5 V-output, I_{OUT} = 10 mA, 10 Hz ≤ f ≤ 100 kHz
- Fast load transient response ($\triangle V_{OUT}$ = ±115 mV (typ.) at I_{OUT} = 1 ⇔ 420 mA, C_{OUT} =1.0 µF)
- High ripple rejection (R.R = 70 dB (typ.) at 2.5 V-output, I_{OUT} = 10 mA, f = 1 kHz)
- Over-current protection
- Over-temperature protection
- Inrush current protection circuit
- Auto-discharge function
- Pull down connection between CONTROL and GND
- Ceramic capacitors can be used (C_{IN} = 1.0µF, C_{OUT} =1.0 µF)
- Ultra small package WCSP4E (0.645 mm x 0.645 mm ; t 0.43 mm (max))

Start of commercial production
2017-04

© 2018-2026
Toshiba Electronic Devices & Storage Corporation


3. Absolute Maximum Ratings (Note) (Ta = 25°C)

Characteristics	Symbol	Rating	Unit
Input voltage	V_{IN}	6.0	V
Control voltage	V_{CT}	-0.3 to 6.0	V
Output current	I_{OUT}	420	mA
Power dissipation	P_D	800 (Note1)	mW
Operation temperature range	T_{opr}	-40 to 85	°C
Junction temperature	T_j	150	°C
Storage temperature range	T_{stg}	-55 to 150	°C

Note: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings and the operating ranges.
Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook (“Handling Precautions”/“Derating Concept and Methods”) and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

Note1: Rating at mounting on a board
Board material: Glass epoxy(FR4)
Board dimension: 40 mm x 40 mm (both sides of board), t = 1.6 mm
Metal pattern ratio: a surface approximately 50%, the reverse side approximately 50%
Through hole: diameter 0.5 mm x 24 pcs

4. Pin Assignment (Top view)



	1	2
A	VIN	VOUT
B	CONTROL	GND

© 2018-2026
Toshiba Electronic Devices & Storage Corporation


5. List of Products Number, Output voltage and Marking

Product No.	Output voltage (V)(typ.)	Marking	Product No.	Output voltage (V)(typ.)	Marking
TCR4DG10*	1.0	A	TCR4DG25	2.5	T
TCR4DG105	1.05	B	TCR4DG27*	2.7	U
TCR4DG11*	1.1	C	TCR4DG275*	2.75	V
TCR4DG115*	1.15	D	TCR4DG28	2.8	W
TCR4DG12	1.2	E	TCR4DG285*	2.85	X
TCR4DG125	1.25	F	TCR4DG29*	2.9	Y
TCR4DG13*	1.3	H	TCR4DG30	3.0	0
TCR4DG135*	1.35	J	TCR4DG31*	3.1	1
TCR4DG15*	1.5	K	TCR4DG32*	3.2	2
TCR4DG175*	1.75	L	TCR4DG325*	3.25	3
TCR4DG18	1.8	M	TCR4DG33	3.3	4
TCR4DG185*	1.85	N	TCR4DG35	3.5	5
TCR4DG19*	1.9	P	TCR4DG36*	3.6	6
TCR4DG23*	2.3	R	TCR4DG42*	4.2	7
TCR4DG245*	2.45	S	TCR4DG45*	4.5	8

Please ask your local retailer about the devices with (*) or other output voltages.

Top Marking (Top view)

Example: TCR4DG10 (1.0 V output)



© 2018-2026
Toshiba Electronic Devices & Storage Corporation

6. Electrical Characteristics

(Unless otherwise specified, V_{IN} = V_{OUT} + 1 V, I_{OUT} = 50 mA, C_{IN} = 1.0 µF, C_{OUT} = 1.0 µF, T_j = 25°C)

Characteristics	Symbol	Test Condition		Min	Typ.	Max	Unit
Output voltage accuracy	V_{OUT}	I_{OUT} = 50 mA (Note 2)	V_{OUT} < 1.8 V	-18	—	+18	mV
			1.8 V ≤ V_{OUT}	-1.0	—	+1.0	%
Input voltage	V_{IN}	I_{OUT} = 1 mA (Note 3)		V_{OUT} + V_{DO}	—	5.5	V
Line regulation	Reg·line	V_{OUT} + 0.5 V ≤ V_{IN} ≤ 5.5 V, I_{OUT} = 1 mA		—	1	15	mV
Load regulation	Reg·load	1 mA ≤ I_{OUT} ≤ 420 mA		—	6	35	mV
Quiescent current	I_B	I_{OUT} = 0 mA	V_{OUT} = 1.0 V	—	65	—	µA
			V_{OUT} = 1.8 V	—	65	—	
			V_{OUT} = 2.5 V	—	68	—	
			V_{OUT} = 4.5 V	—	78	125	
Stand-by current	$I_{B\ (OFF)}$	V_{CT} = 0 V		—	0.1	1	µA
Drop-out voltage	V_{DO}	I_{OUT} = 420 mA (Note 4)		—	193	263	mV
Temperature coefficient	T_{CVO}	-40°C ≤ T_{opr} ≤ 85°C		—	75	—	ppm/°C
Output noise voltage	V_{NO}	V_{IN} = V_{OUT} + 1 V, I_{OUT} = 10 mA, 10 Hz ≤ f ≤ 100 kHz, Ta = 25°C (Note 5)		—	38	—	μV_{rms}
Ripple rejection ratio	R.R.	V_{IN} = V_{OUT} + 1 V, I_{OUT} = 10 mA, f = 1 kHz, V_{Ripple} = 500 mV_{p-p}, Ta = 25°C (Note 5)		—	70	—	dB
Load transient response	⊿V_{OUT}	I_{OUT} = 1 ⇔ 420 mA, C_{OUT} = 1.0 µF		—	±115	—	mV
Control voltage (ON)	$V_{CT\ (ON)}$	—		1.0	—	5.5	V
Control voltage (OFF)	$V_{CT\ (OFF)}$	—		0	—	0.4	V

Note 2: Stable state with fixed I_{OUT} condition.

Note 3: Please refer to Dropout Voltage table (Page 4), and use it within the limits of absolute maximum rating T_{opr} and T_j.

Note 4: The 3.3 V output product. Dropout voltage is the voltage difference between the V_{IN} and V_{OUT} at which V_{OUT} drops to 2% below its nominal value.

Note 5: The 2.5 V output product.

7. Dropout voltage


(I_{OUT} = 420 mA, C_{IN} = 1.0 µF, C_{OUT} = 1.0 µF, T_j = 25°C)

Output voltages	Symbol	Min	Typ.	Max	Unit
1.0 V, 1.05 V	V_{DO}	—	767	991	mV
1.1 V, 1.15V		—	711	851	
1.2 V, 1.25V		—	627	781	
1.3 V		—	571	711	
1.35 V		—	515	683	
1.4 V		—	487	669	
1.5 V ≤ V_{OUT} < 1.8 V		—	431	571	
1.8 V ≤ V_{OUT} < 2.1 V		—	319	473	
2.1 V ≤ V_{OUT} < 2.5 V		—	277	403	
2.5 V ≤ V_{OUT} < 2.8 V		—	235	347	
2.8 V ≤ V_{OUT} < 3.2 V		—	221	291	
3.2 V ≤ V_{OUT} < 3.6 V		—	193	263	
3.6 V ≤ V_{OUT} ≤ 4.5 V		—	151	221	

© 2018-2026
Toshiba Electronic Devices & Storage Corporation

8. Application Note

8.1. Example of Application Circuit




CONTROL voltage	Output voltage
HIGH	ON
LOW	OFF
OPEN	OFF

The figure above shows the recommended configuration for using a Low-Dropout regulator. Insert a capacitor at V_{OUT} and V_{IN} pins for stable input/output operation. (Ceramic capacitors can be used).

8.2. Power Dissipation

Board-mounted power dissipation ratings for TCR4DG series are available in the Absolute Maximum Ratings table. Power dissipation is measured on the board condition shown below.

[The Board Condition]
Board material: Glass epoxy(FR4)
Board dimension: 40 mm x 40 mm (both sides of board), t = 1.6 mm
Metal pattern ratio: a surface approximately 50 %, the reverse side approximately 50 %
Through hole hall: diameter 0.5mm x 24 pcs



8.3. Attention in Use

- Output Capacitors
  Ceramic capacitors can be used for these devices. However, because of the type of the capacitors, there might be unexpected thermal features. Please consider application condition for selecting capacitors. And Toshiba recommends the ESR of ceramic capacitor is under 10 Ω. For stable operation, we recommend over 1 μF.

- Mounting
  The long distance between IC and input output capacitor might affect phase compensation by impedance in wire and inductor. For stable power supply, input output capacitor need to mount near IC as much as possible. Also VIN and GND pattern need to be large and make the wire impedance small as possible.

- Permissible Loss
  Please have enough design patterns for expected maximum permissible loss. And under consideration of ambient temperature, input voltage, output current etc., we recommend proper dissipation ratings for maximum permissible loss; in general maximum dissipation rating is 70 to 80 %.


- Over current Protection and Thermal shutdown function
  Over current protection and Thermal shutdown function are designed in these products, but these are not designed to constantly ensure the suppression of the device within operation limits. Depending on the condition during actual usage, it could affect the electrical characteristic specification and reliability. Also note that if output pins and GND pins are not completely shorted out, these products might break down.
  When using these products, please read through and understand the concept of dissipation for absolute maximum ratings from the above mention or our ‘Semiconductor Reliability Handbook’. Then use these products under absolute maximum ratings in any condition. Furthermore, Toshiba recommends inserting failsafe system into the design.

© 2018-2026
Toshiba Electronic Devices & Storage Corporation


9. Representative Typical Characteristics (Note)

9.1. Output Current vs. Input Voltage


V_{OUT} = 1.0 V




V_{OUT} = 1.8 V



V_{OUT} = 2.5 V




V_{OUT} = 3.0 V




9.2. Quiescent Current vs. Ambient Temperature

V_{OUT} = 1.0 V





V_{OUT} = 3.0 V





© 2018-2026
Toshiba Electronic Devices & Storage Corporation

9.3. Ripple Rejection Ratio vs. Frequency













9.4. Output Voltage vs. Output Current





© 2018-2026
Toshiba Electronic Devices & Storage Corporation






Note: The above characteristics curves are presented for reference only and not guaranteed by production test, unless otherwise noted.

© 2018-2026
Toshiba Electronic Devices & Storage Corporation

10. Package Information

WCSP4E

Unit: mm



Weight: 0.34 mg (typ.)

© 2018-2026
Toshiba Electronic Devices & Storage Corporation

RESTRICTIONS ON PRODUCT USE

Toshiba Corporation and its subsidiaries and affiliates are collectively referred to as “TOSHIBA”.
Hardware, software and systems described in this document are collectively referred to as “Product”.

- TOSHIBA reserves the right to make changes to the information in this document and related Product without notice.
- This document and any information herein may not be reproduced without prior written permission from TOSHIBA. Even with TOSHIBA's written permission, reproduction is permissible only if reproduction is without alteration/omission.
- Though TOSHIBA works continually to improve Product's quality and reliability, Product can malfunction or fail. Customers are responsible for complying with safety standards and for providing adequate designs and safeguards for their hardware, software and systems which minimize risk and avoid situations in which a malfunction or failure of Product could cause loss of human life, bodily injury or damage to property, including data loss or corruption. Before customers use the Product, create designs including the Product, or incorporate the Product into their own applications, customers must also refer to and comply with (a) the latest versions of all relevant TOSHIBA information, including without limitation, this document, the specifications, the data sheets and application notes for Product and the precautions and conditions set forth in the "TOSHIBA Semiconductor Reliability Handbook" and (b) the instructions for the application with which the Product will be used with or for. Customers are solely responsible for all aspects of their own product design or applications, including but not limited to (a) determining the appropriateness of the use of this Product in such design or applications; (b) evaluating and determining the applicability of any information contained in this document, or in charts, diagrams, programs, algorithms, sample application circuits, or any other referenced documents; and (c) validating all operating parameters for such designs and applications. **TOSHIBA ASSUMES NO LIABILITY FOR CUSTOMERS' PRODUCT DESIGN OR APPLICATIONS.**
- **PRODUCT IS NEITHER INTENDED NOR WARRANTED FOR USE IN EQUIPMENTS OR SYSTEMS THAT REQUIRE EXTRAORDINARILY HIGH LEVELS OF QUALITY AND/OR RELIABILITY, AND/OR A MALFUNCTION OR FAILURE OF WHICH MAY CAUSE LOSS OF HUMAN LIFE, BODILY INJURY, SERIOUS PROPERTY DAMAGE AND/OR SERIOUS PUBLIC IMPACT ("UNINTENDED USE").** Except for specific applications as expressly stated in this document, Unintended Use includes, without limitation, equipment used in nuclear facilities, equipment used in the aerospace industry, Class 3 medical devices, equipment used for automobiles, and military vehicles and munitions. **IF YOU USE PRODUCT FOR UNINTENDED USE, TOSHIBA ASSUMES NO LIABILITY FOR PRODUCT.** For details, please contact your TOSHIBA sales representative or contact us via our website.
- Do not disassemble, analyze, reverse-engineer, alter, modify, translate or copy Product, whether in whole or in part.
- Product shall not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable laws or regulations.
- The information contained herein is presented only as guidance for Product use. No responsibility is assumed by TOSHIBA for any infringement of patents or any other intellectual property rights of third parties that may result from the use of Product. No license to any intellectual property right is granted by this document, whether express or implied, by estoppel or otherwise.
- **ABSENT A WRITTEN SIGNED AGREEMENT, EXCEPT AS PROVIDED IN THE RELEVANT TERMS AND CONDITIONS OF SALE FOR PRODUCT, AND TO THE MAXIMUM EXTENT ALLOWABLE BY LAW, TOSHIBA (1) ASSUMES NO LIABILITY WHATSOEVER, INCLUDING WITHOUT LIMITATION, INDIRECT, CONSEQUENTIAL, SPECIAL, OR INCIDENTAL DAMAGES OR LOSS, INCLUDING WITHOUT LIMITATION, LOSS OF PROFITS, LOSS OF OPPORTUNITIES, BUSINESS INTERRUPTION AND LOSS OF DATA, AND (2) DISCLAIMS ANY AND ALL EXPRESS OR IMPLIED WARRANTIES AND CONDITIONS RELATED TO SALE, USE OF PRODUCT, OR INFORMATION, INCLUDING WARRANTIES OR CONDITIONS OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, ACCURACY OF INFORMATION, OR NONINFRINGEMENT.**
- Do not use or otherwise make available Product or related software or technology for any military purposes, including without limitation, for the design, development, use, stockpiling or manufacturing of nuclear, chemical, or biological weapons or missile technology products (mass destruction weapons). Product and related software and technology may be controlled under the applicable export laws and regulations including, without limitation, the Japanese Foreign Exchange and Foreign Trade Law and the U.S. Export Administration Regulations. Export and re-export of Product or related software or technology are strictly prohibited except in compliance with all applicable export laws and regulations.
- Please contact your TOSHIBA sales representative for details as to environmental matters such as the RoHS compatibility of Product. Please use Product in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. **TOSHIBA ASSUMES NO LIABILITY FOR DAMAGES OR LOSSES OCCURRING AS A RESULT OF NONCOMPLIANCE WITH APPLICABLE LAWS AND REGULATIONS.**

Toshiba Electronic Devices & Storage Corporation
https://toshiba.semicon-storage.com/

© 2018-2026
Toshiba Electronic Devices & Storage Corporation

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.