NEW PRODUCT

## Features

- Low $R_{DS(ON)}$:
  - 65mΩ @$V_{GS}$ = -10V
  - 115mΩ @$V_{GS}$ = -4.5V
- Low Input/Output Leakage
- **Lead Free By Design/RoHS Compliant (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**
- **"Green" Device (Note 4)**


## Mechanical Data

- Case: SOT-26
- Case Material - Molded Plastic. UL Flammability Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020D
- Terminals: Finish - Matte Tin Solderable per MIL-STD-202, Method 208
- Terminal Connections: See Diagram
- Marking Information: See Page 4
- Ordering Information: See page 4
- Weight: 0.008 grams (approximate)

SOT-26



TOP VIEW




TOP VIEW
Internal Schematic

## Maximum Ratings @$T_A$ = 25°C unless otherwise specified

| Characteristic | | Symbol | Value | Unit |
|---|---|---|---|---|
| Drain-Source Voltage | | $V_{DSS}$ | -30 | V |
| Gate-Source Voltage | | $V_{GSS}$ | ±20 | V |
| Drain Current (Note 1) Continuous | $T_A$ = 25°C<br>$T_A$ = 70°C | $I_D$ | -4.0<br>-3.0 | A |
| Pulsed Drain Current (Note 2) | | $I_{DM}$ | -14 | A |

## Thermal Characteristics

| Characteristic | Symbol | Value | Unit |
|---|---|---|---|
| Total Power Dissipation (Note 1) | $P_D$ | 1.25 | W |
| Thermal Resistance, Junction to Ambient (Note 1); Steady-State | $R_{\theta JA}$ | 100 | °C/W |
| Operating and Storage Temperature Range | $T_J$, $T_{STG}$ | -55 to +150 | °C |

Notes:
1. Device mounted on 1"x1", FR-4 PC board on 0.1in.$^2$ pads on 2 oz. Copper pads and test pulse width t ≤10s.
2. Repetitive Rating, pulse width limited by junction temperature.
3. No purposefully added lead.
4. Diodes Inc's "Green" policy can be found on our website at http://www.diodes.com/products/lead_free/index.php.


© Diodes Incorporated

NEW PRODUCT

## Electrical Characteristics @$T_A$ = 25°C unless otherwise specified

| Characteristic | Symbol | Min | Typ | Max | Unit | Test Condition |
|---|---|---|---|---|---|---|
| **STATIC PARAMETERS** | | | | | | |
| Drain-Source Breakdown Voltage | $BV_{DSS}$ | -30 | — | — | V | $I_D$ = -250μA, $V_{GS}$ = 0V |
| Zero Gate Voltage Drain Current $T_J$ = 25°C | $I_{DSS}$ | — | — | -1 | μA | $V_{DS}$ = -30V, $V_{GS}$ = 0V |
| Gate-Body Leakage Current | $I_{GSS}$ | — | — | ±100 | nA | $V_{DS}$ = 0V, $V_{GS}$ = ±20V |
| Gate Threshold Voltage | $V_{GS(th)}$ | -1.0 | — | -2.1 | V | $V_{DS}$ = $V_{GS}$, $I_D$ = -250μA |
| On State Drain Current (Note 5) | $I_{D(ON)}$ | -15 | — | — | A | $V_{GS}$ = -4.5V, $V_{DS}$ = -5V |
| Static Drain-Source On-Resistance (Note 5) | $R_{DS(ON)}$ | — | 56<br>98 | 65<br>115 | mΩ | $V_{GS}$ = -10V, $I_D$ = -4.0A<br>$V_{GS}$ = -4.5V, $I_D$ = -3.0A |
| Forward Transconductance (Note 5) | $g_{FS}$ | — | 5.3 | — | S | $V_{DS}$ = -10V, $I_D$ = -4.0A |
| Diode Forward Voltage (Note 5) | $V_{SD}$ | — | 0.79 | -1.2 | V | $I_S$ = -1.7A, $V_{GS}$ = 0V |
| **DYNAMIC PARAMETERS (Note 6)** | | | | | | |
| Input Capacitance | $C_{iss}$ | — | 336 | — | pF | $V_{DS}$ = -25V, $V_{GS}$ = 0V<br>f = 1.0MHz |
| Output Capacitance | $C_{oss}$ | — | 70 | — | pF | |
| Reverse Transfer Capacitance | $C_{rss}$ | — | 49 | — | pF | |
| Gate Resistance | $R_G$ | — | 4.6 | — | Ω | $V_{DS}$ = 0V, $V_{GS}$ = 0V, f = 1.0MHz |
| **SWITCHING CHARACTERISTICS** | | | | | | |
| Total Gate Charge | $Q_g$ | — | 4.0<br>7.8 | — | nC | $V_{DS}$ = -15V, $V_{GS}$ = -4.5V, $I_D$ = -5.0A<br>$V_{DS}$ = -15V, $V_{GS}$ = -10V, $I_D$ = -5.0A |
| Gate-Source Charge | $Q_{gs}$ | — | 1.0 | — | | $V_{DS}$ = -15V, $V_{GS}$ = -4.5V, $I_D$ = -5.0A |
| Gate-Drain Charge | $Q_{gd}$ | — | 2.5 | — | | $V_{DS}$ = -15V, $V_{GS}$ = -4.5V, $I_D$ = -5.0A |
| Turn-On Delay Time | $t_{d(on)}$ | — | 6.0 | — | ns | $V_{DS}$ = -15V, $V_{GS}$ = -10V,<br>$I_D$ = -1.0A, $R_G$ = 6.0Ω |
| Rise Time | $t_r$ | — | 5.0 | — | | |
| Turn-Off Delay Time | $t_{d(off)}$ | — | 17.6 | — | | |
| Fall Time | $t_f$ | — | 9.5 | — | | |

Notes: 5. Test pulse width t = 300μs.
6. Guaranteed by design. Not subject to production testing.




Fig. 1 Typical Output Characteristics




Fig. 2 Typical Transfer Characteristics


© Diodes Incorporated

NEW PRODUCT





Fig. 3 Typical On-Resistance vs. Drain Current and Gate Voltage





Fig. 4 Typical On-Resistance vs. Drain Current and Temperature





Fig. 5 On-Resistance Variation with Temperature





Fig. 6 Typical Capacitance





Fig. 7 Gate Threshold Variation vs. Ambient Temperature





Fig. 8 Diode Forward Voltage vs. Current


© Diodes Incorporated


NEW PRODUCT

## Ordering Information (Note 7)

| Part Number | Case | Packaging |
|---|---|---|
| DMP3098LDM-7 | SOT-26 | 3000/Tape & Reel |

Notes: 7. For packaging details, go to our website at http://www.diodes.com/datasheets/ap02007.pdf.

## Marking Information





DMB = Product Type Marking Code
YM = Date Code Marking
Y = Year (ex: V = 2008)
M = Month (ex: 9 = September)

Date Code Key

| Year | 2008 | 2009 | 2010 | 2011 | 2012 | 2013 | 2014 | 2015 |
|---|---|---|---|---|---|---|---|---|
| Code | V | W | X | Y | Z | A | B | C |


| Month | Jan | Feb | Mar | Apr | May | Jun | Jul | Aug | Sep | Oct | Nov | Dec |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Code | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | O | N | D |

## Package Outline Dimensions




| SOT-26 | | | |
|---|---|---|---|
| Dim | Min | Max | Typ |
| A | 0.35 | 0.50 | 0.38 |
| B | 1.50 | 1.70 | 1.60 |
| C | 2.70 | 3.00 | 2.80 |
| D | — | — | 0.95 |
| H | 2.90 | 3.10 | 3.00 |
| J | 0.013 | 0.10 | 0.05 |
| K | 1.00 | 1.30 | 1.10 |
| L | 0.35 | 0.55 | 0.40 |
| M | 0.10 | 0.20 | 0.15 |
| α | 0° | 8° | — |
| All Dimensions in mm | | | |

## Suggested Pad Layout




| Dimensions | Value (in mm) |
|---|---|
| Z | 3.20 |
| G | 1.60 |
| X | 0.55 |
| Y | 0.80 |
| C | 2.40 |
| E | 0.95 |

IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.


© Diodes Incorporated

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

# Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

### Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

**www.entegreci.com**

### Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

**Kategorilere göz atın**

### Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

**Üreticileri görün**

### Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

**Teklif isteyin**

**www.entegreci.com** | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.