Features

- Low $R_{DS(ON)}$:
  40mΩ @V_{GS} = -4.5V
  70mΩ @V_{GS} = -2.5V
- Low Input/Output Leakage
- **Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)**
- **Halogen and Antimony Free. "Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**
- **PPAP Capable (Note 4)**


Mechanical Data

- Case: SOT26
- Case Material – Molded Plastic. UL Flammability Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020
- Terminals: Finish - Matte Tin Solderable per MIL-STD-202, Method 208 e3
- Terminal Connections: See Diagram
- Weight: 0.008 grams (Approximate)

SOT26



Top View



Top View
Internal Schematic


NOT RECOMMENDED FOR NEW DESIGN

Ordering Information (Note 5)

Part Number	Case	Packaging
DMP2066LDM-7	SOT26	3000/Tape & Reel
DMP2066LDMQ-7	SOT26	3000/Tape & Reel

Notes:
1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
2. See https://www.diodes.com/quality/lead-free/ for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. Automotive products are AEC-Q101 qualified and are PPAP capable. Automotive, AEC-Q101 and standard products are electrically and thermally the same, except where specified. For more information, please refer to https://www.diodes.com/quality/.
5. For packaging details, go to our website at https://www.diodes.com/design/support/packaging/diodes-packaging/.

Marking Information



DMC = Product Type Marking Code
YM = Date Code Marking
Y = Year (ex: F = 2018)
M = Month (ex: 9 = September)

Date Code Key

Year	2008	2009	2010	2011	~	2018	2019	2020
Code	V	W	X	Y	~	F	G	H

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D

© Diodes Incorporated

Maximum Ratings (@T_A = +25°C, unless otherwise specified.)

Characteristic		Symbol	Value	Unit
Drain-Source Voltage		V_{DSS}	-20	V
Gate-Source Voltage		V_{GSS}	±12	V
Drain Current (Note 6) Continuous	T_A = +25°C T_A = +70°C	I_D	-4.6 -3.7	A
Pulsed Drain Current (Note 7)		I_{DM}	-18	A
Body-Diode Continuous Current (Note 6)		I_S	2.0	A

Thermal Characteristics

Characteristic	Symbol	Value	Unit
Total Power Dissipation (Note 6)	P_D	1.25	W
Thermal Resistance, Junction to Ambient (Note 6); Steady-State	$R_{\theta JA}$	100	°C/W
Operating and Storage Temperature Range	T_J, T_{STG}	-55 to +150	°C

Electrical Characteristics (@T_A = +25°C, unless otherwise specified.)

Characteristic		Symbol	Min	Typ	Max	Unit	Test Condition
STATIC PARAMETERS							
Drain-Source Breakdown Voltage		BV_{DSS}	-20	—	—	V	I_D = -250μA, V_{GS} = 0V
Zero Gate Voltage Drain Current	T_J = +25°C	I_{DSS}	—	—	-1	μA	V_{DS} = -20V, V_{GS} = 0V
Gate-Body Leakage Current		I_{GSS}	—	—	±100	nA	V_{DS} = 0V, V_{GS} = ±12V
Gate Threshold Voltage		$V_{GS(TH)}$	-0.6	-0.96	-1.2	V	V_{DS} = V_{GS}, I_D = -250μA
On State Drain Current (Note 8)		$I_{D(ON)}$	-15	—	—	A	V_{GS} = -4.5V, V_{DS} = -5V
Static Drain-Source On-Resistance (Note 8)		$R_{DS(ON)}$	—	29 55	40 70	mΩ	V_{GS} = -4.5V, I_D = -4.6A V_{GS} = -2.5V, I_D = -3.8A
Forward Transconductance (Note 8)		g_{FS}	—	9	—	S	V_{DS} = -10V, I_D = -4.6A
Diode Forward Voltage (Note 8)		V_{SD}	-0.5	-0.72	-1.4	V	I_S = -2.1A, V_{GS} = 0V
Maximum Body-Diode Continuous Current (Note 6)		I_S	—	—	-1.7	A	—
DYNAMIC PARAMETERS (Note 9)							
Input Capacitance		C_{iss}	—	820	—	pF	V_{DS} = -15V, V_{GS} = 0V f = 1.0MHz
Output Capacitance		C_{oss}	—	200	—	pF	
Reverse Transfer Capacitance		C_{rss}	—	160	—	pF	
Gate Resistance		R_G	—	2.5	—	Ω	V_{DS} = 0V, V_{GS} = 0V f = 1.0MHz
SWITCHING CHARACTERISTICS							
Total Gate Charge		Q_G	—	10.1	—	nC	V_{DS} = -10V, V_{GS} = -4.5V, I_D = -4.5A
Gate-Source Charge		Q_{GS}	—	1.5	—		
Gate-Drain Charge		Q_{GD}	—	4.3	—		
Turn-On Delay Time		$t_{D(ON)}$	—	4.4	—	ns	V_{DS} = -10V, V_{GS} = -4.5V, I_D = -1A, R_G = 6.0Ω
Rise Time		t_R	—	9.9	—		
Turn-Off Delay Time		$t_{D(OFF)}$	—	28.0	—		
Fall Time		t_F	—	23.4	—		

NOT RECOMMENDED FOR NEW DESIGN

Notes:
6. Device mounted on 1"x1", FR-4 PC board with 2 oz. Copper and test pulse width t ≤10s.
7. Repetitive Rating, pulse width limited by junction temperature.
8. Test pulse width t = 300μs.
9. Guaranteed by design. Not subject to production testing.

© Diodes Incorporated




Fig. 1 Typical Output Characteristic




Fig. 2 Typical Transfer Characteristic




Fig. 3 Typical On-Resistance
vs. Drain Current and Gate Voltage




Fig. 4 Typical On-Resistance
vs. Drain Current and Temperature




Fig. 5 Normalized On-Resistance vs. Ambient Temperature




Fig. 6 Gate Threshold Variation vs. Ambient Temperature

NOT RECOMMENDED FOR NEW DESIGN

© Diodes Incorporated




Fig. 7 Diode Forward Voltage vs. Current




Fig. 8 Typical Total Capacitance




Fig. 9 Transient Thermal Response


NOT RECOMMENDED FOR NEW DESIGN

© Diodes Incorporated

Package Outline Dimensions

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT26




SOT26			
Dim	Min	Max	Typ
A1	0.013	0.10	0.05
A2	1.00	1.30	1.10
A3	0.70	0.80	0.75
b	0.35	0.50	0.38
c	0.10	0.20	0.15
D	2.90	3.10	3.00
e	-	-	0.95
e1	-	-	1.90
E	2.70	3.00	2.80
E1	1.50	1.70	1.60
L	0.35	0.55	0.40
a	-	-	8°
a1	-	-	7°
All Dimensions in mm			

Suggested Pad Layout

Please see http://www.diodes.com/package-outlines.html for the latest version.

SOT26



Dimensions	Value (in mm)
C	2.40
C1	0.95
G	1.60
X	0.55
Y	0.80
Y1	3.20

NOT RECOMMENDED FOR NEW DESIGN

© Diodes Incorporated

IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2018, Diodes Incorporated

www.diodes.com

NOT RECOMMENDED FOR NEW DESIGN

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.