# Field Stop Trench IGBT
## 650 V, 75 A

# FGHL75T65MQDT

Field stop 4th generation mid speed IGBT technology copacked with full rated current diode.


### Features


- Maximum Junction Temperature: $T_J$ = 175°C
- Positive Temperature Co−efficient for Easy Parallel Operating
- High Current Capability
- Low Saturation Voltage: $V_{CE(Sat)}$ = 1.45 V (Typ.) @ $I_C$ = 75 A
- 100% of the Parts are Tested for $I_{LM}$ (Note 2)
- Smooth and Optimized Switching
- Tight Parameter Distribution
- RoHS Compliant

### Typical Applications

- Solar Inverter
- UPS, ESS
- PFC, Converters

**75 A, 650 V**
**$V_{CESat}$ = 1.45 V**




**TO−247−3L**
**CASE 340CX**

### MARKING DIAGRAM




&Y = ON Semiconductor Logo
&Z = Assembly Plant Code
&3 = 3−Digit Date Code
&K = 2−Digit Lot Traceability Code
FGHL75T65MQDT = Specific Device Code

### MAXIMUM RATINGS

| Rating | Symbol | Value | Unit |
|---|---|---|---|
| Collector−to−Emitter Voltage | $V_{CES}$ | 650 | V |
| Gate−to−Emitter Voltage<br>Transient Gate−to−Emitter Voltage | $V_{GES}$ | ±20<br>±30 | V |
| Collector Current (Note 1) @ $T_C$ = 25°C<br>@ $T_C$ = 100°C | $I_C$ | 80<br>75 | A |
| Pulsed Collector Current (Note 2) | $I_{LM}$ | 300 | A |
| Pulsed Collector Current (Note 3) | $I_{CM}$ | 300 | A |
| Diode Forward Current (Note 1) @ $T_C$ = 25°C<br>@ $T_C$ = 100°C | $I_F$ | 80<br>75 | A |
| Pulsed Diode Maximum Forward Current | $I_{FM}$ | 300 | A |
| Maximum Power Dissipation @ $T_C$ = 25°C<br>@ $T_C$ = 100°C | $P_D$ | 375<br>188 | W |
| Operating Junction and Storage Temperature Range | $T_J$, $T_{STG}$ | −55 to +175 | °C |
| Maximum Lead Temp. for Soldering Purposes (1/8″ from case for 5 s) | $T_L$ | 260 | °C |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Value limit by bond wire
2. $V_{CC}$ = 400 V, $V_{GE}$ = 15 V, $I_C$ = 300 A, $R_G$ = 9 Ω, Inductive Load, 100% tested
3. Repetitive rating: pulse width limited by max. junction temperature

### ORDERING INFORMATION

| Device | Package | Shipping |
|---|---|---|
| FGHL75T65MQDT | TO−247−3L | 30 Units / Tube |

© Semiconductor Components Industries, LLC, 2020

## THERMAL CHARACTERISTICS

| Rating | Symbol | Value | Unit |
|---|---|---|---|
| Thermal resistance junction−to−case, for IGBT | $R_{\theta JC}$ | 0.40 | °C/W |
| Thermal resistance junction−to−case, for Diode | $R_{\theta JC}$ | 0.60 | °C/W |
| Thermal resistance junction−to−ambient | $R_{\theta JA}$ | 40 | °C/W |

## ELECTRICAL CHARACTERISTICS ($T_J$ = 25°C unless otherwise noted)

| Parameter | Test Conditions | Symbol | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| **OFF CHARACTERISTICS** | | | | | | |
| Collector−emitter breakdown voltage, gate−emitter short−circuited | $V_{GE}$ = 0 V, $I_C$ = 1 mA | $BV_{CES}$ | 650 | – | – | V |
| Temperature Coefficient of Breakdown Voltage | $V_{GE}$ = 0 V, $I_C$ = 1 mA | $\frac{\Delta BV_{CES}}{\Delta T_J}$ | – | 0.6 | – | V/°C |
| Collector−emitter cut−off current, gate−emitter short−circuited | $V_{GE}$ = 0 V, $V_{CE}$ = 650 V | $I_{CES}$ | – | – | 250 | μA |
| Gate leakage current, collector−emitter short−circuited | $V_{GE}$ = 20 V, $V_{CE}$ = 0 V | $I_{GES}$ | – | – | ±400 | nA |
| **ON CHARACTERISTICS** | | | | | | |
| Gate−emitter threshold voltage | $V_{GE}$ = $V_{CE}$, $I_C$ = 75 mA | $V_{GE(th)}$ | 3.0 | 4.5 | 6.0 | V |
| Collector−emitter saturation voltage | $V_{GE}$ = 15 V, $I_C$ = 75 A, $T_J$ = 25°C<br>$V_{GE}$ = 15 V, $I_C$ = 75 A, $T_J$ = 150°C | $V_{CE(sat)}$ | –<br>– | 1.45<br>1.65 | 1.8<br>– | V |
| **DYNAMIC CHARACTERISTICS** | | | | | | |
| Input capacitance | $V_{CE}$ = 30 V, $V_{GE}$ = 0 V, f = 1 MHz | $C_{ies}$ | – | 4954 | – | pF |
| Output capacitance | | $C_{oes}$ | – | 163 | – | |
| Reverse transfer capacitance | | $C_{res}$ | – | 14 | – | |
| Gate charge total | $V_{CE}$ = 400 V, $I_C$ = 75 A, $V_{GE}$ = 15 V | $Q_g$ | – | 149 | – | nC |
| Gate−to−emitter charge | | $Q_{ge}$ | – | 27 | – | |
| Gate−to−collector charge | | $Q_{gc}$ | – | 34 | – | |
| **SWITCHING CHARACTERISTICS, INDUCTIVE LOAD** | | | | | | |
| Turn−on delay time | $T_C$ = 25°C, $V_{CC}$ = 400 V, $I_C$ = 37.5 A, $R_G$ = 4.7 Ω, $V_{GE}$ = 15 V, Inductive Load | $t_{d(on)}$ | – | 22 | – | ns |
| Rise time | | $t_r$ | – | 21 | – | |
| Turn−off delay time | | $t_{d(off)}$ | – | 125 | – | |
| Fall time | | $t_f$ | – | 11 | – | |
| Turn−on switching loss | | $E_{on}$ | – | 0.86 | – | mJ |
| Turn−off switching loss | | $E_{off}$ | – | 0.49 | – | |
| Total switching loss | | $E_{ts}$ | – | 1.35 | – | |
| Turn−on delay time | $T_C$ = 25°C, $V_{CC}$ = 400 V, $I_C$ = 75 A, $R_G$ = 4.7 Ω, $V_{GE}$ = 15 V, Inductive Load | $t_{d(on)}$ | – | 24 | – | ns |
| Rise time | | $t_r$ | – | 46 | – | |
| Turn−off delay time | | $t_{d(off)}$ | – | 118 | – | |
| Fall time | | $t_f$ | – | 66 | – | |
| Turn−on switching loss | | $E_{on}$ | – | 2.35 | – | mJ |
| Turn−off switching loss | | $E_{off}$ | – | 1.25 | – | |
| Total switching loss | | $E_{ts}$ | – | 3.6 | – | |

**ELECTRICAL CHARACTERISTICS** ($T_J$ = 25°C unless otherwise noted)

| Parameter | Test Conditions | Symbol | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| **SWITCHING CHARACTERISTICS, INDUCTIVE LOAD** | | | | | | |
| Turn−on delay time | $T_C$ = 150°C, $V_{CC}$ = 400 V, $I_C$ = 37.5 A, $R_G$ = 4.7 Ω, $V_{GE}$ = 15 V, Inductive Load | $t_{d(on)}$ | − | 22 | − | ns |
| Rise time | | $t_r$ | − | 22 | − | |
| Turn−off delay time | | $t_{d(off)}$ | − | 142 | − | |
| Fall time | | $t_f$ | − | 85 | − | |
| Turn−on switching loss | | $E_{on}$ | − | 1.43 | − | mJ |
| Turn−off switching loss | | $E_{off}$ | − | 0.85 | − | |
| Total switching loss | | $E_{ts}$ | − | 2.28 | − | |
| Turn−on delay time | $T_C$ = 150°C, $V_{CC}$ = 400 V, $I_C$ = 75 A, $R_G$ = 4.7 Ω, $V_{GE}$ = 15 V, Inductive Load | $t_{d(on)}$ | − | 24 | − | ns |
| Rise time | | $t_r$ | − | 50 | − | |
| Turn−off delay time | | $t_{d(off)}$ | − | 126 | − | |
| Fall time | | $t_f$ | − | 80 | − | |
| Turn−on switching loss | | $E_{on}$ | − | 3.24 | − | mJ |
| Turn−off switching loss | | $E_{off}$ | − | 1.75 | − | |
| Total switching loss | | $E_{ts}$ | − | 4.99 | − | |
| **DIODE CHARACTERISTICS** | | | | | | |
| Diode Forward Voltage | $I_F$ = 75 A, $T_J$ = 25°C | $V_{FM}$ | − | 1.65 | 2.1 | V |
| | $I_F$ = 75 A, $T_J$ = 150°C | | − | 1.55 | − | |
| **DIODE SWITCHING CHARACTERISTICS, INDUCTIVE LOAD** | | | | | | |
| Reverse Recovery Energy | $T_C$ = 25°C, $V_{CE}$ = 400 V, $I_F$ = 37.5 A, $dI_F/dt$ = 1000 A/μs | $E_{rec}$ | − | 105 | − | μJ |
| Diode Reverse Recovery Time | | $T_{rr}$ | − | 58 | − | ns |
| Diode Reverse Recovery Charge | | $Q_{rr}$ | − | 591 | − | nC |
| Reverse Recovery Energy | $T_C$ = 25°C, $V_{CE}$ = 400 V, $I_F$ = 75 A, $dI_F/dt$ = 1000 A/μs | $E_{rec}$ | − | 235 | − | μJ |
| Diode Reverse Recovery Time | | $T_{rr}$ | − | 107 | − | ns |
| Diode Reverse Recovery Charge | | $Q_{rr}$ | − | 1113 | − | nC |
| Reverse Recovery Energy | $T_C$ = 150°C, $V_{CE}$ = 400 V, $I_F$ = 37.5 A, $dI_F/dt$ = 1000 A/μs | $E_{rec}$ | − | 747 | − | μJ |
| Diode Reverse Recovery Time | | $T_{rr}$ | − | 151 | − | ns |
| Diode Reverse Recovery Charge | | $Q_{rr}$ | − | 2780 | − | nC |
| Reverse Recovery Energy | $T_C$ = 150°C, $V_{CE}$ = 400 V, $I_F$ = 75 A, $dI_F/dt$ = 1000 A/μs | $E_{rec}$ | − | 865 | − | μJ |
| Diode Reverse Recovery Time | | $T_{rr}$ | − | 171 | − | ns |
| Diode Reverse Recovery Charge | | $Q_{rr}$ | − | 3286 | − | nC |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

## TYPICAL CHARACTERISTICS





**Figure 1. Typical Output Characteristics (25°C)**





**Figure 2. Typical Output Characteristics (150°C)**





**Figure 3. Typical Saturation Voltage Characteristics**





**Figure 4. Typical Transfer Characteristics**





**Figure 5. Saturation Voltage vs. Case Temperature**





**Figure 6. Capacitance Characteristics**

## TYPICAL CHARACTERISTICS





**Figure 7. Gate Charge Characteristics**





**Figure 8. SOA Characteristics**





**Figure 9. Turn−On Characteristics vs. Gate Resistance**





**Figure 10. Turn−Off Characteristics vs. Gate Resistance**





**Figure 11. Turn−On Characteristics vs. Collector Current**





**Figure 12. Turn−Off Characteristics vs. Collector Current**

## TYPICAL CHARACTERISTICS





**Figure 13. Switching Loss vs. Gate Resistance**





**Figure 14. Switching Loss vs. Collector Current**





**Figure 15. Forward Characteristics**





**Figure 16. Reverse Recovery Current**





**Figure 17. Reverse Recovery Time**





**Figure 18. Stored Charge**

## TYPICAL CHARACTERISTICS





**Figure 19. Transient Thermal Impedance of IGBT**






**Figure 20. Transient Thermal Impedance of Diode**

## PACKAGE DIMENSIONS

**TO−247−3LD**
CASE 340CX
ISSUE A




NOTES: UNLESS OTHERWISE SPECIFIED.

A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
B. ALL DIMENSIONS ARE IN MILLIMETERS.
C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

| DIM | MILLIMETERS | | |
|---|---|---|---|
| | MIN | NOM | MAX |
| A | 4.58 | 4.70 | 4.82 |
| A1 | 2.20 | 2.40 | 2.60 |
| A2 | 1.40 | 1.50 | 1.60 |
| D | 20.32 | 20.57 | 20.82 |
| E | 15.37 | 15.62 | 15.87 |
| E2 | 4.96 | 5.08 | 5.20 |
| e | ~ | 5.56 | ~ |
| L | 19.75 | 20.00 | 20.25 |
| L1 | 3.69 | 3.81 | 3.93 |
| ØP | 3.51 | 3.58 | 3.65 |
| Q | 5.34 | 5.46 | 5.58 |
| S | 5.34 | 5.46 | 5.58 |
| b | 1.17 | 1.26 | 1.35 |
| b2 | 1.53 | 1.65 | 1.77 |
| b4 | 2.42 | 2.54 | 2.66 |
| c | 0.51 | 0.61 | 0.71 |
| D1 | 13.08 | ~ | ~ |
| D2 | 0.51 | 0.93 | 1.35 |
| E1 | 12.81 | ~ | ~ |
| ØP1 | 6.60 | 6.80 | 7.00 |

**onsemi**, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi's** product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

**LITERATURE FULFILLMENT**:
**Email Requests to:** orderlit@onsemi.com

**onsemi Website:** www.onsemi.com

**TECHNICAL SUPPORT**
**North American Technical Support:**
Voice Mail: 1 800−282−9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

**Europe, Middle East and Africa Technical Support:**
Phone: 00421 33 790 2910
For additional information, please contact your local Sales Representative

◊

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

# Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

### Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

**www.entegreci.com**

### Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

**Kategorilere göz atın**

### Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

**Üreticileri görün**

### Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

**Teklif isteyin**

**www.entegreci.com** | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.