IGBT – Power, Co-PAK
N-Channel, Field Stop VII (FS7), SCR, Power TO247-3L, 1200 V, 1.4 V, 100 A

FGY100T120RWD

BV_{CES}	$V_{CE(SAT)}$	I_C
1200 V	1.4 V	100 A

Description

Using the novel field stop 7th generation IGBT technology and the Gen7 Diode in TO247 3−lead package, FGY100T120RWD offers the optimum performance with low conduction losses and good switching controllability for a high efficiency operation in various applications like motor control, UPS, data center and high−power switch.


Features


- Low Conduction Loss and Optimized Switching
- Maximum Junction Temperature − T_J = 175°C
- Positive Temperature Coefficient for Easy Parallel Operation
- High Current Capability
- 100% of the Parts are Dynamically Tested
- Short Circuit Rated
- RoHS Compliant

Applications

- Motor Control
- UPS
- General Application Requiring High Power Switch


PIN CONNECTIONS





TO247−3LD
CASE 340CD

MARKING DIAGRAM



$Y	= **onsemi** logo
&Z	= Assembly Plant Code
&3	= 3−Digit Date Code
&K	= 2−Digit Lot Traceability Code
FGY100T120RWD	= Specific Device Code

MAXIMUM RATINGS (T_J = 25°C unless otherwise noted)

Parameter		Symbol	Value	Unit
Collector−to−Emitter Voltage		V_{CES}	1200	V
Gate−to−Emitter Voltage		V_{GES}	±20	
Transient Gate−to−Emitter Voltage			±30	
Collector Current	T_C = 25°C	I_C	200	A
	T_C = 100°C		100	
Power Dissipation	T_C = 25°C	P_D	1071	W
	T_C = 100°C		535	
Pulsed Collector Current	T_C = 25°C, t_p = 10 μs (Note 1)	I_{CM}	300	A
Diode Forward Current	T_C = 25°C	I_F	200	
	T_C = 100°C		100	
Pulsed Diode Forward Current	T_C = 25°C, t_p = 10 μs (Note 1)	I_{FM}	300	
Short Circuit Withstand Time V_{GE} = 15 V, V_{CC} = 600 V, T_C = 150°C		T_{SC}	5	μs
Operating Junction and Storage Temperature Range		T_J, T_{STG}	−55 to 175	°C
Lead Temperature for Soldering Purposes		T_L	260	

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

ORDERING INFORMATION

Device	Package	Shipping
FGY100T120RWD	TO247−3LD (Pb−Free)	30 Units / Tube

© Semiconductor Components Industries, LLC, 2022

1. Repetitive rating: pulse width limited by max. Junction temperature.

THERMAL CHARACTERISTICS

Parameter	Symbol	Max Value	Unit
Thermal Resistance, Junction−to−Case for IGBT	$R_{\theta JC}$	0.14	°C/W
Thermal Resistance, Junction−to−Case for Diode		0.23	
Thermal Resistance, Junction−to−Ambient	$R_{\theta JA}$	40	

ELECTRICAL CHARACTERISTICS OF THE IGBT (T_J = 25°C unless otherwise noted)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Collector−to−Emitter Breakdown Voltage	BV_{CES}	V_{GE} = 0 V, I_C = 5 mA	1200	–	–	V
Breakdown Voltage Temperature Coefficient	$\Delta BV_{CES} / \Delta T_J$	V_{GE} = 0 V, I_C = 5 mA	–	1221	–	mV/°C
Collector−to−Emitter Cut−Off Current	I_{CES}	V_{GE} = 0 V, V_{CE} = V_{CES}	–	–	40	μA
Gate−to−Emitter Leakage Current	I_{GES}	V_{GE} = 20 V, V_{CE} = 0 V	–	–	±400	nA
ON CHARACTERISTICS						
Gate−to−Emitter Threshold Voltage	$V_{GE(TH)}$	V_{GE} = V_{CE}, I_C = 100 mA	4.9	5.92	6.7	V
Collector−to−Emitter Saturation Voltage	$V_{CE(SAT)}$	V_{GE} = 15 V, I_C = 100 A, T_J = 25°C	1.15	1.43	1.75	V
		V_{GE} = 15 V, I_C = 100 A, T_J = 175°C	–	1.66	–	
DYNAMIC CHARACTERISTICS						
Input Capacitance	C_{IES}	V_{CE} = 30 V, V_{GE} = 0 V, f = 1 MHz	–	12200	–	pF
Output Capacitance	C_{OES}		–	392	–	
Reverse Transfer Capacitance	C_{RES}		–	44.2	–	
Total Gate Charge	Q_G	V_{CE} = 600 V, V_{GE} = 15 V, I_C = 100 A	–	427	–	nC
Gate to Emitter Charge	Q_{GE}		–	108	–	
Gate to Collector Charge	Q_{GC}		–	161	–	
SWITCHING CHARACTERISTIC, INDUCTIVE LOAD						
Turn−On Delay Time	$t_{d(on)}$	V_{CE} = 600 V, V_{GE} = 15 V, I_C = 50 A, R_G = 4.7 Ω, T_J = 25°C	–	74	–	ns
Turn−Off Delay Time	$t_{d(off)}$		–	464	–	
Rise Time	t_r		–	45	–	
Fall Time	t_f		–	196	–	
Turn-On Switching Loss	E_{on}		–	3.43	–	mJ
Turn−Off Switching Loss	E_{off}		–	4.54	–	
Total Switching Loss	E_{ts}		–	7.97	–	
Turn−On Delay Time	$t_{d(on)}$	V_{CE} = 600 V, V_{GE} = 15 V, I_C = 100 A, R_G = 4.7 Ω, T_J = 25°C	–	80	–	ns
Turn−Off Delay Time	$t_{d(off)}$		–	364	–	
Rise Time	t_r		–	85	–	
Fall Time	t_f		–	180	–	
Turn−On Switching Loss	E_{on}		–	8.13	–	mJ
Turn−Off Switching Loss	E_{off}		–	7.05	–	
Total Switching Loss	E_{ts}		–	15.18	–	

ELECTRICAL CHARACTERISTICS OF THE IGBT (T_J = 25°C unless otherwise noted) (continued)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
SWITCHING CHARACTERISTIC, INDUCTIVE LOAD						
Turn−On Delay Time	$t_{d(on)}$	V_{CE} = 600 V, V_{GE} = 15 V, I_C = 50 A, R_G = 4.7 Ω, T_J = 175°C	−	70	−	ns
Turn−Off Delay Time	$t_{d(off)}$		−	536	−	
Rise Time	t_r		−	50	−	
Fall Time	t_f		−	348	−	
Turn−On Switching Loss	E_{on}		−	5.58	−	mJ
Turn−Off Switching Loss	E_{off}		−	6.83	−	
Total Switching Loss	E_{ts}		−	12.41	−	
Turn−On Delay Time	$t_{d(on)}$	V_{CE} = 600 V, V_{GE} = 15 V, I_C = 100 A, R_G = 4.7 Ω, T_J = 175°C	−	78	−	ns
Turn−Off Delay Time	$t_{d(off)}$		−	412	−	
Rise Time	t_r		−	93	−	
Fall Time	t_f		−	316	−	
Turn−On Switching Loss	E_{on}		−	12.00	−	mJ
Turn−Off Switching Loss	E_{off}		−	10.30	−	
Total Switching Loss	E_{ts}		−	22.30	−	
DIODE CHARACTERISTIC						
Diode Forward Voltage	V_F	I_F = 100 A, T_J = 25°C	1.46	1.80	2.08	V
		I_F = 100 A, T_J = 175°C	−	1.90	−	
DIODE SWITCHING CHARACTERISTIC, INDUCTIVE LOAD						
Reverse Recovery Time	t_{rr}	V_R = 600 V, I_F = 50 A, dI_F/dt = 500 A/μs, T_J = 25°C	−	256	−	ns
Reverse Recovery Charge	Q_{rr}		−	3140	−	nC
Reverse Recovery Energy	E_{rec}		−	1	−	mJ
Peak Reverse Recovery Current	I_{RRM}		−	24.5	−	A
Reverse Recovery Time	t_{rr}	V_R = 600 V, I_F = 100 A, dI_F/dt = 500 A/μs, T_J = 25°C	−	347	−	ns
Reverse Recovery Charge	Q_{rr}		−	4408	−	nC
Reverse Recovery Energy	E_{rec}		−	2	−	mJ
Peak Reverse Recovery Current	I_{RRM}		−	25.8	−	A
Reverse Recovery Time	t_{rr}	V_R = 600 V, I_F = 50 A, dI_F/dt = 500 A/μs, T_J = 175°C	−	424	−	ns
Reverse Recovery Charge	Q_{rr}		−	8610	−	nC
Reverse Recovery Energy	E_{rec}		−	4	−	mJ
Peak Reverse Recovery Current	I_{RRM}		−	40.8	−	A
Reverse Recovery Time	t_{rr}	V_R = 600 V, I_F = 100 A, dI_F/dt = 500 A/μs, T_J = 175°C	−	572	−	ns
Reverse Recovery Charge	Q_{rr}		−	12476	−	nC
Reverse Recovery Energy	E_{rec}		−	5	−	mJ
Peak Reverse Recovery Current	I_{RRM}		−	43.6	−	A

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

TYPICAL CHARACTERISTICS




Figure 1. Output Characteristics




Figure 2. Output Characteristics




Figure 3. Output Characteristics




Figure 4. Transfer Characteristics




Figure 5. Saturation Voltage Characteristics




Figure 6. Saturation Voltage vs Junction Temperature

TYPICAL CHARACTERISTICS (CONTINUED)




Figure 7. Capacitance Characteristics




Figure 8. Gate Charge Characteristics




Figure 9. SOA Characteristics




Figure 10. Turn−On Time vs Gate Resistance




Figure 11. Turn−Off Time vs Gate Resistance




Figure 12. Switching Loss vs Gate Resistance

TYPICAL CHARACTERISTICS (CONTINUED)




Figure 13. Turn−On Time vs Collector Current




Figure 14. Turn−Off Time vs Collector Current




Figure 15. Switching Loss vs Collector Current




Figure 16. Diode Forward Characteristics




Figure 17. Diode Reverse Recovery Current




Figure 18. Diode Reverse Recovery Time

TYPICAL CHARACTERISTICS (CONTINUED)




Figure 19. Diode Stored Charge Characteristics




Figure 20. Transient Thermal Impedance of IGBT





Figure 21. Transient Thermal Impedance of Diode




TO−247−3LD
CASE 340CD
ISSUE A

DATE 18 SEP 2018

NOTES:

A. THIS PACKAGE DOES NOT CONFORM TO ANY STANDARDS.
B. ALL DIMENSIONS ARE IN MILLIMETERS.
C. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH AND TIE BAR PROTRUSIONS.
D. DIMENSION AND TOLERANCE AS PER ASME Y14.5-2009.



DIM	MILLIMETERS		
	MIN	NOM	MAX
A	4.58	4.70	4.82
A1	2.20	2.40	2.60
A2	1.80	2.00	2.20
D	20.32	20.57	20.82
E	15.37	15.62	15.87
E2	4.12	4.32	4.52
e	~	5.45	~
L	19.90	20.00	20.10
L1	3.69	3.81	3.93
Q	5.34	5.46	5.58
b	1.10	1.20	1.30
b2	2.10	2.24	2.39
b4	2.87	3.04	3.20
c	0.51	0.61	0.71
D1	16.63	16.83	17.03
D2	0.51	0.93	1.35
E1	13.40	13.60	13.80

GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
G = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON13857G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−247−3LD**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.