FW297

Power MOSFET
60V, 58mΩ, 4.5A, Dual N-Channel

ON Semiconductor®


www.onsemi.com

V_{DSS}	R_{DS}(on) Max	I_D Max
60V	58mΩ@ 10V	4.5A
	84mΩ@ 4.5V	
	95mΩ@ 4.0V	

Features

- Low On-Resistance
- 4.0V Drive
- ESD Diode-Protected Gate
- Pb-Free, Halogen Free and RoHS Compliance

Electrical Connection
N-Channel




Specifications


Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Value	Unit
Drain to Source Voltage	V_{DSS}	60	V
Gate to Source Voltage	V_{GSS}	±20	V
Drain Current (DC)	I_D	4.5	A
Drain Current (Pulse) PW ≤ 10μs, duty cycle ≤ 1%	I_{DP}	18	A
Power Dissipation When mounted on ceramic substrate (2000mm^2 × 0.8mm) 1 unit, PW≤10s	P_D	1.8	W
Total Dissipation When mounted on ceramic substrate (2000mm^2 × 0.8mm) , PW≤10s	P_T	2.2	W
Junction Temperature	Tj	150	°C
Storage Temperature	Tstg	−55 to +150	°C

Packing Type : TL



Marking



Thermal Resistance Ratings

Parameter	Symbol	Value	Unit
Junction to Ambient 1 unit, PW≤10s *1	$R_{\theta JA}$	69.4	°C/W
Junction to Ambient 2 units, PW≤10s *1	$R_{\theta JA}$	56.8	

Note: *1 When mounted on ceramic substrate (2000mm^2 × 0.8mm)

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

ORDERING INFORMATION

See detailed ordering and shipping information on page 5 of this data sheet.


© Semiconductor Components Industries, LLC, 2015


Electrical Characteristics at Ta = 25°C


Parameter	Symbol	Conditions	Value			Unit
			min	typ	max	
Drain to Source Breakdown Voltage	$V_{(BR)DSS}$	I_D=1mA, V_{GS}=0V	60			V
Zero-Gate Voltage Drain Current	I_{DSS}	V_{DS}=60V, V_{GS}=0V			1	μA
Gate to Source Leakage Current	I_{GSS}	V_{GS}=±16V, V_{DS}=0V			±10	μA
Gate Threshold Voltage	$V_{GS}(th)$	V_{DS}=10V, I_D=1mA	1.2		2.6	V
Forward Transconductance	g_{FS}	V_{DS}=10V, I_D=4.5A		4.7		S
Static Drain to Source On-State Resistance	$R_{DS}(on)1$	I_D=4.5A, V_{GS}=10V		45	58	mΩ
	$R_{DS}(on)2$	I_D=2A, V_{GS}=4.5V		60	84	mΩ
	$R_{DS}(on)3$	I_D=2A, V_{GS}=4.0V		68	95	mΩ
Input Capacitance	Ciss	V_{DS}=20V, f=1MHz		750		pF
Output Capacitance	Coss			59		pF
Reverse Transfer Capacitance	Crss			47		pF
Turn-ON Delay Time	$t_d(on)$	See specified Test Circuit		7		ns
Rise Time	t_r			16		ns
Turn-OFF Delay Time	$t_d(off)$			50		ns
Fall Time	t_f			30		ns
Total Gate Charge	Qg	V_{DS}=30V, V_{GS}=10V, I_D=4.5A		14		nC
Gate to Source Charge	Qgs			2.3		nC
Gate to Drain “Miller” Charge	Qgd			2.8		nC
Forward Diode Voltage	V_{SD}	I_S=4.5A, V_{GS}=0V		0.81	1.2	V


Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.


Switching Time Test Circuit






ID – VDS
Drain Current, ID – A
Drain to Source Voltage, VDS – V
IT17884
10V
6V
4.5V
4.0V
3.0V
VGS=2.5V



ID – VGS
Drain Current, ID – A
Gate to Source Voltage, VGS – V
IT17885
VDS=10V
Ta=75°C
–25°C
25°C



RDS(on) – VGS
Drain to Source
On State Resistance, RDS(on) – mΩ
Gate to Source Voltage, VGS – V
IT17886
Ta=25°C
4.5A
ID=2A



RDS(on) – Ta
Drain to Source
On State Resistance, RDS(on) –mΩ
Ambient Temperature, Ta – °C
IT17887
ID=2A, VGS=4.0V
ID=2A, VGS=4.5V
ID=4.5A, VGS=10V



gFS– ID
Forward Transconductance, gFS – S
Drain Current, ID – A
IT17888
VDS=10V
Ta= –25°C
75°C
25°C



IS – VSD
Souce Current, IS – A
Forward Diode Voltage, VDS – V
IT17889
VGS=0V
Ta=75°C
25°C
–25°C



S/W Time – ID
Switching Time, S/W Time – ns
Drain Current, ID – A
IT17890
VDD=30V
VGS=10V
td(off)
tf
td(on)
tr



Ciss, Coss, Crss – VDS
Ciss, Coss, Crss – pF
Drain to Source Voltage, VDS – V
IT17891
Ciss
Coss
Crss
f=1MHz


Qg – VGS
VDS=30V
ID=4.5A
Gate to Source Voltage, VGS – V
Total Gate Charge, Qg – nC
IT17892


S O A
IDP=18A (PW≤10μs)
ID=4.5A
100μs
1ms
10ms
100ms
DC operation (PW≤10s)
Operation in this area is limited by RDS(on).
Ta=25°C
Single pulse
When mounted on ceramic substrate(2000mm2×0.8mm), 1 unit
Drain Current, ID – A
Drain to Source Voltage, VDS – V
IT17699


PD – Ta
When mounted on ceramic substrate(2000mm2×0.8mm), PW≤10s
Total Dissipation
1 unit
Power Dissipation, PD – W
Ambient Temperature, Ta – °C
IT17700


PD(FET1) – PD(FET2)
When mounted on ceramic substrate(2000mm2×0.8mm), PW≤10s
Power Dissipation (FET1), PD – W
Power Dissipation (FET2), PD – W
IT17701


RθJA – Pulse Time
Duty Cycle=0.5
0.2
0.1
0.05
0.02
0.01
Single Pulse
When mounted on ceramic substrate(2000mm2×0.8mm), PW≤10s
Thermal Resistance, RθJA – °C/W
Pulse Time, PT – s
IT17893


Package Dimensions

FW297-TL-2W


SOIC-8

CASE 751CR
ISSUE O
Unit : mm

1: Source1
2: Gate1
3: Source2
4: Gate2
5: Drain2
6: Drain2
7: Drain1
8: Drain1



Recommended Soldering Footprint



ORDERING INFORMATION

Device	Package	Shipping	Note
FW297-TL-2W	SOIC8 SC-87, SOT-96	2,500 pcs. / Tape & Reel	Pb-Free and Halogen Free

† For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D. http://www.onsemi.com/pub_link/Collateral/BRD8011-D.PDF

Note on usage : Since the FW297 is a MOSFET product, please avoid using this device in the vicinity of highly charged objects.

ON Semiconductor and the ON logo are registered trademarks of Semiconductor Components Industries, LLC (SCILLC) or its subsidiaries in the United States and/or other countries. SCILLC owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of SCILLC's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. SCILLC reserves the right to make changes without further notice to any products herein. SCILLC makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does SCILLC assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. "Typical" parameters which may be provided in SCILLC data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. SCILLC does not convey any license under its patent rights nor the rights of others. SCILLC products are not designed, intended, or authorized for use as components in systems intended for surgical implant into the body, or other applications intended to support or sustain life, or for any other application in which the failure of the SCILLC product could create a situation where personal injury or death may occur. Should Buyer purchase or use SCILLC products for any such unintended or unauthorized application, Buyer shall indemnify and hold SCILLC and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that SCILLC was negligent regarding the design or manufacture of the part. SCILLC is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.