

ECOSPARK® Ignition IGBT

500 mJ, 360 V, N−Channel Ignition IGBT

ISL9V5036S3ST, ISL9V5036P3-F085, ISL9V5036S3ST-F085C





D²PAK−3
(TO−263, 3−Lead)
CASE 418AJ

TO−220−3LD
CASE 340AT

General Description

The ISL9V5036S3ST, ISL9V5036S3ST−F085C and ISL9V5036P3−F085 are the next generation IGBTs that offer outstanding SCIS capability in the D^2−Pak (TO−263) and TO−220 plastic package. These devices are intended for use in automotive ignition circuits, specifically as coil drivers. Internal diodes provide voltage clamping without the need for external components.

ECOSPARK devices can be custom made to specific clamp voltages. Contact your nearest **onsemi** sales office for more information.

Formerly Developmental Type 49443.


Features

- Industry Standard D^2−Pak package
- SCIS Energy = 500 mJ at T_J = 25°C
- Logic Level Gate Drive
- AEC−Q101 Qualified and PPAP Capable
- These Devices are Pb−Free and are RoHS Compliant

Applications

- Automotive Ignition Coil Driver Circuits
- Coil−On Plug Applications

MARKING DIAGRAM



A	= Assembly Location
Y	= Year
WW	= Work Week
XXXX	= Device Code
ZZ	= Assembly Lot Number
G	= Pb−Free Package

ORDERING INFORMATION

See detailed ordering and shipping information on page 8 of this data sheet.

NOTE: Some of the devices on this data sheet have been **DISCONTINUED**. Please refer to the table on page 8.

© Semiconductor Components Industries, LLC, 2009

MAXIMUM RATINGS (T_A = 25°C unless otherwise noted)

Parameter	Symbol	Value	Unit
Collector to Emitter Breakdown Voltage (I_C = 1 mA)	BV_{CER}	390	V
Emitter to Collector Voltage − Reverse Battery Condition (I_C = 10 mA)	BV_{ECS}	24	V
At Starting T_J = 25°C, I_{SCIS} = 38.5A, L = 670 μHy	E_{SCIS25}	500	mJ
At Starting T_J = 150°C, I_{SCIS} = 30A, L = 670 μHy	$E_{SCIS150}$	300	mJ
Collector Current Continuous, at T_C = 25°C, See Figure 9	I_{C25}	46	A
Collector Current Continuous, at T_C = 110°C, See Figure 9	I_{C110}	31	A
Gate to Emitter Voltage Continuous	V_{GEM}	±10	V
Power Dissipation Total T_C = 25°C	P_D	250	W
Power Dissipation Derating T_C > 25°C		1.67	W/°C
Operating Junction Temperature Range	T_J	−40 to 175	°C
Storage Junction Temperature Range	T_{STG}	−40 to 175	°C
Max Lead Temp for Soldering (Leads at 1.6 mm from Case for 10 s)	T_L	300	°C
Max Lead Temp for Soldering (Package Body for 10s)	T_{pkg}	260	°C
Electrostatic Discharge Voltage at100 pF, 1500 Ω	ESD	4	kV

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

THERMAL CHARACTERISTICS

Characteristic	Symbol	Value	Unit
Thermal Resistance Junction−Case	$R_{\theta JC}$	0.6	°C/W

Share Feedback
Your Opinion Matters

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
OFF STATE CHARACTERISTICS							
Collector to Emitter Breakdown Voltage	BV_{CER}	I_C = 2 mA, V_{GE} = 0 V, R_G = 1 kΩ, See Figure 15 T_J = −40 to 150°C		330	360	390	V
Collector to Emitter Breakdown Voltage	BV_{CES}	I_C = 10 mA, V_{GE} = 0 V, R_G = 0, See Figure 15 T_J = −40 to 150°C		360	390	420	V
Emitter to Collector Breakdown Voltage	BV_{ECS}	I_C = −75 mA, V_{GE} = 0 V, T_J = 25°C		30	−	−	V
Gate to Emitter Breakdown Voltage	BV_{GES}	I_{GES} = ±2 mA		±12	±14	−	V
Collector to Emitter Leakage Current	I_{CER}	V_{CER} = 250 V, R_G = 1 kΩ, See Figure 11	T_C = 25°C	−	−	25	μA
			T_C = 150°C	−	−	1	mA
Emitter to Collector Leakage Current	I_{ECS}	V_{EC} = 24 V, See Figure 11	T_C = 25°C	−	−	1	mA
			T_C = 150°C	−	−	40	
Series Gate Resistance	R_1			−	75	−	Ω
Gate to Emitter Resistance	R_2			10	−	30	kΩ
ON STATE CHARACTERISTICS							
Collector to Emitter Saturation Voltage	$V_{CE(SAT)}$	I_C = 10 A, V_{GE} = 4.0 V	T_C = 25°C See Figure 4	−	1.17	1.60	V
Collector to Emitter Saturation Voltage	$V_{CE(SAT)}$	I_C = 15 A, V_{GE} = 4.5 V	T_C = 150°C	−	1.50	1.80	V
DYNAMIC CHARACTERISTICS							
Gate Charge	$Q_{G(ON)}$	I_C = 10 A, V_{CE} = 12 V, V_{GE} = 5 V, See Figure 14		−	32	−	nC
Gate to Emitter Threshold Voltage	$V_{GE(TH)}$	I_{CE} = 1.0 mA, V_{CE} = V_{GE}, See Figure 10	T_C = 25°C	1.3	−	2.2	V
			T_C = 150°C	0.75	−	1.8	
Gate to Emitter Plateau Voltage	V_{GEP}	I_C = 10 A, V_{CE} = 12 V		−	3.0	−	V
SWITCHING CHARACTERISTICS							
Current Turn−On Delay Time−Resistive	$t_{d(ON)R}$	V_{CE} = 14 V, R_L = 1 Ω V_{GE} = 5 V, R_G = 1 kΩ T_J = 25°C, See Figure 12		−	0.7	4	μs
Current Rise Time−Resistive	t_{rR}			−	2.1	7	
Current Turn−Off Delay Time−Inductive	$t_{d(OFF)L}$	V_{CE} = 300 V, L = 2 mH, V_{GE} = 5 V, R_G = 1 kΩ T_J = 25°C, See Figure 12		−	10.8	15	
Current Fall Time−Inductive	t_{fL}			−	2.8	15	
Self Clamped Inductive Switching	SCIS	T_J = 25°C, L = 670 μH, R_G = 1 kΩ, V_{GE} = 5 V, See Figures 1, 2		−	−	500	mJ

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS




Figure 1. Self Clamped Inductive Switching Current vs. Time in Clamp




Figure 2. Self Clamped Inductive Switching Current vs. Inductance




Figure 3. Collector to Emitter On−State Voltage vs. Junction Temperature




Figure 4. Collector to Emitter On−State Voltage vs. Junction Temperature




Figure 5. Collector Current vs. Collector to Emitter On−State Voltage




Figure 6. Collector Current vs. Collector to Emitter On−State Voltage

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS (continued)




Figure 7. Collector to Emitter On−State Voltage vs. Collector Current




Figure 8. Transfer Characteristics




Figure 9. DC Collector Current vs. Case Temperature




Figure 10. Threshold Voltage vs. Junction Temperature




Figure 11. Leakage Current vs. Junction Temperature




Figure 12. Switching Time vs. Junction Temperature

Share Feedback
Your Opinion Matters

TYPICAL CHARACTERISTICS (continued)




Figure 13. Capacitance vs. Collector to Emitter Voltage




Figure 14. Gate Charge




Figure 15. Breakdown Voltage vs. Series Gate Resistance




Figure 16. IGBT Normalized Transient Thermal Impedance, Junction to Case

Share Feedback
Your Opinion Matters

TEST CIRCUITS AND WAVEFORMS




Figure 17. Inductive Switching Test Circuit




Figure 18. t_{ON} and t_{OFF} Switching Test Circuit




Figure 19. Energy Test Circuit




Figure 20. Energy Waveforms

Share Feedback
Your Opinion Matters

SPICE THERMAL MODEL

ISL9V5036S3ST / ISL9V5036P3−F085 / ISL9V5036 S3ST−F085C


```
CTHERM1 th 6 4.0e2
CTHERM2 6 5 3.6e-3
CTHERM3 5 4 4.9e-2
CTHERM4 4 3 3.2e-1
CTHERM5 3 2 3.0e-1
CTHERM6 2 tl 1.6e-2

RTHERM1 th 6 1.0e-2
RTHERM2 6 5 1.4e-1
RTHERM3 5 4 1.0e-1
RTHERM4 4 3 9.0e-2
RTHERM5 3 2 9.4e-2
RTHERM6 2 tl 1.9e-2
```

SABER THERMAL MODEL

SABER thermal model
ISL9V5036S3ST / ISL9V5036P3−F085 / ISL9V5036 S3ST−F085C

```
template thermal_model th tl
thermal_c th, tl
{
ctherm.ctherm1 th 6 = 4.0e2
ctherm.ctherm2 6 5 = 3.6e-3
ctherm.ctherm3 5 4 = 4.9e-2
ctherm.ctherm4 4 3 = 3.2e-1
ctherm.ctherm5 3 2 = 3.0e−1
ctherm.ctherm6 2 tl = 1.6e-2
rtherm.rtherm1 th 6 = 1.0e-2
rtherm.rtherm2 6 5 = 1.4e-1
rtherm.rtherm3 5 4 = 1.0e-1
rtherm.rtherm4 4 3 = 9.0e-2
rtherm.rtherm5 3 2 = 9.4e-2
rtherm.rtherm6 2 tl = 1.9e-2
}
```



PACKAGE MARKING AND ORDERING INFORMATION

Device	Device Marking	Package	Shipping†
ISL9V5036S3ST	V5036S	D2PAK−3 (TO−263, 3−Lead) (Pb−Free)	800 / Tape & Reel
ISL9V5036P3−F085	V5036P	TO−220−3LD (Pb−Free)	50 Units / Tube

DISCONTINUED (Note 1)


ISL9V5036S3ST−F085C	V5036SC	D2PAK−3 (TO−263, 3−Lead) (Pb−Free)	800 / Tape & Reel

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

1. **DISCONTINUED:** This device is not recommended for new design. Please contact your **onsemi** representative for information. The most current information on this device may be available on www.onsemi.com.

ECOSPARK is a registered trademark of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries.


Share Feedback
Your Opinion Matters





TO−220−3LD
CASE 340AT
ISSUE B

DATE 08 AUG 2022

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	4.00	--	4.70
A1	SEE NOTE "F"		
A2	2.10	--	2.85
b	0.55	--	1.00
b2	1.10	--	1.62
b4	1.42	--	1.62
c	0.36	--	0.60
D	13.90	--	16.30
D1	8.13	--	9.40
D2	11.50	--	14.30
D3	15.42	--	16.51
E	9.65	--	10.67
E1	7.59	--	8.65
e	2.40	--	2.67
H1	6.06	--	6.69
L	12.70	--	14.04
L1	2.70	--	4.10
P	3.50	--	4.00
Q	2.50	--	3.40
z	2.13 REF		
z1	2.06 REF		
Θ	3°	–	5°







GENERIC MARKING DIAGRAM*



XXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Assembly Lot Code

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “▪”, may or may not be present. Some products may not follow the Generic Marking.

NOTES:
A) REFERENCE JEDEC, TO-220, VARIATION AB
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONS COMMON TO ALL PACKAGE SUPPLIERS EXCEPT WHERE NOTED [ ].
D) LOCATION OF MOLDED FEATURE MAY VARY (LOWER LEFT CORNER, LOWER CENTER AND CENTER OF THE PACKAGE)
E) DOES NOT COMPLY JEDEC STANDARD VALUE.
F) "A1" DIMENSIONS AS BELOW:
SINGLE GAUGE = 0.51 - 0.61
DUAL GAUGE = 1.10 - 1.45
G) PRESENCE IS SUPPLIER DEPENDENT
H) SUPPLIER DEPENDENT MOLD LOCKING HOLES IN HEATSINK.


DOCUMENT NUMBER:	**98AON13818G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**TO−220−3LD**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.


© Semiconductor Components Industries, LLC, 2019

D²PAK–3 (TO–263, 3–LEAD)
CASE 418AJ
ISSUE F

DATE 11 MAR 2021



SCALE 1:1




RECOMMENDED
MOUNTING FOOTPRINT


* For additional information on our Pb–Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.


NOTES:

1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: INCHES
3. CHAMFER OPTIONAL.
4. DIMENSIONS D AND E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.005 PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY AT DATUM H.
5. THERMAL PAD CONTOUR IS OPTIONAL WITHIN DIMENSIONS E, L1, D1, AND E1.
6. OPTIONAL MOLD FEATURE.
7. ①, ② … OPTIONAL CONSTRUCTION FEATURE CALL OUTS.


	INCHES		MILLIMETERS	
DIM	MIN.	MAX.	MIN.	MAX.
A	0.160	0.190	4.06	4.83
A1	0.000	0.010	0.00	0.25
b	0.020	0.039	0.51	0.99
c	0.012	0.029	0.30	0.74
c2	0.045	0.065	1.14	1.65
D	0.330	0.380	8.38	9.65
D1	0.260	---	6.60	---
E	0.380	0.420	9.65	10.67
E1	0.245	---	6.22	---
e	0.100 BSC		2.54 BSC	
H	0.575	0.625	14.60	15.88
L	0.070	0.110	1.78	2.79
L1	---	0.066	---	1.68
L2	---	0.070	---	1.78
L3	0.010 BSC		0.25 BSC	
M	0°	8°	0°	8°








DETAIL C
TIP LEADFORM
ROTATED 90° CW



VIEW A–A

VIEW A–A
OPTIONAL CONSTRUCTIONS

GENERIC MARKING DIAGRAMS*



IC **Standard** **Rectifier** **SSG**

XXXXXX = Specific Device Code
A = Assembly Location
WL = Wafer Lot
Y = Year
WW = Work Week
W = Week Code (SSG)
M = Month Code (SSG)
G = Pb–Free Package
AKA = Polarity Indicator

*This information is generic. Please refer to device data sheet for actual part marking. Pb–Free indicator, “G” or microdot “ ▪”, may or may not be present. Some products may not follow the Generic Marking.

DOCUMENT NUMBER:	**98AON56370E**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red.
DESCRIPTION:	**D²PAK–3 (TO–263, 3–LEAD)**	**PAGE 1 OF 1**

onsemi and ONSEMI are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

© Semiconductor Components Industries, LLC, 2011

onsemi, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at www.onsemi.com/support/sales

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.