

# Silicon Carbide (SiC) MOSFET – EliteSiC, 20 mohm, 900 V, M2, TO-247-4L

# NTH4L020N090SC1

| $V_{(BR)DSS}$ | $R_{DS(ON)}$ MAX | $I_D$ MAX |
|---|---|---|
| 900 V | 28 mΩ @ 15 V | 118 A |




**N−CHANNEL MOSFET**




**TO−247−4L**
**CASE 340CJ**

### Features

- Typ. $R_{DS(on)}$ = 20 mΩ @ $V_{GS}$ = 15 V
  Typ. $R_{DS(on)}$ = 16 mΩ @ $V_{GS}$ = 18 V
- Ultra Low Gate Charge ($Q_{G(tot)}$ = 196 nC)
- Low Effective Output Capacitance ($C_{oss}$ = 296 pF)
- 100% UIL Tested
- This Device is Halide Free and RoHS Compliant with exemption 7a, Pb−Free 2LI (on second level interconnection)

### Typical Applications

- UPS
- DC-DC Converter
- Boost Inverter


### MAXIMUM RATINGS ($T_J$ = 25°C unless otherwise noted)

| Parameter | | | Symbol | Value | Unit |
|---|---|---|---|---|---|
| Drain−to−Source Voltage | | | $V_{DSS}$ | 900 | V |
| Gate−to−Source Voltage | | | $V_{GS}$ | +22/−8 | V |
| Recommended Operation Values of Gate−Source Voltage | | $T_C$ < 175°C | $V_{GSop}$ | +15/−5 | V |
| Continuous Drain Current $R_{\theta JC}$ | Steady State | $T_C$ = 25°C | $I_{DC}$ | 116 | A |
| Power Dissipation $R_{\theta JC}$ | Steady State | $T_C$ = 25°C | $P_{DC}$ | 484 | W |
| Continuous Drain Current $R_{\theta JC}$ | Steady State | $T_C$ = 100°C | $I_{DC}$ | 82 | A |
| Power Dissipation $R_{\theta JC}$ | Steady State | $T_C$ = 100°C | $P_{DC}$ | 242 | W |
| Pulsed Drain Current (Note 2) | | $T_A$ = 25°C | $I_{DM}$ | 504 | A |
| Operating Junction and Storage Temperature Range | | | $T_J$, $T_{stg}$ | −55 to +175 | °C |
| Source Current (Body Diode) | | | $I_S$ | 106 | A |
| Single Pulse Drain−to−Source Avalanche Energy ($I_L$ = 23 $A_{pk}$, L = 1 mH) (Note 3) | | | $E_{AS}$ | 264 | mJ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.
2. Repetitive rating, limited by max junction temperature.
3. $E_{AS}$ of 162 mJ is based on starting $T_J$ = 25°C; L = 1 mH, $I_{AS}$ = 23 A, $V_{DD}$ = 100 V, $V_{GS}$ = 15 V.

### MARKING DIAGRAM




| | |
|---|---|
| H4L020090SC1 | = Specific Device Code |
| &Z | = Assembly Plant Code |
| &3 | = Date Code (Year & Week) |
| &K | = Lot |
| $Y | = **onsemi** Logo |

### ORDERING INFORMATION

See detailed ordering and shipping information on page 6 of this data sheet.

© Semiconductor Components Industries, LLC, 2019

**Table 1. THERMAL CHARACTERISTICS**

| Parameter | Symbol | Max | Unit |
|---|---|---|---|
| Thermal Resistance Junction−to−Case (Note 1) | $R_{\theta JC}$ | 0.31 | °C/W |
| Thermal Resistance Junction−to−Ambient (Note 1) | $R_{\theta JA}$ | 40 | °C/W |

**Table 2. ELECTRICAL CHARACTERISTICS** ($T_J$ = 25°C unless otherwise stated)

| Parameter | Symbol | Test Condition | | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|---|
| **OFF CHARACTERISTICS** | | | | | | | |
| Drain−to−Source Breakdown Voltage | $V_{(BR)DSS}$ | $V_{GS}$ = 0 V, $I_D$ = 1 mA | | 900 | | | V |
| Drain−to−Source Breakdown Voltage Temperature Coefficient | $V_{(BR)DSS}/T_J$ | $I_D$ = 1 mA, refer to 25°C | | | 500 | | mV/°C |
| Zero Gate Voltage Drain Current | $I_{DSS}$ | $V_{GS}$ = 0 V, $V_{DS}$ = 900 V | $T_J$ = 25°C | | | 100 | μA |
| | | | $T_J$ = 175°C | | | 250 | μA |
| Gate−to−Source Leakage Current | $I_{GSS}$ | $V_{GS}$ = +22/−8 V, $V_{DS}$ = 0 V | | | | ±1 | μA |
| **ON CHARACTERISTICS** | | | | | | | |
| Gate Threshold Voltage | $V_{GS(TH)}$ | $V_{GS}$ = $V_{DS}$ , $I_D$ = 20 mA | | 1.8 | 2.7 | 4.3 | V |
| Recommended Gate Voltage | $V_{GOP}$ | | | −5 | | +15 | V |
| Drain−to−Source On Resistance | $R_{DS(on)}$ | $V_{GS}$ = 15 V, $I_D$ = 60 A, $T_J$ = 25°C | | | 20 | 28 | mΩ |
| | | $V_{GS}$ = 18 V, $I_D$ = 60 A, $T_J$ = 25°C | | | 16 | | |
| | | $V_{GS}$ = 15 V, $I_D$ = 60 A, $T_J$ = 175°C | | | 27 | | |
| Forward Transconductance | $g_{FS}$ | $V_{DS}$ = 20 V, $I_D$ = 60 A | | | 49 | | S |
| **CHARGES, CAPACITANCES & GATE RESISTANCE** | | | | | | | |
| Input Capacitance | $C_{ISS}$ | $V_{GS}$ = 0 V, f = 1 MHz, $V_{DS}$ = 450 V | | | 4415 | | pF |
| Output Capacitance | $C_{OSS}$ | | | | 296 | | |
| Reverse Transfer Capacitance | $C_{RSS}$ | | | | 24 | | |
| Total Gate Charge | $Q_{G(TOT)}$ | $V_{GS}$ = −5/15 V, $V_{DS}$ = 720 V, $I_D$ = 60 A | | | 196 | | nC |
| Threshold Gate Charge | $Q_{G(TH)}$ | | | | 42 | | |
| Gate−to−Source Charge | $Q_{GS}$ | | | | 78 | | |
| Gate−to−Drain Charge | $Q_{GD}$ | | | | 55 | | |
| Gate−Resistance | $R_G$ | f = 1 MHz | | | 1.6 | | Ω |
| **SWITCHING CHARACTERISTICS** | | | | | | | |
| Turn−On Delay Time | $t_{d(ON)}$ | $V_{GS}$ = −5/15 V, $V_{DS}$ = 720 V, $I_D$ = 60 A, $R_G$ = 2.5 Ω, Inductive Load | | | 29 | | ns |
| Rise Time | $t_r$ | | | | 28 | | |
| Turn−Off Delay Time | $t_{d(OFF)}$ | | | | 54 | | |
| Fall Time | $t_f$ | | | | 14 | | |
| Turn−On Switching Loss | $E_{ON}$ | | | | 611 | | μJ |
| Turn−Off Switching Loss | $E_{OFF}$ | | | | 293 | | |
| Total Switching Loss | $E_{TOT}$ | | | | 904 | | |
| **DRAIN−SOURCE DIODE CHARACTERISTICS** | | | | | | | |
| Continuous Drain−Source Diode Forward Current | $I_{SD}$ | $V_{GS}$ = −5 V, $T_J$ = 25°C | | | | 106 | A |
| Pulsed Drain−Source Diode Forward Current (Note 2) | $I_{SDM}$ | $V_{GS}$ = −5 V, $T_J$ = 25°C | | | | 504 | A |
| Forward Diode Voltage | $V_{SD}$ | $V_{GS}$ = −5 V, $I_{SD}$ = 30 A, $T_J$ = 25°C | | | 3.8 | | V |

**Table 2. ELECTRICAL CHARACTERISTICS** ($T_J$ = 25°C unless otherwise stated) (continued)

| Parameter | Symbol | Test Condition | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| **DRAIN−SOURCE DIODE CHARACTERISTICS** | | | | | | |
| Reverse Recovery Time | $t_{RR}$ | $V_{GS}$ = −5/15 V, $I_{SD}$ = 60 A, $dI_S/dt$ = 1000 A/μs, $V_{DS}$ = 720 V | | 30 | | ns |
| Reverse Recovery Charge | $Q_{RR}$ | | | 244 | | nC |
| Reverse Recovery Energy | $E_{REC}$ | | | 11 | | μJ |
| Peak Reverse Recovery Current | $I_{RRM}$ | | | 16 | | A |
| Charge Time | Ta | | | 17 | | ns |
| Discharge Time | Tb | | | 13 | | ns |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

## TYPICAL CHARACTERISTICS





**Figure 1. On−Region Characteristics**





**Figure 2. Normalized On−Resistance vs. Drain Current and Gate Voltage**





**Figure 3. On−Resistance Variation with Temperature**





**Figure 4. On−Resistance vs. Gate−to−Source Voltage**





**Figure 5. Transfer Characteristics**





**Figure 6. Diode Forward Voltage vs. Current**

## TYPICAL CHARACTERISTICS (continued)





**Figure 7. Gate−to−Source Voltage vs. Total Charge**





**Figure 8. Capacitance vs. Drain−to−Source Voltage**





**Figure 9. Unclamped Inductive Switching Capability**





**Figure 10. Maximum Continuous Drain Current vs. Case Temperature**





**Figure 11. Safe Operating Area**





**Figure 12. Single Pulse Maximum Power Dissipation**

## TYPICAL CHARACTERISTICS (continued)






**Figure 13. Junction−to−Ambient Transient Thermal Response Curve**

## PACKAGE MARKING AND ORDERING INFORMATION

| Part Number | Top Marking | Package | Packing Method | Quantity |
|---|---|---|---|---|
| NTH4L020N090SC1 | H4L020090SC1 | TO−247−4L | Tube | 30 Units |

**TO−247−4LD**
CASE 340CJ
ISSUE A

DATE 16 SEP 2019




NOTES:

A. NO INDUSTRY STANDARD APPLIES TO THIS PACKAGE.
B. DIMENSIONS ARE EXCLUSIVE OF BURRS,MOLD FLASH,AND TIE BAR EXTRUSIONS.
C. ALL DIMENSIONS ARE IN MILLIMETERS.
D. DRAWING CONFORMS TO ASME Y14.5-2009.

| DIM | MILLIMETERS | | |
|---|---|---|---|
| | MIN | NOM | MAX |
| A | 4.80 | 5.00 | 5.20 |
| A1 | 2.10 | 2.40 | 2.70 |
| A2 | 1.80 | 2.00 | 2.20 |
| b | 1.07 | 1.20 | 1.33 |
| b1 | 1.20 | 1.40 | 1.60 |
| b2 | 2.02 | 2.22 | 2.42 |
| c | 0.50 | 0.60 | 0.70 |
| D | 22.34 | 22.54 | 22.74 |
| D1 | 16.00 | 16.25 | 16.50 |
| D2 | 0.97 | 1.17 | 1.37 |
| e | 2.54 BSC | | |
| e1 | 5.08 BSC | | |
| E | 15.40 | 15.60 | 15.80 |
| E1 | 12.80 | 13.00 | 13.20 |
| E/2 | 4.80 | 5.00 | 5.20 |
| L | 18.22 | 18.42 | 18.62 |
| L1 | 2.42 | 2.62 | 2.82 |
| p | 3.40 | 3.60 | 3.80 |
| p1 | 6.60 | 6.80 | 7.00 |
| Q | 5.97 | 6.17 | 6.37 |
| S | 5.97 | 6.17 | 6.37 |

| | | |
|---|---|---|
| **DOCUMENT NUMBER:** | **98AON13852G** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| **DESCRIPTION:** | **TO−247−4LD** | **PAGE 1 OF 1** |

**onsemi** and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

**onsemi**, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

**TECHNICAL PUBLICATIONS**:
**Technical Library:** www.onsemi.com/design/resources/technical−documentation
**onsemi Website:** www.onsemi.com

**ONLINE SUPPORT**: www.onsemi.com/support
**For additional information, please contact your local Sales Representative at** www.onsemi.com/support/sales

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

# Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

### Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

**www.entegreci.com**

### Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

**Kategorilere göz atın**

### Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

**Üreticileri görün**

### Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

**Teklif isteyin**

**www.entegreci.com** | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.