# Silicon Carbide (SiC) MOSFET - EliteSiC, 32 mohm, 650 V, M3S, TO-247-3L

# NTHL032N065M3S

| $V_{(BR)DSS}$ | $R_{DS(ON)}$ TYP | $I_D$ MAX |
|---|---|---|
| 650 V | 32 mΩ @ $V_{GS}$ = 18 V | 51 A |

### Features

- Typical $R_{DS(on)}$ = 32 mΩ @ $V_{GS}$ = 18 V
- Ultra Low Gate Charge ($Q_{G(tot)}$ = 55 nC)
- High Speed Switching with Low Capacitance ($C_{oss}$ = 114 pF)
- 100% Avalanche Tested
- This Device is Halide Free and RoHS Compliant with Exemption 7a, Pb-Free 2LI (on second level interconnection)

### Applications

- SMPS, Solar Inverters, UPS, Energy Storages, EV Charging Infrastructure


### MAXIMUM RATINGS ($T_J$ = 25 °C unless otherwise noted)


| Parameter | | Symbol | Value | Unit |
|---|---|---|---|---|
| Drain-to-Source Voltage | | $V_{DSS}$ | 650 | V |
| Gate-to-Source Voltage | | $V_{GS}$ | −10/ +22.6 | V |
| Continuous Drain Current | $T_C$ = 25 °C | $I_D$ | 51 | A |
| Power Dissipation | | $P_D$ | 200 | W |
| Continuous Drain Current (Note 1) | $T_C$ = 100 °C | $I_D$ | 27 | A |
| Power Dissipation | | $P_D$ | 100 | W |
| Pulsed Drain Current (Note 2) | $T_C$ = 25 °C, $t_p$ = 100 μs | $I_{DM}$ | 157 | A |
| Continuous Source-Drain Current | $T_C$ = 25 °C, $V_{GS}$ = −3 V | $I_S$ | 30 | A |
| | $T_C$ = 100 °C, $V_{GS}$ = −3 V | | 17 | |
| Pulsed Source-Drain Current (Body Diode) (Note 2) | $T_C$ = 100 °C, $V_{GS}$ = −3 V, $t_p$ = 100 μs | $I_{SM}$ | 132 | A |
| Single Pulse Avalanche Energy (Note 3) | $I_{LPK}$ = 16.7 A, L = 1 mH | $E_{AS}$ | 139 | mJ |
| Operating Junction and Storage Temperature Range | | $T_J$, $T_{stg}$ | −55 to +175 | °C |
| Lead Temperature for Soldering Purposes (1/8″ from case for 10 seconds) | | $T_L$ | 270 | °C |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. 27 A is limited by package. Power chip max drain current is 36 A if limited by max junction temperature.
2. Single pulse, limited by max junction temperature.
3. $E_{AS}$ of 139 mJ is based on starting $T_J$ = 25 °C, L = 1 mH, $I_{AS}$ = 16.7 A, $V_{DD}$ = 100 V, $V_{GS}$ = 18 V


### N-CHANNEL MOSFET



**TO-247-3LD**
**CASE 340CX**

### MARKING DIAGRAM




HL032N065M3S = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
ZZ = Lot Traceability

### ORDERING INFORMATION

| Device | Package | Shipping |
|---|---|---|
| NTHL032N065M3S | TO-247-3L | 30 Units / Tube |

© Semiconductor Components Industries, LLC, 2024

## THERMAL CHARACTERISTICS

| Parameter | Symbol | Value | Unit |
|---|---|---|---|
| Thermal Resistance, Junction-to-Case (Note 4) | $R_{\theta JC}$ | 0.75 | °C/W |
| Thermal Resistance, Junction-to-Ambient (Note 4) | $R_{\theta JA}$ | 40 | |

4. The entire application environment impacts the thermal resistance values shown, they are not constants and are only valid for the particular conditions noted.

## RECOMMENDED OPERATING CONDITIONS

| Parameter | Symbol | Value | Unit |
|---|---|---|---|
| Operation Values of Gate-to-Source Voltage | $V_{GSop}$ | −5...−3<br>+18 | V |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

## ELECTRICAL CHARACTERISTICS ($T_J$ = 25 °C unless otherwise specified)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| **OFF CHARACTERISTICS** | | | | | | |
| Drain-to-Source Breakdown Voltage | $V_{(BR)DSS}$ | $V_{GS}$ = 0 V, $I_D$ = 1 mA, $T_J$ = 25 °C | 650 | – | – | V |
| Drain-to-Source Breakdown Voltage Temperature Coefficient | $\Delta V_{(BR)DSS}/\Delta T_J$ | $I_D$ = 1 mA, Referenced to 25 °C | – | 90 | – | mV/°C |
| Zero Gate Voltage Drain Current | $I_{DSS}$ | $V_{DS}$ = 650 V, $T_J$ = 25 °C | – | – | 10 | μA |
| | | $V_{DS}$ = 650 V, $T_J$ = 175 °C (Note 6) | – | – | 500 | μA |
| Gate-to-Source Leakage Current | $I_{GSS}$ | $V_{GS}$ = −10 V, $V_{DS}$ = 0 V | −1 | – | – | μA |
| | | $V_{GS}$ = +22.6 V, $V_{DS}$ = 0 V | – | – | 1 | |
| **ON CHARACTERISTICS** | | | | | | |
| Drain-to-Source On Resistance | $R_{DS(on)}$ | $V_{GS}$ = 18 V, $I_D$ = 15 A, $T_J$ = 25 °C | – | 32 | 44 | mΩ |
| | | $V_{GS}$ = 18 V, $I_D$ = 15 A, $T_J$ = 175 °C (Note 6) | – | 49 | – | |
| | | $V_{GS}$ = 15 V, $I_D$ = 15 A, $T_J$ = 25 °C | – | 41 | – | |
| | | $V_{GS}$ = 15 V, $I_D$ = 15 A, $T_J$ = 175 °C (Note 6) | – | 52 | – | |
| Gate Threshold Voltage | $V_{GS(TH)}$ | $V_{GS}$ = $V_{DS}$, $I_D$ = 7.5 mA, $T_J$ = 25 °C | 2 | 2.7 | 4 | V |
| Forward Transconductance | $g_{FS}$ | $V_{DS}$ = 10 V, $I_D$ = 15 A (Note 6) | – | 9.9 | – | S |
| **CHARGES, CAPACITANCES & GATE RESISTANCE** | | | | | | |
| Input Capacitance | $C_{ISS}$ | $V_{DS}$ = 400 V, $V_{GS}$ = 0 V, f = 1 MHz (Note 6) | – | 1410 | – | pF |
| Output Capacitance | $C_{OSS}$ | | – | 114 | – | |
| Reverse Transfer Capacitance | $C_{RSS}$ | | – | 9.6 | – | |
| Total Gate Charge | $Q_{G(TOT)}$ | $V_{DD}$ = 400 V, $I_D$ = 15 A, $V_{GS}$ = −3/18 V (Note 6) | – | 55 | – | nC |
| Gate-to-Source Charge | $Q_{GS}$ | | – | 15 | – | |
| Gate-to-Drain Charge | $Q_{GD}$ | | – | 14 | – | |
| Gate Resistance | $R_G$ | f = 1 MHz | – | 5.0 | – | Ω |
| **SWITCHING CHARACTERISTICS** | | | | | | |
| Turn-On Delay Time | $t_{d(ON)}$ | $V_{GS}$ = −3/18 V, $V_{DD}$ = 400 V, $I_D$ = 15 A, $R_G$ = 4.7 Ω, $T_J$ = 25 °C (Notes 5 and 6) | – | 10 | – | ns |
| Turn-Off Delay Time | $t_{d(OFF)}$ | | – | 30 | – | |
| Rise Time | $t_r$ | | – | 24 | – | |
| Fall Time | $t_f$ | | – | 8.8 | – | |
| Turn-On Switching Loss | $E_{ON}$ | | – | 107 | – | μJ |
| Turn-Off Switching Loss | $E_{OFF}$ | | – | 21 | – | |
| Total Switching Loss | $E_{TOT}$ | | – | 128 | – | |



Share Feedback
Your Opinion Matters

**ELECTRICAL CHARACTERISTICS** ($T_J$ = 25 °C unless otherwise specified) (continued)

| Parameter | Symbol | Test Conditions | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| **SWITCHING CHARACTERISTICS** | | | | | | |
| Turn-On Delay Time | $t_{d(ON)}$ | $V_{GS}$ = −3/18 V, $V_{DD}$ = 400 V, $I_D$ = 15 A, $R_G$ = 4.7 Ω, $T_J$ = 175 °C (Notes 5 and 6) | – | 8.8 | – | ns |
| Turn-Off Delay Time | $t_{d(OFF)}$ | | – | 33 | – | |
| Rise Time | $t_r$ | | – | 23 | – | |
| Fall Time | $t_f$ | | – | 10 | – | |
| Turn-On Switching Loss | $E_{ON}$ | | – | 113 | – | μJ |
| Turn-Off Switching Loss | $E_{OFF}$ | | – | 31 | – | |
| Total Switching Loss | $E_{TOT}$ | | – | 144 | – | |
| **SOURCE-TO-DRAIN DIODE CHARACTERISTICS** | | | | | | |
| Forward Diode Voltage | $V_{SD}$ | $I_{SD}$ = 15 A, $V_{GS}$ = −3 V, $T_J$ = 25 °C | – | 4.5 | 6.0 | V |
| | | $I_{SD}$ = 15 A, $V_{GS}$ = −3 V, $T_J$ = 175 °C (Note 6) | – | 4.2 | – | |
| Reverse Recovery Time | $t_{RR}$ | $V_{GS}$ = −3 V, $I_S$ = 15 A, dI/dt = 1000 A/μs, $V_{DS}$ = 400 V, $T_J$ = 25 °C (Note 6) | – | 15.4 | – | ns |
| Charge Time | $t_a$ | | – | 8.7 | – | |
| Discharge Time | $t_b$ | | – | 6.7 | – | |
| Reverse Recovery Charge | $Q_{RR}$ | | – | 67 | – | nC |
| Reverse Recovery Energy | $E_{REC}$ | | – | 3.6 | – | μJ |
| Peak Reverse Recovery Current | $I_{RRM}$ | | – | 8.6 | – | A |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

5. EON/EOFF result is with body diode.
6. Defined by design, not subject to production test.



Share Feedback
Your Opinion Matters

## TYPICAL CHARACTERISTICS





**Figure 1. Output Characteristics**





**Figure 2. Output Characteristics**





**Figure 3. Transfer Characteristics**





**Figure 4. On-Resistance vs Gate Voltage**





**Figure 5. On-Resistance vs Drain Current**





**Figure 6. On-Resistance vs Junction Temperature**



Share Feedback
Your Opinion Matters

## TYPICAL CHARACTERISTICS





**Figure 7. Capacitance Characteristics**





**Figure 8. Stored Energy vs Drain to Source Voltage**





**Figure 9. Gate Charge Characteristics**





**Figure 10. Reverse Conduction Characteristics**





**Figure 11. Reverse Conduction Characteristics**





**Figure 12. Safe Operating Area**



Share Feedback
Your Opinion Matters

## TYPICAL CHARACTERISTICS





**Figure 13. Avalanche Current vs Pulse Time (UIS)**





**Figure 14. Maximum Power Dissipation vs. Case Temperature**





**Figure 15. Inductive Switching Loss vs Collector Current**





**Figure 16. Inductive Switching Loss vs Collector Current**





**Figure 17. Inductive Switching Loss vs Drain Voltage**





**Figure 18. Inductive Switching Loss vs Gate Resistance**



Share Feedback
Your Opinion Matters

## TYPICAL CHARACTERISTICS





**Figure 19. Inductive Switching Loss vs Gate Resistance**





**Figure 20. Thermal Response Characteristics**



Share Feedback
Your Opinion Matters

## REVISION HISTORY

| Revision | Description of Changes | Date |
|---|---|---|
| 9 | Updated static gate source voltage ratings in maximum ratings table. | 6/15/2026 |


This document has undergone updates prior to the inclusion of this revision history table. The changes tracked here only reflect updates made on the noted approval dates.




Share Feedback
Your Opinion Matters

**TO−247−3LD**
CASE 340CX
ISSUE A

DATE 06 JUL 2020






NOTES: UNLESS OTHERWISE SPECIFIED.

A. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
B. ALL DIMENSIONS ARE IN MILLIMETERS.
C. DRAWING CONFORMS TO ASME Y14.5 - 2009.
D. DIMENSION A1 TO BE MEASURED IN THE REGION DEFINED BY L1.
E. LEAD FINISH IS UNCONTROLLED IN THE REGION DEFINED BY L1.

| DIM | MILLIMETERS | | |
|---|---|---|---|
| | MIN | NOM | MAX |
| A | 4.58 | 4.70 | 4.82 |
| A1 | 2.20 | 2.40 | 2.60 |
| A2 | 1.40 | 1.50 | 1.60 |
| D | 20.32 | 20.57 | 20.82 |
| E | 15.37 | 15.62 | 15.87 |
| E2 | 4.96 | 5.08 | 5.20 |
| e | ~ | 5.56 | ~ |
| L | 19.75 | 20.00 | 20.25 |
| L1 | 3.69 | 3.81 | 3.93 |
| ØP | 3.51 | 3.58 | 3.65 |
| Q | 5.34 | 5.46 | 5.58 |
| S | 5.34 | 5.46 | 5.58 |
| b | 1.17 | 1.26 | 1.35 |
| b2 | 1.53 | 1.65 | 1.77 |
| b4 | 2.42 | 2.54 | 2.66 |
| c | 0.51 | 0.61 | 0.71 |
| D1 | 13.08 | ~ | ~ |
| D2 | 0.51 | 0.93 | 1.35 |
| E1 | 12.81 | ~ | ~ |
| ØP1 | 6.60 | 6.80 | 7.00 |

## GENERIC MARKING DIAGRAM*




XXXXX = Specific Device Code
A = Assembly Location
Y = Year
WW = Work Week
G = Pb−Free Package

*This information is generic. Please refer to device data sheet for actual part marking. Pb−Free indicator, “G” or microdot “ ▪”, may or may not be present. Some products may not follow the Generic Marking.

| | | |
|---|---|---|
| **DOCUMENT NUMBER:** | **98AON93302G** | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped “CONTROLLED COPY” in red. |
| **DESCRIPTION:** | **TO−247−3LD** | **PAGE 1 OF 1** |

**onsemi** and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

**onsemi**, , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

**TECHNICAL PUBLICATIONS**:
**Technical Library:** www.onsemi.com/design/resources/technical−documentation
**onsemi Website:** www.onsemi.com

**ONLINE SUPPORT**: www.onsemi.com/support
**For additional information, please contact your local Sales Representative at** www.onsemi.com/support/sales

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

# Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

### Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

**www.entegreci.com**

### Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

**Kategorilere göz atın**

### Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

**Üreticileri görün**

### Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

**Teklif isteyin**

**www.entegreci.com** | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.