MOSFET - Power, Single N-Channel, SUPERFET® V, FAST, TO220

600 V, 185 mΩ, 15 A

NTP185N60S5H

V_{DSS}	$R_{DS(ON)}$ MAX	I_D MAX
600 V	185 mΩ @ 10 V	15 A

Description


The SUPERFET V MOSFET FAST series helps maximize system efficiency by the extremely low switching losses in hard switching application.


Features

- 650 V @ T_J = 150°C
- Typ. $R_{DS(on)}$ = 148 mΩ
- 100% Avalanche Tested
- Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

Applications


- Telecom / Server Power Supplies
- EV Charger / UPS / Solar / Industrial Power Supplies





TO−220−3LD
CASE 340AT

MARKING DIAGRAM



T185N60S5H = Specific Device Code
A = Assembly Plant Code
YWW = Date Code (Year & Week)
ZZ = Lot

ABSOLUTE MAXIMUM RATINGS (T_J = 25°C, Unless otherwise noted)

Parameter		Symbol	Value	Unit
Drain−to−Source Voltage		V_{DSS}	600	V
Gate−to−Source Voltage	DC	V_{GSS}	±30	V
	AC (f > 1 Hz)		±30	
Continuous Drain Current	T_C = 25°C	I_D	15	A
	T_C = 100°C		9	
Power Dissipation	T_C = 25°C	P_D	116	W
Pulsed Drain Current (Note 1)	T_C = 25°C	I_{DM}	53	A
Pulsed Source Current (Body Diode) (Note 1)	T_C = 25°C	I_{SM}	53	A
Operating Junction and Storage Temperature Range		T_J, T_{STG}	−55 to +150	°C
Source Current (Body Diode)		I_S	15	A
Single Pulse Avalanche Energy	I_L = 3.6 A, R_G = 25 Ω	E_{AS}	124	mJ
Avalanche Current		I_{AS}	3.6	A
Repetitive Avalanche Energy (Note 1)		E_{AR}	1.16	mJ
MOSFET dv/dt		dv/dt	120	V/ns
Peak Diode Recovery dv/dt (Note 2)			20	
Lead Temperature for Soldering Purposes (1/8″ from case for 10 seconds)		T_L	260	°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Repetitive rating: pulse−width limited by maximum junction temperature.
2. I_{SD} ≤ 7.5 A, di/dt ≤ 200 A/μs, V_{DD} ≤ 400 V, starting T_J = 25°C.

ORDERING INFORMATION

Device	Package	Shipping
NTP185N60S5H	TO220	50 Units / Tube

© Semiconductor Components Industries, LLC, 2021

THERMAL CHARACTERISTICS

Parameter	Symbol	Value	Unit
Thermal Resistance, Junction−to−Case, Max.	$R_{\theta JC}$	1.08	°C/W
Thermal Resistance, Junction−to−Ambient, Max.	$R_{\theta JA}$	62.5	

ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise noted)

Parameter	Test Conditions	Symbol	Min	Typ	Max	Unit
OFF CHARACTERISTICS						
Drain−to−Source Breakdown Voltage	V_{GS} = 0 V, I_D = 1 mA, T_J = 25°C	$V_{(BR)DSS}$	600	–	–	V
Drain−to−Source Breakdown Voltage Temperature Coefficient	I_D = 10 mA, Referenced to 25°C	$\Delta V_{(BR)DSS}/\Delta T_J$	–	630	–	mV/°C
Zero Gate Voltage Drain Current	V_{GS} = 0 V, V_{DS} = 600 V, T_J = 25°C	I_{DSS}	–	–	1	μA
Gate−to−Source Leakage Current	V_{GS} = ±30 V, V_{DS} = 0 V	I_{GSS}	–	–	±100	nA
ON CHARACTERISTICS						
Drain−to−Source On Resistance	V_{GS} = 10 V, I_D = 7.5 A, T_J = 25°C	$R_{DS(on)}$	–	148	185	mΩ
Gate Threshold Voltage	V_{GS} = V_{DS}, I_D = 1.4 mA, T_J = 25°C	$V_{GS(th)}$	2.7	–	4.3	V
Forward Trans−conductance	V_{DS} = 20 V, I_D = 7.5 A	g_{FS}	–	18	–	S
CHARGES, CAPACITANCES & GATE RESISTANCE						
Input Capacitance	V_{DS} = 400 V, V_{GS} = 0 V, f = 250 kHz	C_{ISS}	–	1350	–	pF
Output Capacitance		C_{OSS}	–	25	–	
Time Related Output Capacitance	I_D = Constant, V_{DS} = 0 V to 400 V, V_{GS} = 0 V	$C_{OSS(tr.)}$	–	372	–	
Energy Related Output Capacitance	V_{DS} = 0 V to 400 V, V_{GS} = 0 V	$C_{OSS(er.)}$	–	42	–	
Total Gate Charge	V_{DD} = 400 V, I_D = 7.5 A, V_{GS} = 10 V	$Q_{G(tot)}$	–	25	–	nC
Gate−to−Source Charge		Q_{GS}	–	7	–	
Gate−to−Drain Charge		Q_{GD}	–	8	–	
Gate Resistance	f = 1 MHz	R_G	–	0.9	–	Ω
SWITCHING CHARACTERISTICS						
Turn-On Delay Time	V_{GS} = 0/10 V, V_{DD} = 400 V, I_D = 7.5 A, R_G = 10 Ω	$t_{d(on)}$	–	18	–	ns
Rise Time		t_r	–	9	–	
Turn-Off Delay Time		$t_{d(off)}$	–	53	–	
Fall Time		t_f	–	4	–	
SOURCE-TO−DRAIN DIODE CHARACTERISTICS						
Forward Diode Voltage	V_{GS} = 0 V, I_{SD} = 7.5 A, T_J = 25°C	V_{SD}	–	–	1.2	V
Reverse Recovery Time	V_{GS} = 0 V, I_{SD} = 7.5 A, dI/dt = 100 A/μs, V_{DD} = 400 V	t_{RR}	–	251	–	ns
Reverse Recovery Charge		Q_{RR}	–	3028	–	nC

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

TYPICAL CHARACTERISTICS




Figure 1. On−Region Characteristics




Figure 2. Transfer Characteristics




Figure 3. On−Resistance Variation vs. Drain Current and Gate Voltage




Figure 4. Diode Forward Voltage vs. Source Current




Figure 5. Capacitance Characteristics




Figure 6. Gate Charge Characteristics

TYPICAL CHARACTERISTICS




Figure 7. Breakdown Voltage Variation vs. Temperature




Figure 8. On−Resistance Variation vs. Temperature




Figure 9. Maximum Safe Operating Area




Figure 10. Maximum Drain Current vs. Case Temperature




Figure 11. E_{OSS} vs. Drain−to−Source Voltage

TYPICAL CHARACTERISTICS




Figure 12. Transient Thermal Impedance




Figure 13. Gate Charge Test Circuit & Waveform




Figure 14. Resistive Switching Test Circuit & Waveforms




Figure 15. Unclamped Inductive Switching Test Circuit & Waveforms





Figure 16. Peak Diode Recovery dv/dt Test Circuit & Waveforms

SUPERFET is a registered trademark of Semiconductor Components Industries, LLC or its subsidiaries in the United States and/or other countries.

PACKAGE DIMENSIONS

TO−220−3LD
CASE 340AT
ISSUE A



onsemi, ONSEMI , and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi's** product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Email Requests to: orderlit@onsemi.com

onsemi Website: www.onsemi.com

TECHNICAL SUPPORT
North American Technical Support:
Voice Mail: 1 800−282−9855 Toll Free USA/Canada
Phone: 011 421 33 790 2910

Europe, Middle East and Africa Technical Support:
Phone: 00421 33 790 2910
For additional information, please contact your local Sales Representative

◊

ENTEGRECİ

Bu belge www.entegreci.com üzerinden sunulmaktadır.

Elektronik komponent tedarikinde Entegreci

Entegreci, Eskişehir merkezli, Türkiye geneline satış yapan bir elektronik komponent mağazasıdır. Entegreler (IC), mikrodenetleyiciler, transistörler, diyotlar, pasif elemanlar, konnektörler, modüller ve geliştirme kartları tek adetten seri üretim adetlerine kadar satılır. Ürün sayfalarında güncel stok durumunu, fiyatı ve datasheet bağlantısını bulabilirsiniz.

Parça koduyla arama

Üretici parça numarasını yazın; stok ve fiyatı hemen görün.

www.entegreci.com

Ürün kategorileri

Entegreden kapasitöre tüm elektronik komponent kategorileri.

Kategorilere göz atın

Üreticiler

Aradığınız üreticinin ürünlerini tek sayfada inceleyin.

Üreticileri görün

Toplu alım ve teklif

Listede olmayan ya da yüksek adetli parçalar için teklif isteyin.

Teklif isteyin

www.entegreci.com | **destek@entegreci.com** | **0850 305 90 34**

Entegreci is an online electronic components store based in Türkiye. Search by manufacturer part number to see stock, prices and datasheets for integrated circuits, microcontrollers, transistors, passive components and connectors, or request a quote for parts that are not listed.

Bu sayfa Entegreci tarafından eklenmiştir. Belgenin önceki sayfaları asıl yayıncısına aittir ve içeriği değiştirilmemiştir; en güncel sürüm için belgenin yayıncısına başvurun.